



# SMT-4345

43inch UHD monitor with two windows PIP/PBP



## Key Features

- 43 inch UHD Monitor, support up to  $3840 \times 2160@60\text{Hz}$
- Brightness  $300 \text{ cd/m}^2$ , Contrast 1200:1
- Viewing Angle (H/V) :  $178^\circ/178^\circ$ , Response Time : 8ms
- Video Input : HDMI(2), DP(1), two windows PIP/PBP
- Panel Life : 30,000 hours
- Designed and tested on 24/7 operation

# SMT-4345

43inch UHD monitor with two windows PIP/PBP



## Specifications

### Display

|                     |                       |
|---------------------|-----------------------|
| Type                | LED Monitor           |
| Screen Size         | 43inch                |
| Max. Resolution     | 3840x2160             |
| Brightness          | 300 cd/m <sup>2</sup> |
| Contrast Ratio      | 1200:1                |
| Aspect Ratio        | 16:9                  |
| Viewing Angle (H/V) | 178°/178°             |
| Display Color       | 1.07B                 |
| Response Time       | 8ms                   |
| Panel Life          | 30,000 hours          |

### Interface

|                     |                  |                                     |
|---------------------|------------------|-------------------------------------|
| Video               | Connectors       | HDMI(2), DP(1), two windows PIP/PBP |
| HDMI                | Connector        | HDMI x 2                            |
|                     | Available Format | 3840x2160@60Hz                      |
| DP                  | Connector        | DP                                  |
|                     | Available Format | 3840x2160@60Hz                      |
| Audio               | Connector        | Audio Out                           |
|                     | Output Signal    | Speakers : 6Ω 2W x 2                |
| Application Support |                  | Remote controller                   |

### On Screen Display

|           |                                                                                                                                    |
|-----------|------------------------------------------------------------------------------------------------------------------------------------|
| Functions | VESA™ DPMS Compatible                                                                                                              |
| Language  | English, French, German, Italian, Simplified Chinese, Traditional Chinese, Korean, Japanese, Espanola, Portuguese, Russian, Arabic |

### General

|            |                   |                        |
|------------|-------------------|------------------------|
| Electrical | Input Voltage     | AC 100 ~ 240V(50/60Hz) |
|            | Power Consumption | 85W                    |

General

|               |                                  |                                     |
|---------------|----------------------------------|-------------------------------------|
| Environmental | Operating Temperature            | 0 ~ +40°C (+32°F ~ +104°F)          |
|               | Operating Humidity               | 10% ~ 80% (non-condensing)          |
| Mechanical    | Dimensions without Stand (WxHxD) | 954.9x570.3x79.8mm (37.6x22.5x3.2") |
|               | Weight                           | 5.8kg(12.8lb)                       |
|               | Packing Dimension (WxHxD)        | 1077x780x200mm (42.4x30.7x7.9")     |
|               | Packing Weight                   | 10.5kg(23.2lb)                      |
|               | Cabinet Color                    | Black                               |
|               | VESA Mounts Interface            | 200x200mm                           |

# SMT-4345

43inch UHD monitor with two windows PIP/PBP



## CAD

Unit: mm [inch]

