

VERIFICATION OF FCC PART 15 COMPLIANCE

*KES hereby verify that the subject product complies with all the
electromagnetic emission specified in the FCC Rule Part 15*

Product Description:	NETWORK CAMERA
Model/Brand Name:	SNO-L6083RN
Variant Model:	-
FCC Rule Part(s):	FCC 47CFR Part 15 Subpart B Class A Part 15.107(b) & Part 15.109(b)
FCC Procedure:	Verification
Applicant Name:	Samsung Techwin Co., Ltd.
Applicant Address:	84, Jeongdong-ro, Seongsan-gu, Changwon-si, Gyeongsangnam-do, Korea
Manufacturer Name:	TIANJIN SANSUNG TECHWIN OPTO- ELECTRONIC CO.,LTD.
Manufacturer Address:	No.11 Weiliu Road. Micro-Electronic Industrial Park Jingang Road Tianjin, 300385, China
Test Report Reference No.:	KES-E1-15T0045

NETWORK CAMERA, Model SNO-L6083RN has been tested in accordance with the measurement procedures specified in FCC 47CFR Part 15 Subpart B class A and has been shown to be complied with the electromagnetic emission limits specified in FCC Rule Part 15 Subpart B class A. A testing of the sample product has been valid for the sample tested based on the reference test report, KES-E1-15T0045

Date of Issue: 02. 26. 2015

Dong Hun, Jang
Technical Manager
Signature:



KES.Co., Ltd.

C-3701, 40, Simin-daero 365beon-gil, Dongan-gu, Anyang-si, Gyeonggi-do, 431-716, Korea
Tel: +82-31-425-6200 //Fax: +82-31-424-0450



KES Co., Ltd.

C-3701, Simin-daero 365-40,
Dongan-gu, Anyang-si, Gyeonggi-do, 431-716, Korea
Tel: +82-31-425-6200 / Fax: +82-31-424-0450
www.kes.co.kr

Test report No.:
KES-E1-15T0045
Page (1) of (35)

EMI Test Report for FCC

DoC / Verification

Test Report No. : KES-E1-15T0045
Date of Issue : 02. 26. 2015
Description of Product : NETWORK CAMERA
Model No. : SNO-L6083RN
Variant Model : -
Applicant : Samsung Techwin Co., Ltd.
Applicant's Address : 84, Jeongdong-ro, Seongsan-gu, Changwon-si, Gyeongsangnam-do, Korea
Manufacturer : TIANJIN SAMSUNG TECHWIN OPTO-ELECTRONIC CO.,LTD
Manufacturer's Address : No.11 Weiliu Road. Micro-Electronic Industrial Park Jingang Road Tianjin 300385, China
Standards : FCC Part 15 Subpart B
- Part 15.107(b) : Conducted Emission
- Part 15.109(b) : Radiated Emission
Date of Receipt : 02.05.2015
Test Date : 02.10.2015
Test Results : ☒ Pass ☐ Fail
The test results relate only to the items tested.

Tested by:

Dae Hyun, Kim
Test Engineer

Reviewed by:

Dong Hun, Jang
Technical Manager



Testing Laboratories for Safety and RF Compliance
C-3701 40, Simin-daero 365beon-gil, Dongan-gu, Anyang-si, Gyeonggi-do, 431-716, Korea
Tel: +82-31-425-6200 / Fax: +82-31-424-0450

Testing Laboratories for EMC Compliance
473-29, Gayeoro, Yeoju-si, Gyeonggi-do, 469-803, Korea
Tel : +82-31-883-5092 / Fax: +82-31-883-5169

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The test results in the report in only apply to the tested sample.



TABLE OF CONTENTS

1	General Information	3
1.1	Introduction	3
1.2	Geographic location	4
1.3	Laboratory Accreditations and Listings	5
1.4	Product Description	6
1.5	Equipment Under Test	8
1.6	Support Equipments	8
1.7	External I/O Cabling	8
1.8	Special Accessories	9
1.9	E.U.T Modifications	9
1.10	Configuration of Test System	9
2	Summary of tests	10
2.1	Conducted Emission Measurements	11
2.2	Radiated Emission Measurements	15
3	Product Labelling Requirements	23
3.1	FCC Statement	23
4	Test Setup Photographs	24
4.1	Conducted Emission	24
4.2	Radiated Emission	25
5	External Photographs	27
6	Internal Photographs	29
	Appendix A - Schematics/Block Diagram	35
	Appendix B - User's Manual	36



KES Co., Ltd.

C-3701, Simin-daero 365-40,
Dongan-gu, Anyang-si, Gyeonggi-do, 431-716, Korea
Tel: +82-31-425-6200 / Fax: +82-31-424-0450
www.kes.co.kr

Test report No.:
KES-E1-15T0045
Page (3) of (35)

1. General Information

1.1 Introduction

The EMI Test Report of Information Technology Equipment is prepared on behalf of named applicant in accordance with the ANSI C63.4-2009. The test results reported in this document relate only to the item that was tested.

The detailed description of the measurement facility was found to be in compliance with the requirement of Section 2.948 of the FCC Rules. The Federal Communications Commission has the reports on file and is listed under Registration Number. The scope of the accreditation covers the FCC Method - 47 CFR Part 15 or 18 of the Commission's Rules.

All measurements contained in this report were conducted in accordance with ANSI C63.4-2009. The instrumentation utilized for the measurements conforms with CISPR16 Specification for Radio Disturbance and Immunity Measuring Apparatus and Methods. Some accessories are used to increase sensitivity and prevent overloading of the measuring instrument. Calibration checks are performed yearly on the instruments by a local calibration laboratories.

All radiated and conducted emission measurements are performed manually at KES Co., Ltd. (hereinafter referred to as "KES"), 473-29, Gayeo-ro, Yeosu-si, Gyeonggi-do, 469-803 Korea

The radiated emission measurements required by the FCC Rules were performed on 3 meter or 10 meter, Open Area Test Site, test range maintained by KES. Complete ANSI 63.4-2009 description and site attenuation measurement data records are maintained at the test facility and have been placed on file with the Federal Communications Commission. The power line conducted emission measurements were performed in a shielded enclosure also located at the same facility.

The KES EMC test facilities in Yeosu-si are designated testing laboratory according to ISO/IEC 17025 by Radio Research Agency(RRA), Korea Communications Commission.

1.2 Geographic location



KES Office Latitude : 37°23'54.59"N, Longitude : 126°58'14.66"E



KES OATS Latitude : 37°13'58.03"N, Longitude : 127°37'21.95"E

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The test results in the report in only apply to the tested sample.

**KES Co., Ltd.**

C-3701, Simin-daero 365-40,
Dongan-gu, Anyang-si, Gyeonggi-do, 431-716, Korea
Tel: +82-31-425-6200 / Fax: +82-31-424-0450
www.kes.co.kr

Test report No.:
KES-E1-15T0045
Page (5) of (35)

1.3 Laboratory Accreditations and Listings

Country	Agency	Scope of Accreditation	Logo
USA	FCC	3 & 10 meter Open Area Test Sites and one conducted site to perform FCC Part 15/18 measurements.	
KOREA	KCC	EMC (10 meter Open Area Test Site and two conducted sites) Radio(3 & 10 meter Open Area Test Sites and one conducted site)	 KR0100
Canada	IC	3 & 10 meter Open Area Test Sites and one conducted site	 4769B-1
Europe	TUV_SUD	EMC EN 55011, EN 55022, EN 61000-3-2, EN 61000-3-3, EN 61000-6-1, EN 61000-6-2, EN 61000-6-3, EN 61000-6-4, EN 55014-1, EN 61326 EN 50130-4, EN 55024, EN 55014-2 EN 61204-3, EN 60601-1-2, EN 61000-4-2, EN 61000-4-3, EN 61000-4-4, EN 61000-4-5, EN 61000-4-6, EN 61000-4-8, EN 61000-4-11	

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The test results in the report in only apply to the tested sample.



1.4 Product Description

Samsung Techwin Co., Ltd., NETWORK CAMERA, Model No: SNO-L6083RN or the "E.U.T".

Main Specifications of EUT are

Imaging Device	1/2.9" 2.19M CMOS
Total Pixels	2,000(H) x 1,121(V)
Effective Pixels	1,984(H) x 1,105(V)
Scanning System	Progressive
Min. Illumination	Color:0.3Lux(1/30sec,F1.8,50IRE),0.005Lux(2sec,50IRE) Color:0.1Lux(1/30sec,F1.8,30IRE) B/W : 0 Lux (IR LED on)
Focal Length (Zoom Ratio)	3.6mm
Max. Aperture Ratio	F1.8
Angular Field of View	H: 86.5°, V: 47.8°, D: 101.2° (±5%)
Min. Object Distance	0.5m
Lens Type	Fixed
Mount Type	Board type
IR Viewable Length	15m
Camera Title	Off / On (Displayed up to 15 characters)
Day & Night	True Day & Night
Backlight Compensation	Off / BLC
Contrast Enhancement	SSDR(SamsungSuperDynamicRange) (Off / On)
Digital Noise Reduction	SSNR(Off / On)
Motion Detection	Off / On (4ea rectangler zones)
Privacy Masking	Off / On (6ea rectangler zones)
Gain Control	Off / Low / Middle / High
White Balance	ATW / AWC / Manual / Indoor / Outdoor
LDC(Lens distortion control)	On/Off (5 levels with Min/Max)
Electronic Shutter Speed	Minimum / Maximum / Anti flicker
Flip / Mirror	Flip / Mirror / Hallway view
Intelligent Video Analytics	Motion Detection with metadata, Tampering
Alarm Triggers	Motiondetection, Tampering Detection, SD card error
Alarm Events	FileuploadviaFTPE-Mail LocalstoragerecordingatEvent NotificationviaE-Mail



KES Co., Ltd.
C-3701, Simin-daero 365-40,
Dongan-gu, Anyang-si, Gyeonggi-do, 431-716, Korea
Tel: +82-31-425-6200 / Fax: +82-31-424-0450
www.kes.co.kr

Test report No.:
KES-E1-15T0045
Page (7) of (35)

Ethernet	RJ-45 (10/100BASE-T)
Video Compression Format	H.264, MJPEG
Resolution	1920x1080 / 1280x960 / 1280x720 / 1024x768 / 800x600 / 720x576 / 640x480 / 320x240
Max. Framerate	H.264:Max30fpsatallresolutions MJPEG:Max1fpsat1920x1080/1280x1024/1280x720/1024x768,Max.15fpsatotherresolution
Video Quality Ajustment	H.264:TargetBitrateLevelControl MJPEG:QualityLevelControl
Bitrate control method	H.264:CBRorVBR MJPEG:VBR
Streaming Capability	Multiple Streaming(Up to 3 Profiles)
Audio I/O	Line-in
Audio Compression Format	G.711u-law/G.726Selectable G.726(ADPCM)8KHz,G.7118KHz G.726:16Kbps,24Kbps,32Kbps,40Kbps
Audio Communication	Uni-directional
IP	IPv4, IPv6
Protocol	TCP/IP,UDP/IP,RTP(UDP),RTP(TCP),RTCP,RTSP,NTP,HTTP,HTTPS,SSL,DHCP,PPPoE,FTP,SMTP,ICMP,IGMP,SNMPv1/v2c/v3(MIB-2),ARP,DNS,DDNS,QoS,PIM-SM,UPnP,Bonjour
Security	HTTPS(SSL)LoginAuthentication DigestLoginAuthentication IPAddressFiltering UseraccessLog 802.1XAuthentication
Streaming Method	Unicast / Multicast
Max. User Access	6 users at Unicast Mode
Edge storage	MicroSD/SDHCMax32G,NAS (MotionimagesrecordedinthetSDmemorycardcanbedownloaded) (ManualrecordingatLocalPC)
Application Programming Interface	ONVIFProfileS,G SUNAPI(HTTPAPI)
Webpage Language	English,French,German,Spanish,Italian,Chinese,Korean, Russian,Japanese,Swedish,Denish,Portuguese,Turkish,Polish,Czech,Rumanian,Serbian,Dutch,Croatia,Hungary,Greek,Finnish,Norwegian
Web Viewer	SupportedOS:WindowsXP/VISTA/7/8/8.1,MACOSX10.7~10.10 SupportedBrowser:MicrosoftInternetExplorer(Ver.8~11),MozillaFirefox(Ver.9~35), Google Chrome (Ver. 15~40), Apple Safari (Ver. 8.0.2(Mac OS X 10.10), 8.0.2(Mac OS X 10.9), 6.0.2 (Mac OS X 10.8, 10.7 only), 5.1.7) * Mac OS X only
Central Management Software	SmartViewer
Operating Temperature / Humidity	-30°C ~ +55°C / Less than 90% RH
Storage Temperature / Humidity	-30°C~+60°C(-22°F~+140°F)/ Less than 90% RH
Ingress Protection	IP66
Input Voltage / Current	PoE
Power Consumption	Max. 7.0W
Color / Material	Dark gray / Plastic
Dimension (WxHxD)	Φ58.6mm x 86mm(선철드 제외)
Weight	300g

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The test results in the report in only apply to the tested sample.



1.5 Equipment Under Test

Description	Model Number	Serial Number	Manufacturer	Remarks
NETWORK CAMERA	SNO-L6083RN	-	TIANJIN SAMSUNG TECHWIN OPTO-ELECTRONIC CO., LTD	EUT

1.6 Support Equipments

Description	Model Number	Serial Number	Manufacturer	Remarks
Notebook	SNO-L6083RN	-	SAMSUNG TECHONOLGY CO., LTD	-
NOTEBOOK	LG15N54	410NZET022292	LG Electronics Inc.	-
Adapter	ADP-90WH B	84ZW19F1557	DELTA ELECTRONICS(JIANGSU) LTD.	-
PoE Adapter	PD3001GC/AC	RD9356082016964 200	Power Dsine	-
Mike	CMK-303	-	CAMAC	-

1.7 External I/O Cabling

Description	Length (m)	Port / From	Port/To	Remarks
NETWORK CAMERA	3.0	PoE / NETWORK CAMERA	PoE / PoE Adapter	Unshielded
PoE Adapter	2.5	RJ-45 / PoE Adapter	RJ-45 / NOTEBOOK	Unshielded
NETWORK CAMERA	1.6	2.5 mm / NETWORK CAMERA	2.5 mm / Mike	Unshielded


1.8 Special Accessories

As shown in section 1.10, all interface cables used for compliance testing are shielded as normally supplied or by use respective component manufacturers.

1.9 E.U.T Modifications

No modifications were made to the E.U.T in order to achieve and maintain compliance to the standards described in this report.

1.10 Configuration of Test System



※ Test Operating Mode

- Ping test
- web view monitoring

**KES Co., Ltd.**

C-3701, Simin-daero 365-40,
Dongan-gu, Anyang-si, Gyeonggi-do, 431-716, Korea
Tel: +82-31-425-6200 / Fax: +82-31-424-0450
www.kes.co.kr

Test report No.:
KES-E1-15T0045
Page (10) of (35)

2. Summary of Tests

FCC Part Section(s)	Parameter	Test Condition	Status (note 1)
15.109(b)	Emission limits	Radiated	C
15.107(b)	Conducted limits	Conducted	N/A

Note 1 : C=Complies N/C=Not Complies N/T=Not Tested N/A=Not Applicable

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The test results in the report in only apply to the tested sample.



2.1 Conducted Emission Measurements

2.1.1 Test Methods

The power line conducted emission measurements were performed in a shielded enclosure, using the setup in accordance with ANSI C63.4-2009 conducted emission measurement procedure.

2.1.2 Test Equipments

Description	Manufacturer	Model Number	Serial Number	Cal. Due
EMI Receiver/Signal Analyzer	Narda S.T.S / PMM	PMM 9010F	020WW31006	04. 04. 2015
LISN	R&S	ENV216	101137	02. 10. 2016
LISN	EMCO	3810/2	2228	-
Electro wave Shieldroom	SEMITEC	-	-	-

2.1.3 Test Environments

Ambient Temperatures	Relative Humidity
see the data	see the data

2.1.4 Test Limits


Frequency (MHz)	15.107 Conducted limits			
	Class B (dB μ V)		Class A (dB μ V)	
	Quasi-peak	Average	Quasi-peak	Average
0.15 to 0.50	66.0 to 56.0	56.0 to 46.0	79.0	66.0
0.50 to 5.00	56.0	46.0	73.0	60.0
5.00 to 30.00	60.0	50.0	73.0	60.0

2.1.5 Test Procedure

Conducted emission levels were measured on each current-carrying line with the EMI TEST Receiver operating in the CISPR quasi-peak mode (or peak mode if applicable). The Receiver's 6 dB bandwidth was set to 9 kHz. The initial step in collecting conducted data is a EMI TEST Receiver peak scan of the measurement range. If the conducted emission exceed the average limit with the instrument set to the quasi-peak mode, the measurements are made in the average mode. The emission spectrum was scanned from 150 kHz to 30 MHz. The highest emission amplitudes relative to the appropriate limits were measured and have been recorded. Quasi-peak readings are distinguished with a "QP".

The conducted emission test was performed with the E.U.T exercise program loaded, and the emissions were scanned between 150 kHz to 30 MHz on the HOT side and NEUTRAL side, herein referred to as H and N, respectively.

2.1.6 Test Configuration



2.1.7 Test Results

N/A : This E.U.T operate by POE power.



KES Co., Ltd.

C-3701, Simin-daero 365-40,
Dongan-gu, Anyang-si, Gyeonggi-do, 431-716, Korea
Tel: +82-31-425-6200 / Fax: +82-31-424-0450
www.kes.co.kr

Test report No.:
KES-E1-15T0045
Page (13) of (35)

2.1.8 Test Data

Temperature: °C Humidity: % R.H. Test Date: Tested by:
Polarization: HOT

N/A

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The test results in the report in only apply to the tested sample.



KES Co., Ltd.

C-3701, Simin-daero 365-40,
Dongan-gu, Anyang-si, Gyeonggi-do, 431-716, Korea
Tel: +82-31-425-6200 / Fax: +82-31-424-0450
www.kes.co.kr

Test report No.:
KES-E1-15T0045
Page (14) of (35)

Polarization: NEUTRAL

N/A

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The test results in the report in only apply to the tested sample.



2.2 Radiated Emission Measurements

2.2.1 Test Methods

The radiated emission measurements were performed in a Open Area Test Site (OATS) and 3 m full chamber, using the setup in accordance with ANSI C63.4-2009 radiated emission measurement procedure.

2.2.2 Test Equipments

Description	Manufacturer	Model Number	Serial Number	Cal. Due
EMI TEST Receiver	R & S	ESVS10	826008/014	04. 04. 2015
Trilog-Broadband Antenna	SCHWARZBECK	VULB 9168	9168-385	05. 09. 2015
OATS	KES	-	-	-
Antenna Mast	DAEIL EMC	-	-	-
Turn Table	DAEIL EMC	-	-	-
EMI TEST Receiver	R & S	ESR7	101190	08. 13. 2015
PREAMPLIFIER	8449B	H.P	3008A00538	07. 23. 2015
Double Ridged Horn Antenna	A-H-SYSTEM,INC	SAS-571	781	05. 13. 2015
RS Chamber (EMI 18GHz)	SEMITEC	-	-	-
Antenna Mast	AUDIX	-	-	-
Turn Table	AUDIX	-	-	-

2.2.3 Test Environments

Ambient Temperatures	Relative Humidity
see the data	see the data

2.2.4 Test Limits

Frequency (MHz)	15.109 Radiated emission limits			
	Class B @ 3 m		Class A @ 10 m	
	(dB μ V/m)	(μ V/m)	(dB μ V/m)	(μ V/m)
30 to 88	40.0	100	39.0	90
88 to 216	43.5	150	43.5	150
216 to 960	46.0	200	46.4	210
above 960	54.0	500	49.5	300

Frequency (MHz)	CISPR Publication 22			
	Class B @ 3 m (dB μ V/m)		Class A @ 3 m (dB μ V/m)	
	PK	AV	PK	AV
above 1 000	74	54	80	60

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The test results in the report in only apply to the tested sample.

2.2.5 Test Procedure

Before final measurements of radiated emission were made at the OATS, the E.U.T was scanned in semi-anechoic chamber in order to determine its emission spectrum signature. The physical arrangement of the test system and associated cabling was varied in order to determine the effect on the E.U.T's emission in amplitude, direction and frequency. This process was repeated during final radiated emission measurements at the OATS range, at each frequency, in order to ensure that maximum emissions amplitudes were attained.

The radiated emission test was performed with E.U.T exercise program loaded, and the emissions were scanned between 30 MHz to 1 000 MHz using a R&S ESVS10 EMI TEST Receiver and 1 000 MHz to 6 000 MHz using a spectrum analyzer. The EMI TEST Receiver's 6 dB bandwidth was set to 120 kHz and 1 MHz, and EMI TEST Receiver was operated in the CISPR quasi-peak detection mode. At each frequency, the E.U.T was rotated 360 degrees, and the antenna was raised and lowered from 1 to 4 meters in order to determine the maximum emission levels. Measurements were taken using both HORIZONTAL and VERTICAL antenna polarization, herein referred to as H and V, respectively.

- above 1 GHz : Antenna height is fixed to 1.00 m

2.2.6 Field Strength Calculation

F.S = Field Strength

M.R = Meter Reading

A.F = Antenna Factor

C.L = Cable Loss


A.G= Amplifier Gain

* Below 1 GHz : $F.S(dB\mu V/m) = M.R(dB\mu V) + [A.F(dB/m) + C.L(dB)]$


* Above 1 GHz : $F.S(dB\mu V/m) = M.R(dB\mu V) + [A.F(dB/m) + C.L(dB)] - A.G(dB)$

2.2.7 Test Configuration

* Below 1 GHz



* Above 1 GHz



**KES Co., Ltd.**

C-3701, Simin-daero 365-40,
Dongan-gu, Anyang-si, Gyeonggi-do, 431-716, Korea
Tel: +82-31-425-6200 / Fax: +82-31-424-0450
www.kes.co.kr

Test report No.:
KES-E1-15T0045
Page (18) of (35)

2.2.8 Test Results

Below 1 GHz: According to the data in section 2.2.9, the E.U.T complied with the FCC 15.109 limits.

Above 1 GHz :According to the data in section 2.2.9, the E.U.T complied with the CISPR22 standards.

2.2.9 Test Data*** Below 1 GHz**

Temperature: 3.0 °C Humidity: 38.0 % R.H. Test Date: 02. 10. 2015 Tested by: Dae Hyun, Kim

Frequency (MHz)	Amplitude (dB μ V/m)	Antenna		Correction Factor		Corrected Amplitude (dB μ V/m)	Applicable Limit (dB μ V/m)	Margin (dB)
		Polar. (H/V)	Height (m)	Ant. (dB)	Cable (dB)			
35.746	19.400	V	1.000	12.890	1.320	33.610	39.000	5.390
149.308	17.400	H	4.000	13.010	2.900	33.310	43.500	10.190
149.806	17.000	V	1.000	13.030	2.910	32.940	43.500	10.560
259.247	25.500	H	3.280	12.060	3.960	41.520	46.400	4.880
334.025	22.000	H	4.000	14.140	4.640	40.780	46.400	5.620
371.320	20.400	H	2.840	14.950	4.920	40.270	46.400	6.130
482.195	17.200	V	1.680	17.360	5.770	40.330	46.400	6.070

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The test results in the report in only apply to the tested sample.




KES Co., Ltd.

C-3701, Simin-daero 365-40,
Dongan-gu, Anyang-si, Gyeonggi-do, 431-716, Korea
Tel: +82-31-425-6200 / Fax: +82-31-424-0450
www.kes.co.kr

Test report No.:
KES-E1-15T0045
Page (19) of (35)

* Above 1 GHz

Temperature: 20.2 °C Humidity: 36.1 % R.H. Test Date: 02. 10. 2015 Tested by: Dae Hyun, Kim



Site : chamber
Condition: FCC 1 GHZ - 5 GHZ PK(A) 3m HORN ANT (2014.03.10) horizontal
: RBW:1000.000kHz VBW:1000.000kHz SWT:Auto
Project : NETWORK CAMERA
EUT : SNO-L6083RN
Mode :
Memo : 1 ~ 3 GHz

		Read	Ant	Cable	Preamp	TPos	Limit	Over		
	Freq	Level	Factor	Loss	Factor		Line	Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	deg	dBuV/m	dB		
1 pp	1002.00	39.39	23.00	5.44	36.20	36	60.00	-28.37	horizontal	Average
2	1002.00	53.67	23.00	5.44	36.20	36	80.00	-34.09	horizontal	Peak
3	1596.00	29.27	25.63	6.88	35.20	15	60.00	-33.42	horizontal	Average
4	1596.00	46.25	25.63	6.88	35.20	15	80.00	-36.44	horizontal	Peak
5	1794.00	29.24	26.88	7.36	34.87	226	60.00	-31.39	horizontal	Average
6	1794.00	48.19	26.88	7.36	34.87	226	80.00	-32.44	horizontal	Peak
7	1998.00	29.57	28.18	7.86	34.53	172	60.00	-28.92	horizontal	Average
8 pk	1998.00	48.83	28.18	7.86	34.53	172	80.00	-29.66	horizontal	Peak
9	2192.00	26.80	28.60	8.26	34.40	118	60.00	-30.74	horizontal	Average
10	2192.00	43.88	28.60	8.26	34.40	118	80.00	-33.66	horizontal	Peak
11	2448.00	26.30	29.15	8.80	34.22	205	60.00	-29.97	horizontal	Average
12	2448.00	39.70	29.15	8.80	34.22	205	80.00	-36.57	horizontal	Peak


This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The test results in the report in only apply to the tested sample.



KES Co., Ltd.

C-3701, Simin-daero 365-40,
Dongan-gu, Anyang-si, Gyeonggi-do, 431-716, Korea
Tel: +82-31-425-6200 / Fax: +82-31-424-0450
www.kes.co.kr

Test report No.:
KES-E1-15T0045
Page (20) of (35)



Site : chamber
Condition: FCC 1 GHz - 5 GHz PK(A) 3m HORN ANT (2014.03.10) vertical
: RBW:1000.000kHz VBW:1000.000kHz SWT:Auto
Project : NETWORK CAMERA
EUT : SNO-L6083RN
Mode :
Memo : 1 ~ 3 GHz

	Freq	Read Level	Ant Factor	Cable Loss	Preamp Factor	TPos	Limit Line	Over Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	deg	dBuV/m	dB		
1 pp	1002.00	41.74	23.00	5.44	36.20	202	60.00	-26.02	vertical	Average
2	1002.00	56.63	23.00	5.44	36.20	202	80.00	-31.13	vertical	Peak
3	1596.00	29.30	25.63	6.88	35.20	195	60.00	-33.39	vertical	Average
4	1596.00	46.75	25.63	6.88	35.20	195	80.00	-35.94	vertical	Peak
5	1798.00	29.86	26.91	7.37	34.87	195	60.00	-30.73	vertical	Average
6	1798.00	49.02	26.91	7.37	34.87	195	80.00	-31.57	vertical	Peak
7	1994.00	29.13	28.15	7.85	34.54	22	60.00	-29.41	vertical	Average
8 pk	1994.00	48.15	28.15	7.85	34.54	22	80.00	-30.39	vertical	Peak
9	2198.00	27.93	28.61	8.28	34.39	122	60.00	-29.57	vertical	Average
10	2198.00	45.97	28.61	8.28	34.39	122	80.00	-31.53	vertical	Peak
11	2400.00	27.26	29.05	8.70	34.25	282	60.00	-29.24	vertical	Average
12	2400.00	42.96	29.05	8.70	34.25	282	80.00	-33.54	vertical	Peak


This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The test results in the report in only apply to the tested sample.



KES Co., Ltd.

C-3701, Simin-daero 365-40,
Dongan-gu, Anyang-si, Gyeonggi-do, 431-716, Korea
Tel: +82-31-425-6200 / Fax: +82-31-424-0450
www.kes.co.kr

Test report No.:
KES-E1-15T0045
Page (21) of (35)



Site : chamber
Condition: FCC 1 GHz - 5 GHz PK(A) 3m HORN ANT (2014.03.10) horizontal
: RBW:1000.000kHz VBW:1000.000kHz SWT:Auto
Project : NETWORK CAMERA
EUT : SNO-L6083RN
Mode :
Memo : 3 ~ 5 GHz

	Freq	Read Level	Ant Factor	Cable Loss	Preamplifier Factor	TPos	Limit Line	Over Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	deg	dBuV/m	dB		
1	3294.00	23.75	30.36	10.42	34.17	337	60.00	-29.64	horizontal	Average
2	3294.00	35.55	30.36	10.42	34.17	337	80.00	-37.84	horizontal	Peak
3	4107.00	22.45	31.94	11.70	34.78	208	60.00	-28.69	horizontal	Average
4	4107.00	35.06	31.94	11.70	34.78	208	80.00	-36.08	horizontal	Peak
5	4386.00	22.18	32.00	12.16	34.29	238	60.00	-27.95	horizontal	Average
6	4386.00	34.85	32.00	12.16	34.29	238	80.00	-35.28	horizontal	Peak
7 pp	4770.00	22.79	32.95	12.79	33.61	70	60.00	-25.08	horizontal	Average
8 pk	4770.00	35.67	32.95	12.79	33.61	70	80.00	-32.20	horizontal	Peak


This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The test results in the report in only apply to the tested sample.



KES Co., Ltd.

C-3701, Simin-daero 365-40,
Dongan-gu, Anyang-si, Gyeonggi-do, 431-716, Korea
Tel: +82-31-425-6200 / Fax: +82-31-424-0450
www.kes.co.kr

Test report No.:
KES-E1-15T0045
Page (22) of (35)



Site : chamber
Condition: FCC 1 GHz - 5 GHz PK(A) 3m HORN ANT (2014.03.10) vertical
: RBW:1000.000kHz VBW:1000.000kHz SWT:Auto
Project : NETWORK CAMERA
EUT : SNO-L6083RN
Mode :
Memo : 3 ~ 5 GHz

	Freq	Read Level	Ant Factor	Cable Loss	Preamplifier Factor	TPos	Limit Line	Over Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	deg	dBuV/m	dB		
1	3195.00	25.45	30.32	10.26	34.06	216	60.00	-28.03	vertical	Average
2 pk	3195.00	44.91	30.32	10.26	34.06	216	80.00	-28.57	vertical	Peak
3	3723.00	24.42	31.09	11.09	34.66	163	60.00	-28.06	vertical	Average
4	3723.00	38.42	31.09	11.09	34.66	163	80.00	-34.06	vertical	Peak
5	3831.00	22.92	31.42	11.26	34.78	339	60.00	-29.18	vertical	Average
6	3831.00	34.76	31.42	11.26	34.78	339	80.00	-37.34	vertical	Peak
7	3930.00	22.62	31.71	11.41	34.89	281	60.00	-29.15	vertical	Average
8	3930.00	34.99	31.71	11.41	34.89	281	80.00	-36.78	vertical	Peak
9 pp	4782.00	22.95	32.99	12.81	33.59	216	60.00	-24.84	vertical	Average
10	4782.00	36.79	32.99	12.81	33.59	216	80.00	-31.00	vertical	Peak

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The test results in the report in only apply to the tested sample.



KES Co., Ltd.

C-3701, Simin-daero 365-40,
Dongan-gu, Anyang-si, Gyeonggi-do, 431-716, Korea
Tel: +82-31-425-6200 / Fax: +82-31-424-0450
www.kes.co.kr

Test report No.:
KES-E1-15T0045
Page (23) of (35)

3. Product Labelling Requirements

3.1 FCC Statement

Product shall be labelled the following statement on the user's manual:

This device complies with part 15 of the FCC Rules. Operation in subject to the following two conditions: (1) This device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.

Note : When the device is so small or for such use that it is not practicable to place the statement on it, the information shall be placed in prominent location in the instruction manual or pamphlet supplied to the user. However, the FCC identifier or unique identifier, as appropriate, must be displayed on the device.



4. Test Setup Photographs


4.1 Conducted Emission

N/A

N/A



4.2 Radiated Emission

- Below 1 GHz



This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The test results in the report in only apply to the tested sample.

- Above 1 GHz



This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The test results in the report in only apply to the tested sample.

5. External Photographs

5.1 E.U.T: Front View



5.2 E.U.T: Rear View



5.3 E.U.T: Label View (Location)



This device complies with part 15 of the FCC Rules. Operation in subject to the following two conditions: (1) This device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.

6. Internal Photographs

6.1 E.U.T: Internal View




This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The test results in the report in only apply to the tested sample.


6.2 E.U.T: Internal View(Top) - Main Board




E.U.T: Internal View(Bottom) - Main Board



6.3 E.U.T: Internal View(Top) - Sensor Board



E.U.T: Internal View(Bottom) - Sensor Board




This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The test results in the report in only apply to the tested sample.

6.4 E.U.T: Internal View(Top) - LED Board




E.U.T: Internal View(Bottom) - LED Board




This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The test results in the report in only apply to the tested sample.

6.5 E.U.T: Internal View(Top) - Lens Board



E.U.T: Internal View(Bottom) - Lens Board



This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The test results in the report in only apply to the tested sample.



KES Co., Ltd.

C-3701, Simin-daero 365-40,
Dongan-gu, Anyang-si, Gyeonggi-do, 431-716, Korea
Tel: +82-31-425-6200 / Fax: +82-31-424-0450
www.kes.co.kr

Test report No.:
KES-E1-15T0045
Page (34) of (35)

Appendix A - Schematics/Block Diagram

Please see attached document(s).

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The test results in the report in only apply to the tested sample.



KES Co., Ltd.

C-3701, Simin-daero 365-40,
Dongan-gu, Anyang-si, Gyeonggi-do, 431-716, Korea
Tel: +82-31-425-6200 / Fax: +82-31-424-0450
www.kes.co.kr

Test report No.:
KES-E1-15T0045
Page (35) of (35)

Appendix B - User's Manual

Please see attached document(s).

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The test results in the report in only apply to the tested sample.