

CERTIFICATE of EMC Compliance

Report No : EMC-FCC-E2468
Type of equipment : Network Camera
Model Name : SNP-6321HN
Variant Model Name : SNP-L6233HN
Applicant : Samsung Techwin Co., Ltd.
84, Jeongdong-ro, Seongsan-gu,
Changwon-si, Gyeongsangnam-do, Korea
Manufacturer#1 : Samsung Techwin Co., Ltd.
84, Jeongdong-ro, Seongsan-gu,
Changwon-si, Gyeongsangnam-do, Korea
Manufacturer#2 : TIANJIN SAMSUNG TECHWIN
OPTO-ELECTRONIC CO., LTD
No.11 Weilliu Road. Micro-Electronic Industrial
Park Jingang Road Tianjin 300385, China
Test standards : FCC part 15 subpart B, Class A
Classification : Verification

The above equipment was tested by EMC compliance Testing Laboratory for with the requirements of FCC Rules and Regulations. The results of testing in this report apply to the product / system which was tested only.

These results are deemed satisfactory evidence of compliance with ICES-003 of the Canadian Interference-Causing Equipment Regulations.

Laboratory

EMC compliance Ltd.
65, Sinwon-ro, Yeongtong-gu,
Suwon-si, Gyeonggi-do, 443-390, Korea

Tel: 82 70 5008 1021
Fax: 82 505 299 8311



Yeom, Han-Seok/ Manager

EMI TEST REPORT

Test report No : EMC-FCC-E2468
Type of Equipment : Network Camera
Model Name : SNP-6321HN
Variant Model Name : SNP-L6233HN
Applicant : Samsung Techwin Co., Ltd.
84, Jeongdong-ro, Seongsan-gu,
Changwon-si, Gyeongsangnam-do, Korea
Manufacturer#1 : Samsung Techwin Co., Ltd.
84, Jeongdong-ro, Seongsan-gu,
Changwon-si, Gyeongsangnam-do, Korea
Manufacturer#2 : TIANJIN SAMSUNG TECHWIN
OPTO-ELECTRONIC CO., LTD
No.11 Weiliu Road. Micro-Electronic Industrial
Park Jingang Road Tianjin 300385, China
Test standards : FCC part 15 subpart B, Class A
Classification : Verification
Test Procedure and Items
- Radiated Emissions Measurement : ANSI C63.4-2009
Testing Laboratory : EMC Compliance Ltd.
Test result : Complied

The above equipment was tested by EMC compliance Testing Laboratory for compliance with the requirements of FCC Rules and Regulations. The results of testing in this report apply to the product/system which was tested only. Other similar equipment will not necessarily produce the same results due to production tolerance and measurement uncertainties.

These results are deemed satisfactory evidence of compliance with ICES-003 of the Canadian Interference-Causing Equipment Regulations.

Date of receipt: 2014. 10. 07

Date of testing: 2014. 10. 17 ~ 10. 20

Issued date: 2014. 10. 24

Tested by: 
JUNG, YONG-JUN

Approved by: 
YEOM, HAN-SEOK

Contents

1. Applicant information	3
2. Laboratory information	4
3. Test system configuration.....	5
3.1 Operation environment	5
3.2 Measurement Uncertainty	6
4. Description of E.U.T.	7
4.1 General information.....	7
4.2 Product description	9
4.3 Auxiliary equipments.....	9
4.4 Test configuration	10
4.5 Operating conditions.....	12
5. Summary of test results.....	13
5.1 Summary of EMI emission test results	13
6. Test results	14
6.1 Radiated Emission	14
7. E.U.T. photographs.....	24

1. Applicant information

Applicant: Samsung Techwin Co., Ltd.
Address: 84, Jeongdong-ro, Seongsan-gu, Changwon-si,
Gyeongsangnam-do, Korea
Telephone: +82-70-7147-8361
Fax: +82-31-277-2784
E-mail: js2002.kang@samsung.com
Contact name: **Kang Jei Soon**

Manufacturer#1: Samsung Techwin Co., Ltd.
Address: 84, Jeongdong-ro, Seongsan-gu, Changwon-si,
Gyeongsangnam-do, Korea
Telephone: +82-70-7147-8361
Fax: +82-31-277-2784
E-mail: js2002.kang@samsung.com
Contact name: **Kang Jei Soon**

Manufacturer#2: TIANJIN SAMSUNG TECHWIN OPTO-ELECTRONIC CO., LTD
Address: No.11 Weiliu Road. Micro-Electronic Industrial Park
Jingang Road Tianjin 300385, China

2. Laboratory information

Address

EMC compliance Ltd.

65, Sinwon-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 443-390, Korea

Telephone Number: 82 70 5008 1021

Facsimile Number: 82 505 299 8311


FCC CAB.: KR0040

VCCI Registration No. : R-3327, G-198, C-3706, T-1849

Industry Canada Registration No.: 8035A

KOLAS NO.: 231

SITE MAP



3. Test system configuration

3.1 Operation environment

	Temperature	Humidity	Pressure
Chamber(10 m)	: 20.1 ~ 21.7 °C	30.7 ~ 50.0 % R.H.	-

Test site

These testing items were performed following locations;

Test item	Test site
Conducted Emission	Shielded Room
Radiated Emission	10 m Chamber

3.2 Measurement Uncertainty

All measurements involve certain levels of uncertainties, especially in field of EMC.

The factors contributing to uncertainties are test receiver, cable loss, antenna factor calibration, Antenna directivity, antenna factor variation with height, antenna phase center variation, antenna frequency interpolation, measurement distance variation, site imperfection, mismatch, and system repeatability. Based on CISPR 16-4-2, the measurement uncertainty level with a 95 % confidence level was applied.

Conducted emission measurement (C.L: Approx 95 %, k = 2)		
Shielded Room (CE#1)	9 kHz ~ 150 kHz: ± 3.75 dB	
	150 kHz ~ 30 MHz: ± 3.36 dB	
Shielded Room (CE#2)	9 kHz ~ 150 kHz: ± 3.79 dB	
	150 kHz ~ 30 MHz: ± 3.42 dB	
Radiated Emission measurement (C.L: Approx 95 %, k = 2)		
10 m Chamber (#F4)	30 MHz ~ 300 MHz	3 m: + 4.87 dB, - 4.99 dB 10 m: + 4.86 dB, - 4.98 dB
	300 MHz ~ 1 000 MHz	3 m: + 5.04 dB, - 5.14 dB 10 m: + 4.91 dB, - 5.02 dB
	1 GHz ~ 6 GHz	3 m: + 6.03 dB, - 6.06 dB
10 m Chamber (#F2)	30 MHz ~ 300 MHz	3 m: + 4.94 dB, - 5.06 dB 10 m: + 4.93 dB, - 5.05 dB
	300 MHz ~ 1 000 MHz	3 m: + 4.97 dB, - 5.08 dB 10 m: + 4.84 dB, - 4.96 dB
	1 GHz ~ 6 GHz	3 m: + 6.03 dB, - 6.05 dB
10 m Chamber	6 GHz ~ 18 GHz	3 m: + 6.60 dB, - 6.78 dB

4. Description of E.U.T.

4.1 General information

Spec.	SNP-6321	SNP-6321H
	DV	
Video		
Imaging Device	1/2.8" Progressive Scan CMOS	
Total Pixels	1952(H) x 1236(V), 2.41M	
Effective Pixels	1944(H) x 1224(V), 2.38M	
Scanning System	Progressive	
Min. Illumination	Color : 0.3 Lux (1/30sec, F1.6, 50IRE, AGC High모드) B/W : 0.03 Lux (1/30sec, F1.6, 50IRE AGC High모드) Color : 0.15 Lux (1/30sec, F1.6, 30IRE)	
S / N Ratio	50dB	
Video Out	CVBS : 1.0 Vp-p / 75Ω composite, 720x480(N), 720x576(P), for installation	
Lens		
Focal Length (Zoom Ratio)	4.44~142.6mm(Optical 32X)	
Max. Aperture Ratio	1.6 (Wide) ~ 4.4 (Tele)	
Angular Field of View	H : 62.8°(Wide) ~ 2.23°(Tele) /	
Min. Object Distance	Wide 1.5m ,Tele 2m	Wide 1.5m ,Tele1.9m
Focus Control	Auto / Manual / One Push	
Lens Type	DC Auto Iris	
Mount Type	Board-in type	
Pan / Tilt / Rotate		
Pan Range	360° Endless	
Pan Speed	Preset : 700°/sec, Manual : 0.024°/sec ~120°/sec	
Tilt Range	210°(-15° ~195°)	
Tilt Speed	Preset : 700°/sec, Manual : 0.024°/sec ~120°/sec	
Sequence	Preset (255 ea), Swing, Group (6 ea), Trace, Tour (1 ea), Auto Run, Schedule	
Preset Accuracy	±0.2°	
Azimuth	Yes (East/West/South/North)	
Operational		
Camera Title	Off / On (Displayed up to 45 characters)	
Day & Night	Auto (ICR) / Color / B/W	
Backlight Compensation	Off / BLC	
Wide Dynamic Range	120dB ↑	
Contrast Enhancement	SSDR (Samsung Super Dynamic Range) (Off / On)	
Digital Noise Reduction	SSNR.III (2D+3D Noise Filter) (Off / On)	
Digital Image Stabilization	Off / On	
Defog	Auto/Manual/Off	
Motion Detection	Off / On (4ea Rectangle zone)	
Privacy Masking	Off / On (32 Zones of Rectangle zone) with Zoom Thresold Mosaic option	
Gain Control	Off / Low / Middle / High	
White Balance	ATW / AWC / Manual / Indoor / Outdoor / Mercury	
Electronic Shutter Speed	Minimum / Maximum / Anti flicker (2 ~ 1/12,000sec)	
Digital Zoom	16x area zoom funtion support digital zoom 2x	
Flip / Mirror	Off / On	
Intelligent Video Analytics	Tampering, Virtual Line, Enter/Exit, Appear / Disappear, Audio Detection, Face Detection	
Serial Interface	RS-485 - Samsung-T/E, Pelco-D/P, Sungjin, Panasonic, Bosch, AD, GE, Vicon, Honeywell	
Alarm I/O	Input 4ea / Output 2ea (Relay)	
Alarm Triggers	Motion detection, Tampering, Audio Detection, Face Detecton	
Alarm events	File upload via FTP and E-Mail Notification via E-Mail, TCP and HTTP local storage(SD/SDHC/SDXC) or NAS recording at Network disconnected & Event (Alarm Triggers) External output	
Audio In	Selectable (Mic IN/Line IN), Max output level: 1 Vrms Supply voltage: 2.5VDC(4mA), Input impedance: approx. 2K Ohm	
Audio out	Line out (3.5mm stereo mini jack)	

Network		
Ethernet	RJ-45 (10/100BASE-T)	
Video Compression Format	H.264 (MPEG-4 Part 10/AVC), Motion JPEG	
Resolution	1920x1080 / 1280x1024 / 1280x960 / 1280x720 / 1024x768 / 800x600 / 800x450 / 720x576 / 640x480 / 640x360 / 320x240 / 320x180	
Max. Framerate	H.264 : Max 60fps at all resolutions Motion JPEG : 1920x1080 / 1280x1024 / 1280x960 / 1280x720 / 1024x768 : Max. 15 fps 800x600/800x450/720x576/640x480/640x360/320x240/320x180 : Max. 30fps	
Smart Codec	O	
Video Quality Adjustment	H.264 : Compression Level, Target Bitrate Level Control MJPEG : Quality Level Control	
Bitrate Control Method	H.264 : CBR or VBR, Motion JPEG : VBR	
Streaming Capability	Multiple Streaming (Up to 10 Profiles)	
Audio Compression Format	G.711 u-law / G.726 Selectable G.726 (ADPCM) 8KHz, G.711 8KHz G.726 : 16Kbps, 24Kbps, 32Kbps, 40Kbps	
Audio Communication	Bi-directional	
IP	IPv4, IPv6	
Protocol	TCP/IP, UDP/IP, RTP(UDP), RTP(TCP), RTCP, RTSP, NTP, HTTP, HTTPS, SSL, DHCP, PPPoE, FTP, SMTP, ICMP, IGMP, SNMPv1/v2c/v3(MIB-2), ARP, DNS, DDNS, QoS, PIM-SM, UPnP, Bonjour	
Security	HTTPS(SSL) Login Authentication Digest Login Authentication IP Address Filtering User access Log 802.1x Authentication	
Streaming Method	Unicast / Multicast	
Max. User Access	15 users at Unicast Mode	
Edge Storage	SD/SDHC/SDXC slot for supporting memory card - motion Images recorded in the SD/SDHC/SDXC memory card can be downloaded. Instant Recording to the local PC NAS(Network Attached Storage)	
Application Programming Interface	ONVIF Profile S SUNAPI (HTTP API) SVNP 1.2	
Webpage Language	English, French, German, Spanish, Italian, Chinese, Korean, Russian, Japanese, Swedish, Danish, Portuguese, Turkish, Polish, Czech, Rumanian, Serbian, Dutch, Croatia, Hungary, Greek, Finnish, Norwegian	
Web Viewer	Supported OS : Windows XP / VISTA / 7 / 8, MAC OS X 10.7 Supported Browser : Microsoft Internet Explorer (Ver.8~11), Mozilla Firefox (Ver. 9~19), Google Chrome (Ver. 15~25), Apple Safari (Ver. 6.0.2(Mac OS X 10.8, 10.7 Only), 5.1.7) * Mac OS X Only	
Central Management Software	SmartViewer, SSM	
Environmental		
Operating Temperature / Humidity	-10°C ~ +55°C(+14°F ~ +131°F) / Less than 90% RH	AC24V : -50°C ~ +55°C (-58°F ~ +131°F) / Less than 90% RH PoE+ : -30°C ~ +55°C (-22°F ~ +131°F) / Less than 90% RH
Storage Temperature / Humidity	-30°C ~ +60°C (-22°F ~ +140°F) / Less than 90% RH	-60°C ~ +60°C (-76°F ~ +140°F) / Less than 90% RH
Ingress Protection	-	IP66
Vandal Resistance	IK10 (with SHP-3701H : using IK10 accessory housing)	IK10
Electrical		
Input Voltage / Current	AC24V±10%,PoE+(IEEE802.3at,Class3)	
Power Consumption	20W MAX	25W Max(DC Heater On), 65W Max(AC24V & DC Heater On)
Mechanical		
Color / Material	Ivory / Plastic + Metal	
Dimension (WxHxD)	Ø152.0 x H218.0 mm	Ø220.0 x H293.6 mm
Weight	1.8kg	3.2kg

4.2 Product description


Type of product	Network Camera
Model name (Basic)	SNP-6321HN
Model name (Variant)	SNP-L6233HN
Difference	Buyer model name.
Trade name	-
Serial no	Engineering Sample
Testing voltage	AC 24 V , PoE
Product rating	AC 24 V , PoE
Internal clock frequency	Above 108 MHz
Note	* AC/AC Adaptor was not provided by the manufacturer. * PoE Switch was not provided by the manufacturer.

4.3 Auxiliary equipments

Type	Model / Part #	Serial number	Manufacturer
Note PC	NT271B5E	JGFE91DF600046D	SAMSUNG
USB Mouse	1088	8165906051010	Microsoft
Headset #1	ES-303	-	inkel
Headset #2	SHS-250V	-	SAMSUNG
Controller	WTX-1300		Wonwoo
JIG	-	-	-
SD Card(2GB)	-	-	-
AC/AC Adaptor (AC 24 V)	DLA24300SKA	-	Dream Electronics
PoE Switch	-	-	-


4.4 Test configuration

#1- AC 24V



Note *	Start		End		Cable	
	Name	I/O port	Name	I/O port	Length (m)	Spec.
1	EUT (Network Camera)	Power	AC/AC Adaptor	Power	1.6	Non-Shield
2		LAN(RJ-45)	Note PC	LAN(RJ-45)	3.0	Non-Shield
3		RS-485	Controller	RS-485	3.0	Non-Shield
4		Alarm	JIG	Alarm	3.0	Non-Shield
5		Audio In/Out	Headset #1	Audio In/Out	3.0	Non-Shield
6		GND	GND	GND	2.0	Non-Shield
7		SD Card	SD Card	SD Card	Direct	-
8	Note PC	USB	USB Mouse	USB	1.8	Shield
9		MIC/SPK	Headset #2	MIC/SPK	2.0	Non-Shield

#2- PoE



* Power supplied from PoE Switch

Note *	Start		End		Cable	
	Name	I/O port	Name	I/O port	Length (m)	Spec.
1	EUT (Network Camera)	LAN(PoE)	PoE Switch	LAN(PoE)	3.0	Non-Shield
2		RS-485	Controller	RS-485	3.0	Non-Shield
3		Alarm	JIG	Alarm	3.0	Non-Shield
4		Audio In/Out	Headset #1	Audio In/Out	3.0	Non-Shield
5		GND	GND	GND	2.0	Non-Shield
6		SD Card	SD Card	SD Card	Direct	-
7	Note PC	LAN(RJ-45)	PoE Switch	LAN(RJ-45)	3.0	Non-Shield
8		USB	USB Mouse	USB	1.8	Shield
9		MIC/SPK	Headset #2	MIC/SPK	2.0	Non-Shield

4.5 Operating conditions

The EUT was configured as normal intended use.

Test mode	Normal operating
1	Web Viewer Monitoring Test.
	Ping Test.
	Audio In/Out Test.
	Alarm Test.
	Control Test.
	SD Card recording Test.

* Note: 2 types of powers are available for the product, that are AC 24 V, PoE.

Therefore, tests were performed for 2 different types of powers.

5. Summary of test results

In the above configuration tested, The EUT complied with the requirement of the specification

5.1 Summary of EMI emission test results

FCC Part 15 Subpart B (Class A)

ANSI C63.4 – 2009

Applied	Test items	Test method	Result
☐	Conducted Emission	ANSI C63.4 – 2009	N/A
☒	Radiated Emission	ANSI C63.4 – 2009	Complied

6. Test results

6.1 Radiated Emission

Test specification	FCC Part 15, Section 15.109(g), Class A		
Testing voltage	AC 24 V, PoE		
Test facility	10 m Chamber (#F2, #F4)		
Test distance	10 m, 3 m		
Date	2014. 10. 17 ~ 10. 20		
Temperature (°C)	20.1~ 21.7 °C	Humidity (% R.H.)	30.7 ~ 50.0 % R.H.
Software Program	EP5/RE Ver 4.6.0(Toyo)		
Remarks	Complied		

6.1.1 Limits of radiated emission measurement

Frequency [MHz]	Class A (dB(μ V/m)) @ 10 m	Class B (dB(μ V/m)) @ 3 m
30-88	39	40
88-216	43.5	43.5
216-960	46.4	46
Above 960	49.5	54

* Note- Alternative standard: CISPR, Pub. 22 *

6.1.2 Measurement procedure

The test was done at a 10 m chamber with a quasi-peak detector. EUT was placed on a non-metallic table height of 0.8 m above the reference ground plane. Cables were folded back and forth forming a bundle 0.3 m to 0.4 m long and were hanged at a 0.4 m height to the ground plane.

Cables connected to EUT were fixed to cause maximum emission. Test was made with the antenna positioned in both the horizontal and vertical planes of polarization. The measurement antenna was varied in height above the conducting ground plane to obtain the maximum signal strength.

6.1.3 Used equipments

* 30 MHz ~ 1 GHz

Equipment	Model no.	Serial no.	Makers	Next Cal. Date	Used
Test Receiver	ESR	101078	R&S	2015.02.24	☒
Bi-Log Antenna	VULB 9168	440	SCHWARZBECK	2016.08.28	☒
Amplifier	310N	284608	SONOMA INSTRUMENT	2015.04.16	☒
3 dB Attenuator	8491B	22981	HP	2015.03.04	☒
Antenna Mast	MA4000-EP	303	Innco Systems	-	☒
Turn Table	DT2000S-1t	079	Innco Systems	-	☒

* 1 GHz ~ 6 GHz

Equipment	Model no.	Serial no.	Makers	Next Cal. Date	Used
Test Receiver	ESCI7	100732	R&S	2015.01.27	☒
Antenna Mast	AM4.0	079/3440509	MATURO	-	☒
Turn Table	CO2000-SOFT	-	MATURO	-	☒
Preamplifier	8449B	3008A01802	AGILENT	2015.08.05	☒
Horn ANT	3115	00086706	ETS	2015.09.01	☒

6.1.4 Sample calculation

The field strength is calculated adding the antenna Factor, cable loss and, Antenna pad adding, subtracting the amplifier gain from the measured reading.

The sample calculation is as follow:

$$\text{Result} = \text{M.R} + \text{C.F}(\text{A.F} + \text{C.L} + 3 \text{ dB Att} - \text{A.G})$$

M.R = Meter Reading

C.F = Correction Factor

A.F = Antenna Factor

C.L = Cable Loss

A.G= Amplifier Gain


3 dB Att = 3 dB Attenuator

If M.R is 30 dB, A.F 12 dB, C.L 5 dB, 3 dB, A.G 35 dB



The result is $30 + 12 + 5 + 3 - 35 = 15 \text{ dB}(\mu\text{V/m})$

6.1.5 Photographs of test setup


* 30 MHz ~ 1 GHz (#1- AC 24V)




* 1 GHz ~ 6 GHz (#1- AC 24V)



* 30 MHz ~ 1 GHz (#2-PoE)




* 1 GHz ~ 6 GHz (#2-PoE)



6.1.6 Radiated emission measurement result

* Graph and Data


* 30 MHz ~ 1 GHz (SNP-6321HN)_#1- AC 24V



Final Result

No.	Frequency [MHz]	(P)	Reading QP [dB(μV)]	c.f [dB(1/m)]	Result QP [dB(μV/m)]	Limit QP [dB(μV/m)]	Margin QP [dB]	Height [cm]	Angle [deg]
1	70.740	V	46.2	-14.7	31.5	39.0	7.5	100.0	32.4
2	88.564	H	48.0	-18.2	29.8	43.5	13.7	400.0	79.2
3	107.115	V	49.3	-15.9	33.4	43.5	10.1	100.0	290.2
4	165.558	V	45.8	-12.0	33.8	43.5	9.7	100.0	171.2
5	528.095	H	37.4	-3.4	34.0	46.5	12.5	100.0	140.6
6	816.064	H	35.8	2.7	38.5	46.5	8.0	100.0	259.6
7	944.104	H	33.8	5.3	39.1	46.5	7.4	100.0	136.0
8	976.114	H	32.9	5.9	38.8	49.5	10.7	100.0	143.6


* 1 GHz ~ 6 GHz (SNP-6321HN)_#1- AC 24V



Final Result

No.	Frequency [MHz]	(P)	Reading AV [dB(uV)]	Reading PK [dB(uV)]	c.f [dB(i/m)]	Result AV [dB(uV/m)]	Result PK [dB(uV/m)]	Limit AV [dB(uV/m)]	Limit PK [dB(uV/m)]	Margin AV [dB]	Margin PK [dB]	Height [cm]	Angle [deg]	Remark
1	1000.625	V	43.5	51.6	-10.7	32.8	40.9	60.0	80.0	27.2	39.1	100.0	190.5	
2	1071.875	V	41.7	50.8	-10.4	31.3	40.4	60.0	80.0	28.7	39.6	100.0	186.7	
3	1103.750	V	38.9	51.2	-10.2	28.7	41.0	60.0	80.0	31.3	39.0	100.0	226.3	
4	1135.625	H	38.3	48.7	-10.0	28.3	38.7	60.0	80.0	31.7	41.3	100.0	208.1	
5	1669.375	V	35.6	42.5	-5.7	29.9	36.8	60.0	80.0	30.1	43.2	100.0	165.5	
6	2001.250	H	33.2	44.1	-3.0	30.2	41.1	60.0	80.0	29.8	38.9	100.0	168.0	


* 30 MHz ~ 1 GHz (SNP-6321HN)_#2- PoE



Final Result

No.	Frequency [MHz]	(P)	Reading QP [dB(μV)]	c.f [dB(1/m)]	Result QP [dB(μV/m)]	Limit QP [dB(μV/m)]	Margin QP [dB]	Height [cm]	Angle [deg]
1	46.369	V	43.7	-13.2	30.5	39.0	8.5	100.0	315.1
2	65.648	V	39.7	-13.9	25.8	39.0	13.2	100.0	39.1
3	93.293	V	51.2	-18.0	33.2	43.5	10.3	100.0	155.2
4	173.924	H	39.2	-12.6	26.6	43.5	16.9	400.0	165.7
5	199.993	H	42.1	-14.6	27.5	43.5	16.0	400.0	238.1
6	527.974	H	38.0	-3.4	34.6	46.5	11.9	100.0	338.9
7	816.064	H	35.4	2.7	38.1	46.5	8.4	100.0	213.8
8	976.114	H	33.3	5.9	39.2	49.5	10.3	100.0	141.4

* 1 GHz ~ 6 GHz (SNP-6321HN)_#2- PoE



Final Result

No.	Frequency [MHz]	(P)	Reading AV [dB(uV)]	Reading PK [dB(uV)]	c.f [dB(1/m)]	Result AV [dB(uV/m)]	Result PK [dB(uV/m)]	Limit AV [dB(uV/m)]	Limit PK [dB(uV/m)]	Margin AV [dB]	Margin PK [dB]	Height [cm]	Angle [deg]	Remark
1	1000.000	H	45.4	55.7	-10.7	34.7	45.0	60.0	80.0	25.3	35.0	100.0	349.4	
2	1072.500	H	43.2	50.6	-10.4	32.8	40.2	60.0	80.0	27.2	39.8	100.0	337.3	
3	1104.375	V	39.5	48.1	-10.2	29.3	37.9	60.0	80.0	30.7	42.1	100.0	11.3	
4	1135.625	V	37.6	47.4	-10.0	27.6	37.4	60.0	80.0	32.4	42.6	100.0	11.3	
5	1663.125	V	35.8	43.3	-5.8	30.0	37.5	60.0	80.0	30.0	42.5	100.0	342.9	
6	1999.375	H	34.1	46.2	-3.0	31.1	43.2	60.0	80.0	28.9	36.8	100.0	324.4	

7. E.U.T. photographs

Front View



Rear View



Left View



Right View



Top View



Bottom View



Label





FCC Label Location

This device complies with part 15 of the FCC Rules. Operation is subject to the following two conditions:
(1) This device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.


Inside





Main Board





CCD Board





SUB Board #1



SUB Board #2



Interface Board



Drive Board

