

TESTING CERTIFICATE

EMC Compliance Ltd.

65, Sinwon-ro, Yeongtong-gu,
Suwon-si, Gyeonggi-do,
443-390, Korea
TEL: 82 70 5008 1021
FAX: 82 505 299 8311

Certificate No.: EMC-K-E0188

Page(1) / (38) Pages



1. Applicant

Name: Samsung Techwin Co., Ltd.
Address: 84, Jeongdong-ro, Seongsan-gu, Changwon-si,
Gyeongsangnam-do, Korea
Date of Receipt: December 12, 2014

2. Manufacturer

Name#1: Samsung Techwin Co., Ltd.
Name#2: TIANJIN SAMSUNG TECHWIN
OPTO-ELECTRONIC CO., LTD

3. Use of Report:

Completed report

4. Test Sample:

Network Camera, SNP-6320RHP

5. Date of Test:

December 15 ~ 26, 2014

6. Test method used:

AS/NZS CISPR 22:2009+A1:2010, Class A

7. Testing Environment:


Temperature: (23.2 ± 2.3) °C,
Relative Humidity: (17.75 ± 4.55) % R.H.

8. Test Results:

Refer to page 13 ~ page 23
(Measurement uncertainty: Refer to page 6)

This result shown in this report refer only to the sample(s) tested unless otherwise stated.

This Test Report cannot be reproduced, except in full, without the written approval of
EMC Compliance Laboratory.

Affirmation	Tested by  Name: JUNG, YONG-JUN	Technical Manager  Name: YEOM, HAN-SEOK
-------------	--	--

The above test certificate is the accredited test results by Korea Laboratory Accreditation Scheme, which signed the ILAC-MRA.

2014. 12. 29

EMC Compliance Ltd.

Accredited by KOLAS, Republic of KOREA



Contents

1. Applicant information	3
2. Laboratory information	4
3. Test system configuration.....	5
3.1 Operation environment	5
3.2 Measurement Uncertainty.....	6
4. Description of E.U.T.	7
4.1 General information.....	7
4.2 Product description	9
4.3 Auxiliary equipments.....	9
4.4 Test configuration	10
4.5 Operating conditions.....	11
5. Summary of test results	12
5.1 Summary of EMI emission test results	12
6. Test results	13
6.1 Conducted Emission	13
6.2 Radiated Emission	18
7. E.U.T. photographs.....	24

1. Applicant information

Applicant: Samsung Techwin Co., Ltd.
Address: 84, Jeongdong-ro, Seongsan-gu, Changwon-si,
Gyeongsangnam-do, Korea
Telephone: +82-70-7147-8361
Fax: +82-31-277-2784
E-mail: js2002.kang@samsung.com
Contact name: **Kang Jei Soon**

Manufacturer#1: Samsung Techwin Co., Ltd.
Address: 84, Jeongdong-ro, Seongsan-gu, Changwon-si,
Gyeongsangnam-do, Korea
Telephone: +82-70-7147-8361
Fax: +82-31-277-2784
E-mail: js2002.kang@samsung.com
Contact name: **Kang Jei Soon**

Manufacturer#2: TIANJIN SAMSUNG TECHWIN OPTO-ELECTRONIC CO., LTD
Address: No.11 Weiliu Road. Micro-Electronic Industrial Park
Jingang Road Tianjin 300385, China

2. Laboratory information

Address

EMC compliance Ltd.

65, Sinwon-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 443-390, Korea

Telephone Number: 82 70 5008 1021

Facsimile Number: 82 505 299 8311


FCC Site Designation No: KR0040, FCC Site Registration No: 687132

VCCI Registration No. : R-3327, G-198, C-3706, T-1849

Industry Canada Registration No.: 8035A

KOLAS NO.: 231

SITE MAP



3. Test system configuration

3.1 Operation environment

	Temperature	Humidity	Pressure
Chamber(10 m)	: 25.5 °C	13.2 % R.H.	-
Shielded room(CE)	: 20.9 °C	22.3 % R.H.	-

Test site

These testing items were performed following locations;

Test item	Test site
Conducted Emission	Shielded Room
Radiated Emission	10 m Chamber

3.2 Measurement Uncertainty

All measurements involve certain levels of uncertainties, especially in field of EMC.

The factors contributing to uncertainties are test receiver, cable loss, antenna factor calibration, Antenna directivity, antenna factor variation with height, antenna phase center variation, antenna frequency interpolation, measurement distance variation, site imperfection, mismatch, and system repeatability. Based on CISPR 16-4-2, the measurement uncertainty level with a 95 % confidence level was applied.

Conducted emission measurement (C.L: Approx 95 %, k = 2)		
Shielded Room (CE#1)	9 kHz ~ 150 kHz	± 3.75 dB
	150 kHz ~ 30 MHz	± 3.36 dB
Shielded Room (CE#2)	9 kHz ~ 150 kHz	± 3.79 dB
	150 kHz ~ 30 MHz	± 3.42 dB
Radiated Emission measurement (C.L: Approx 95 %, k = 2)		
10 m Chamber (#F4)	30 MHz ~ 300 MHz	3 m: + 4.87 dB, - 4.99 dB 10 m: + 4.86 dB, - 4.98 dB
	300 MHz ~ 1 000 MHz	3 m: + 5.04 dB, - 5.14 dB 10 m: + 4.91 dB, - 5.02 dB
	1 GHz ~ 6 GHz	3 m: + 6.03 dB, - 6.06 dB
10 m Chamber (#F2)	30 MHz ~ 300 MHz	3 m: + 4.94 dB, - 5.06 dB 10 m: + 4.93 dB, - 5.05 dB
	300 MHz ~ 1 000 MHz	3 m: + 4.97 dB, - 5.08 dB 10 m: + 4.84 dB, - 4.96 dB
	1 GHz ~ 6 GHz	3 m: + 6.03 dB, - 6.05 dB
Radio Frequency Electromagnetic Fields (C.L: Approx 95 %, k = 2)		
± 1.82 dB		
Disturbance power Electromagnetic Fields (C.L: Approx 95 %, k = 2)		
± 3.30 dB		

4. Description of E.U.T.

4.1 General information

Video	
Imaging Device	1/2.9" 2M CMOS
Total Pixels	1952(H) x 1116(V), 2.18M
Effective Pixels	1944(H) x 1104(V), 2.14M
Scanning System	Progressive Scan
Min. Illumination	Color : 0.3 Lux/F1.6(1/30sec, F1.6, 50IRE), 0.005Lux(2sec, F1.6, 50IRE) Color : 0.1 Lux/F1.6(1/30sec, F1.6, 30IRE), 0.0005Lux(2sec, F1.6, 30IRE) 0 Lux (IR LED On)
S / N Ratio	50dB
Video Out	CVBS : 1.0 Vp-p / 75Ω composite, 720x480(N), 720x576(P), for installation
Lens	
Focal Length (Zoom Ratio)	32x(4.4 ~ 140.8 mm)
Max. Aperture Ratio	F1.6 (Wide) ~ F 4.9 (Tele)
Angular Field of View	H : 63.68°(Wide) ~ 2.24°(Tele) / V : 37.52°(Wide) ~ 1.28°(Tele)
Min. Object Distance	1.5m (3.28ft)
Focus Control	AF / One-Shot AF / Manual
Lens Type	DC Auto Iris
Mount Type	Board-in type
Pan / Tilt / Rotate	
Pan Range	360° Endless
Pan Speed	Preset : 250°/sec , Manual : 0.024°/sec ~120°/sec
Tilt Range	190°(-5° ~185°)
Tilt Speed	Preset : 250°/sec , Manual : 0.024°/sec ~120°/sec
Rotate Range	-
Sequence	Preset (255 ea), Swing, Group (6 ea), Trace, Tour, Auto Run, Schedule
Preset Accuracy	±0.2°
Azimuth	Yes (East/West/South/North OSD)
Auto Tracking	Off / On
Operational	
IR LED	2ea
Viewable Length	150m
Camera Title	Off / On (Displayed up to 15 characters)
Day & Night	Auto (ICR) / Color / B/W
Backlight Compensation	Off / BLC / WDR / HLC
Wide Dynamic Range	120dB
Contrast Enhancement	SSDR (Samsung Super Dynamic Range) (Off / On)
Digital Noise Reduction	SSNR(2D+3D Noise Filter) (Off / On)
Digital Image Stabilization	Off / On
Defog	Auto/Manual/Off
Motion Detection	Yes(4ea, Rectangular zones)
Privacy Masking	Off / On (32ea, Rectangular zones) - Color : Grey/Green/Red/Blue/Black/White - Zoom ratio option for mask mode
Gain Control	Off / Low / Medium / High / Manual
White Balance	ATW / AWC / Manual / Indoor / Outdoor / Mercury / Sodium
Electronic Shutter Speed	Minimum / Maximum / Anti flicker (2 ~ 1/12,000sec)
Digital Zoom	16x , area zoom function support digital zoom 2x
Flip / Mirror	Off / On
Intelligent Video Analytics	Tampering(Scene Change), Virtual Line, Enter/Exit, Appear / Disappear, Audio Detection, Face Detection(5ea)
Alarm I/O	Input 4ea / Output 3ea (Relay type)
Remote Control Interface	RS-485/422
RS-485 Protocol	Samsung-T/E, Pelco-D/P, Panasonic, Honeywell, AD, Vicon, GE, BOSCH
Alarm Triggers	Alarm Input, Motion Detection, Intelligent Video Analytics, Network Disconnect
Alarm events	• File upload via FTP, E-Mail • Notification via E-Mail, TCP • local storage(SD/SDHC) or NAS recording at Network disconnected • External output • PTZ preset
Audio In	Selectable (Mic IN/Line IN), Supply voltage: 2.5VDC(4mA), Input impedance: approx. 2K Ohm
Audio out	Line out (3.5mm stereo mini jack), Max output level: 1 Vrms

Network	
Ethernet	RJ-45 (10/100BASE-T)
Video Compression Format	H.264 (MPEG-4 Part 10/AVC) : Main/Baseline/High , Motion JPEG
Resolution	1920x1080, 1280x1024, 1280x960, 1280x720, 1024x768, 800x600, 720x576, 640x480, 640x360, 320x240, 320x180
Max. Framerate	H.264 : Max. 60fps at all resolutions Motion JPEG : 1920x1080, 1280x1024, 1280x960, 1280x720, 1024x768 : 최대 15 fps 800x600, 720x576, 640x480, 640x360, 320x240, 320x180 : 최대 30fps
Smart Codec	Manual Mode (area-based : 5EA) Face detection Mode
Video Quality Adjustment	H.264 : Compression Level, Target Bitrate Level Control MJPEG : Quality Level Control
Bitrate Control Method	H.264 : CBR or VBR, Motion JPEG : VBR
Streaming Capability	Multiple Streaming (Up to 10 Profiles)
Audio Compression Format	G.711 u-law / G.726 Selectable G.726 (ADPCM) 8KHz, G.711 8KHz G.726 : 16Kbps, 24Kbps, 32Kbps, 40Kbps
Audio Communication	Bi-directional (2-Way)
IP	IPv4, IPv6
Protocol	TCP/IP, UDP/IP, RTP(UDP), RTP(TCP), RTCP, RTSP, NTP, HTTP, HTTPS, SSL, DHCP, PPPoE, FTP, SMTP, ICMP, IGMP, SNMPv1/v2c/v3(MIB-2), ARP, DNS, DDNS, QoS, PIM-SM, UPnP, Bonjour
Security	HTTPS(SSL) Login Authentication Digest Login Authentication IP Address Filtering User access Log 802.1X Authentication (EAP-TLS, EAP-LEAP)
Streaming Method	Unicast / Multicast
Max. User Access	15 users at Unicast Mode
Edge Storage	SD/SDHC/SDXC(up to 128G) - motion Images recorded in the SD/SDHC/SDXC memory card can be downloaded. NAS(Network Attached Storage) Local PC for Instant Recording
Application Programming Interface	ONVIF Profile S SUNAPI(HTTP API) SVNP 1.2 Samsung Camera Application Platform
Webpage Language	English, Korean, Chinese, French, Italian, Spanish, German, Japanese, Russian, Swedish, Danish, Portuguese, Czech, Polish, Turkish, Rumanian, Serbian, Dutch, Croatia, Hungary, Greek, Norsk, Finnish
Web Viewer	Supported OS : Windows XP / VISTA / 7 / 8, MAC OS X 10.7 Supported Browser : Microsoft Internet Explorer (Ver.8~11), Mozilla Firefox (Ver. 9~19), Google Chrome (Ver. 15~25), Apple Safari (Ver. 6.0.2(Mac OS X 10.8, 10.7 Only), 5.1.7) * Mac OS X Only
Central Management Software	SmartViewer, SSM
Environmental	
Operating Temperature /	-50°C ~ +55°C (-58°F ~ +131°F) / Less than 90% RH
Storage Temperature / Humidity	-60°C ~ +60°C (-22°F ~ +140°F) / Less than 90% RH
Ingress Protection	IP66
Vandal Resistance	IK10
Electrical	
Input Voltage / Current	24V AC
Power Consumption	Max. 30W(Heater Off) / 35W(Heater Off, IR ON), 90W(Heater On, IR ON)
Mechanical	
Color / Material	Ivory/Aluminum
Dimension (WxHxD)	H399.5mm x Ø248 (Ø9.76" x 15.73")
Weight	7.1Kg


4.2 Product description

Type of product	Network Camera
Model name (Basic)	SNP-6320RHP
Model name (Variant)	SNP-L6233RHP
Difference	Buyer model name.
Trade name	-
Serial no	-
Testing voltage	AC 24 V
Product rating	AC 24 V
Internal clock frequency	Above 108 MHz
Note	* AC/AC adaptor was not provided by the manufacturer.

4.3 Auxiliary equipments

Type	Model / Part #	Serial number	Manufacturer
Note PC	NT271B5E	JGFE91DF600046D	SAMSUNG
USB Mouse	SMH-214UB	M2UBTAKQ335310R	SAMSUNG
Headset #1	SHS-250V	-	SAMSUNG
Headset #2	SHS-250V	-	SAMSUNG
JIG	-	-	-
SD Card (2GB)	-	-	-
AC/AC Adaptor	DRL-246000AC	-	Dream Electronic

4.4 Test configuration



Note *	Start		End		Cable	
	Name	I/O port	Name	I/O port	Length (m)	Spec.
1	EUT (Network Camera)	Power	AC/AC Adaptor	Power	1.2	Non-Shield
2		SD Card	SD Card	SD Card	Direct	-
3		LAN(RJ-45)	Note PC	LAN(RJ-45)	3.0	Non-Shield
4		GND	GND	GND	2.0	Non-Shield
5		Alarm In/Out	JIG	Alarm In/Out	3.0	Non-Shield
6		Audio In/Out	Headset #1	Audio In/Out	3.0	Non-Shield
7	Note PC	USB	USB Mouse	USB	1.8	Shield
8		MIC/SPK	Headset #2	MIC/SPK	2.0	Non-Shield

4.5 Operating conditions

The EUT was configured as normal intended use.

Test mode	Normal operating
1	Web viewer monitoring test
	Ping test.
	Alarm In/Out test.
	Audio In/Out test.
	Recording test.

5. Summary of test results

5.1 Summary of EMI emission test results

Applied	Test items	Test method	Result
☒	Conducted Emission	AS/NZS CISPR 22:2009+A1:2010, Class A	13 Page ~ 17 Page
☒	Radiated Emission	AS/NZS CISPR 22:2009+A1:2010, Class A	18 Page ~ 23 Page

6. Test results

6.1 Conducted Emission

Test specification	AS/NZS CISPR 22:2009+A1:2010, Class A		
Testing voltage	AC 24 V		
Test facility	Shielded room (CE#1)		
Date	2014. 12. 15		
Temperature (°C)	20.9 °C	Humidity (% R.H.)	22.3 % R.H.
Remarks	Complied		

6.1.1 Limits of conducted emission measurement

☐ AC main

Frequency MHz	Class A dB μ V		Class B dB μ V	
	Quasi-peak	Average	Quasi-peak	Average
0.15 ~ 0.5	79	66	66 ~ 56 *	56 ~ 46*
0.5 ~ 5	73	60	56	46
5 ~ 30	73	60	60	50

*The limit decreases linearly with the logarithm of frequency.

☒ Telecommunication

Frequency MHz	Class A Voltage Limits dB μ V		Current Limits dB μ A	
	Quasi-Peak	Average	Quasi-Peak	Average
0.15 ~ 0.5	97 to 87	84 to 74	53 to 43	40 to 30
0.5 ~ 30	87	74	43	30
Frequency MHz	Class B Limits dB μ V		Current Limits dB μ A	
	Quasi-Peak	Average	Quasi-Peak	Average
0.15 ~ 0.5	84 to 74	74 to 64	40 to 30	30 to 20
0.5 ~ 30	74	64	30	20

* The limits decrease linearly with the logarithm of the frequency in the range 0.15 MHz to 0.5 MHz

* The current and voltage disturbance limits are derived for use with an impedance stabilization Network (ISN) which presents a common mode (asymmetric mode) impedance of 150 Ω to the telecommunication port under test (conversion factor is $20 \log_{10} 150/I = 44$ dB).

6.1.2 Measurement procedure

The measurements were performed in a shielded room. EUT was setup as shown in photograph and placed on a non-metallic table height of 0.8 m above the reference ground plane. The rear of table was located 0.4 m to the vertical conducted plane. EUT was power through the LISN, which was bonded to the ground plane. The LISN power was filtered. Each EUT power lead, except ground (safety) lead was individually connected through a LISN to input power source. EUT signal cables that hung closer than 0.4 m to the Horizontal metal ground 0.3 m ~ 0.4 m long. The power cord was bundles in the center. All peripheral equipment was powered from a sub LISN. The LISN and ISN were positioned 0.8 m from the EUT. Peak and Average detection were used in preliminary testing and Quasi-peak and Average detections were used at final measurement. Both lines of power cord, hot and neutral, were measured.

6.1.3 Used equipments

Equipment	Model	Serial No.	Makers	Next Cal. Date	Used
Test Receiver	ESCI7	100732	R&S	2015.01.27	☐
Test Receiver	ESCI	100001	R&S	2015.07.14	☒
Test Receiver	ESCI	100710	R&S	2015.10.13	☐
TWO-LINE V-NETWORK	ENV216	101358	R&S	2015.10.02	☒
TWO-LINE V-NETWORK	ESH3-Z5	100267	R&S	2015.06.24	☒
8-WIRE ISN	NTFM 8158 CAT5	CAT5-8158-0028	SCHWARZBECK	2015.03.07	☒
8-WIRE ISN	NTFM 8158 CAT3	CAT3-8158-0020	SCHWARZBECK	2015.03.07	☐

6.1.4 Photographs of test setup


* Telecommunication



6.1.5 Conducted emission measurement result

* Telecommunication port


LCL 65 dB (LAN Port)_10 Mbps (SNP-6320RHP)



Final Result

--- ISN-CAT5 Phase ---											
No.	Frequency	Reading	Reading	c.f	Result	Result	Limit	Limit	Margin	Margin	
	[MHz]	QP	CAV		QP	CAV	QP	AV	QP	CAV	
		[dB(uV)]	[dB(uV)]	[dB]	[dB(uV)]	[dB(uV)]	[dB(uV)]	[dB(uV)]	[dB]	[dB]	
1	3.14934	31.0	27.2	9.4	40.4	36.6	87.0	74.0	46.6	37.4	
2	6.24974	41.1	29.4	9.4	50.5	38.8	87.0	74.0	36.5	35.2	
3	6.3035	38.9	30.7	9.4	48.3	40.1	87.0	74.0	38.7	33.9	
4	7.49938	43.5	33.8	9.4	52.9	43.2	87.0	74.0	34.1	30.8	
5	9.99899	47.6	34.2	9.4	57.0	43.6	87.0	74.0	30.0	30.4	
6	10.70614	25.9	19.0	9.4	35.3	28.4	87.0	74.0	51.7	45.6	
7	14.21873	27.6	21.8	9.5	37.1	31.3	87.0	74.0	49.9	42.7	
8	19.9969	49.4	35.6	9.5	58.9	45.1	87.0	74.0	28.1	28.9	

LCL 65 dB (LAN Port)_100 Mbps (SNP-6320RHP)



Final Result

--- ISN-CAT5 Phase ---										
No.	Frequency [MHz]	Reading QP [dB(uV)]	Reading CAV [dB(uV)]	c.f [dB]	Result QP [dB(uV)]	Result CAV [dB(uV)]	Limit QP [dB(uV)]	Limit AV [dB(uV)]	Margin QP [dB]	Margin CAV [dB]
1	1.26702	34.9	31.7	9.4	44.3	41.1	87.0	74.0	42.7	32.9
2	5.23526	36.9	32.9	9.4	46.3	42.3	87.0	74.0	40.7	31.7
3	6.70104	34.0	30.7	9.4	43.4	40.1	87.0	74.0	43.6	33.9
4	16.22777	46.7	43.6	9.5	56.2	53.1	87.0	74.0	30.8	20.9
5	18.2429	48.4	45.7	9.5	57.9	55.2	87.0	74.0	29.1	18.8
6	20.25824	47.5	45.1	9.5	57.0	54.6	87.0	74.0	30.0	19.4
7	23.12832	49.9	47.8	9.6	59.5	57.4	87.0	74.0	27.5	16.6
8	26.60928	47.1	45.5	9.6	56.7	55.1	87.0	74.0	30.3	18.9

6.2 Radiated Emission

Test specification	AS/NZS CISPR 22:2009+A1:2010, Class A		
Testing voltage	AC 24 V		
Test facility	10 m Chamber (#F2)		
Test distance	10 m, 3 m		
Date	2014. 12. 26		
Temperature (°C)	25.5 °C	Humidity (% R.H.)	13.2 % R.H.
Remarks	Complied		

6.2.1 Limits of radiated emission measurement

☒ Limits below 1 GHz

Frequency MHz	Class A dB μ V/m @ 10 m	Class B dB μ V/m @ 10 m
30 ~ 230	40	30
230 ~ 1 000	47	37

☒ Limits above 1 GHz

Frequency MHz	Class A @ 3 m		Class B @ 3 m	
	Average limit dB μ V/m	Peak limit dB μ V/m	Average limit dB μ V/m	Peak limit dB μ V/m
1 ~ 3	56	76	50	70
3 ~ 6	60	80	54	74

Note - The lower limit applies at the transition frequency.

6.2.2 Measurement procedure

The test was done at a 10 m chamber with a quasi-peak detector. EUT was placed on a non-metallic table height of 0.8 m above the reference ground plane. Cables were folded back and forth forming a bundle 0.3 m to 0.4 m long and were hanged at a 0.4 m height to the ground plane.

Cables connected to EUT were fixed to cause maximum emission. Test was made with the antenna positioned in both the horizontal and vertical planes of polarization. The measurement antenna was varied in height above the conducting ground plane to obtain the maximum signal strength.

6.2.3 Used equipments

Equipment	Model no.	Serial no.	Makers	Next Cal. Date	Used
Test Receiver	ESCI7	100732	R&S	2015.01.27	☒
Test Receiver	ESCI	100001	R&S	2015.07.14	☐
Test Receiver	ESCI	100710	R&S	2015.10.13	☐
Test Receiver	ESR	101078	R&S	2015.02.24	☐
Bi-Log Antenna	VULB 9168	440	SCHWARZBECK	2016.08.28	☒
Amplifier	310N	284608	SONOMA INSTRUMENT	2015.04.16	☒
3 dB Attenuator	8491B	22981	HP	2015.03.04	☒
Antenna Mast	MA4000-EP	303	Innco Systems	-	☒
Turn Table	DT2000S-1t	079	Innco Systems	-	☒
Preamplifier	8449B	3008A02343	AGILENT	2015.10.13	☒
Horn ANT	3115	00155772	ETS	2015.02.26	☒
Spectrum Analyzer	E4407B	US39010142	AGILENT	2015.10.13	☐

6.2.4 Sample calculation

The field strength is calculated adding the antenna Factor, cable loss and, Antenna pad adding, subtracting the amplifier gain from the measured reading.

The sample calculation is as follow:

$$\text{Result} = \text{M.R} + \text{C.F}(\text{A.F} + \text{C.L} + 3 \text{ dB Att} - \text{A.G})$$

M.R = Meter Reading

C.F = Correction Factor

A.F = Antenna Factor

C.L = Cable Loss

A.G= Amplifier Gain

3 dB Att = 3 dB Attenuator


If M.R is 30 dB, A.F 12 dB, C.L 5 dB, 3 dB, A.G 35 dB

The result is



$$30 + 12 + 5 + 3 - 35 = 15 \text{ dB}\mu\text{V/m}$$

6.2.5 Photographs of test setup

* 30 MHz ~ 1 GHz




* 1 GHz ~ 6 GHz



6.2.6 Radiated emission measurement result

* Graph and Data


* 30 MHz ~ 1 GHz (SNP-6320RHP)



Final Result

No.	Frequency [MHz]	(P)	Reading QP [dB(μV)]	c.f [dB(1/m)]	Result QP [dB(μV/m)]	Limit QP [dB(μV/m)]	Margin QP [dB]	Height [cm]	Angle [deg]
1	33.031	V	48.8	-14.4	34.4	40.0	5.6	100.0	40.9
2	49.885	V	40.5	-12.9	27.6	40.0	12.4	100.0	101.2
3	149.916	H	39.4	-11.9	27.5	40.0	12.5	400.0	224.0
4	175.015	H	40.1	-12.5	27.6	40.0	12.4	400.0	248.1
5	274.925	V	54.7	-10.9	43.8	47.0	3.2	100.0	14.4
6	296.993	H	55.2	-10.1	45.1	47.0	1.9	400.0	245.0
7	325.001	V	46.5	-9.2	37.3	47.0	9.7	100.0	12.7
8	594.055	H	38.8	-1.2	37.6	47.0	9.4	100.0	299.3

* 1 GHz ~ 6 GHz (SNP-6320RHP)



Final Result

No.	Frequency [MHz]	(P)	Reading AV [dB(μV)]	Reading PK [dB(μV)]	c.f [dB(1/m)]	Result AV [dB(μV/m)]	Result PK [dB(μV/m)]	Limit AV [dB(μV/m)]	Limit PK [dB(μV/m)]	Margin AV [dB]	Margin PK [dB]	Height [cm]	Angle [deg]
1	1113.125	H	34.4	45.5	-5.4	29.0	40.1	56.0	76.0	27.0	35.9	100.0	46.3
2	1708.750	V	31.0	38.7	0.1	31.1	38.8	56.0	76.0	24.9	37.2	100.0	167.7
3	2301.875	H	33.9	41.2	1.9	35.8	43.1	56.0	76.0	20.2	32.9	100.0	348.2
4	2376.250	H	34.3	41.0	1.9	36.2	42.9	56.0	76.0	19.8	33.1	100.0	4.3
5	2450.000	V	31.1	40.8	2.0	33.1	42.8	56.0	76.0	22.9	33.2	100.0	351.1
6	2991.875	H	30.8	40.0	3.8	34.6	43.8	56.0	76.0	21.4	32.2	100.0	190.6

7. E.U.T. photographs

Front View



Rear View



Left View



Right View




Top View




Bottom View




Inside





Module Main Board



SUB Board #1



SUB Board #2




CCD Board





Interface Board





Motion Board





Terminal Board




Tilt Sensor Board



SD Card Board



IR Board



Power Board

