

TESTING CERTIFICATE

EMC Compliance Ltd. 65, Sinwon-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 443-390, Korea TEL: 82 31 336 9919 FAX: 82 505 299 8311	Certificate No.: EMC-CE-4514 Page(1) / (28) Pages	 
--	--	---

1. Applicant

Name: Samsung Techwin Co., Ltd.
 Address: 84, Jeongdong-ro, Seongsan-gu,
 Changwon-si, Gyeongsangnam-do, Korea
 Date of Receipt: December 19, 2013

2. Manufacturer

Name#1: Samsung Techwin Co., Ltd.
 Name#2: TIANJIN SAMSUNG TECHWIN
 OPTO-ELECTRONIC CO., LTD

3. Use of Report:

Completed report

4. Test Sample:

Network Camera, SNV-6013P

5. Date of Test:

January 09, 2014

6. Test method used:

AS/NZS CISPR 22:2009+A1:2010, Class A



7. Testing Environment:

Temperature: $(19.9 \pm 2.1) ^\circ\text{C}$,
 Relative Humidity: $(27.3 \pm 3.9) \% \text{ R.H.}$

8. Test Results:

Refer to page 12 ~ page 22
 (Measurement uncertainty: Refer to page 6)

This result shown in this report refer only to the sample(s) tested unless otherwise stated.
 This Test Report cannot be reproduced, except in full, without the written approval of
 EMC Compliance Laboratory.


Affirmation	Tested by  Name: CHO, MOON-SUP	Technical Manager  Name: YEOM, HAN-SEOK
-------------	---	---

The above test certificate is the accredited test results by Korea Laboratory Accreditation Scheme, which signed the ILAC-MRA.

2014-01-11

EMC Compliance Ltd.

Accredited by KOLAS, Republic of KOREA



Contents

1. Applicant information	3
2. Laboratory information	4
3. Test system configuration	5
3.1 Operation environment	5
3.2 Measurement Uncertainty	6
4. Description of E.U.T.	7
4.1 General information.....	7
4.2 Product description.....	9
4.3 Auxiliary equipments.....	9
4.4 Test configuration	10
4.5 Operating conditions	10
5. Summary of test results	11
5.1 Summary of EMI emission test results.....	11
6. Test results	12
6.1 Conducted Emission.....	12
6.2 Radiated Emission	17
7. E.U.T. photographs	23

1. Applicant information

Applicant: Samsung Techwin Co., Ltd.
Address: 84, Jeongdong-ro, Seongsan-gu,
Changwon-si, Gyeongsangnam-do, Korea
Telephone: +82-70-7147-8361
Fax: +82-31-277-2784
E-mail: js2002.kang@samsung.com
Contact name: **Kang Jei Soon**

Manufacturer#1: Samsung Techwin Co., Ltd.
Address: 84, Jeongdong-ro, Seongsan-gu,
Changwon-si, Gyeongsangnam-do, Korea
Telephone: +82-70-7147-8361
Fax: +82-31-277-2784
E-mail: js2002.kang@samsung.com
Contact name: **Kang Jei Soon**

Manufacturer#2: TIANJIN SAMSUNG TECHWIN OPTO-ELECTRONIC CO., LTD
Address: No.11 Weiliu Road, Micro-Electronic Industrial Park
Jingang Road Tianjin 300385, China

2. Laboratory information

Address

EMC compliance Ltd.

65, Sinwon-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 443-390, Korea

Telephone Number: 82 31 336 9919

Facsimile Number: 82 505 299 8311


FCC CAB.: KR0040

VCCI Registration No. : R-3327, G-198, C-3706, T-1849

Industry Canada Registration No.: 8035A

KOLAS NO.: 231

SITE MAP



3. Test system configuration

3.1 Operation environment

	Temperature	Humidity	Pressure
Chamber(10 m)	: 17.8 °C	23.4 % R.H.	-
Shielded room(CE)	: 22.0 °C	31.2 % R.H.	-

Test site

These testing items were performed following locations;

Test item	Test site
Conducted Emission	Shielded Room
Radiated Emission	10 m Chamber

3.2 Measurement Uncertainty

All measurements involve certain levels of uncertainties, especially in field of EMC.

The factors contributing to uncertainties are test receiver, cable loss, antenna factor calibration, Antenna directivity, antenna factor variation with height, antenna phase center variation, antenna frequency interpolation, measurement distance variation, site imperfection, mismatch, and system repeatability. Based on CISPR 16-4-2, the measurement uncertainty level with a 95 % confidence level was applied.

Conducted emission measurement (C.L: Approx 95 %, k = 2)		
Shielded Room (CE#1)	9 kHz ~ 150 kHz: ± 3.82 dB	
	150 kHz ~ 30 MHz: ± 3.43 dB	
Shielded Room (CE#2)	9 kHz ~ 150 kHz: ± 3.82 dB	
	150 kHz ~ 30 MHz: ± 3.43 dB	
Shielded Room (CE#3)	9 kHz ~ 150 kHz: ± 4.00 dB	
	150 kHz ~ 30 MHz: ± 3.63 dB	
Radiated Emission measurement (C.L: Approx 95 %, k = 2)		
10 m Chamber (#F4)	30 MHz ~ 300 MHz	3 m: + 4.56 dB, - 4.58 dB 10 m: + 4.56 dB, - 4.56 dB
	300 MHz ~ 1 000 MHz	3 m: + 4.84 dB, - 4.85 dB 10 m: + 4.71 dB, - 4.72 dB
	1 GHz ~ 6 GHz	3 m: + 6.19 dB, - 6.20 dB
10 m Chamber (#F2)	30 MHz ~ 300 MHz	3 m: + 4.86 dB, - 4.88 dB 10 m: + 4.86 dB, - 4.86 dB
	300 MHz ~ 1 000 MHz	3 m: + 4.98 dB, - 4.99 dB 10 m: + 4.85 dB, - 4.87 dB
	1 GHz ~ 6 GHz	3 m: + 6.19 dB, - 6.20 dB

4. Description of E.U.T.

4.1 General information

Video	
Imaging Device	1/2.8" PS Exmor 2.38M CMOS (IMX136)
Total Pixels	1952(H) X 1116(V)
Effective Pixels	1944(H) X 1104(V)
Scanning System	Progressive
Min. Illumination	Color : 0.1 Lux (1/30sec, F1.2, 50IRE), 0.0017Lux (2sec, F1.2, 50IRE) B/W : 0.01 Lux (1/30sec, F1.2, 50IRE)
S / N Ratio	-
Video Out	CVBS : 1.0 Vp-p / 75Ω composite, 706x480(N), 704x576(P), for installation - DIP connector type
Lens	
Focal Length (Zoom Ratio)	2.8mm(Fixed)
Max. Aperture Ratio	F1.8
Angular Field of View	H : 112° / V : 62°
Min. Object Distance	200mm
Lens Type	Fixed
Mount Type	Board-in type
Operational	
Camera Title	Off / On (Displayed up to 45 characters)
Day & Night	Auto(S/W) / Color / B/W
Backlight Compensation	Off / BLC
Wide Dynamic Range	120dB ↑
Contrast Enhancement	SSDR (Samsung Super Dynamic Range) (Off / On)
Digital Noise Reduction	SSNRIII (2D+3D Noise Filter) (Off / On)
Digital Image Stabilization	Off / On
Defog	Off / Auto/Manual
Motion Detection	Off / On (4ea 4 Points Polygonal zones)
Privacy Masking	Off / On (32 Zones with 4 Points of Polygonal)
Gain Control	Off / Low / Middle / High
White Balance	ATW / AWC / Manual / Indoor / Outdoor
Electronic Shutter Speed	Minimum / Maximum / Anti flicker (2 ~ 1/12,000sec)
Digital Zoom	16X
Flip / Mirror	Off / On
Intelligent Video Analytics	Tampering, Virtual Line, Enter/Exit, Appear / Disappear, Face Detection
Alarm Triggers	Motion detection, Tampering, Face Detecton, Video Analytics, Network Disconnection
Alarm events	File upload via FTP and E-Mail Notification via E-Mail, TCP and HTTP local storage(SD/SDHC/SDXC) recording at Event

Network	
Ethernet	RJ-45 (10/100BASE-T)
Video Compression Format	H.264 (MPEG-4 Part 10/AVC), Motion JPEG
Resolution	1920x1080 / 1280x1024 / 1280x960 / 1280x720 / 1024x768 / 800x600 / 800x450 / 640x480 / 640x360 / 320x240 / 320x180
Max. Framerate	H.264 : Max 60fps at all resolutions Motion JPEG : 1920x1080 / 1280x1024 / 1280x960 / 1280x720 / 1024x768 : Max. 15 fps 800x600 / 800x450 / 640x480 / 640x360 / 320x240 / 320x180 : Max. 30fps
Smart Codec	Yes (Area Based Method)
Video Quality Adjustment	H.264 : Compression Level, Target Bitrate Level Control MJPEG : Quality Level Control
Bitrate Control Method	H.264 : CBR or VBR Motion JPEG : VBR
Streaming Capability	Multiple Streaming (Up to 10 Profiles)
IP	IPv4, IPv6
Protocol	TCP/IP, UDP/IP, RTP(UDP), RTP(TCP), RTCP, RTSP, NTP, HTTP, HTTPS, SSL, DHCP, PPPoE, FTP, SMTP, ICMP, IGMP, SNMPv1/v2c/v3(MIB-2), ARP, DNS, DDNS, QoS, PIM-SM, UPnP, Bonjour
Security	HTTPS(SSL) Login Authentication Digest Login Authentication IP Address Filtering User access Log 802.1x Authentication
Streaming Method	Unicast / Multicast
Max. User Access	15 users at Unicast Mode
Memory Slot	Micro SD/SDHC/SDXC - motion Images recorded in the SD/SDHC/SDXC memory card can be downloaded.
Application Programming Interface	ONVIF Profile S SUNAPI 2.0 SVNP 1.2
Webpage Language	English, French, German, Spanish, Italian, Chinese, Korean, Russian, Japanese, Swedish, Danish, Portuguese, Turkish, Polish, Czech, Rumanian, Serbian, Dutch, Croatia, Hungary, Greek, Finnish, Norwegian
Web Viewer	Supported OS : Windows XP / VISTA / 7 / 8, MAC OS X 10.7 or higher Supported Browser : Microsoft Internet Explorer (Ver. 7~10) or higher, Mozilla Firefox (Ver. 9~19) or higher, Google Chrome (Ver. 15~25) or higher, Apple Safari (Ver. 6.0.2(Mac OS X 10.8, 10.7 Only), 5.1.7) or higher * Mac OS X Only
Central Management Software	SmartViewer 4.x
Environmental	
Operating Temperature / Humidity	-10°C ~ +55°C(+14°F ~ +131°F) / Less than 90% RH
Storage Temperature / Humidity	-30°C ~ +60°C (-22°F ~ +140°F) / Less than 90% RH
Ingress Protection	IP66 Grade
Vandal Resistance	IK10
Electrical	
Input Voltage / Current	PoE(IEEE802.3af, Class3)
Power Consumption	7.5W
Mechanical	
Color / Material	TOP(IVORY), BOTTOM(IVORY) / TOP(Aluminium), BOTTOM(Aluminium)
Dimension (WxHxD)	Ø113 x H63.7
Weight	550g


4.2 Product description

Type of product	Network Camera
Model name (Basic)	SNV-6013P
Model name (Variant)	-
Difference	-
Trade name	-
Serial no	Engineering Sample
Testing voltage	PoE
Product rating	PoE
Internal clock frequency	Above 108 MHz
Note	* PoE Switch was not provided by the manufacturer.

4.3 Auxiliary equipments

Type	Model / Part #	Serial number	Manufacturer
PoE Switch	FS108P	1DL20C3L00542	NETGEAR
Note PC	C1321	472680432038	FUJITSU
USB Mouse	1088	8165906051134	Microsoft
Headset	SHS-250V	-	SAMSUNG

4.4 Test configuration



Note *	Start		End		Cable	
	Name	I/O port	Name	I/O port	Length (m)	Spec.
1	EUT (Network Camera)	LAN(PoE)	PoE Switch	LAN(PoE)	3.0	Non-Shield
2	Note PC	LAN(RJ-45)	PoE Switch	LAN(RJ-45)	3.0	Non-Shield
3		USB	USB Mouse	USB	1.8	Shield
4		MIC&SPK	Headset	MIC&SPK	2.0	Non-Shield

4.5 Operating conditions

The EUT was configured as normal intended use.

Test mode	Normal operating
1	Web viewer test.
	Ping test.

5. Summary of test results

5.1 Summary of EMI emission test results

Applied	Test items	Test method	Result
☒	Conducted Emission	AS/NZS CISPR 22:2009, Class A	12 Page ~ 16 Page
☒	Radiated Emission	AS/NZS CISPR 22:2009, Class A	17 Page ~ 22 Page

6. Test results

6.1 Conducted Emission

Test specification	EN 55022:2010, Class A		
Testing voltage	PoE		
Test facility	Shielded room (CE#2)		
Date	2014. 01. 09		
Temperature (°C)	22.0 °C	Humidity (% R.H.)	31.2 % R.H.
Remarks	Complied		

6.1.1 Limits of conducted emission measurement

☐ AC main

Frequency [MHz]	Class A (dB(μV))		Class B (dB(μV))	
	Quasi-peak	Average	Quasi-peak	Average
0.15 ~ 0.5	79	66	66 ~ 56 *	56 ~ 46*
0.5 ~ 5	73	60	56	46
5 ~ 30	73	60	60	50

*The limit decreases linearly with the logarithm of frequency.

☒ Telecommunication

Frequency [MHz]	Class A Voltage Limits (dB(μV))		Current Limits (dB(μA))	
	Quasi-Peak	Average	Quasi-Peak	Average
0.15 ~ 0.5	97 to 87	84 to 74	53 to 43	40 to 30
0.5 ~ 30	87	74	43	30
Frequency [MHz]	Class B Limits (dB(μV))		Current Limits (dB(μA))	
	Quasi-Peak	Average	Quasi-Peak	Average
0.15 ~ 0.5	84 to 74	74 to 64	40 to 30	30 to 20
0.5 ~ 30	74	64	30	20

* The limits decrease linearly with the logarithm of the frequency in the range 0.15 MHz to 0.5 MHz

* The current and voltage disturbance limits are derived for use with an impedance stabilization Network (ISN) which presents a common mode (asymmetric mode) impedance of 150 Ω to the telecommunication port under test (conversion factor is $20 \log_{10} 150/I = 44$ dB).

6.1.2 Measurement procedure


The measurements were performed in a shielded room. EUT was setup as shown in photograph and placed on a non-metallic table height of 0.8 m above the reference ground plane. The rear of table was located 0.4 m to the vertical conducted plane. EUT was power through the LISN, which was bonded to the ground plane. The LISN power was filtered. Each EUT power lead, except ground (safety) lead was individually connected through a LISN to input power source. EUT signal cables that hung closer than 0.4 m to the Horizontal metal ground 0.3 m ~ 0.4 m long. The power cord was bundles in the center. All peripheral equipment was powered from a sub LISN. The LISN and ISN were positioned 0.8 m from the EUT. Peak and Average detection were used in preliminary testing and Quasi-peak and Average detections were used at final measurement. Both lines of power cord, hot and neutral, were measured.

6.1.3 Used equipments

Equipment	Model	Serial No.	Makers	Next Cal. Date	Used
Test Receiver	ESCI7	100732	R&S	2014.02.18	☐
Test Receiver	ESCI	100001	R&S	2014.07.25	☒
Test Receiver	ESCI	100710	R&S	2014.10.28	☐
LISN	ENV216	101352	R&S	2014.01.07	☐
LISN	NNLK8121	8121-472	SCHWARZBECK	2014.07.08	☒
8-WIRE ISN	NTFM 8158 CAT5	CAT5-8158-0028	SCHWARZBECK	2014.04.13	☒
8-WIRE ISN	NTFM 8158 CAT3	CAT3-8158-0020	SCHWARZBECK	2014.04.13	☐
ISN	ST08	24342	TESEQ	2014.06.21	☐
ISN	ENY81	101545	R&S	2014.08.29	☐

6.1.4 Photographs of test setup


* Telecommunication



6.1.5 Conducted emission measurement result

* Telecommunication port

LAN Port (LCL 55 dB)_10 Mbps (SNV-6013P)




Final Result

--- No Title2 Phase ---

No.	Frequency [MHz]	Reading QP [dB(μV)]	Reading CAV [dB(μV)]	c.f [dB]	Result QP [dB(μV)]	Result CAV [dB(μV)]	Limit QP [dB(μV)]	Limit AV [dB(μV)]	Margin QP [dB]	Margin CAV [dB]
1	1.26672	34.0	31.6	9.8	43.8	41.4	87.0	74.0	43.2	32.6
2	5.90801	39.2	36.1	9.6	48.8	45.7	87.0	74.0	38.2	28.3
3	7.92314	42.2	39.1	9.6	51.8	48.7	87.0	74.0	35.2	25.3
4	9.38935	41.0	37.4	9.6	50.6	47.0	87.0	74.0	36.4	27.0
5	12.74797	43.2	40.0	9.6	52.8	49.6	87.0	74.0	34.2	24.4
6	13.41941	44.7	41.5	9.6	54.3	51.1	87.0	74.0	32.7	22.9
7	16.2229	46.6	43.4	9.6	56.2	53.0	87.0	74.0	30.8	21.0
8	16.22837	46.7	43.5	9.6	56.3	53.1	87.0	74.0	30.7	20.9

LAN Port (LCL 65 dB)_100 Mbps (SNV-6013P)



Final Result

--- No Title2 Phase ---

No.	Frequency [MHz]	Reading QP [dB(uV)]	Reading CAV [dB(uV)]	c.f [dB]	Result QP [dB(uV)]	Result CAV [dB(uV)]	Limit QP [dB(uV)]	Limit AV [dB(uV)]	Margin QP [dB]	Margin CAV [dB]
1	0.22314	31.0	30.9	10.2	41.2	41.1	93.7	80.7	52.5	39.6
2	0.93065	32.0	30.1	9.8	41.8	39.9	87.0	74.0	45.2	34.1
3	1.26809	34.0	31.5	9.8	43.8	41.3	87.0	74.0	43.2	32.7
4	3.03854	34.2	31.6	9.7	43.9	41.3	87.0	74.0	43.1	32.7
5	8.71725	41.9	38.3	9.6	51.5	47.9	87.0	74.0	35.5	26.1
6	11.89243	43.0	39.6	9.6	52.6	49.2	87.0	74.0	34.4	24.8
7	13.41916	44.7	41.3	9.6	54.3	50.9	87.0	74.0	32.7	23.1
8	16.22855	46.7	43.4	9.6	56.3	53.0	87.0	74.0	30.7	21.0

6.2 Radiated Emission

Test specification	AS/NZS CISPR 22:2009, Class A		
Testing voltage	PoE		
Test facility	10 m Chamber (#F2)		
Test distance	10 m, 3 m		
Date	2014. 01. 09		
Temperature (°C)	17.8 °C	Humidity (% R.H.)	23.4 % R.H.
Remarks	Complied		

6.2.1 Limits of radiated emission measurement

☒ Limits below 1 GHz

Frequency MHz	Class A dB μ V/m @ 10 m	Class B dB μ V/m @ 10 m
30 ~ 230	40	30
230 ~ 1 000	47	37

☒ Limits above 1 GHz

Frequency MHz	Class A @ 3 m		Class B @ 3 m	
	Average limit dB μ V/m	Peak limit dB μ V/m	Average limit dB μ V/m	Peak limit dB μ V/m
1 ~ 3	56	76	50	70
3 ~ 6	60	80	54	74

Note - The lower limit applies at the transition frequency.

6.2.2 Measurement procedure

The test was done at a 10 m chamber with a quasi-peak detector. EUT was placed on a non-metallic table height of 0.8 m above the reference ground plane. Cables were folded back and forth forming a bundle 0.3 m to 0.4 m long and were hanged at a 0.4 m height to the ground plane. Cables connected to EUT were fixed to cause maximum emission. Test was made with the antenna positioned in both the horizontal and vertical planes of polarization. The measurement antenna was varied in height above the conducting ground plane to obtain the maximum signal strength.

6.2.3 Used equipments

Equipment	Model no.	Serial no.	Makers	Next Cal. Date	Used
Test Receiver	ESCI7	100732	R&S	2014.02.18	☒
Test Receiver	ESCI	100001	R&S	2014.07.25	☐
Test Receiver	ESCI	100710	R&S	2014.10.28	☐
Test Receiver	ESR	101078	R&S	2014.10.17	☐
Bi-Log Antenna	VULB 9168	440	SCHWARZBECK	2015.10.16	☒
Amplifier	310N	293004	SONOMA INSTRUMENT	2014.10.31	☒
3 dB Attenuator	8491B	22981	HP	2014.03.19	☒
Antenna Mast	MA4000-EP	303	Innco Systems	-	☒
Turn Table	DT2000S-1t	079	Innco Systems	-	☒
Amplifier	8449B	3008A02343	AGILENT	2014.10.31	☒
Horn ANT	3115	00155772	ETS	2014.03.20	☒
Spectrum Analyzer	FSP7	100289	R&S	2014.11.25	☐

6.2.4 Sample calculation

The field strength is calculated adding the antenna Factor, cable loss and, Antenna pad adding, subtracting the amplifier gain from the measured reading.

The sample calculation is as follow:

$$\text{Result} = \text{M.R} + \text{C.F}(\text{A.F} + \text{C.L} + 3 \text{ dB Att} - \text{A.G})$$

M.R = Meter Reading

C.F = Correction Factor

A.F = Antenna Factor

C.L = Cable Loss

A.G= Amplifier Gain 3 dB Att = 3 dB Attenuator



If M.R is 30 dB, A.F 12 dB, C.L 5 dB, 3 dB, A.G 35 dB

The result is



$$30 + 12 + 5 + 3 - 35 = 15 \text{ dB}\mu\text{V/m}$$

6.2.5 Photographs of test setup

* 30 MHz ~ 1 GHz




* 1 GHz ~ 6 GHz



6.2.6 Radiated emission measurement result

* Graph and Data


* 30 MHz ~ 1 GHz (SNV-6013P)



Final Result

No.	Frequency [MHz]	(P)	Reading QP [dB(uV)]	c.f [dB(1/m)]	Result QP [dB(uV/m)]	Limit QP [dB(uV/m)]	Margin QP [dB]	Height [cm]	Angle [deg]
1	55.220	V	43.4	-14.7	28.7	40.0	11.3	100.0	313.3
2	69.164	V	44.1	-16.6	27.5	40.0	12.5	100.0	145.7
3	102.386	V	48.7	-18.3	30.4	40.0	9.6	399.0	248.7
4	111.601	V	47.2	-17.3	29.9	40.0	10.1	100.0	23.3
5	145.794	V	40.9	-13.6	27.3	40.0	12.7	100.0	11.9
6	202.781	H	36.6	-16.1	20.5	40.0	19.5	100.0	35.1
7	497.782	V	36.9	-6.7	30.2	47.0	16.8	100.0	0.3
8	666.078	V	38.7	-3.0	35.7	47.0	11.3	100.0	162.4

* 1 GHz ~ 6 GHz (SNV-6013P)



Final Result

No.	Frequency [MHz]	(P)	Reading AV [dB(μV)]	Reading PK [dB(μV)]	c.f [dB(1/m)]	Result AV [dB(μV/m)]	Result PK [dB(μV/m)]	Limit AV [dB(μV/m)]	Limit PK [dB(μV/m)]	Margin AV [dB]	Margin PK [dB]	Height [cm]	Angle [deg]
1	1004.375	V	38.7	51.4	-6.9	31.8	44.5	56.0	76.0	24.2	31.5	100.0	91.7
2	1665.000	H	36.2	45.1	-0.7	35.5	44.4	56.0	76.0	20.5	31.6	100.0	300.9
3	1847.500	H	34.5	44.5	0.5	35.0	45.0	56.0	76.0	21.0	31.0	100.0	249.8
4	2336.875	H	35.3	43.6	2.5	37.8	46.1	56.0	76.0	18.2	29.9	100.0	3.7
5	2461.250	H	34.1	45.8	3.0	37.1	48.8	56.0	76.0	18.9	27.2	100.0	5.5
6	3889.375	H	30.9	40.3	9.2	40.1	49.5	60.0	80.0	19.9	30.5	100.0	102.6

7. E.U.T. photographs

Front View



Rear View



Left View



Right View




Top View



Bottom View





Port



Inside



Main Board



CCD Board

