



SPA-B1000

Ponte de áudio IP



Key Features

- Nível máximo de entrada: L, R: +6dBV máximo
- Alimentação: PoE (IEEE 802.3 af tipo 1 Classe 0), DC 24V
- Memória interna: 1 GBytes
- Memória externa (Micro SD): SDHC de até 32 GB (SANDISK)
- Protocolo suportado: IPv4, HTTP, HTTPS, mDNS, DNS, NTP, TCP, UDP, DHCP, ARP, ICMP
- Formato de áudio suportado: WAV, MP3 em mono/estéreo de 64 kbps a 320 kbps (streaming de arquivos).
- Taxa de amostragem de 16 kHz a 48 kHz

SPA-B1000

Ponte de áudio IP



Specifications

Product	
IP Audio Type	IP Audio Module
Line Input	
Maximum Input Level	L, R : +6 dBV Max
Amplifier	
Description	Built in 10W Class D
Network	
Ethernet	10/100 Base-T
Memory	
Internal Memory	1 GBytes
External Memory (Micro SD)	SDHC upto 32GB (SANDISK)
Contact	
Contact Input. Dry contact	One Channel
Contact Output. Dry contact (NO)	One channel
General	
Operating Temperature	-20°~+50°C(-4°F~+122°F)
Operating Humidity	10~95%RH(Non-Condensing)
IP Code	N/A
Weight	0.24Kg (0.53lb)
Size	123(W)*80(H)*30.6(W)mm
Color	White
Certificate	EMC : KS C 9832/9835,EN 55.32/55035,FCC Part 15 Subpart B,ICES-003, Safety : UL 62368-1,CAN/CSA 62368-1
Power	
PoE	PoE (IEEE 802.3 af type 1 Class 3), Max.10W, DC24V
Power	N/A

Network Protocol

Security	Password protection : admin, setup, user, guest (sha-2, Digest authentication, User access log)
Supported Protocols	IPv4, HTTP, HTTPS, mDNS, DNS, NTP, TCP, UDP, DHCP, ARP, ICMP

System Integration

Application Programming Interface	SUNAPI(HTTP API)
Event & Preset	Virtual Contact, Dry contact
Functional Monitoring	Connection verification, Built-in system logging


SPA-B1000

Ponte de áudio IP




CAD

Unit: mm [inch]



Reference image



© Hanwha Vision Co.,Ltd. All rights reserved.

SPA-B1000	V1.0	24.07.18
MODEL NAME	Version	DATE
Unit:mm[inch]	Paper Size :A2	SCALE:1/1
 Hanwha Vision		