



SPA-C100B

IP Ceiling Speaker



Key Features

- Output Level: +6dBV $\pm$ 3dB
- Frequency Response: 20Hz ~ 20kHz
- Amplifier: Built in 10W Class D
- Power: PoE (IEEE 802.3 af type 1 Class 3), PoE+ (IEEE 802.3 at type 2 Class 4)
- Internal Memory: 1 GBytes
- Max. Sound Pressure Level: 100dB
- Frequency Range (-10dB): 120Hz~20kHz
- Sensitivity (1Watt): 90dB
- Supported Protocol: IPv4, HTTP, HTTPS, SIP, mDNS, DNS, NTP, TCP, UDP, DHCP, ARP, ICMP, SNMP(v3)
- TTS: English(US, UK), German, French, Spanish, Russian
- Audio Monitoring: Speaker, Connection test

SPA-C100B

IP Ceiling Speaker



Specifications

Product	
IP Audio Type	IP Ceiling Speaker
Line Output	
Output Level	+6 dBV $\pm$ 3 dB
Frequency Response	20Hz~20kHz
THD + N Ratio (AES17LPF)	Less than 0.1%
S/N Ratio (20kHz LPF, A-WTD)	Greater than 91 dB
Amplifier	
Description	Built in 10W Class D
Network	
Ethernet	10/100 Base-T
Memory	
Internal Memory	1 GBytes
External Memory (Micro SD)	SDHC upto 32GB (SANDISK)
Contact	
Contact Input. Dry contact	One Channel
Contact Output. Dry contact (NO)	One channel
General	
Operating Temperature	-20 $^{\circ}$ ~+50 $^{\circ}$ C (-4 $^{\circ}$ F~+122 $^{\circ}$ F)
Operating Humidity	10~85%RH(Non-Condensing)
IP Code	N/A
Weight	1.8Kg (3.97lb)
Size	ϕ 269*142.5(H)mm
Color	Black
Certificate	EMC : KS C 9832/9835, EN 55032/55035, Safety : KC 62368-1
Power	
PoE	PoE (IEEE 802.3 af type 1 Class 3)

Power

PoE+	(IEEE 802.3 at type 2 Class 4)
------	--------------------------------

Embedded MIC

Input Sensitivity	Sound Level Meter
Frequency Response	Sound Level Meter

Audio

Supported Audio Format	WAV, MP3 in mono/stereo from 64 kbps to 320 kbps. Sampling rate from 16kHz up to 48 kHz
------------------------	---

Speaker

Speaker Component	2 Way 8" LF Drive & 2" HF Driver. Passive type
Max. Sound Pressure Level (PoE)	96 dB
Max. Sound Pressure Level (PoE+)	100 dB
Frequency Range (-10 dB)	120 Hz~20 kHz
Sensitivity (1 Watt)	90 dB
Coverage Pattern	(HxV) : 90° (1 kHz) / 60° (4 kHz)

Network Protocol

Security	Password protection : admin, setup, user, guest (sha-2, Digest authentication, User access log)
Supported Protocols	IPv4, HTTP, SIP, mDNS, DNS, NTP, TCP, UDP, DHCP, ARP, ICMP

System Integration

Application Programming Interface	SUNAPI(HTTP API), ONVIF Profile S
Multi-source Dynamic PA control	Multi-source up to 48 (Multicast) (Audio 24CH + Mic 24CH), Up to 256 Zone Control (Multicast), Up to 20 Zone Control (Unicast), Up to 255 Groups
VoIP	Tested with SIP clients such as Grandstream,Yealink,Cisco,MicroSIP softphone and PBX supplier such as Asterisk, Supported SIP features : DTMF (RFC2833), Supported codecs : PCMU,PCMA,Speex/8000,Speex/16000
TTS	English (US, UK), German, French, Spanish, Russian
Audio Monitoring	Speaker test by graphic level meter (Built in test tool)
Event & Preset	Virtual Contact, Dry contact
Functional Monitoring	Connection verification, Built-in system logging


SPA-C100B

IP Ceiling Speaker



CAD

Unit: mm [inch]



3	MODEL2	
2	MODEL1	
1	SPA-C100BW	'22.7.15
No.	MODEL NAME	DATE
Unit: mm [inch] SCALE: 1/1 © Hanwha Techwin		

© Hanwha Techwin Co., Ltd. All rights reserved.