

SPA-D1000

IP Audio Module

Key Features

- Scheduler
- Background Music (BGM)
- Text To Speech (TTS)
- 10W / 8 Ohm Analog Speaker Output
- 1GB Internal Storage, Single Micro SD slot (Up to 32GB)
- Built-in Relay
- Supports SUNAPI, SIP, & P2P-SIP protocols
- PoE, PoE+ powered

Design and specifications are subject to change without notice. The latest product information / specification can be found at HanwhaVision.com
Hanwha Vision is formerly known as Hanwha Techwin.

© Hanwha Vision CO., LTD. All rights reserved.

SPA-D1000

IP Audio Module



Specifications

Product	
IP Audio Type	IP Audio Module
Line Ouput	
Output Level	+6 dBV ±3 dB
Frequency Response	20Hz~20kHz
THD + N Ration (AES17LPF)	Less than 0.1%
S/N Ration (20kHz LPF, A-WTD)	Greater than 91 dB
Amplifier	
Description	Built in 10W Class D
Network	
Ethernet	10/100 Base-T
Memory	
Internal Memory	1 GBytes
External Memory (Micro SD)	SDHC upto 32GB (SANDISK)
Contact	
Contact Input. Dry contact	One Channel
Contact Output. Dry contact (NO)	One channel
General	
Operating Temperature	-20°~+50°C(-4°F~+122°F)
Operating Humidity	10~85%RH(Non-Condensing)
IP Code	N/A
Weight	0.24Kg (0.53lb)
Size	123(W)*80(H)*30.6(W)mm
Color	White
Certificate	EMC : KS C 9832/9835,EN 55.32/55035,FCC Part 15 Subpart B,ICES-003, Safety : KC 62368-1,UL 62368-1,CAN/CSA 62368-1
Power	
PoE	PoE (IEEE 802.3 af type 1 Class 3)

Design and specifications are subject to change without notice. The latest product information / specification can be found at HanwhaVision.com
Hanwha Vision is formerly known as Hanwha Techwin.

© Hanwha Vision CO., LTD. All rights reserved.

Power

PoE+	(IEEE 802.3 at type 2 Class 4)

Embeded MIC

Input Sensitivity	Sound Level Meter
Frequency Response	Sound Level Meter

Audio

Supported Audio Format	WAV, MP3 in mono/stereo from 64 kbps to 320 kbps. Sampling rate from 16kHz up to 48 kHz

Network Protocol

Security	Password protection : admin, setup, user, guest (sha-2, Digest authentication, User access log)
Supported Protocols	IPv4, HTTP, SIP, mDNS, DNS, NTP, TCP, UDP, DHCP, ARP, ICMP

System Integration

Application Programming Interface	SUNAPI(HTTP API), ONVIF Profile S
Multi-source Dynamic PA control	Multi-source up to 48 (Multicast) (Audio 24CH + Mic 24CH) (Up to 15 audio channels can be broadcast simultaneously), Up to 256 Zone Control (Multicast), Up to 20 Zone Control (Unicast), Up to 255 Groups
VoIP	Tested with SIP clients such as Grandstream,Yealink,Cisco,MicroSIP softphone and PBX supplier such as Asterisk, Supported SIP features : DTMF (RFC2833), Supported codecs : PCMU,PCMA,speex/8000,speex/16000
TTS	English (US, UK), German, French, Spanish, Russian
Audio Monitoring	Speaker test by graphic level meter (Built in test tool)
Event & Preset	Virtual Contact, Dry contact
Functional Monitoring	Connection verification, Built-in system logging


Design and specifications are subject to change without notice. The latest product information / specification can be found at HanwhaVision.com
Hanwha Vision is formerly known as Hanwha Techwin.

© Hanwha Vision CO., LTD. All rights reserved.

SPA-D1000


IP Audio Module





CAD

Unit: mm [inch]



Design and specifications are subject to change without notice. The latest product information / specification can be found at HanwhaVision.com
Hanwha Vision is formerly known as Hanwha Techwin.

© Hanwha Vision CO., LTD. All rights reserved.