

SPA-H100B

IP reproduktor s houkačkou

Key Features

- 124dB Max. hladina akustického tlaku
- Built in 10W Class D Zesilovač
- 111dB Citlivost
- 650Hz ~ 5.3kHz Frekvenční odezva
- Napájení: PoE (IEEE 802.3 af typ 1 třída 3), PoE+ (IEEE 802.3 at typ 2 třída 4)
- Interní paměť: 1 GBytes
- Frekvenční rozsah (-10dB): 650Hz~5.3kHz
- IP kód: IP66
- Podporované protokoly: IPv4, HTTP, SIP, mDNS, DNS, NTP, TCP, UDP, DHCP, ARP, ICMP
- TTS: angličtina (US, UK), němčina, francouzština, španělština, ruština

Design and specifications are subject to change without notice. The latest product information / specification can be found at HanwhaVision.com
Hanwha Vision is formerly known as Hanwha Techwin.

© Hanwha Vision CO., LTD. All rights reserved.

SPA-H100B

IP reproduktor s houkačkou





Specifications

Product	
IP Audio Type	IP Horn Speaker
Amplifier	
Description	Built in 10W Class D
Network	
Ethernet	10/100 Base-T
Memory	
Internal Memory	1 GBytes
Contact	
Contact Input. Dry contact	One Channel
Contact Output. Dry contact (NO)	One channel
General	
Operating Temperature	-40°C~+55°C(-40°F~+131°F) (Cold start : -35°C/-31°F)
Operating Humidity	10~85%RH(Non-Condensing)
IP Code	IP66
Weight	3.7Kg (8.16lb)
Size	241(W) x 155(H) x 307(D)mm
Color	Black
Certificate	EMC : KS C 9832/9835,EN 55.32/55035,FCC Part 15 Subpart B,ICES-003, Safety : UL 62368-1,CAN/CSA 62368-1
Power	
PoE	PoE (IEEE 802.3 af type 1 Class 3)
PoE+	(IEEE 802.3 at type 2 Class 4)
Power	N/A
Embeded MIC	
Input Sensitivity	Sound Level Meter
Frequency Response	Sound Level Meter

Design and specifications are subject to change without notice. The latest product information / specification can be found at HanwhaVision.com
Hanwha Vision is formerly known as Hanwha Techwin.

© Hanwha Vision CO., LTD. All rights reserved.

Audio

Supported Audio Format	WAV, MP3 in mono/stereo from 64 kbps to 320 kbps. Sampling rate from 16kHz up to 48 kHz

Speaker

Speaker Component	1" HF Driver. Dome type
Max. Sound Pressure Level (PoE)	121 dB
Max. Sound Pressure Level (PoE+)	124 dB
Frequency Range (-10 dB)	650 Hz ~ 5.3 kHz
Sensitivity (1 Watt)	111 dB
Coverage Pattern	(HxV) : 130° X 160° (1 kHz) / 30° X 50°(1 kHz)

Network Protocol

Security	Password protection : admin, setup, user, guest (sha-2, Digest authentication, User access log)
Supported Protocols	IPv4, HTTP, SIP, mDNS, DNS, NTP, TCP, UDP, DHCP, ARP, ICMP

System Integration

Application Programming Interface	SUNAPI(HTTP API), ONVIF Profile S
Multi-source Dynamic PA control	Multi-source up to 48 (Multicast) (Audio 24CH + Mic 24CH) (Up to 15 audio channels can be broadcast simultaneously), Up to 256 Zone Control (Multicast), Up to 20 Zone Control (Unicast), Up to 255 Groups
VoIP	Tested with SIP clients such as Grandstream,Yealink,Cisco,MicroSIP softphone and PBX supplier such as Asterisk, Supported SIP features : DTMF (RFC2833), Supported codecs : PCMU,PCMA,speex/8000,speex/16000
TTS	English (US, UK), German, French, Spanish, Russian
Audio Monitoring	Speaker test by graphic level meter (Built in test tool)
Event & Preset	Virtual Contact, Dry contact
Functional Monitoring	Connection verification, Built-in system logging

Design and specifications are subject to change without notice. The latest product information / specification can be found at HanwhaVision.com
Hanwha Vision is formerly known as Hanwha Techwin.

© Hanwha Vision CO., LTD. All rights reserved.

SPA-H100B


IP reproduktor s houkačkou





CAD

Unit: mm [inch]



Design and specifications are subject to change without notice. The latest product information / specification can be found at HanwhaVision.com
Hanwha Vision is formerly known as Hanwha Techwin.

© Hanwha Vision CO., LTD. All rights reserved.