



SPA-M2000

IP Microphone



Key Features

- Desktop SIP Microphone for use with IPAS
- Monitor Amp 1W/8Ω
- DC24V
- PoE
- SUNAPI
- SIP

SPA-M2000

IP Microphone



Specifications

Product	
IP Audio Type	IP Microphone
Line Input	
Maximum Input Level	-7 dBV, Aux Input Volume Max
Amplifier	
Description	1W/8Ω, Monitor Amp
Network	
Ethernet	10/100 Base-T
General	
Operating Temperature	-10°~+40°C(-14°F~+104°F)
Operating Humidity	10~85%RH(Non-Condensing)
IP Code	N/A
Weight	1.3 Kg (2.87lb)
Size	200(W) x 73(H) x 206(L)mm
Color	Black
Certificate	EMC : KS C 9832/9835,EN 55.32/55035,FCC Part 15 Subpart B,ICES-003, Safety : KC 62368-1,UL 62368-1,CAN/CSA 62368-1
Power	
PoE	PoE (IEEE 802.3 af type 1 Class 3)
Power	DC24V, Max 12W
Embedded MIC	
Input Sensitivity	-50 dBV± 3 dB (Mic Volume Max)
Frequency Response	100Hz~6kHz
Network Protocol	
Security	Password protection : admin, setup, user, guest (sha-2, Digest authentication, User access log), Digest authentication, User access log
Supported Protocols	IPv4, HTTP, HTTPS, SIP, mDNS, DNS, NTP, TCP, UDP, DHCP, ARP, ICMP

System Integration

Application Programming Interface	SUNAPI(HTTP API)
VoIP	Tested with SIP clients such as Grandstream,Yealink,Cisco,MicroSIP softphone and PBX supplier such as Asterisk, Supported SIP features : DTMF (RFC2833), Supported codecs : PCMU,PCMA,speex/8000,speex/16000
Functional Monitoring	Connection verification, Built-in system logging

SPA-M2000

IP Microphone



CAD

Unit: mm [inch]

