



SPA-P100W

IP Pendant Speaker (White)




Key Features

- 101dB Max. Sound Pressure Level
- Built in 10W Class D Amplifier
- 91dB Sensitivity
- 130Hz ~ 20kHz Frequency Response
- Two-way audio
- Scheduler function
- Background Music (BGM)
- Text To Speech (TTS)
- Frequency Range 130Hz-20kHz
- 1GB Internal Storage, Micro SD slot (up to 32GB)
- Built-in Relay
- SUNAPI, SIP, & P2P-SIP protocols
- PoE, PoE+ power support
- White Color

SPA-P100W

IP Pendant Speaker (White)



Specifications

Product	
IP Audio Type	IP Pendant Speaker
Amplifier	
Description	Built in 10W Class D
Network	
Ethernet	10/100 Base-T
Memory	
Internal Memory	1 GBytes
External Memory (Micro SD)	SDHC upto 32GB (SANDISK)
Contact	
Contact Input. Dry contact	One Channel
Contact Output. Dry contact (NO)	One channel
General	
Operating Temperature	-20°~+50°C (-4°F~+122°F)
Operating Humidity	10~85%RH(Non-Condensing)
IP Code	N/A
Weight	2.1Kg (4.63lb)
Size	ø269*256(H)mm
Color	White
Certificate	EMC : KS C 9832/9835, EN 55.32/55035, FCC Part 15 Subpart B, ICES-003, Safety : UL 2043, UL 62368-1, CAN/CSA 62368-1
Power	
PoE	PoE (IEEE 802.3 af type 1 Class 3)
PoE+	(IEEE 802.3 at type 2 Class 4)
Embedded MIC	
Input Sensitivity	Sound Level Meter
Frequency Response	Sound Level Meter

Audio

Supported Audio Format	WAV, MP3 in mono/stereo from 64 kbps to 320 kbps. Sampling rate from 16kHz up to 48 kHz
-------------------------------	---

Speaker

Speaker Component	2 Way 8" LF Drive & 2" HF Driver. Passive type
Max. Sound Pressure Level (PoE)	97 dB
Max. Sound Pressure Level (PoE+)	101 dB
Frequency Range (-10 dB)	130Hz~20kHz
Sensitivity (1 Watt)	91 dB
Coverage Pattern	(HxV) : 130°(1kHz) / 60°(4kHz)

Network Protocol


Security	Password protection : admin, setup, user, guest (sha-2, Digest authentication, User access log)
Supported Protocols	IPv4, HTTP, SIP, mDNS, DNS, NTP, TCP, UDP, DHCP, ARP, ICMP

System Integration

Application Programming Interface	SUNAPI(HTTP API), ONVIF Profile S
VoIP	Tested with SIP clients such as Grandstream, Yealink, Cisco, MicroSIP softphone and PBX supplier such as Asterisk. Supported SIP features : DTMF (RFC2833), Supported codecs : PCMU, PCMA, speex/8000, speex/16000
TTS	English (US, UK), German, French, Spanish, Russian
Audio Monitoring	Speaker test by graphic level meter (Built in test tool)
Event & Preset	Virtual Contact, Dry contact
Functional Monitoring	Connection verification, Built-in system logging


SPA-P100W

IP Pendant Speaker (White)



CAD

Unit: mm [inch]



3	MODEL2	
2	MODEL1	
1	SPA-P100BW	23.05.10
No.	MODEL NAME	DATE
Unit: mm[inch] SCALE: 1/1  Hanwha Techwin		

© Hanwha Techwin Co., Ltd. All rights reserved.