



SPA-S1000

Servidor de audio IP



Key Features

- Expansión del sistema: Hasta 512 altavoces
- Protocolo soportado: IPv4, HTTP, SIP, mDNS, DNS, NTP, TCP, UDP, DHCP, ARP, ICMP
- TTS: Inglés (EE.UU., Reino Unido), alemán, francés, español, ruso
- Ethernet 100/1000 Base-T

SPA-S1000

Servidor de audio IP



Specifications

Product	
IP Audio Type	IP Audio Server
Network	
Ethernet	10/100 Base-T
General	
Operating Temperature	-10°~+40°C(-14°F~+104°F)
Operating Humidity	10~85%RH(Non-Condensing)
IP Code	N/A
Network Protocol	
Supported Protocols	IPv4, HTTP, SIP, mDNS, DNS, NTP, TCP, UDP, DHCP, ARP, ICMP
System Integration	
Application Programming Interface	SUNAPI(HTTP API)
Multi-source Dynamic PA control	Multi-source up to 48 (Multicast) (Audio 24CH + Mic 24CH) (Up to 15 audio channels can be broadcast simultaneously), UP to 512 Zone Control (Multicast), Up to 20 Zone Control (Unicast), Up to 255 Groups
Functional Monitoring	Connection verification, Built-in system logging


SPA-S1000

Servidor de audio IP



CAD

Unit: mm [inch]



3	MODEL2	
2	MODEL1	
1	SPA-S1000	'22.7.15
No.	MODEL NAME	DATE
Unit: mm[inch] SCALE: 1/1  Hanwha Techwin		

© Hanwha Techwin Co., Ltd. All rights reserved.