

SPC-1010

Contrôleur système PTZ

Key Features

- Afficheur à cristaux liquides avec texte sur 2 lignes
- Jusqu'à 255 unites de PTZ cameras
- Conception compacte
- Levier de commande 3D pour commander la fonction PTZ
- Prise en charge multiprotocolaire (RS-485, RS-422)

Design and specifications are subject to change without notice. The latest product information / specification can be found at HanwhaVision.com
Hanwha Vision is formerly known as Hanwha Techwin.

© Hanwha Vision CO., LTD. All rights reserved.

SPC-1010

Contrôleur système PTZ





Specifications

Communication		
Interface		RS-485/422 (Remote control: 1km)
Interface Protocol	Units to Control	Up to 255 camera (suitable for medium to large system)
	PTZ Camera	Samsung-T/E, Pelco-D/P, Panasonic, Vicon, AD, Honeywell
Baud Rate (RS-485/422)		2400 ~ 57,600bps
Operational		
LCD Display		16 x 12 character LCD
Joystick		3 Axis twist zoom
Environmental		
Operating Temperature		0˚C ~ 45˚C
Operating humidity		10% ~ 70%
Electrical		
Input Voltage		12V DC, 140mA
Mechanical		
Dimensions (WxhxD)		280.0x100.0x180.0mm
Weight		Approx. 0.7kg (without adaptor)

Design and specifications are subject to change without notice. The latest product information / specification can be found at HanwhaVision.com
Hanwha Vision is formerly known as Hanwha Techwin.

© Hanwha Vision CO., LTD. All rights reserved.