



SPC-2001

Controller



Key Features

- Superior system compatibility by CMS (SSM, Wisenet Viewer) using PC
- 3D joystick control
- Quick and easy installation
- Hall-effect 3 Axis

※ Please refer to the Manual of the product to be connected for detailed functions

SPC-2001

Controller



Specifications

Communication		
Interface		4-pin USB Type A Port
Operational		
Joystick		Hall-effect 3 Axis
Button		12ea
Performance		
Range of Movement	X/Y-Axis	-28° ~ +28°
	Z Axis	-23.5° ~ +23.5°
Center		Two Spring, Two Directions
Minimum Power		0.109 [N · m]
Operating Power		0.151 [N · m]
Maximum Power		0.169 [N · m]
Environmental		
Operating Temperature		0°C to +40°C (20% ~ 85% RH)
Electrical		
Operating Voltage		(DC 5 [V]), Vdd = 5 [V] (±0.5 [V]) via USB
Operating Current		50 [mA]
Mechanical		
Dimensions (WxhxD)		182x182x106mm
Weight		405g
Materials		
Housing		ABS
Handle		Poly Carbonate
Cover		Rubber (Button)
Shaft		SUM24L + Ni plating
Cable Length		2 [m]
Color		Black

Software

Drivers	Standard DirectX Drivers (DirectInput)
---------	--

SPC-2001

Controller



CAD

Unit: mm [inch]

