



SPC-2001

Controller



Key Features

- Superior system compatibility by CMS (SSM, Wisenet Viewer) using PC
- 3D joystick control
- Quick and easy installation
- Hall-effect 3 Axis

※ Please refer to the Manual of the product to be connected for detailed functions

SPC-2001

Controller



Specifications

Communication

Interface	4-pin USB Type A Port
-----------	-----------------------

Operational

Joystick	Hall-effect 3 Axis
Button	12ea

Performance

Range of Movement	X/Y-Axis	-28° ~ +28°
	Z Axis	-23.5° ~ +23.5°
Center	Two Spring, Two Directions	
Minimum Power	0.109 [N · m]	
Operating Power	0.151 [N · m]	
Maximum Power	0.169 [N · m]	

Environmental

Operating Temperature	0°C to +40°C (20% ~ 85% RH)
-----------------------	-----------------------------

Electrical

Operating Voltage	(DC 5 [V]), Vdd = 5 [V] (±0.5 [V]) via USB
Operating Current	50 [mA]

Mechanical

Dimensions (WxHxD)	182x182x106mm
Weight	405g

Materials

Housing	ABS
Handle	Poly Carbonate
Cover	Rubber (Button)
Shaft	SUM24L + Ni plating
Cable Length	2 [m]
Color	Black

Software

Drivers	Standard DirectX Drivers (DirectInput)
---------	--

SPC-2001

Controller



CAD

Unit: mm [inch]

