



SPC-7000

システム制御コントローラー



Key Features

- 5" TFT タッチ LCD
- ネットワーク/アナログカメラ/SSM/DVR 制御
- ユーザーフレンドリーなデザインと使いやすいキーボード
- PTZ 機能を制御するための 3 軸ジョイスティック
- ジョイスティック/ジョグシャトルが右/左入替可能
- USB インターフェース対応 (SSM 用 × 1、バックアップ・FW 更新用 × 1)
- 高速カメラタイルマッピング、構成のインポート/エクスポート

SPC-7000

システム制御コントローラー



Specifications

Communication		
Control Equipment		Network Camera / SSM / Analog Camera / DVR
Interface		Ethernet (Network camera), USB (SSM) 1ea, USB 1ea (Upgrade, Config import/export, Image snapshot), RS-485/422 (Analog Camera, DVR) 1ea, RS-485/422 (Cascade among controllers) 1ea
Interface Protocol	Ethernet	SUNAPI
	USB	Dedicated
	RS-485/422	SRD, Pelco-D/P, Panasonic, Vicon, AD, Honeywell, Bosch, Elmo, GE, Samsung-T/E
	Units to Control	Network Camera : Max. 255ea, SSM : 1ea, Analog Camera / DVR : Max. 255ea
Baud Rate (RS-485/422)		2400 ~ 57,600bps
Network Protocol		TCP, HTTP, DHCP, IPv4
Operational		
LCD Display		5" TFT LCD
Joystick		3 Axis twist zoom
Jog Shuttle		SSM / DVR playback control
Control		
Camera		Pan / Tilt / Zoom, Focus, Auto focus, Preset, Group, Tour, Swing, Trace, Auto tracking, Alarm off/on, Freeze
Video Wall		Camera-tile (Channel) mapping, Layout (Display division mode) change
Recorder		Recording / Playback control, Alarm off, Menu
Device Management		Built-in device registration / Modification on LCD
User Management		Admin + 9 operators
Import / Export		Configuration import / export
Miscellaneous		
Video Snapshot		Still image (Network camera) export using USB memory
Input		Alphabet input (Virtual keyboard)
Language		English, Spanish, French, Italian, German, Turkish, Polish, Russian, Korean, Chinese, Japanese

Environmental

Operating Temperature	0°C ~ 40°C (+32°F ~ +104°F)
Operating humidity	20% ~ 85%

Electrical

Input Voltage	12V DC
Power Consumption	Max. 6.4W

Mechanical

Dimensions (WxHxD)	459.1x59.1x177.9mm (18.07"x2.33"x 7")
Weight	1.5Kg (3.3 lb)

SPC-7000

システム制御コントローラー



CAD

Unit: mm [inch]

