



SPC-7000

Пульт управления сетевой универсальный с джойстиком



Key Features

- Сенсорный TFT ЖК-дисплей 5"
- Управление сетевыми / аналоговыми камерами / SSM / DVR
- Удобная конструкция, простая в использовании клавиатура
- Трехкоординатный джойстик для управления функцией PTZ (панорамирование, наклон, зум)
- Съёмный джойстик для универсального использования (управление правой/левой рукой)
- Поддержка интерфейса USB (1 для SSM, 1 для захвата изображения / обновления)
- Быстрое назначение камер окнам на экране, импорт / экспорт конфигурации

SPC-7000

Пульт управления сетевой
универсальный с джойстиком



Specifications

Communication

Control Equipment		Network Camera / SSM / Analog Camera / DVR
Interface		Ethernet (Network camera), USB (SSM) 1ea, USB 1ea (Upgrade, Config import/export, Image snapshot), RS-485/422 (Analog Camera, DVR) 1ea, RS-485/422 (Cascade among controllers) 1ea
Interface Protocol	Ethernet	SUNAPI
	USB	Dedicated
	RS-485/422	SRD, Pelco-D/P, Panasonic, Vicon, AD, Honeywell, Bosch, Elmo, GE, Samsung-T/E
	Units to Control	Network Camera : Max. 255ea, SSM : 1ea, Analog Camera / DVR : Max. 255ea
Baud Rate (RS-485/422)		2400 ~ 57,600bps
Network Protocol		TCP, HTTP, DHCP, IPv4

Operational

LCD Display	5" TFT LCD
Joystick	3 Axis twist zoom
Jog Shuttle	SSM / DVR playback control

Control

Camera	Pan / Tilt / Zoom, Focus, Auto focus, Preset, Group, Tour, Swing, Trace, Auto tracking, Alarm off/on, Freeze
Video Wall	Camera-tile (Channel) mapping, Layout (Display division mode) change
Recorder	Recording / Playback control, Alarm off, Menu
Device Management	Built-in device registration / Modification on LCD
User Management	Admin + 9 operators
Import / Export	Configuration import / export

Miscellaneous

Video Snapshot	Still image (Network camera) export using USB memory
Input	Alphabet input (Virtual keyboard)
Language	English, Spanish, French, Italian, German, Turkish, Polish, Russian, Korean, Chinese, Japanese

Environmental

Operating Temperature	0°C ~ 40°C (+32°F ~ +104°F)
Operating humidity	20% ~ 85%

Electrical

Input Voltage	12V DC
Power Consumption	Max. 6.4W

Mechanical

Dimensions (WxHxD)	459.1x59.1x177.9mm (18.07"x2.33"x 7")
Weight	1.5Kg (3.3 lb)

SPC-7000

Пульт управления сетевой
универсальный с джойстиком



CAD

Unit: mm [inch]

