



SPD-152

1 Monitor Decoder



Key Features

- Max 64ch, 8M@60fps decoding performance
- Dual HDMI display port(HDMI#1 UHD, HDMI#2 FHD)
- Various installation : Monitor-Back and Pole mount
- ONVIF, SUNAPI, RTSP
- PoE and DC 12V Dual power

SPD-152

1 Monitor Decoder



Specifications

システム		
CPU		Emdbded CPU
Operating System		Embedded Linux
ビデオ出力	HDMI#1	1EA (up-to 4K), Audio support
	HDMI#2	1EA (up-to 1080p), Audio not support
	Video-out Format	3840 X 2160@30Hz (HDMI#1) 2560 X 1440@30Hz (HDMI#1) 1920 X 1080@60Hz (HDMI#1, HDMI#2) 1280 X 1024@60Hz (HDMI#1, HDMI#2) 1280 X 720@60Hz (HDMI#1, HDMI#2)
外部	Ethernet	1EA (10/100/1000BASE-T)
	USB	2EA(USB 2.0)
	LED	Power, Network
ネットワーク	帯域幅	Max. 150Mbps
Environmental		
動作温度		0°C to +40°C (32°F to 104°F)
Operating Humidity		20% ~ 85% RH
電源		
Power Input		12VDC, PoE (IEEE802.3af)
消費電力		Max. 11.0W (12V DC), Max. 12.95W (PoE)
Mechanical		
Color / Material		Black / Metal & Plastic
Dimension(WxHxD)		140.0 x 29.5 x 115.4mm(5.51 x 1.16 x 4.54")
重量		260g (0.58 lb)
ソフトウェア		
映像	コーデック	H.265/H.264/MJPEG
	Max. Decoding Performance	8M@60fps, 12ch*2MP@30fps
	Division/Monitor	Clone mode : (HDMI#1) Max. 64, Expand mode : (HDMI#1) Max. 36,(HDMI#2) Max. 25
	レイアウト	Up to 20, Sequence support
音声	コーデック	G.711 / G.726 / AAC

ソフトウェア

管理	Local UI, Web-Viewer, SSM
Time Setting	NTP/Manual
Export/Import	Configuration Export/Import
ログ	Max. 100,000 (System log)
プロトコル	RTP, RTSP, HTTP, CGI (SUNAPI), ONVIF
セキュリティ	IP address filtering, User access Log, 802.1x, Encryption, Device certificate(Hanwha Techwin Root CA), Signed firmware

SPD-152

1 Monitor Decoder



CAD

Unit: mm [inch]

