



SPI-BBN0

BCR Camera LED module




Key Features

- Blue LED Module for 3MP BCR Camera
- Power Consumption: 6.9 W
- LED Quantity: 16EA
- IP66/IP67(camera and front cover must be assembled)
- Operating Temperature / Humidity: -40°C~+55°C / 0~95% RH
- Compatible Camera: TNS-7000M
- Compatible Lenses: SLM-5M16, SLM-5M25

SPI-BBN0

BCR Camera LED module




Specifications

Environmental	
Operating Temperature / Humidity	-40°C~+55°C / 0~95% RH
Storage Temperature / Humidity	-40°C ~ +60°C / Less than 95% RH
認証	FCC, UL, CE, KC, IEC 62471 IP66/IP67(camera and front cover must be assembled)
電源	
Input Voltage	24 VDC ± 10%
消費電力	18 W
Mechanical	
Product dimensions / weight	W101.2 x D53.8 x H78.2 / 200g
Supported products	TNS-7000M
LED	
null	455nm
Quantity	16EA
Angle	FWHM : 17° 10~% : 32°


SPI-BBN0

BCR Camera LED module



CAD

Unit: mm [inch]



4	SPI-BBM0, SPI-BBM1, SPI-BBW0 SPI-BRM0, SPI-BRM1, SPI-BRW0	'25.11.28
3	SPI-BBN0, SPI-BRN0	'25.09.30
2	SPI-BWM0, SPI-BWM1, SPI-BWW0	'25.08.13
1	SPI-BWN0	'25.06.02
No.	MODEL NAME	DATE

© Hanwha Vision Co., Ltd. All rights reserved.

Unit: mm [inch] SCALE: 1/1

 Hanwha Vision