

SPP-C00402EP



# SPP-C00402EP

Cable with push-pull connectors (2M)



## Key Features

- 2m RJ45 Push-pull ruggedized Cable

# SPP-C00402EP

Cable with push-pull connectors  
(2M)



## Specifications

### Environmental

|                                  |                                                      |
|----------------------------------|------------------------------------------------------|
| Operating Temperature / Humidity | -50°C~+60°C(-58°F~+140°F)/0~100% RH(condensing)      |
| Storage Temperature / Humidity   | -50°C~+50°C(-58°F~+122°F)/0~100% RH(condensing)      |
| Certification                    | IP66, IP68(Dedicated Camera Connection Requirements) |

### Mechanical

|                             |                                                                                 |
|-----------------------------|---------------------------------------------------------------------------------|
| Color                       | Black, Yellow                                                                   |
| Material                    | Thermoplastic, Copper Alloy                                                     |
| Product dimensions / weight | 2m(78.74")/128g(0.28lb)                                                         |
| Supported products          | TNP-A6550RW, TNP-A6550RWB, TNP-A7430RW, TNP-A7430RWB, TNP-A9430RW, TNP-A9430RWB |

### Cable

|              |    |
|--------------|----|
| Cable Length | 2m |
|--------------|----|