



# SPS-A100M

## Audio Beacon



### Key Features

- 5 Микрофоны MEMS
- Two-way Audio Support Full-duplex
- 90dB Встроенный динамик
- AI Sound Classification Glass, Screaming, etc.
- Five built-in MEMS microphones
- Built-in LED ring indicator for clear status alerts
- AI-based sound classification included
- Best sound(audio file), Event metadata support
- Accurate sound origin detection with direction-finding algorithms
- Support for 3rd party VMS integration

# SPS-A100M

Audio Beacon



## Specifications

### Video

|                |             |                                                                                                          |
|----------------|-------------|----------------------------------------------------------------------------------------------------------|
| Resolution     |             | 1920x1080, 1280x1024, 1280x960, 1280x720, 1024x768, 800x600, 800x448, 720x576, 720x480, 640x480, 640x360 |
| Max. Framerate | H.265/H.264 | 10fps                                                                                                    |
|                | MJPEG       | 5fps                                                                                                     |
|                | Others      | Static image video                                                                                       |
| Video Out      |             | USB: Micro USB Type C, setting true north point using Wisenet installation                               |

### Operational

|                                          |                                                                                                                                                                                    |
|------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Alarm Interface                          | 2 configurable I/O ports                                                                                                                                                           |
| Alarm Triggers                           | Analytics, Network disconnect, Alarm input, App event(Sound classification), Time schedule, MQTT subscription, Case tampering                                                      |
| Audio Streaming                          | Two-way/one-way selectable, Full duplex, Echo cancellation, Noise reduction                                                                                                        |
| Alarm Events When Alarm Trigger Occurred | File upload(audio): e-mail/FTP, Notification: e-mail,Alarm output, Handover: PTZ preset,send message by HTTP/HTTPS/TCP,Audio clip playback(6MB,WAV), MQTT: publication,LED,Speaker |
| Audio In                                 | Built-in MEMS 5mics                                                                                                                                                                |
| Audio Out                                | Built-in speaker, Max. Sound Pressure Level 90dB at 1m(3.28ft), Frequency Range: 144Hz~20kHz                                                                                       |
| Light Type                               | LED Ring(Green, Blue, Red, Pink, Sky blue, Purple), for event action                                                                                                               |

### Analytics

|                                     |                                                                                              |
|-------------------------------------|----------------------------------------------------------------------------------------------|
| Analytics Events Based on AI Engine | Sound classification                                                                         |
| Classified Sound Type               | Crashing glass, Screaming, Vehicle horn, Tire screech                                        |
| Event Metadata                      | Sound type, Sound direction, Confidence, Timestamp, Best sound(audio file), dB( $\pm 10$ dB) |
| Sound Direction                     | Ceiling mounting: $\pm 15$ degrees                                                           |

### Network

|                   |                                                                                                                       |
|-------------------|-----------------------------------------------------------------------------------------------------------------------|
| Ethernet          | RJ-45(10/100 BASE-T)                                                                                                  |
| Audio Compression | G.711 u-law /G.726 selectable,G.726(ADPCM) 8kHz,G.711 8kHz, G.726: 16kbps,24kbps,32kbps,40kbps, AAC-LC: 16kHz(48kbps) |

## Network

|                                   |                    |                                                                                                                                                                                                                                                        |
|-----------------------------------|--------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Streaming                         | Unicast            | Up to 6 users                                                                                                                                                                                                                                          |
|                                   | Multicast          | Support                                                                                                                                                                                                                                                |
|                                   | Multiple Streaming | Up to 6 profiles                                                                                                                                                                                                                                       |
| Protocol                          |                    | IPv4, IPv6, TCP/IP, UDP/IP, RTP(UDP), RTP(TCP), RTCP, RTSP, NTP, HTTP, HTTPS, SSL/TLS, DHCP, FTP, SMTP, ICMP, IGMP, SNMPv1/v2c/v3(MIB-2), ARP, DNS, DDNS, QoS, UPnP, Bonjour, LLDP, SRTP(TCP, UDP Unicast), MQTT, SIP 2.0(RFC 3261 and companion RFCs) |
| Application Programming Interface | ONVIF              | S                                                                                                                                                                                                                                                      |
|                                   | Others             | SUNAPI(HTTP API), Hanwha Vision Open Platform, AI Sound Classification pack included                                                                                                                                                                   |

## Security

|                        |                                                                         |
|------------------------|-------------------------------------------------------------------------|
| OS / Firmware Protect  | Encrypted firmware, Secure boot, Signed firmware                        |
| User authentication    | Digest authentication, Prevent brute-force attack                       |
| Network authentication | IEEE 802.1X(EAP-TLS, EAP-LEAP, EAP-PEAP, MSCHAPv2)                      |
| Secure Communication   | SRTP, HTTPS, WSS(WebSocket Secure)                                      |
| Access Control         | IP-based access control                                                 |
| Data Protect           | Encryption credentials, Encrypt compress for live recording file export |
| Audit                  | Access / System / Event Log management                                  |
| Device ID              | Device certificate(Hanwha Vision Root CA)                               |
| Secure Storage         | Secure element                                                          |
| Security Certificate   | Secure element(FIPS 140-3 level3, CC EAL6+)                             |

## General

|        |       |       |
|--------|-------|-------|
| Memory | RAM   | 4GB   |
|        | Flash | 512MB |

## Environmental & Electrical

|                     |             |                           |
|---------------------|-------------|---------------------------|
| Operating Condition | Temperature | -20°C~+55°C(-4°F~+122°F)  |
|                     | Humidity    | 0~90% RH(non-condensing)  |
| Storage Condition   | Temperature | -50°C~+60°C(-58°F~+140°F) |
|                     | Humidity    | 0~90% RH(non-condensing)  |
| Input Voltage       |             | PoE+(IEEE802.3at, Class4) |
| Power Consumption   | PoE         | Max 18.5W, typical 8.2W   |

## Mechanical

|                    |                                                |
|--------------------|------------------------------------------------|
| Color              | White                                          |
| Material           | Plastic, Aluminum                              |
| RAL Code           | RAL9003                                        |
| Product Dimensions | 215.1(W)x135.1(D)x52.8(H)mm(8.47"x5.32"x2.08") |

---

## Mechanical

|                         |                                                    |
|-------------------------|----------------------------------------------------|
| Product Weight          | 973g(2.15 lb)                                      |
| Compatible Conduit Hole | Support conduit compatibility via optional adaptor |
| Compatible Gang Box     | Single, Double, 4" Octagon, Square                 |

## Certifications & Standards

|             |                                                                                                                                                                             |
|-------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| EMC         | FCC 47 CFR 15 Subpart B Class A, ICES-3(A)/NMB-3(A), CE/UKCA - EN 55032 Class A, EN 50130-4, EN 61000-3-2, EN 61000-3-3, VCCI CISPR 32 Class A, RCM AS/NZS CISPR 32 Class A |
| Safety      | UL 62368-1, CAN/CSA C22.2 NO. 62368-1, IEC/EN 62471                                                                                                                         |
| Environment | IEC/EN 63000                                                                                                                                                                |

# SPS-A100M


Audio Beacon





CAD

Unit: mm [inch]

## SPS-A100M AI Sound Detector



Reference image



|               |           |
|---------------|-----------|
| Revision      | V1.1      |
| Revision Date | 25/02/27  |
| Paper Size    | A0        |
| Unit          | mm [inch] |
| Scale         | 1 : 1     |

©Hanwha Vision Co., Ltd. All right reserved.

## Compatible Devices

---



SBP-060BA