



SPS-A100M

Audio Beacon



Key Features

- 5 MEMSマイクロフォン
- Two-way Audio Support Full-duplex
- 90dB 内蔵スピーカー
- AI Sound Classification Glass, Screaming, etc.
- Five built-in MEMS microphones
- Built-in speaker(Max. Sound Pressure Level(PoE+) 90dB)
- Built-in LED ring indicator for clear status alerts
- AI-based sound classification included
- Best sound(audio file), Event metadata support
- Accurate sound origin detection with direction-finding algorithms
- Support for 3rd party VMS integration

SPS-A100M

Audio Beacon



Specifications

Video		
Resolution		1920x1080, 1280x1024, 1280x960, 1280x720, 1024x768, 800x600, 800x448, 720x576, 720x480, 640x480, 640x360
Max. Framerate	H.265/H.264	10fps
	MJPEG	5fps
	Others	Static image video
Video Out		USB: Micro USB Type C, setting true north point using Wisenet installation
Operational		
Alarm Interface		2 configurable I/O ports
Alarm Triggers		Analytics, Network disconnect, Alarm input, App event(Sound classification), Time schedule, MQTT subscription, Case tampering
Audio Streaming		Two-way/one-way selectable, Full duplex, Echo cancellation, Noise reduction
Alarm Events When Alarm Trigger Occurred		File upload(audio): e-mail/FTP, Notification: e-mail,Alarm output, Handover: PTZ preset,send message by HTTP/HTTPS/TCP,Audio clip playback(6MB,WAV), MQTT: publication,LED,Speaker
Audio In		Built-in MEMS 5mics
Audio Out		Built-in speaker, Max. Sound Pressure Level 90dB at 1m(3.28ft), Frequency Range: 144Hz~20kHz
Light Type		LED Ring(Green, Blue, Red, Pink, Sky blue, Purple), for event action
Analytics		
Analytics Events Based on AI Engine		Sound classification
Classified Sound Type		Crashing glass, Screaming, Vehicle horn, Tire screech
Event Metadata		Sound type, Sound direction, Confidence, Timestamp, Best sound(audio file), dB(± 10 dB)
Sound Direction		Ceiling mounting: ± 15 degrees
Network		
Ethernet		RJ-45(10/100 BASE-T)
Audio Compression		G.711 u-law /G.726 selectable,G.726(ADPCM) 8kHz,G.711 8kHz, G.726: 16kbps,24kbps,32kbps,40kbps, AAC-LC: 16kHz(48kbps)

Network

Streaming	Unicast	Up to 6 users
	Multicast	Support
	Multiple Streaming	Up to 6 profiles
Protocol		IPv4, IPv6, TCP/IP, UDP/IP, RTP(UDP), RTP(TCP), RTCP, RTSP, NTP, HTTP, HTTPS, SSL/TLS, DHCP, FTP, SMTP, ICMP, IGMP, SNMPv1/v2c/v3(MIB-2), ARP, DNS, DDNS, QoS, UPnP, Bonjour, LLDP, SRTP(TCP, UDP Unicast), MQTT, SIP 2.0(RFC 3261 and companion RFCs)
Application Programming Interface	ONVIF	S
	Others	SUNAPI(HTTP API), Hanwha Vision Open Platform, AI Sound Classification pack included

Security

OS / Firmware Protect	Encrypted firmware, Secure boot, Signed firmware
User authentication	Digest authentication, Prevent brute-force attack
Network authentication	IEEE 802.1X(EAP-TLS, EAP-LEAP, EAP-PEAP, MSCHAPv2)
Secure Communication	SRTP, HTTPS, WSS(WebSocket Secure)
Access Control	IP-based access control
Data Protect	Encryption credentials, Encrypt compress for live recording file export
Audit	Access / System / Event Log management
Device ID	Device certificate(Hanwha Vision Root CA)
Secure Storage	Secure element
Security Certificate	Secure element(FIPS 140-3 level3, CC EAL6+)

General

Memory	RAM	4GB
	Flash	512MB

Environmental & Electrical

Operating Condition	Temperature	-20°C~+55°C(-4°F~+122°F)
	Humidity	0~90% RH(non-condensing)
Storage Condition	Temperature	-50°C~+60°C(-58°F~+140°F)
	Humidity	0~90% RH(non-condensing)
Input Voltage		PoE+(IEEE802.3at, Class4)
Power Consumption	PoE	Max 18.5W, typical 8.2W

Mechanical

Color	White
Material	Plastic, Aluminum
RAL Code	RAL9003
Product Dimensions	215.1(W)x135.1(D)x52.8(H)mm(8.47"x5.32"x2.08")

Mechanical

Product Weight	973g(2.15 lb)
Compatible Conduit Hole	Support conduit compatibility via optional adaptor
Compatible Gang Box	Single, Double, 4" Octagon, Square

Certifications & Standards

EMC	FCC 47 CFR 15 Subpart B Class A, ICES-3(A)/NMB-3(A), CE/UKCA - EN 55032 Class A, EN 50130-4, EN 61000-3-2, EN 61000-3-3, VCCI CISPR 32 Class A, RCM AS/NZS CISPR 32 Class A
Safety	UL 62368-1, CAN/CSA C22.2 NO. 62368-1, IEC/EN 62471
Environment	IEC/EN 63000

SPS-A100M


Audio Beacon





CAD

Unit: mm [inch]

SPS-A100M AI Sound Detector



Reference image



Revision	V1.1
Revision Date	25/02/27
Paper Size	A0
Unit	mm [inch]
Scale	1 : 1

©Hanwha Vision Co., Ltd. All right reserved.

Compatible Devices



SBP-060BA