



Network

Купольные

SPS-A8016

All-In-One Camera



Key Features

- 5MP Image Resolution
- 3 Built-in MEMS Microphones
- Sound Classification AI-based
- IK08 Rated
- Built-in speaker (Peak Sound Pressure Level 97.5dB(PoE+))
- Full-duplex two-way audio support (Echo Cancellation & Noise Reduction)
- Built-in LED ring indicator for clear status alerts
- Object Classification & AI-based Analytics
- Dynamic Privacy Masking

SPS-A8016

All-In-One Camera



Specifications

Video

Imaging Device	Size	1/2.8"
	Type	CMOS
Resolution		2560x1920, 2560x1440, 1920x1080, 1600x1200, 1280x960, 1280x720, 1024x768, 800x600, 640x480, 640x360, 320x240, 320x180
Max. Framerate	H.265/H.264	30fps/25fps(60Hz/50Hz)
	MJPEG	30fps(@5MP Max. 5fps)
Min. Illumination (Lux)	Color(1/30sec, 30IRE)	0.06
	BW(1/30sec, 30IRE)	0.006
Video Out		USB: USB Type C. Preview and installation ONLY. Requires WiFi dongle.

Lens

Focal Length (mm)		3.0
Max Aperture Ratio (F number)	Wide	1.6
	Tele	1.6
Angular Field of View	Horizontal	100°
	Vertical	74°
	Diagonal	130°
Min. Object Distance		0.4m(1.31ft)
Focus Control		Manual
Lens Type		Fixed iris

Pan / Tilt / Rotate

Pan / Tilt / Rotate Range	Pan	0°~351°
	Tilt	0°~53°
	Rotate	±90°

Operational

Day & Night	Auto(ICR)
Backlight Compensation	BLC, HLC, WDR, SSDR
Wide Dynamic Range (dB)	120

Operational

Digital Noise Reduction		WiseNR II (Based on AI engine), SSNR V
Digital Image Stabilization		Support
Defog		Support
Motion Detection	Quantity	8ea
	Shape	8point Polygonal zones
Privacy Masking	Quantity	32ea
	Shape	Polygonal zones
	Color / Option	Gray, Green, Red, Blue, Black, White, Mosaic, Purple, Yellow
	Dynamic Privacy Masking: Color / Option	Gray, Green, Red, Blue, Black, White, Mosaic, Purple, Yellow
Gain Control		Off, Max gain, Manual
White Balance		ATW, NarrowATW, AWC, Manual, Indoor, Outdoor
LDC		Support(Fill/stretch mode)
Electronic Shutter	Mode	Minimum, Maximum, Anti flicker, Prefer shutter control(Based on AI engine)
	Speed Range	2~1/30,000sec
Video Rotation		Flip, Mirror, Hallway view(90°/270°)
Alarm Interface	In/Out	2 configurable I/O ports
	Others	Support alarm I/O via optional I/O box
Alarm Triggers		Analytics, Network disconnect, Alarm input, App event, Time schedule, MQTT subscription, Case tampering, Day/Night, Storage disruption
Alarm Events When Alarm Trigger Occurred		File upload(image): e-mail/FTP/SFTP, File upload(video clip): FTP/SFTP, Notification: e-mail, Recording: SD/SDHC/SDXC or NAS recording at event triggers,Alarm output, Handover: PTZ preset,send message by HTTP/HTTPS/TCP,Audio clip playback, MQTT: publication,LED Status
Audio Streaming		Two-way/one-way selectable, Full duplex, Echo cancellation, Noise reduction
Audio In		Built-in 3mics
Audio Out		Built-in speaker
Speaker	Max. Sound Pressure Level	Max SPL 81dB(PoE), 90dB(PoE+) at 1m(3.28ft) Peak SPL 97.5dB(PoE+) at 1m(3.28ft)
	Frequency Range	144Hz~20kHz
LED	Color	Green, Blue, Red, Pink, Sky blue, Purple, Color palette
	Mode	Constant, Flashing, Rotating, Fade-in, Fade-out, Strobe

Analytics

Classified Object Type		Person, Face, Vehicle, License plate
Attributes	Person	Upper/Lower clothes color, Gender, Bag
	Vehicle	Type(car, bus, truck, motorcycle, bicycle), Color
	Face	Age, Gender, Face mask, Glasses
Similarity Search		Support

Analytics

Thumbnail		BestShot
Analytics Events	Based on AI Engine	Object detection, Virtual line(Crossing/Direction), Virtual area(Loitering/Intrusion/Enter/Exit), Motion detection, Face mask detection, Social distancing detection, Slip & fall detection, Sound classification
	Normal	Defocus detection, Tampering, Audio detection
Business Intelligence	Based on AI Engine	People counting, Queue management, Heatmap, Vehicle counting, Crowd counting

Network

Ethernet		Metal shielded RJ-45(10/100BASE-T)
Video Compression		H.265/H.264: Main/Baseline/High, MJPEG
Audio Compression		G.711(PCM): 8kHz(64kbps), G.726(ADPCM): 8kHz(16/24/32/40kbps), AAC-LC: 16kHz(48kbps), OPUS: 16kHz(64kbps)
Smart Codec		Manual, WiseStream(Based on AI engine)
Bitrate Control		H.265/H.264: CBR or VBR, MJPEG: VBR
Streaming	Unicast	Up to 20 users
	Multicast	Support
	Multiple Streaming	Up to 5 profiles
Protocol		IPv4, IPv6, TCP/IP, UDP/IP, RTP(UDP), RTP(TCP), RTCP, RTSP, NTP, HTTP, HTTPS, SSL/TLS, DHCP, FTP, SFTP, SMTP, ICMP, IGMPv2, SNMPv1/v2c/v3(MIB-2), ARP, DNS, DDNS, QoS, UPnP, Bonjour, LLDP, CDP, SRTP(TCP, UDP Unicast), MQTT, PIM-SM, SMTP(StartTLS), SIP, Syslog
SIP support (VoIP, Peer-to-peer, SIP/PBX integration)		SIP 2.0(RFC 3261 and companion RFCs)
Application Programming Interface	ONVIF	S, G, T, M
	Others	SUNAPI(HTTP API), Hanwha Vision Open Platform
Direct Cloud Connection		Support

Security

OS / Firmware Protect		Encrypted firmware, Secure boot, Signed firmware
User authentication		Digest authentication, Prevent brute-force attack
Network authentication		IEEE 802.1X(EAP-TLS, EAP-LEAP, EAP-PEAP, MSCHAPv2)
Secure Communication		HTTPS, WSS(WebSocket Secure), SRTP
Access Control		IP-based access control, MAC-based access control, Auto logout
Data Protect		Encryption credentials, Encrypt compress for live recording file export
Audit		Access / System / Event Log management
Device ID		Device certificate(Hanwha Vision Root CA)
Secure Storage		SDcard partition encrypt(AES-256), Secure element
Supply Chain Security		SBOM
Security Certificate		Secure element(FIPS 140-3 level3, CC EAL6+), Consumer IoT Security Standard (ETSI EN 303 645), Security Built-in Process Certification (IEC 62443-4-1)

General

Memory	RAM	4GB
	Flash	8GB eMMC
Edge Storage	Micro SD/SDHC/SDXC	Max. 1TB x 1slot
Edge Storage(OnCloud)	Micro SD/SDHC/SDXC	Max. 1TB x 1slot *Hanwha Vision branded microSD cards have been certified and recommended for OnCloud edge recording.

Environmental & Electrical

Operating Condition	Temperature	-20°C~+55°C(-4°F~+131°F)
	Humidity	0~90% RH(non-condensing)
Storage Condition	Temperature	-50°C~+60°C(-58°F~+140°F)
	Humidity	0~90% RH(non-condensing)
Input Voltage		PoE(IEEE802.3af, Class3), PoE+(IEEE802.3at, Class4)
Power Consumption	PoE	PoE+ : Max. 20W, typical 6.2W(excluding Speaker and LED) PoE : Max. 9.0W, typical 6.2W(excluding Speaker and LED)
WisePower		Power monitoring, Eco mode

Mechanical

Color	White
Material	Aluminum, Hard-coated dome
RAL Code	RAL9003
Product Dimensions	215.1(W)x135.1(D)x52.8(H)mm(8.47"x5.32"x2.08")
Product Weight	1219g(2.7lb)
Compatible Conduit Hole	19.1mm(3/4")(M25)
Compatible Gang Box	Single, Double, 4" Octagon, Square

Certifications & Standards

EMC	FCC 47 CFR 15 Subpart B Class A, ICES-3(A)/NMB-3(A), CE/UKCA - EN55032 Class A, EN 50130-4, EN 61000-3-2, EN 61000-3-3, VCCI CISPR 32 Class A, RCM AS-NZS CISPR 32 Class A, KS C 9832 Class A, KS C 9835
Safety	UL 62368-1, CAN/CSA C22.2 NO. 62368-1, IEC 62471
Environment	IEC/EN 63000, IEC 62262 IK08

AI Detection Distance

Person(1.8m/5.9ft)	Wide	up to 26m(85ft)
Vehicle(1.45m/4.8ft)	Wide	up to 34m(113ft)

DORI (EN62676-4 standard)

Detect (25PPM/ 8PPF)	Wide	43.9m(144ft)
Observe (63PPM/ 19PPF)	Wide	17.6m(57.6ft)
Recognize (125PPM/ 38PPF)	Wide	8.8m(28.8ft)

DORI (EN62676-4 standard)

Identify (250PPM/ 76PPF)	Wide	4.4m(14.4ft)
-----------------------------	------	--------------


SPS-A8016

All-In-One Camera



CAD

Unit: mm [inch]



© Hanwha Vision Co.,Ltd. All rights reserved.

Compatible Devices

						
SBP-140CMB	SBP-180CMB	SBP-180CMS	SBP-150CMP	SBP-300CMP	SBP-900CMP	SBP-C15H
						
SBP-C15P	SBP-150CMI	SBP-300CMI	SBP-300CMW1	SBP-900CMW	SBP-300CMTW	SBP-300CMTS
						
SBP-250WMW	SBP-400WMW	SBP-200WMW	SBP-300WMW	SBP-115PFA	SBP-300PMW2	SBP-156KMW
						
SBP-300KMW1	SBP-156LMW1	SBP-300LMW	SBP-150NBW	SPM-4210	SBP-060BA	