IEC | IECEE CB SCHEME

Ref. Certif. No.

SG-OF-10174

IEC SYSTEM FOR MUTUAL RECOGNITION OF TEST CERTIFICATES FOR ELECTRICAL EQUIPMENT (IECEE) CB SCHEME

SYSTEME CEI D'ACCEPTATION MUTUELLE DE CERTIFICATS D'ESSAIS DES EQUIPEMENTS ELECTRIQUES (IECEE)METHODE OC

CB TEST CERTIFICATE
CERTIFICAT D'ESSAI OC

Product Produit	Video recorder (Digital Video Recorder)
Name and address of the applicant Nom et adresse du demandeur	SAMSUNG TECHWIN CO., LTD. 42, Sungju-dong, Changwon-si, Gyeongsangnam-do 641-716, REPUBLIC OF KOREA
Name and address of the manufacturer Nom et adresse du fabricant	SAMSUNG TECHWIN CO., LTD., 42, Sungju-dong, Changwon-si,, Gyeongsangnam-do 641-716, REPUBLIC OF KOREA
Name and address of the factory Nom et adresse de l'usine	SAMSUNG TECHWIN CO., LTD., 42, Sungju-dong, Changwon-si,, Gyeongsangnam-do 641-716, REPUBLIC OF KOREA For further information please see attachment
Ratings and principal characteristics Valeurs nominales et caractéristiques principales	Rated voltage: 100-240 V a.c. Rated frequency: 50/60 Hz Rated current: 4-1.5 A Protection class: I
Trade mark (if any) Marque de fabrique (si elle existe)	SAMSUNG
Model/type Ref. Ref. de type	SRD-1680DN, SRD-1680DP, SRD-880DN, SRD-880DP
Additional information (if necessary) Information complémentaire (si nécessaire)	See Test Report for National and Group Differences.
A sample of the product was tested and found to be in conformity with Un échantillon de ce produit a été essayé et a été considéré conforme à la	IEC 60950-1/A1:2009
as shown in the Test Report Ref. No. which forms part of this certificate comme indiqué dans le Rapport d'essais numéro de référence qui constitue une partie de ce certificat	TÜV SÜD PSB Pte Ltd 077-2324813-000

This CB Test Certificate is issued by the National Certification Body
Ce Certificat d'essai OC est établi par l'Organisme **National de Certification**

Date, 2013-09-05
CBS 13 09 40676 102

(James Jeon)

TÜV SÜD

TÜV SÜD PSB Pte Ltd · 1 Science Park Drive · Singapore 118221

PSB Singapore

Ref. Certif. No.

CB Certificate Ref. No. SG-OF-10174

Additional factory information

Name and address of the factory
Nom et adresse de l'usine

TIANJIN SAMSUNG TECHWIN OPTO-ELECTRONIC CO., LTD.
11 WEILIU RD, MICRO-ELECTRONIC INDUSTRIAL PARK, TEDA, TIANJIN, 300385, People's Republic of China

PSB Singapore

Date: 2013-09-05

Signature: (James Jeon)

Test Report issued under the responsibility of:

NCB TÜV SÜD PSB
1 Science Park Drive, 118221 Singapore

TEST REPORT

IEC 60950-1
Information technology equipment – Safety – Part 1: General requirements

Report Number. .....:	077-2324813-000
Date of issue.....:	2013-09-04
Total number of pages	48 pages
Testing Laboratory.....:	TÜV SÜD Korea Laboratory (TKL)
Address .....:	#315 and 316, MARIO Tower, 222-12, Guro-Dong, Guro-Gu, Seoul 152-050, Republic of Korea
Applicant's name.....:	SAMSUNG TECHWIN CO., LTD. (40676)
Address .....:	42, Sungju-dong, Changwon-si, Gyeongsangnam-do 641-716, Republic of Korea
Manufacturer's name……..:	SAMSUNG TECHWIN CO., LTD. (40676)
Address .....:	42, Sungju-dong, Changwon-si, Gyeongsangnam-do 641-716, Republic of Korea
Test specification:	
Standard .....:	IEC 60950-1:2005 (Second Edition) + Am 1:2009
Test procedure .....:	CB Scheme
Non-standard test method……..:	N/A
Test Report Form No.....:	IEC60950_1C
Test Report Form(s) Originator .....:	SGS Fimko Ltd
Master TRF.....:	Dated 2012-08

Copyright © 2012 Worldwide System for Conformity Testing and Certification of Electrotechnical Equipment and Components (IECEE), Geneva, Switzerland. All rights reserved.

This publication may be reproduced in whole or in part for non-commercial purposes as long as the IECEE is acknowledged as copyright owner and source of the material. IECEE takes no responsibility for and will not assume liability for damages resulting from
the reader's interpretation of the reproduced material due to its placement and context.

If this Test Report Form is used by non-IECEE members, the IECEE/IEC logo and the reference to the CB Scheme procedure shall be removed.

This report is not valid as a CB Test Report unless signed by an approved CB Testing Laboratory and appended to a CB Test Certificate issued by an NCB in accordance with IECEE 02.

Test item description .....:	Digital Video Recorder
Trade Mark .....:	SAMSUNG
Manufacturer .....:	SAMSUNG TECHWIN CO., LTD. (40676) 42, Sungju-dong, Changwon-si, Gyeongsangnam-do 641-716, Republic of Korea
Model/Type reference.....:	SRD-1680DN, SRD-1680DP, SRD-880DN, SRD-880DP
Ratings .....:	AC 100-240 V~, 50/60 Hz, 4-1.5 A

Testing procedure and testing location:		
☒ **Testing Laboratory**:	TÜV SÜD Korea Laboratory (TKL)	
Testing location/ address .....:	#315 and 316, MARIO Tower, 222-12, Guro-Dong, Guro-Gu, Seoul 152-050, Republic of Korea	
☐ **Associated Laboratory:**	N/A	
Testing location/ address .....:	N/A	
Tested by (name + signature) .....:	Kevin Park	.....
Approved by (name + signature) .....:	Charlie Kim	.....
☐ Testing procedure: **TMP**		
Testing location/ address .....:	N/A	
Tested by (name + signature) .....:	N/A	.....
Approved by (name + signature) .....:	N/A	.....
☐ Testing procedure: **WMT**		
Testing location/ address .....:	N/A	
Tested by (name + signature) .....:	N/A	.....
Witnessed by (name + signature) ....:	N/A	.....
Approved by (name + signature) .....:	N/A	.....
☐ Testing procedure: **SMT**		
Testing location/ address .....:	N/A	
Tested by (name + signature) .....:	N/A	.....
Approved by (name + signature) .....:	N/A	.....
Supervised by (name + signature) ...:	N/A	.....
☐ Testing procedure: **RMT**		
Testing location/ address .....:	N/A	
Tested by (name + signature) .....:	N/A	.....
Approved by (name + signature) .....:	N/A	.....
Supervised by (name + signature) ...:	N/A	.....

List of Attachments (including a total number of pages in each attachment):

Attachment 1: 17 pages (European group differences and national differences EN 60950-1:2006+A11:2009+A1:2010+A12:2011)

Attachment 2: 5 pages (Photograph)

Summary of testing:

Tests performed (name of test and test clause):	**Testing location:**
All clauses	TÜV SÜD Korea Laboratory (TKL) #315 and 316, MARIO Tower, 222-12, Guro-Dong, Guro-Gu, Seoul 152-050, Republic of Korea

Summary of compliance with National Differences

List of countries addressed: European group differences.

☒ The product fulfils the requirements of the standard IEC 60950-1:2005+A1:2009 and EN 60950-1:2006+A11:2009+A1:2010+A12:2011.

Copy of marking plate

The artwork below may be only a draft. The use of certification marks on a product must be authorized by the respective NCBs that own these marks.

(Additional requirements for markings. See 1.7 NOTE)






SAMSUNG
DIGITAL VIDEO RECORDER
MODEL:SRD-1680DP
AC 100-240V~ 50/60Hz 4-1.5A
M/C: SRD-1680DP1T/EX Fac. ID: T
Jul 2013 S/N: C5QT6V2Z700001A
ETHERNER ADD: 00-16-6C-7C-B6-6B
SAMSUNG TECHWIN CO.,LTD.
MADE BY SAMSUNG IN CHINA
CLASS 1 LASER PRODUCT
I.T.E.
US LISTED
9T96 E158873
N5167
CAUTION
RISK OF ELECTRIC SHOCK
DO NOT OPEN
Z6804 1328 09A
SAMSUNG
DIGITAL VIDEO RECORDER
MODEL:SRD-880DP
AC 100-240V~ 50/60Hz 4-1.5A
M/C: SRD-880DP1T/EX Fac. ID: T
Jul 2013 S/N: C5QT6V2Z700002A
ETHERNER ADD: 00-16-6C-7C-B6-6C
SAMSUNG TECHWIN CO.,LTD.
MADE BY SAMSUNG IN CHINA
CLASS 1 LASER PRODUCT
I.T.E.
US LISTED
9T96 E158873
N5167
CAUTION
RISK OF ELECTRIC SHOCK
DO NOT OPEN
Z6804 1328 09A

Test item particulars	
Equipment mobility.....	[X] movable [] hand-held [] transportable [] stationary [] for building-in [] direct plug-in
Connection to the mains	[X] pluggable equipment [X] type A [] type B [] permanent connection [X] detachable power supply cord [] non-detachable power supply cord [] not directly connected to the mains
Operating condition.....	[X] continuous [] rated operating / resting time:
Access location	[X] operator accessible [] restricted access location
Over voltage category (OVC)	[] OVC I [X] OVC II [] OVC III [] OVC IV [] other:
Mains supply tolerance (%) or absolute mains supply values	-10 %, +10 %
Tested for IT power systems	[] Yes [X] No
IT testing, phase-phase voltage (V)	N/A
Class of equipment	[X] Class I [] Class II [] Class III [] Not classified
Considered current rating of protective device as part of the building installlation (A)	16 A
Pollution degree (PD)	[] PD 1 [X] PD 2 [] PD 3
IP protection class	IPX0
Altitude during operation (m)	Up to 2000 m
Altitude of test laboratory (m)	70 m
Mass of equipment (kg)	6.8 kg
Possible test case verdicts:	
- test case does not apply to the test object ..... :	N/A (or N)
- test object does meet the requirement..... :	P (Pass)
- test object does not meet the requirement..... :	F (Fail)
Testing::	
Date of receipt of test item ..... :	2013-07-03
Date(s) of performance of tests ..... :	2013-08-14 to 2013-08-27

General remarks:

The test results presented in this report relate only to the object tested.
This report shall not be reproduced, except in full, without the written approval of the Issuing testing laboratory.
"(see Enclosure #)" refers to additional information appended to the report.
"(see appended table)" refers to a table appended to the report.

Throughout this report a ☐ comma / ☒ point is used as the decimal separator.

Manufacturer's Declaration per sub-clause 6.2.5 of IECEE 02:	
The application for obtaining a CB Test Certificate includes more than one factory location and a declaration from the Manufacturer stating that the sample(s) submitted for evaluation is (are) representative of the products from each factory has been provided.....:	☒ Yes ☐ Not applicable
When differences exist; they shall be identified in the General product information section.	
Name and address of factory (ies) ..... :	1. SAMSUNG TECHWIN CO., LTD. (40676) 42, Sungju-dong, Changwon-si, Gyeongsangnam-do 641-716, Republic of Korea 2. TIANJIN SAMSUNG TECHWIN OPTO-ELECTRONIC CO., LTD. (70297) 11 WEILIU RD, MICRO-ELECTRONIC INDUSTRIAL PARK, TEDA, TIANJIN 300385, People's Republic of China

General product information:

1. Model SRD-1680DN is basic model, which was tested and it was the representative of the other models.
2. Model SRD-1680DP, SRD-880DN and SRD-880DP are identical to basic model SRD-1680DN except for model designation, Camera input channel and Video signal as below;

Model name	Camera input channel	Video signal
SRD-1680DN	16	NTSC
SRD-1680DP	16	PAL
SRD-880DN	8	NTSC
SRD-880DP	8	PAL

3. The maximum ambient temperature permitted by the manufacturer (Tma): 40 °C

Abbreviations used in the report:

- normal conditions	N.C.	- single fault conditions	S.F.C
- functional insulation	OP	- basic insulation	BI
- double insulation	DI	- supplementary insulation	SI
- between parts of opposite polarity	BOP	- reinforced insulation	RI

Indicate used abbreviations (if any)

IEC 60950-1			
Clause	Requirement + Test	Result - Remark	Verdict

1	**GENERAL**		P

1.5	**Components**		P
1.5.1	General		P
	Comply with IEC 60950-1 or relevant component standard	(see appended table 1.5.1)	P
1.5.2	Evaluation and testing of components	Certified components are used in accordance with their ratings, certifications and they comply with applicable parts of this standard. Components not certified are used in accordance with their ratings and they comply with applicable parts of IEC 60950-1 and the relevant component standard. Components, for which no relevant IEC-standard exists, have been tested under the conditions occurring in the equipment, using applicable parts of IEC 60950-1.	P
1.5.3	Thermal controls	No thermal controls.	N/A
1.5.4	Transformers	Evaluated during separate certification of power supply.	N/A
1.5.5	Interconnecting cables	The interconnecting cables contain only SELV.	P
1.5.6	Capacitors bridging insulation	Evaluated during separate certification of power supply.	N/A
1.5.7	Resistors bridging insulation	Evaluated during separate certification of power supply.	N/A
1.5.7.1	Resistors bridging functional, basic or supplementary insulation		N/A
1.5.7.2	Resistors bridging double or reinforced insulation between a.c. mains and other circuits		N/A
1.5.7.3	Resistors bridging double or reinforced insulation between a.c. mains and antenna or coaxial cable		N/A
1.5.8	Components in equipment for IT power systems		N/A
1.5.9	Surge suppressors	Evaluated during separate certification of power supply.	N/A
1.5.9.1	General		N/A
1.5.9.2	Protection of VDRs		N/A
1.5.9.3	Bridging of functional insulation by a VDR		N/A

IEC 60950-1			
Clause	Requirement + Test	Result - Remark	Verdict
1.5.9.4	Bridging of basic insulation by a VDR		N/A
1.5.9.5	Bridging of supplementary, double or reinforced insulation by a VDR		N/A
1.6	**Power interface**		P
1.6.1	AC power distribution systems		P
1.6.2	Input current	(see appended table 1.6.2)	P
1.6.3	Voltage limit of hand-held equipment	No hand-held equipment.	N/A
1.6.4	Neutral conductor	Neutral is insulated from earth with basic insulation throughout the equipment.	P
1.7	**Marking and instructions**		P
1.7.1	Power rating and identification markings		P
1.7.1.1	Power rating marking		P
	Multiple mains supply connections.....:	No multiple mains	N/A
	Rated voltage(s) or voltage range(s) (V) .....:	AC 100-240 V~	P
	Symbol for nature of supply, for d.c. only .....:	The equipment is for a.c. supply.	N/A
	Rated frequency or rated frequency range (Hz) ....:	50/60 Hz	P
	Rated current (mA or A) .....:	4-1.5 A	P
1.7.1.2	Identification markings		P
	Manufacturer's name or trade-mark or identification mark .....:	SAMSUNG	P
	Model identification or type reference .....:	SRD-1680DN, SRD-1680DP, SRD-880DN, SRD-880DP	P
	Symbol for Class II equipment only .....:	Class I equipment.	N/A
	Other markings and symbols .....:	(see the copy of marking plate)	P
1.7.2	Safety instructions and marking		P
1.7.2.1	General		P
1.7.2.2	Disconnect devices	Appliance inlet	P
1.7.2.3	Overcurrent protective device	Pluggable equipment type A	N/A
1.7.2.4	IT power distribution systems		N/A
1.7.2.5	Operator access with a tool		N/A
1.7.2.6	Ozone		N/A
1.7.3	Short duty cycles	The equipment is intended for continuous operation.	N/A

IEC 60950-1			
Clause	Requirement + Test	Result - Remark	Verdict
1.7.4	Supply voltage adjustment .....:	No voltage selector.	N/A
	Methods and means of adjustment; reference to installation instructions .....:		N/A
1.7.5	Power outlets on the equipment .....:		N/A
1.7.6	Fuse identification (marking, special fusing characteristics, cross-reference) .....:	Evaluated during separate certification of power supply.	N/A
1.7.7	Wiring terminals		N/A
1.7.7.1	Protective earthing and bonding terminals .....:	Evaluated during separate certification of power supply.	N/A
1.7.7.2	Terminals for a.c. mains supply conductors	Appliance inlet used.	N/A
1.7.7.3	Terminals for d.c. mains supply conductors		N/A
1.7.8	Controls and indicators		P
1.7.8.1	Identification, location and marking .....:	The function of controls affecting safety is obvious without knowledge of language etc.	P
1.7.8.2	Colours .....:	Only functional user colour.	P
1.7.8.3	Symbols according to IEC 60417 .....:	The switch is marked with the symbol for "stand-by" (IEC 60417-5009).	P
1.7.8.4	Markings using figures .....:	No controls.	N/A
1.7.9	Isolation of multiple power sources .....:	No multiple power sources.	N/A
1.7.10	Thermostats and other regulating devices .....:	No such devices	N/A
1.7.11	Durability	The marking withstand the required test.	P
1.7.12	Removable parts	No removable parts.	N/A
1.7.13	Replaceable batteries .....:	The lithium battery is not placed in an operator access area. The required warning is in the installation/operation manual	P
	Language(s) .....:	English	—
1.7.14	Equipment for restricted access locations.....:	Equipment not intended for installation in restricted access locations.	N/A

IEC 60950-1			
Clause	Requirement + Test	Result - Remark	Verdict

2	**PROTECTION FROM HAZARDS**		P
2.1	Protection from electric shock and energy hazards		P
2.1.1	Protection in operator access areas		P
2.1.1.1	Access to energized parts	No part of ELV or hazardous voltages are accessible.	P
	Test by inspection .....:	No hazard.	P
	Test with test finger (Figure 2A) .....:	No hazard.	P
	Test with test pin (Figure 2B) .....:	No hazard.	P
	Test with test probe (Figure 2C) .....:	No TNV circuits	N/A
2.1.1.2	Battery compartments	No battery compartments.	N/A
2.1.1.3	Access to ELV wiring	No internal wiring at ELV accessible to the operator.	N/A
	Working voltage (Vpeak or Vrms); minimum distance through insulation (mm)		—
2.1.1.4	Access to hazardous voltage circuit wiring		N/A
2.1.1.5	Energy hazards .....:	No energy hazard in operator access area.	P
2.1.1.6	Manual controls	No shafts of knobs etc. at ELV or hazardous voltage.	N/A
2.1.1.7	Discharge of capacitors in equipment		P
	Measured voltage (V); time-constant (s) .....:	0 V d.c. at 1 s	—
2.1.1.8	Energy hazards – d.c. mains supply		N/A
	a) Capacitor connected to the d.c. mains supply ..:		N/A
	b) Internal battery connected to the d.c. mains supply .....:		N/A
2.1.1.9	Audio amplifiers .....:	No audio amplifiers.	N/A
2.1.2	Protection in service access areas	Checked by inspection, unintentional contact is unlikely during service operations.	P
2.1.3	Protection in restricted access locations	Equipment not intended for installation in restricted access locations.	N/A

2.2	**SELV circuits**		P
2.2.1	General requirements	Evaluated during separate certification of power supply.	P
2.2.2	Voltages under normal conditions (V) .....:	<SELV	P
2.2.3	Voltages under fault conditions (V) .....:	<SELV	P

IEC 60950-1			
Clause	Requirement + Test	Result - Remark	Verdict
2.2.4	Connection of SELV circuits to other circuits .....:	SELV circuits are only connected to other SELV circuits.	P
2.3	**TNV circuits**		N/A
2.3.1	Limits	No TNV circuits	N/A
	Type of TNV circuits .....:		—
2.3.2	Separation from other circuits and from accessible parts		N/A
2.3.2.1	General requirements		N/A
2.3.2.2	Protection by basic insulation		N/A
2.3.2.3	Protection by earthing		N/A
2.3.2.4	Protection by other constructions .....:		N/A
2.3.3	Separation from hazardous voltages		N/A
	Insulation employed.....:		—
2.3.4	Connection of TNV circuits to other circuits		N/A
	Insulation employed.....:		—
2.3.5	Test for operating voltages generated externally		N/A
2.4	**Limited current circuits**		N/A
2.4.1	General requirements	No limited current circuits	N/A
2.4.2	Limit values		N/A
	Frequency (Hz) .....:		—
	Measured current (mA) .....:		—
	Measured voltage (V) .....:		—
	Measured circuit capacitance (nF or µF).....:		—
2.4.3	Connection of limited current circuits to other circuits		N/A
2.5	**Limited power sources**	(see appended table 2.5)	P
	a) Inherently limited output		P
	b) Impedance limited output	Approved power distribution Switch provided for USB ports (see appended table 1.5.1)	P
	c) Regulating network limited output under normal operating and single fault condition		N/A
	d) Overcurrent protective device limited output		N/A

IEC 60950-1			
Clause	Requirement + Test	Result - Remark	Verdict

	Max. output voltage (V), max. output current (A), max. apparent power (VA) .....:	(see appended table 2.5)	—
	Current rating of overcurrent protective device (A) .:		—
	Use of integrated circuit (IC) current limiters		—

2.6	**Provisions for earthing and bonding**		P
2.6.1	Protective earthing	Accessible conductive parts are reliably connected to protective earth.	P
2.6.2	Functional earthing	Functional earthing is separated from hazardous voltages by basic insulation and protective earth.	P
2.6.3	Protective earthing and protective bonding conductors		P
2.6.3.1	General		P
2.6.3.2	Size of protective earthing conductors	Evaluated during separate certification of power supply.	N/A
	Rated current (A), cross-sectional area (mm^2), AWG.....:		—
2.6.3.3	Size of protective bonding conductors	Evaluated during separate certification of power supply.	N/A
	Rated current (A), cross-sectional area (mm^2), AWG.....:		—
	Protective current rating (A), cross-sectional area (mm^2), AWG.....:		—
2.6.3.4	Resistance of earthing conductors and their terminations; resistance (Ω), voltage drop (V), test current (A), duration (min) .....:	From the appliance inlet to the chassis : 0.016 Ω, 0.51 V, 32 A, 2 min 0.019 Ω, 0.76 V, 40 A, 2 min	P
2.6.3.5	Colour of insulation.....:	Evaluated during separate certification of power supply.	N/A
2.6.4	Terminals		P
2.6.4.1	General		P
2.6.4.2	Protective earthing and bonding terminals		N/A
	Rated current (A), type, nominal thread diameter (mm).....:		—
2.6.4.3	Separation of the protective earthing conductor from protective bonding conductors	Appliance inlet used.	P
2.6.5	Integrity of protective earthing		P
2.6.5.1	Interconnection of equipment		N/A

IEC 60950-1			
Clause	Requirement + Test	Result - Remark	Verdict
2.6.5.2	Components in protective earthing conductors and protective bonding conductors	There are no switches or overcurrent protective devices in the protective earthing / bonding conductors.	P
2.6.5.3	Disconnection of protective earth	Appliance inlet used.	P
2.6.5.4	Parts that can be removed by an operator	No operator removable parts with protective earth connection except supply cord.	P
2.6.5.5	Parts removed during servicing	Protective earthed parts cannot be removed in a way which impairs safety.	P
2.6.5.6	Corrosion resistance	Evaluated during separate certification of power supply.	N/A
2.6.5.7	Screws for protective bonding	Evaluated during separate certification of power supply.	N/A
2.6.5.8	Reliance on telecommunication network or cable distribution system		N/A
2.7	**Overcurrent and earth fault protection in primary circuits**		P
2.7.1	Basic requirements	Protective devices are integrated in the equipment.	P
	Instructions when protection relies on building installation		N/A
2.7.2	Faults not simulated in 5.3.7		N/A
2.7.3	Short-circuit backup protection	Pluggable type A equipment	P
2.7.4	Number and location of protective devices .....:	Evaluated during separate certification of power supply.	N/A
2.7.5	Protection by several devices		N/A
2.7.6	Warning to service personnel.....:		N/A
2.8	**Safety interlocks**		N/A
2.8.1	General principles	No safety interlocks	N/A
2.8.2	Protection requirements		N/A
2.8.3	Inadvertent reactivation		N/A
2.8.4	Fail-safe operation		N/A
	Protection against extreme hazard		N/A
2.8.5	Moving parts		N/A
2.8.6	Overriding		N/A
2.8.7	Switches, relays and their related circuits		N/A

IEC 60950-1			
Clause	Requirement + Test	Result - Remark	Verdict
2.8.7.1	Separation distances for contact gaps and their related circuits (mm) .....:		N/A
2.8.7.2	Overload test		N/A
2.8.7.3	Endurance test		N/A
2.8.7.4	Electric strength test		N/A
2.8.8	Mechanical actuators		N/A
2.9	**Electrical insulation**		P
2.9.1	Properties of insulating materials	Neither natural rubber, materials containing asbestos nor hygroscopic materials are used as insulation.	P
2.9.2	Humidity conditioning	48 h	P
	Relative humidity (%), temperature (°C) .....:	93 %, 30 °C	—
2.9.3	Grade of insulation	Insulation is considered to be functional, basic, supplementary, reinforced or double insulation.	P
2.9.4	Separation from hazardous voltages	The accessible conductive parts, including SELV circuits and their related windings, are separated from parts at hazardous voltage by double insulation or reinforced insulation.	P
	Method(s) used .....:	Method 1 is used.	—
2.10	**Clearances, creepage distances and distances through insulation**		N/A
2.10.1	General	Evaluated during separate certification of power supply.	N/A
2.10.1.1	Frequency .....:		N/A
2.10.1.2	Pollution degrees .....:		N/A
2.10.1.3	Reduced values for functional insualtion		N/A
2.10.1.4	Intervening unconnected conductive parts		N/A
2.10.1.5	Insulation with varying dimensions		N/A
2.10.1.6	Special separation requirements		N/A
2.10.1.7	Insulation in circuits generating starting pulses		N/A
2.10.2	Determination of working voltage		N/A
2.10.2.1	General		N/A
2.10.2.2	RMS working voltage		N/A

IEC 60950-1			
Clause	Requirement + Test	Result - Remark	Verdict
2.10.2.3	Peak working voltage		N/A
2.10.3	Clearances	Evaluated during separate certification of power supply.	N/A
2.10.3.1	General		N/A
2.10.3.2	Mains transient voltages		N/A
	a) AC mains supply .....:		N/A
	b) Earthed d.c. mains supplies .....:		N/A
	c) Unearthed d.c. mains supplies .....:		N/A
	d) Battery operation .....:		N/A
2.10.3.3	Clearances in primary circuits	Evaluated during separate certification of power supply.	N/A
2.10.3.4	Clearances in secondary circuits		N/A
2.10.3.5	Clearances in circuits having starting pulses		N/A
2.10.3.6	Transients from a.c. mains supply .....:		N/A
2.10.3.7	Transients from d.c. mains supply .....:		N/A
2.10.3.8	Transients from telecommunication networks and cable distribution systems .....:		N/A
2.10.3.9	Measurement of transient voltage levels		N/A
	a) Transients from a mains suplply		N/A
	For an a.c. mains supply .....:		N/A
	For a d.c. mains supply .....:		N/A
	b) Transients from a telecommunication network :		N/A
2.10.4	Creepage distances		N/A
2.10.4.1	General		N/A
2.10.4.2	Material group and caomparative tracking index		N/A
	CTI tests .....:		—
2.10.4.3	Minimum creepage distances		N/A
2.10.5	Solid insulation		N/A
2.10.5.1	General	Evaluated during separate certification of power supply.	N/A
2.10.5.2	Distances through insulation		N/A
2.10.5.3	Insulating compound as solid insulation		N/A
2.10.5.4	Semiconductor devices		N/A
2.10.5.5.	Cemented joints		N/A
2.10.5.6	Thin sheet material – General		N/A
2.10.5.7	Separable thin sheet material		N/A
	Number of layers (pcs) .....:		—

IEC 60950-1			
Clause	Requirement + Test	Result - Remark	Verdict
2.10.5.8	Non-separable thin sheet material		N/A
2.10.5.9	Thin sheet material – standard test procedure		N/A
	Electric strength test		—
2.10.5.10	Thin sheet material – alternative test procedure		N/A
	Electric strength test		—
2.10.5.11	Insulation in wound components		N/A
2.10.5.12	Wire in wound components		N/A
	Working voltage .....:		N/A
	a) Basic insulation not under stress .....:		N/A
	b) Basic, supplemetary, reinforced insulation .....:		N/A
	c) Compliance with Annex U .....:		N/A
	Two wires in contact inside wound component; angle between 45° and 90° .....:		N/A
2.10.5.13	Wire with solvent-based enamel in wound components		N/A
	Electric strength test		—
	Routine test		N/A
2.10.5.14	Additional insulation in wound components		N/A
	Working voltage .....:		N/A
	- Basic insulation not under stress .....:		N/A
	- Supplemetary, reinforced insulation .....:		N/A
2.10.6	Construction of printed boards		N/A
2.10.6.1	Uncoated printed boards		N/A
2.10.6.2	Coated printed boards		N/A
2.10.6.3	Insulation between conductors on the same inner surface of a printed board		N/A
2.10.6.4	Insulation between conductors on different layers of a printed board		N/A
	Distance through insulation		N/A
	Number of insulation layers (pcs).....:		N/A
2.10.7	Component external terminations		N/A
2.10.8	Tests on coated printed boards and coated components		N/A
2.10.8.1	Sample preparation and preliminary inspection		N/A
2.10.8.2	Thermal conditioning		N/A
2.10.8.3	Electric strength test		N/A
2.10.8.4	Abrasion resistance test		N/A

IEC 60950-1			
Clause	Requirement + Test	Result - Remark	Verdict
2.10.9	Thermal cycling		N/A
2.10.10	Test for Pollution Degree 1 environment and insulating compound		N/A
2.10.11	Tests for semiconductor devices and cemented joints		N/A
2.10.12	Enclosed and sealed parts		N/A

IEC 60950-1			
Clause	Requirement + Test	Result - Remark	Verdict
3	**WIRING, CONNECTIONS AND SUPPLY**		P
3.1	General		P
3.1.1	Current rating and overcurrent protection	Adequate cross sectional areas on internal wiring.	P
3.1.2	Protection against mechanical damage	Wireways are smooth and free from edges.	P
3.1.3	Securing of internal wiring	Internal wiring is secured against excessive strain, loosening of terminals and damage to the conductor insulation.	P
3.1.4	Insulation of conductors	Insulation on internal conductors is considered to be of adequate quality and suitable for the application and the working voltage involved.	P
3.1.5	Beads and ceramic insulators	No beads or similar ceramic insulators on conductors.	N/A
3.1.6	Screws for electrical contact pressure	Electrical screw connection is only connecting protective earth to chassis. Metal screw engages more than 2 threads. Screws made of insulating material are not used where electrical connections, including protective earthing are involved.	P
3.1.7	Insulating materials in electrical connections	No contact pressure through insulating materials.	P
3.1.8	Self-tapping and spaced thread screws	Thread-cutting or space thread screws are not used for electrical connections.	P
3.1.9	Termination of conductors		N/A
	10 N pull test		N/A
3.1.10	Sleeving on wiring	Sleeves are not used as supplementary insulation.	N/A

3.2	**Connection to a mains supply**		P
3.2.1	Means of connection	Appliance inlet	P
3.2.1.1	Connection to an a.c. mains supply		P
3.2.1.2	Connection to a d.c. mains supply		N/A
3.2.2	Multiple supply connections	Only one supply connection.	N/A

IEC 60950-1			
Clause	Requirement + Test	Result - Remark	Verdict
3.2.3	Permanently connected equipment	The equipment is not intended for permanent connection to the mains.	N/A
	Number of conductors, diameter of cable and conduits (mm) .....:		—
3.2.4	Appliance inlets	(see appended table 1.5.1)	P
3.2.5	Power supply cords		P
3.2.5.1	AC power supply cords		P
	Type .....:	(see appended table 1.5.1)	—
	Rated current (A), cross-sectional area (mm^2), AWG .....:	4-1.5 A, Min. 0.75 mm^2, Min. 18 AWG (see appended table 1.5.1)	—
3.2.5.2	DC power supply cords		N/A
3.2.6	Cord anchorages and strain relief	Equipment provided with an appliance inlet.	N/A
	Mass of equipment (kg), pull (N) .....:		—
	Longitudinal displacement (mm) .....:		—
3.2.7	Protection against mechanical damage		N/A
3.2.8	Cord guards		N/A
	Diameter or minor dimension D (mm); test mass (g) .....:		—
	Radius of curvature of cord (mm).....:		—
3.2.9	Supply wiring space	Equipment provided with an appliance inlet.	N/A

3.3	**Wiring terminals for connection of external conductors**		N/A
3.3.1	Wiring terminals	Appliance inlet provided.	N/A
3.3.2	Connection of non-detachable power supply cords		N/A
3.3.3	Screw terminals		N/A
3.3.4	Conductor sizes to be connected		N/A
	Rated current (A), cord/cable type, cross-sectional area (mm^2) .....:		—
3.3.5	Wiring terminal sizes		N/A
	Rated current (A), type, nominal thread diameter (mm) .....:		—
3.3.6	Wiring terminal design		N/A
3.3.7	Grouping of wiring terminals		N/A
3.3.8	Stranded wire		N/A

IEC 60950-1			
Clause	Requirement + Test	Result - Remark	Verdict

3.4	**Disconnection from the mains supply**		P
3.4.1	General requirement		P
3.4.2	Disconnect devices	Appliance coupler	P
3.4.3	Permanently connected equipment	Not permanently connected equipment.	N/A
3.4.4	Parts which remain energized	No parts remain energized.	N/A
3.4.5	Switches in flexible cords		N/A
3.4.6	Number of poles - single-phase and d.c. equipment	The disconnect device disconnects both poles simultaneously.	P
3.4.7	Number of poles - three-phase equipment	Single phase equipment.	N/A
3.4.8	Switches as disconnect devices		N/A
3.4.9	Plugs as disconnect devices		N/A
3.4.10	Interconnected equipment		N/A
3.4.11	Multiple power sources		N/A

3.5	**Interconnection of equipment**		P
3.5.1	General requirements		P
3.5.2	Types of interconnection circuits .....:	SELV circuit – SELV circuit	P
3.5.3	ELV circuits as interconnection circuits	No ELV interconnections.	N/A
3.5.4	Data ports for additional equipment	see clause 2.5	P

IEC 60950-1			
Clause	Requirement + Test	Result - Remark	Verdict

4	**PHYSICAL REQUIREMENTS**		P
4.1	Stability		P
	Angle of 10°	Unit does not overbalance at 10°.	P
	Test force (N) .....:		N/A

4.2	**Mechanical strength**		P
4.2.1	General		P
	Rack-mounted equipment.		N/A
4.2.2	Steady force test, 10 N	Evaluated during separate certification of power supply.	N/A
4.2.3	Steady force test, 30 N	No hazard.	P
4.2.4	Steady force test, 250 N	No hazard.	P
4.2.5	Impact test		P
	Fall test	No hazard.	P
	Swing test	No hazard.	P
4.2.6	Drop test; height (mm) .....:		N/A
4.2.7	Stress relief test	Test is carried out at 70 °C / 7 h. No risk of shrinkage or distortion on enclosures due to release of internal stresses.	P
4.2.8	Cathode ray tubes		N/A
	Picture tube separately certified .....:		N/A
4.2.9	High pressure lamps	No high pressure lamps in the equipment.	N/A
4.2.10	Wall or ceiling mounted equipment; force (N) .....:		N/A

4.3	**Design and construction**		P
4.3.1	Edges and corners	All edges and corners are rounded and smoothed.	P
4.3.2	Handles and manual controls; force (N)..... :		N/A
4.3.3	Adjustable controls		N/A
4.3.4	Securing of parts	No loosening of parts impairing creepage distances or clearances is likely to occur.	P
4.3.5	Connection by plugs and sockets		N/A
4.3.6	Direct plug-in equipment	No direct plug-in equipment.	N/A
	Torque .....:		—

IEC 60950-1			
Clause	Requirement + Test	Result - Remark	Verdict
	Compliance with the relevant mains plug standard .....:		N/A
4.3.7	Heating elements in earthed equipment	No heating elements provided.	N/A
4.3.8	Batteries	(see appended table 4.3.8)	P
	- Overcharging of a rechargeable battery		N/A
	- Unintentional charging of a non-rechargeable battery		P
	- Reverse charging of a rechargeable battery		N/A
	- Excessive discharging rate for any battery		N/A
4.3.9	Oil and grease		N/A
4.3.10	Dust, powders, liquids and gases		N/A
4.3.11	Containers for liquids or gases		N/A
4.3.12	Flammable liquids .....:		N/A
	Quantity of liquid (l) .....:		N/A
	Flash point (°C) .....:		N/A
4.3.13	Radiation		P
4.3.13.1	General		P
4.3.13.2	Ionizing radiation		N/A
	Measured radiation (pA/kg) .....:		—
	Measured high-voltage (kV) .....:		—
	Measured focus voltage (kV) .....:		—
	CRT markings .....:		—
4.3.13.3	Effect of ultraviolet (UV) radiation on materials		N/A
	Part, property, retention after test, flammability classification .....:		N/A
4.3.13.4	Human exposure to ultraviolet (UV) radiation .....:		N/A
4.3.13.5	Lasers (including laser diodes) and LEDs		P
4.3.13.5.1	Lasers (including laser laser diodes)	Certified DVD Writer drive used. (see appended table 1.5.1)	P
	Laser class .....:	Class 1	—
4.3.13.5.2	Light emitting diodes (LEDs)	The LED used for functional in dicator.	—
4.3.13.6	Other types .....:		N/A

4.4	**Protection against hazardous moving parts**		P
4.4.1	General		P

IEC 60950-1			
Clause	Requirement + Test	Result - Remark	Verdict
4.4.2	Protection in operator access areas .....:		N/A
	Household and home/office document/media shredders		N/A
4.4.3	Protection in restricted access locations .....:		N/A
4.4.4	Protection in service access areas		N/A
4.4.5	Protection against moving fan blades		P
4.4.5.1	General		P
	Not considered to cause pain or injury. a)……..:	The moving fan blade of cooling fan is classified as a). (see appended table 1.5.1)	P
	Is considered to cause pain, not injury. b) ……:		N/A
	Considered to cause injury. c) ……:		N/A
4.4.5.2	Protection for users	The cooling fan is not accessible for user.	N/A
	Use of symbol or warning ……:		N/A
4.4.5.3	Protection for service persons	The moving fan blade of cooling fan is classified as a)	P
	Use of symbol or warning ……:		N/A

4.5	**Thermal requirements**		P
4.5.1	General		P
4.5.2	Temperature tests	(see appended table 4.5)	P
	Normal load condition per Annex L .....:	L.7	—
4.5.3	Temperature limits for materials	(see appended table 4.5)	P
4.5.4	Touch temperature limits	(see appended table 4.5)	P
4.5.5	Resistance to abnormal heat .....:	Evaluated during separate certification of power supply.	N/A

4.6	**Openings in enclosures**		P
4.6.1	Top and side openings		P
	Dimensions (mm) .....:	No hazardous parts within 5° angle.	—
4.6.2	Bottoms of fire enclosures		P
	Construction of the bottom, dimensions (mm) .....:	Fire enclosure construction is considered to comply with the requirements. No bottom openings within 5° angle.	—
4.6.3	Doors or covers in fire enclosures		N/A

IEC 60950-1			
Clause	Requirement + Test	Result - Remark	Verdict
4.6.4	Openings in transportable equipment		N/A
4.6.4.1	Constructional design measures		N/A
	Dimensions (mm) .....:		—
4.6.4.2	Evaluation measures for larger openings		N/A
4.6.4.3	Use of metallized parts		N/A
4.6.5	Adhesives for constructional purposes		N/A
	Conditioning temperature (°C), time (weeks) .....:		—
4.7	**Resistance to fire**		P
4.7.1	Reducing the risk of ignition and spread of flame		P
	Method 1, selection and application of components wiring and materials	(see appended table 4.7)	P
	Method 2, application of all of simulated fault condition tests	(see appended table 5.3)	P
4.7.2	Conditions for a fire enclosure		P
4.7.2.1	Parts requiring a fire enclosure		P
4.7.2.2	Parts not requiring a fire enclosure		N/A
4.7.3	Materials		P
4.7.3.1	General	(see appended table 1.5.1)	P
4.7.3.2	Materials for fire enclosures		P
4.7.3.3	Materials for components and other parts outside fire enclosures		P
4.7.3.4	Materials for components and other parts inside fire enclosures		P
4.7.3.5	Materials for air filter assemblies	No air filters in the equipment.	N/A
4.7.3.6	Materials used in high-voltage components	No high-voltage components.	N/A

IEC 60950-1			
Clause	Requirement + Test	Result - Remark	Verdict

5	**ELECTRICAL REQUIREMENTS AND SIMULATED ABNORMAL CONDITIONS**		**P**
5.1	**Touch current and protective conductor current**		P
5.1.1	General		P
5.1.2	Configuration of equipment under test (EUT)		P
5.1.2.1	Single connection to an a.c. mains supply		P
5.1.2.2	Redundant multiple connections to an a.c. mains supply		P
5.1.2.3	Simultaneous multiple connections to an a.c. mains supply		P
5.1.3	Test circuit		P
5.1.4	Application of measuring instrument	Measuring instrument D.1 is used.	P
5.1.5	Test procedure		P
5.1.6	Test measurements		P
	Supply voltage (V) .....:	(see appended table 5.1)	—
	Measured touch current (mA) .....:	(see appended table 5.1)	—
	Max. allowed touch current (mA) .....:	(see appended table 5.1)	—
	Measured protective conductor current (mA) .....:		—
	Max. allowed protective conductor current (mA)...:		—
5.1.7	Equipment with touch current exceeding 3,5 mA		N/A
5.1.7.1	General .....:		N/A
5.1.7.2	Simultaneous multiple connections to the supply		N/A
5.1.8	Touch currents to telecommunication networks and cable distribution systems and from telecommunication networks	Not connected to a telecommunication network and cable distribution systems	N/A
5.1.8.1	Limitation of the touch current to a telecommunication network or to a cable distribution system		N/A
	Supply voltage (V) .....:		—
	Measured touch current (mA) .....:		—
	Max. allowed touch current (mA) .....:		—
5.1.8.2	Summation of touch currents from telecommunication networks	Not connected to a telecommunication network.	N/A
	a) EUT with earthed telecommunication ports .....:		N/A
	b) EUT whose telecommunication ports have no reference to protective earth		N/A

5.2	**Electric strength**	P

IEC 60950-1			
Clause	Requirement + Test	Result - Remark	Verdict
5.2.1	General	(see appended table 5.2)	P
5.2.2	Test procedure	(see appended table 5.2)	P
5.3	**Abnormal operating and fault conditions**		P
5.3.1	Protection against overload and abnormal operation	(see appended table 5.3)	P
5.3.2	Motors	Approved DC fan used.	N/A
5.3.3	Transformers	Evaluated during separate certification of power supply.	N/A
5.3.4	Functional insulation.....:	c)	P
5.3.5	Electromechanical components		N/A
5.3.6	Audio amplifiers in ITE .....:		N/A
5.3.7	Simulation of faults	(see appended table 5.3)	P
5.3.8	Unattended equipment		N/A
5.3.9	Compliance criteria for abnormal operating and fault conditions		P
5.3.9.1	During the tests	No fire, emission of molten metal or deformation was noted during the tests.	P
5.3.9.2	After the tests	No reduction of clearance and creepage distances. Electric strength test is made on basic, supplementary and reinforced insulation.	P

IEC 60950-1			
Clause	Requirement + Test	Result - Remark	Verdict

6	**CONNECTION TO TELECOMMUNICATION NETWORKS**		N/A
6.1	Protection of telecommunication network service persons, and users of other equipment connected to the network, from hazards in the equipment		N/A
6.1.1	Protection from hazardous voltages		N/A
6.1.2	Separation of the telecommunication network from earth		N/A
6.1.2.1	Requirements	No TNV circuits.	N/A
	Supply voltage (V) .....:		—
	Current in the test circuit (mA) .....:		—
6.1.2.2	Exclusions .....:		N/A

6.2	**Protection of equipment users from overvoltages on telecommunication networks**		N/A
6.2.1	Separation requirements		N/A
6.2.2	Electric strength test procedure		N/A
6.2.2.1	Impulse test		N/A
6.2.2.2	Steady-state test		N/A
6.2.2.3	Compliance criteria		N/A

6.3	**Protection of the telecommunication wiring system from overheating**		N/A
	Max. output current (A) .....:		—
	Current limiting method .....:		—

IEC 60950-1			
Clause	Requirement + Test	Result - Remark	Verdict

7	**CONNECTION TO CABLE DISTRIBUTION SYSTEMS**		N/A
7.1	General	Not connected to a cable distribution system.	N/A
7.2	Protection of cable distribution system service persons, and users of other equipment connected to the system, from hazardous voltages in the equipment		N/A
7.3	Protection of equipment users from overvoltages on the cable distribution system		N/A
7.4	Insulation between primary circuits and cable distribution systems		N/A
7.4.1	General		N/A
7.4.2	Voltage surge test		N/A
7.4.3	Impulse test		N/A

IEC 60950-1			
Clause	Requirement + Test	Result - Remark	Verdict

A	**ANNEX A, TESTS FOR RESISTANCE TO HEAT AND FIRE**		N/A
A.1	Flammability test for fire enclosures of movable equipment having a total mass exceeding 18 kg, and of stationary equipment (see 4.7.3.2)		N/A
A.1.1	Samples .....:		—
	Wall thickness (mm).....:		—
A.1.2	Conditioning of samples; temperature (°C) .....:		N/A
A.1.3	Mounting of samples .....:		N/A
A.1.4	Test flame (see IEC 60695-11-3)		N/A
	Flame A, B, C or D .....:		—
A.1.5	Test procedure		N/A
A.1.6	Compliance criteria		N/A
	Sample 1 burning time (s) .....:		—
	Sample 2 burning time (s) .....:		—
	Sample 3 burning time (s) .....:		—
A.2	Flammability test for fire enclosures of movable equipment having a total mass not exceeding 18 kg, and for material and components located inside fire enclosures (see 4.7.3.2 and 4.7.3.4)		N/A
A.2.1	Samples, material.....:		—
	Wall thickness (mm).....:		—
A.2.2	Conditioning of samples; temperature (°C) .....:		N/A
A.2.3	Mounting of samples .....:		N/A
A.2.4	Test flame (see IEC 60695-11-4)		N/A
	Flame A, B or C .....:		—
A.2.5	Test procedure		N/A
A.2.6	Compliance criteria		N/A
	Sample 1 burning time (s) .....:		—
	Sample 2 burning time (s) .....:		—
	Sample 3 burning time (s) .....:		—
A.2.7	Alternative test acc. to IEC 60695-11-5, cl. 5 and 9		N/A
	Sample 1 burning time (s) .....:		—
	Sample 2 burning time (s) .....:		—
	Sample 3 burning time (s) .....:		—
A.3	Hot flaming oil test (see 4.6.2)		N/A
A.3.1	Mounting of samples		N/A
A.3.2	Test procedure		N/A

IEC 60950-1			
Clause	Requirement + Test	Result - Remark	Verdict
A.3.3	Compliance criterion		N/A
B	**ANNEX B, MOTOR TESTS UNDER ABNORMAL CONDITIONS (see 4.7.2.2 and 5.3.2)**		N/A
B.1	General requirements		N/A
	Position .....:		—
	Manufacturer .....:		—
	Type .....:		—
	Rated values .....:		—
B.2	Test conditions		N/A
B.3	Maximum temperatures		N/A
B.4	Running overload test		N/A
B.5	Locked-rotor overload test		N/A
	Test duration (days) .....:		—
	Electric strength test: test voltage (V) .....:		—
B.6	Running overload test for d.c. motors in secondary circuits		N/A
B.6.1	General		N/A
B.6.2	Test procedure		N/A
B.6.3	Alternative test procedure		N/A
B.6.4	Electric strength test; test voltage (V) .....:		N/A
B.7	Locked-rotor overload test for d.c. motors in secondary circuits		N/A
B.7.1	General		N/A
B.7.2	Test procedure		N/A
B.7.3	Alternative test procedure		N/A
B.7.4	Electric strength test; test voltage (V) .....:		N/A
B.8	Test for motors with capacitors		N/A
B.9	Test for three-phase motors		N/A
B.10	Test for series motors		N/A
	Operating voltage (V) .....:		—
C	**ANNEX C, TRANSFORMERS (see 1.5.4 and 5.3.3)**		N/A
	Position .....:	Evaluated during separate certification of power supply.	—
	Manufacturer .....:		—

IEC 60950-1			
Clause	Requirement + Test	Result - Remark	Verdict

	Type .....:		—
	Rated values .....:		—
	Method of protection.....:		—
C.1	Overload test		N/A
C.2	Insulation		N/A
	Protection from displacement of windings.....:		N/A

D	**ANNEX D, MEASURING INSTRUMENTS FOR TOUCH-CURRENT TESTS (see 5.1.4)**		P
D.1	Measuring instrument		P
D.2	Alternative measuring instrument		N/A

E	**ANNEX E, TEMPERATURE RISE OF A WINDING (see 1.4.13)**	N/A

F	**ANNEX F, MEASUREMENT OF CLEARANCES AND CREEPAGE DISTANCES (see 2.10 and Annex G)**	N/A

G	**ANNEX G, ALTERNATIVE METHOD FOR DETERMINING MINIMUM CLEARANCES**		N/A
G.1	Clearances		N/A
G.1.1	General		N/A
G.1.2	Summary of the procedure for determining minimum clearances		N/A
G.2	Determination of mains transient voltage (V)		N/A
G.2.1	AC mains supply .....:		N/A
G.2.2	Earthed d.c. mains supplies .....:		N/A
G.2.3	Unearthed d.c. mains supplies .....:		N/A
G.2.4	Battery operation .....:		N/A
G.3	Determination of telecommunication network transient voltage (V) .....:		N/A
G.4	Determination of required withstand voltage (V)		N/A
G.4.1	Mains transients and internal repetitive peaks .....:		N/A
G.4.2	Transients from telecommunication networks .....:		N/A
G.4.3	Combination of transients		N/A
G.4.4	Transients from cable distribution systems		N/A
G.5	Measurement of transient voltages (V)		N/A
	a) Transients from a mains supply		N/A

IEC 60950-1			
Clause	Requirement + Test	Result - Remark	Verdict
	For an a.c. mains supply		N/A
	For a d.c. mains supply		N/A
	b) Transients from a telecommunication network		N/A
G.6	Determination of minimum clearances .....:		N/A
H	**ANNEX H, IONIZING RADIATION (see 4.3.13)**		N/A
J	**ANNEX J, TABLE OF ELECTROCHEMICAL POTENTIALS (see 2.6.5.6)**		N/A
	Metal(s) used .....:		—
K	**ANNEX K, THERMAL CONTROLS (see 1.5.3 and 5.3.8)**		N/A
K.1	Making and breaking capacity		N/A
K.2	Thermostat reliability; operating voltage (V) .....:		N/A
K.3	Thermostat endurance test; operating voltage (V) .....:		N/A
K.4	Temperature limiter endurance; operating voltage (V) .....:		N/A
K.5	Thermal cut-out reliability		N/A
K.6	Stability of operation		N/A
L	**ANNEX L, NORMAL LOAD CONDITIONS FOR SOME TYPES OF ELECTRICAL BUSINESS EQUIPMENT (see 1.2.2.1 and 4.5.2)**		P
L.1	Typewriters		N/A
L.2	Adding machines and cash registers		N/A
L.3	Erasers		N/A
L.4	Pencil sharpeners		N/A
L.5	Duplicators and copy machines		N/A
L.6	Motor-operated files		N/A
L.7	Other business equipment		P
M	**ANNEX M, CRITERIA FOR TELEPHONE RINGING SIGNALS (see 2.3.1)**		N/A
M.1	Introduction		N/A
M.2	Method A		N/A
M.3	Method B		N/A
M.3.1	Ringing signal		N/A
M.3.1.1	Frequency (Hz) .....:		—

IEC 60950-1			
Clause	Requirement + Test	Result - Remark	Verdict
M.3.1.2	Voltage (V) .....:		—
M.3.1.3	Cadence; time (s), voltage (V) .....:		—
M.3.1.4	Single fault current (mA) .....:		—
M.3.2	Tripping device and monitoring voltage .....:		N/A
M.3.2.1	Conditions for use of a tripping device or a monitoring voltage		N/A
M.3.2.2	Tripping device		N/A
M.3.2.3	Monitoring voltage (V) .....:		N/A
N	**ANNEX N, IMPULSE TEST GENERATORS (see 1.5.7.2, 1.5.7.3, 2.10.3.9, 6.2.2.1, 7.3.2, 7.4.3 and Clause G.5)**		N/A
N.1	ITU-T impulse test generators		N/A
N.2	IEC 60065 impulse test generator		N/A
P	**ANNEX P, NORMATIVE REFERENCES**		—
Q	**ANNEX Q, Voltage dependent resistors (VDRs) (see 1.5.9.1)**		N/A
	a) Preferred climatic categories .....:		N/A
	b) Maximum continuous voltage .....:		N/A
	c) Pulse current .....:		N/A
R	**ANNEX R, EXAMPLES OF REQUIREMENTS FOR QUALITY CONTROL PROGRAMMES**		N/A
R.1	Minimum separation distances for unpopulated coated printed boards (see 2.10.6.2)		N/A
R.2	Reduced clearances (see 2.10.3)		N/A
S	**ANNEX S, PROCEDURE FOR IMPULSE TESTING (see 6.2.2.3)**		N/A
S.1	Test equipment		N/A
S.2	Test procedure		N/A
S.3	Examples of waveforms during impulse testing		N/A
T	**ANNEX T, GUIDANCE ON PROTECTION AGAINST INGRESS OF WATER (see 1.1.2)**		N/A
			—

IEC 60950-1			
Clause	Requirement + Test	Result - Remark	Verdict

U	**ANNEX U, INSULATED WINDING WIRES FOR USE WITHOUT INTERLEAVED INSULATION (see 2.10.5.4)**		N/A
			—

V	**ANNEX V, AC POWER DISTRIBUTION SYSTEMS (see 1.6.1)**		N/A
V.1	Introduction		N/A
V.2	TN power distribution systems		N/A

W	**ANNEX W, SUMMATION OF TOUCH CURRENTS**		N/A
W.1	Touch current from electronic circuits		N/A
W.1.1	Floating circuits		N/A
W.1.2	Earthed circuits		N/A
W.2	Interconnection of several equipments		N/A
W.2.1	Isolation		N/A
W.2.2	Common return, isolated from earth		N/A
W.2.3	Common return, connected to protective earth		N/A

X	**ANNEX X, MAXIMUM HEATING EFFECT IN TRANSFORMER TESTS (see clause C.1)**		N/A
X.1	Determination of maximum input current		N/A
X.2	Overload test procedure		N/A

Y	**ANNEX Y, ULTRAVIOLET LIGHT CONDITIONING TEST (see 4.3.13.3)**		N/A
Y.1	Test apparatus .....:		N/A
Y.2	Mounting of test samples .....:		N/A
Y.3	Carbon-arc light-exposure apparatus .....:		N/A
Y.4	Xenon-arc light exposure apparatus .....:		N/A

Z	**ANNEX Z, OVERVOLTAGE CATEGORIES (see 2.10.3.2 and Clause G.2)**		N/A

AA	**ANNEX AA, MANDREL TEST (see 2.10.5.8)**		N/A

BB	**ANNEX BB, CHANGES IN THE SECOND EDITION**		—

CC	**ANNEX CC, Evaluation of integrated circuit (IC) current limiters**		N/A
CC.1	General		N/A

IEC 60950-1			
Clause	Requirement + Test	Result - Remark	Verdict

CC.2	Test program 1……..:		N/A
CC.3	Test program 2……..:		N/A

DD	**ANNEX DD, Requirements for the mounting means of rack-mounted equipment**		N/A
DD.1	General	The rack mounting server no provided with slide/rails.	N/A
DD.2	Mechanical strength test, variable N……..:		N/A
DD.3	Mechanical strength test, 250N, including end stops……:		N/A
DD.4	Compliance……:		N/A

EE	**ANNEX EE, Household and home/office document/media shredders**		N/A
EE.1	General		N/A
EE.2	Markings and instructions		N/A
	Use of markings or symbols……:		N/A
	Information of user instructions, maintenance and/or servicing instructions……:		N/A
EE.3	Inadvertent reactivation test……:		N/A
EE.4	Disconnection of power to hazardous moving parts:		N/A
	Use of markings or symbols……:		N/A
EE.5	Protection against hazardous moving parts		N/A
	Test with test finger (Figure 2A) ……:		N/A
	Test with wedge probe (Figure EE1 and EE2) ……:		N/A

IEC 60950-1			
Clause	Requirement + Test	Result - Remark	Verdict

1.5.1	TABLE: List of critical components	P

Object/part No.	Manufacturer/ trademark	Type/model	Technical data	Standard (Edition / year)	Mark(s) of conformity[1])
Power cord set	Longwell	LP-34A H05VV-F LS-60	16 A, 250 V~ 3 x 0.75 mm^2 10 A, 250 V~	EN 60779	FIMKO
Switching Power Supply	FSP Group Inc.	FSP250-50GUB	Input: 100-240 V~, 50-60 Hz, 4-1.5 A, Class I DC output: +3.3 V / 17.0 A, +5 V / 18.0 A, +12 V / 17.0 A, -12 V / 0.8 A, +5 Vsb / 2.0 A, +3.3 V and +5 V = Max. 105 W	IEC 60950-1	NEMKO
Hard Disk Drive	SEAGATE TECHNOLOGY L L C or equivalent	ST2000VM003 or equivalent	5 V d.c., 0.55 A 12 V d.c., 0.37 A	IEC 60950-1	TUV NORD
DVD Writer	Toshiba Samsung Storage Technology or equivalent	SH-216 or equivalent	Class 1 Laser Product 5 V d.c. 12 V d.c.	IEC 60950-1	NEMKO
DC Fan	Nidec	U60T12MHA7-52	12 V d.c., 0.09 A N: 3200 r/min m: 0.04 kg r: 28 mm a): 0.294	EN 60950-1	TUV SUD
Lithium battery (BAT1)	Hitachi Maxell Ltd	CR2032	3.0 V d.c., Max Abnormal Charging Current 10 mA	UL 1642	UL
Protection IC (IC21) for Lithium battery	Maxim Integrated Products	DS3232M	V_{BAT}: 3.0 V Active Supply Current: 250 uA Reverse Charging Protection IC	UL 60950-1	UL

IEC 60950-1			
Clause	Requirement + Test	Result - Remark	Verdict

Object/part No.	Manufacturer/ trademark	Type/model	Technical data	Standard (Edition / year)	Mark(s) of conformity[1])
Power Distribution Switch(IC28, IC29) for USB ports	Texas Instruments, Inc.	TPS2062	Voltage Range: 2.7-5.5 V d.c. Maximum Continuous Current: 1 A Protective Current: 5 A	IEC 60950-1 UL Subject 2367	NEMKO (NO59537) UL
Front enclosure	Cheil Industries Inc Chemicals Div	TH-1100(+)	V-0, 80 °C Min. 2.0 mm thickness	IEC 60695-11-10 UL 94	UL
Others enclosure	Interchangeable	Interchangeable	Metal, Min. 0.7 mm thickness	IEC 60950-1	Tested in equipment
PCB	Interchangeable	Interchangeable	Min. V-1 or better, Min. 105 °C, 1.6 mm thickness	UL 796	UL
supplementary information					

1.5.1	TABLE: Opto Electronic Devices	N/A

Manufacturer.....:

Type .....:

Separately tested .....:

Bridging insulation.....:

External creepage distance .....:

Internal creepage distance.....:

Distance through insulation.....:

Tested under the following conditions.....:

Input .....:

Output .....:

supplementary information

Evaluated during separate certification of power supply.

IEC 60950-1			
Clause	Requirement + Test	Result - Remark	Verdict

1.6.2	TABLE: Electrical data (in normal conditions)						P
U (V)	I (A)	Irated (A)	P (W)	Fuse #	Ifuse (A)	Condition/status	
90	1.003	-	90.6	-	-	Max. Normal Load (50 Hz)	
100	0.909	4	89.9	-	-	Max. Normal Load (50 Hz)	
240	0.427	1.5	87.8	-	-	Max. Normal Load (50 Hz)	
264	0.454	-	87.5	-	-	Max. Normal Load (50 Hz)	
90	1.018	-	91.2	-	-	Max. Normal Load (60 Hz)	
100	0.913	4	90.6	-	-	Max. Normal Load (60 Hz)	
240	0.425	1.5	88.1	-	-	Max. Normal Load (60 Hz)	
264	0.449	-	86.3	-	-	Max. Normal Load (60 Hz)	
supplementary information							
Max. Normal load: The EUT crossed reading and writing data between HDD and DVD Writer and all USB connectors loaded with the current at 1.0 A. Additional load 12 V, 2.61 A and 5 V, 2.65 A were connected to the power supply.							

2.1.1.5 c) 1)	TABLE: max. V, A, VA test				N/A
Voltage (rated) (V)	Current (rated) (A)	Voltage (max.) (V)	Current (max.) (A)	VA (max.) (VA)	
supplementary information:					
Evaluated during separate certification of power supply.					

2.1.1.5 c) 2)	TABLE: stored energy		N/A
Capacitance C (µF)	Voltage U (V)	Energy E (J)	
supplementary information:			
Evaluated during separate certification of power supply.			

IEC 60950-1			
Clause	Requirement + Test	Result - Remark	Verdict

2.2	TABLE: evaluation of voltage limiting components in SELV circuits	N/A

Component (measured between)	max. voltage (V) (normal operation)		Voltage Limiting Components
	V peak	V d.c.	

Fault test performed on voltage limiting components	Voltage measured (V) in SELV circuits (V peak or V d.c.)
supplementary information:	
Evaluated during separate certification of power supply.	

2.5	TABLE: limited power sources	P

Circuit output tested: See below

Note: Measured Uoc (V) with all load circuits disconnected: See below

Components / Pin No.			Condition (Normal / Single Fault)	Uoc (V)	I_{sc} (A)		VA	
					Meas.	Limit	Meas.	Limit
HDMI	Pin 2	GND	L5 Short	5.06	2.50	8	4.64	100
USB 1	Pin 1	GND	Normal	5.08	3.29	8	11.52	100
USB 2	Pin 1	GND	Normal	5.08	3.50	8	9.10	100

supplementary information:

Sc=Short circuit, Oc=Open circuit

Data ports:

HDMI: 

, USB: 

2.10.2	Table: working voltage measurement	N/A

Location	RMS voltage (V)	Peak voltage (V)	Comments

IEC 60950-1			
Clause	Requirement + Test	Result - Remark	Verdict

supplementary information:			
Evaluated during separate certification of power supply.			

2.10.3 and 2.10.4	TABLE: Clearance and creepage distance measurements					N/A
Clearance (cl) and creepage distance (cr) at/of/between:	U peak (V)	U r.m.s. (V)	Required cl (mm)	cl (mm)	Required cr (mm)	cr (mm)
Functional:						
Basic/supplementary:						
Reinforced:						
supplementary information:						
Evaluated during separate certification of power supply.						

2.10.5	TABLE: Distance through insulation measurements				N/A
Distance through insulation (DTI) at/of:	U peak (V)	U rms (V)	Test voltage (V)	Required DTI (mm)	DTI (mm)
supplementary information:					
Evaluated during separate certification of power supply.					

4.3.8	TABLE: Batteries	P
The tests of 4.3.8 are applicable only when appropriate battery data is not available	Appropriate battery data is available. (see appended table 1.5.1)	P
Is it possible to install the battery in a reverse polarity position?	No	N/A

	Non-rechargeable batteries			Rechargeable batteries					
	Discharging		Un-intentional charging	Charging		Discharging		Reversed charging	
	Meas. current	Manuf. Specs.		Meas. current	Manuf. Specs.	Meas. current	Manuf. Specs.	Meas. current	Manuf. Specs.
Max. current during normal condition			Considered for real time clock battery.						

IEC 60950-1			
Clause	Requirement + Test	Result - Remark	Verdict

Max. current during fault condition			Considered for real time clock battery.						

Test results:		Verdict
- Chemical leaks		N/A
- Explosion of the battery		N/A
- Emission of flame or expulsion of molten metal		N/A
- Electric strength tests of equipment after completion of tests		N/A
supplementary information:		

IEC 60950-1			
Clause	Requirement + Test	Result - Remark	Verdict

4.3.8	TABLE: Batteries	P

Battery category .....: lithium/manganese dioxide coin cells
Manufacturer .....: (see appended table 1.5.1)
Type / model .....: (see appended table 1.5.1)
Voltage .....: (see appended table 1.5.1)
Capacity .....: -
Tested and Certified by (incl. Ref. No.) .....: (see appended table 1.5.1)
Circuit protection diagram:



Supplementary information:

Certified protect IC used.
(see appended table 1.5.1)

MARKINGS AND INSTRUCTIONS (1.7.12, 1.7.15)	
Location of replaceable battery	In service access areas
Language(s) ……:	English
Close to the battery ……:	No
In the servicing instructions ……:	No
In the operating instructions ……..:	Yes

IEC 60950-1			
Clause	Requirement + Test	Result - Remark	Verdict

4.5	TABLE: Thermal requirements			P
	Supply voltage (V) .....:	90 V a.c. / 60 Hz	264 V a.c. / 50 Hz	—
	Ambient T_{min} (°C) .....:	See below	See below	—
	Ambient T_{max} (°C) .....:	See below	See below	—
Maximum measured temperature T of part/at::		T (°C) at Tma		Allowed T_{max} (°C)
1.	Front Cover (Plastic)	43.4	43.4	95
2.	Top Enclosure (Metal)	45.3	45.2	70
3.	DC fan body	47.3	47.3	100
4.	BAT1 body	51.9	51.9	-
5.	U1 Heatsink	67.5	67.6	-
6.	PWB near L25	58.8	58.7	105
7.	HDD Body	56.2	55.7	-
8.	ODD Rear body (Metal)	47.0	46.8	-
9.	AC Inlet body	51.0	50.2	70
10.	L1 coil (SMPS)	58.8	57.3	120(B)
11.	T1 coil (SMPS)	61.5	61.0	110(B)
12.	T1 core (SMPS)	61.5	61.1	110(B)
13.	T2 coil (SMPS)	50.7	50.4	110(B)
14.	T2 core (SMPS)	52.9	52.5	110(B)
15.	Ambient	40.0 (29.4 °C)	40.0(29.1 °C)	-

supplementary information:

Maximum temperature T at Tma(40 °C) is calculated. (T at Tma = T- t_2+Tma)

Temperature T of winding:	t_1 (°C)	R_1 (Ω)	t_2 (°C)	R_2 (Ω)	T (°C)	Allowed T_{max} (°C)	Insulation class

supplementary information:

4.5.5	TABLE: Ball pressure test of thermoplastic parts		N/A
	Allowed impression diameter (mm)	≤ 2 mm	—
Part		Test temperature (°C)	Impression diameter (mm)

IEC 60950-1			
Clause	Requirement + Test	Result - Remark	Verdict

supplementary information:		
Evaluated during separate certification of power supply		

4.7	TABLE: Resistance to fire				P
Part	Manufacturer of material	Type of material	Thickness (mm)	Flammability class	Evidence
supplementary information:					
(see appended table 1.5.1)					

5.1	TABLE: touch current measurement		P
Measured between:	Measured (mA)	Limit (mA)	Comments/conditions
Accessible metal enclosure	0.52	3.5	-
supplementary information:			
Supply voltage: 264 V a.c., 60 Hz			

5.2	TABLE: Electric strength tests, impulse tests and voltage surge tests		P
Test voltage applied between:	Voltage shape (AC, DC, impulse, surge)	Test voltage (V)	Breakdown Yes / No
Functional:			
Basic/supplementary:			
Unit: Primary-Protective earth	AC	1864	No
Reinforced:			
Unit: Primary-Secondary	AC	3000	No
supplementary information:			

IEC 60950-1			
Clause	Requirement + Test	Result - Remark	Verdict

5.3	**TABLE: Fault condition tests**		P
	Ambient temperature (°C) .....:	See below	—
	Power source for EUT: Manufacturer, model/type, output rating .....:	-	—

Component No.	Fault	Supply voltage (V)	Test time	Fuse #	Fuse current (A)	Observation
Openings	Blocked	264	1 h 36 min	-	0.45	Temperature Stabilized. SMPS T1 coil: 59.1 °C, ambient: 28.9 °C. No component damaged. No hazard.
DC Fan	Locked	264	2 h 1 min	-	0.45	Temperature Stabilized. SMPS T1 coil: 50.9 °C, ambient: 30.2 °C No component damaged. No hazard.
*HDMI pin 2-GND	Overload	264	10 min	-	-	Max. 2.50 A loaded. L5 damaged. No hazard.
USB 1 pin 1-GND	Overload	264	10 min	-	-	Max. 3.29 A loaded. No component damaged. No hazard.
USB 2 pin 1-GND	Overload	264	10 min	-	-	Max. 3.50 A loaded. No component damaged. No hazard.

supplementary information:

The following electric strength test were conducted after above tests.
- Primary-Secondary: 3000 V a.c.
- Primary-Protective earth: 1864 V a.c.

*: Tested 3 times.

IEC 60950-1			
Clause	Requirement + Test	Result - Remark	Verdict

C.2	TABLE: transformers						N/A
Loc.	Tested insulation	Working voltage peak / V (2.10.2)	Working voltage rms / V (2.10.2)	Required electric strength (5.2)	Required clearance / mm (2.10.3)	Required creepage distance / mm (2.10.4)	Required distance thr. insul. (2.10.5)
Loc.	Tested insulation			Test voltage/ V	Measured clearance / mm	Measured creepage dist./ mm	Measured distance thr. insul. / mm; number of layers
supplementary information:							
Evaluated during separate certification of power supply.							

C.2	TABLE: transformers	N/A

Transformer

IEC 60950-1			
Clause	Requirement + Test	Result - Remark	Verdict

List of test equipment used:
(Note: This is an example of the required attachment. Other forms with a different layout but containing similar information are also acceptable.)

Clause	Measurement / testing	Testing / measuring equipment / material used		Range used	Calibration date	Calibration due date
Supplementary information: No listing of test equipment used necessary for chosen CBTL test procedure.						

Attachment 1 - European group differences and national differences (EN 60950-1:2006+A11:2009+A1:2010+A12:2011)

IEC60950_1C - ATTACHMENT			
Clause	Requirement + Test	Result - Remark	Verdict

ATTACHMENT TO TEST REPORT IEC 60950-1
EUROPEAN GROUP DIFFERENCES AND NATIONAL DIFFERENCES

Information technology equipment – Safety –

Part 1: General requirements

Differences according to.....:	EN 60950-1:2006/A11:2009/A1:2010/A12:2011
Attachment Form No.....:	EU_GD_IEC60950_1C_II
Attachment Originator .....:	SGS Fimko Ltd
Master Attachment.....:	Date 2011-08

Copyright © 2011 IEC System for Conformity Testing and Certification of Electrical Equipment (IECEE), Geneva, Switzerland. All rights reserved.

EN 60950-1:2006/A11:2009/A1:2010/A12:2011 – CENELEC COMMON MODIFICATIONS

IEC 60950-1, GROUP DIFFERENCES (CENELEC common modifications EN)			
Clause	Requirement + Test	Result - Remark	Verdict
Contents	Add the following annexes: Annex ZA (normative) Normative references to international publications with their corresponding European publications Annex ZB (normative) Special national conditions		P
General	Delete all the “country” notes in the reference document (IEC 60950-1:2005) according to the following list: 1.4.8 Note 2; 1.5.1 Note 2 & 3; 1.5.7.1 Note 1.5.8 Note 2; 1.5.9.4 Note; 1.7.2.1 Note 4, 5 & 6 2.2.3 Note; 2.2.4 Note; 2.3.2 Note 2.3.2.1 Note 2; 2.3.4 Note 2; 2.6.3.3 Note 2 & 3 2.7.1 Note; 2.10.3.2 Note 2; 2.10.5.13 Note 3 3.2.1.1 Note; 3.2.4 Note 3.; 2.5.1 Note 2 4.3.6 Note 1 & 2; 4.7 Note 4; 4.7.2.2 Note 4.7.3.1Note 2; 5.1.7.1 Note 3 & 4; 5.3.7 Note 1 6 Note 2 & 5; 6.1.2.1 Note 2; 6.1.2.2 Note 6.2.2 Note; 6.2.2.1 Note 2; 6.2.2.2 Note 7.1 Note 3; 7.2 Note; 7.3 Note 1 & 2 G.2.1 Note 2; Annex H Note 2		P
General (A1:2010)	Delete all the “country” notes in the reference document (IEC 60950-1:2005/A1:2010) according to the following list: 1.5.7.1 Note; 6.1.2.1 Note 2 6.2.2.1 Note 2; EE.3 Note		P

Attachment 1 - European group differences and national differences (EN 60950-1:2006+A11:2009+A1:2010+A12:2011)

IEC60950_1C - ATTACHMENT			
Clause	Requirement + Test	Result - Remark	Verdict
1.3.Z1	Add the following subclause: 1.3.Z1 Exposure to excessive sound pressure The apparatus shall be so designed and constructed as to present no danger when used for its intended purpose, either in normal operating conditions or under fault conditions, particularly providing protection against exposure to excessive sound pressures from headphones or earphones. NOTE Z1 A new method of measurement is described in EN 50332-1, Sound system equipment: Headphones and earphones associated with portable audio equipment - Maximum sound pressure level measurement methodology and limit considerations - Part 1: General method for “one package equipment”, and in EN 50332-2, Sound system equipment: Headphones and earphones associated with portable audio equipment - Maximum sound pressure level measurement methodology and limit considerations - Part 2: Guidelines to associate sets with headphones coming from different manufacturers.		N/A
(A12:2011)	In EN 60950-1:2006/A12:2011 Delete the addition of 1.3.Z1 / EN 60950-1:2006 Delete the definition 1.2.3.Z1 / EN 60950-1:2006 /A1:2010		N/A
1.5.1	Add the following NOTE: NOTE Z1 The use of certain substances in electrical and electronic equipment is restricted within the EU: see Directive 2002/95/EC		N/A
1.7.2.1 (A1:2010)	In addition, for a PORTABLE SOUND SYSTEM, the instructions shall include a warning that excessive sound pressure from earphones and headphones can cause hearing loss.		N/A
1.7.2.1 (A12.2011)	In EN 60950-1:2006/A12:2011 Delete NOTE Z1 and the addition for Portable Sound System. Add the following clause and annex to the existing standard and amendments.		N/A
	Zx Protection against excessive sound pressure from personal music players		N/A

Attachment 1 - European group differences and national differences (EN 60950-1:2006+A11:2009+A1:2010+A12:2011)

IEC60950_1C - ATTACHMENT			
Clause	Requirement + Test	Result - Remark	Verdict
	Zx.1 General This sub-clause specifies requirements for protection against excessive sound pressure from personal music players that are closely coupled to the ear. It also specifies requirements for earphones and headphones intended for use with personal music players. A personal music player is a portable equipment for personal use, that: - is designed to allow the user to listen to recorded or broadcast sound or video; and - primarily uses headphones or earphones that can be worn in or on or around the ears; and - allows the user to walk around while in use. NOTE 1 Examples are hand-held or body-worn portable CD players, MP3 audio players, mobile phones with MP3 type features, PDA's or similar equipment. A personal music player and earphones or headphones intended to be used with personal music players shall comply with the requirements of this sub-clause. The requirements in this sub-clause are valid for music or video mode only. The requirements do not apply: - while the personal music player is connected to an external amplifier; or - while the headphones or earphones are not used. NOTE 2 An external amplifier is an amplifier which is not part of the personal music player or the listening device, but which is intended to play the music as a standalone music player. The requirements do not apply to: - hearing aid equipment and professional equipment; NOTE 3 Professional equipment is equipment sold through special sales channels. All products sold through normal electronics stores are considered not to be professional equipment.		N/A

Attachment 1 - European group differences and national differences (EN 60950-1:2006+A11:2009+A1:2010+A12:2011)

IEC60950_1C - ATTACHMENT			
Clause	Requirement + Test	Result - Remark	Verdict
	□ □ analogue personal music players (personal music players without any kind of digital processing of the sound signal) that are brought to the market before the end of 2015. NOTE 4 This exemption has been allowed because this technology is falling out of use and it is expected that within a few years it will no longer exist. This exemption will not be extended to other technologies. For equipment which is clearly designed or intended for use by young children, the limits of EN 71-1 apply.		
	Zx.2 Equipment requirements No safety provision is required for equipment that complies with the following: □ □ equipment provided as a package (personal music player with its listening device), where the acoustic output $L_{Aeq,T}$ is ≤ 85 dBA measured while playing the fixed "programme simulation noise" as described in EN 50332-1; and □ □ a personal music player provided with an analogue electrical output socket for a listening device, where the electrical output is ≤ 27 mV measured as described in EN 50332-2, while playing the fixed "programme simulation noise" as described in EN 50332-1. NOTE 1 Wherever the term acoustic output is used in this clause, the 30 s A-weighted equivalent sound pressure level $L_{Aeq,T}$ is meant. See also Zx.5 and Annex Zx. All other equipment shall: a) protect the user from unintentional acoustic outputs exceeding those mentioned above; and b) have a standard acoustic output level not exceeding those mentioned above, and automatically return to an output level not exceeding those mentioned above when the power is switched off; and		N/A

Attachment 1 - European group differences and national differences (EN 60950-1:2006+A11:2009+A1:2010+A12:2011)

IEC60950_1C - ATTACHMENT			
Clause	Requirement + Test	Result - Remark	Verdict
	c) provide a means to actively inform the user of the increased sound pressure when the equipment is operated with an acoustic output exceeding those mentioned above. Any means used shall be acknowledged by the user before activating a mode of operation which allows for an acoustic output exceeding those mentioned above. The acknowledgement does not need to be repeated more than once every 20 h of cumulative listening time; and NOTE 2 Examples of means include visual or audible signals. Action from the user is always required. NOTE 3 The 20 h listening time is the accumulative listening time, independent how often and how long the personal music player has been switched off. d) have a warning as specified in Zx.3; and e) not exceed the following: 1) equipment provided as a package (player with Its listening device), the acoustic output shall be ≤ 100 dBA measured while playing the fixed “programme simulation noise” described in EN 50332-1; and 2) a personal music player provided with an analogue electrical output socket for a listening device, the electrical output shall be ≤ 150 mV measured as described in EN 50332-2, while playing the fixed “programme simulation noise” described in EN 50332-1. For music where the average sound pressure (long term $L_{Aeq,T}$) measured over the duration of the song is lower than the average produced by the programme simulation noise, the warning does not need to be given as long as the average sound pressure of the song is below the basic limit of 85 dBA. In this case T becomes the duration of the song. NOTE 4 Classical music typically has an average sound pressure (long term $L_{Aeq,T}$) which is much lower than the average programme simulation noise. Therefore, if the player is capable to analyse the song and compare it with the programme simulation noise, the warning does not need to be given as long as the average sound pressure of the song is below the basic limit of 85 dBA. For example, if the player is set with the programme simulation noise to 85 dBA, but the average music level of the song is only 65 dBA, there is no need to give a warning or ask an acknowledgement as long as the average sound level of the song is not above the basic limit of 85 dBA.		

Attachment 1 - European group differences and national differences (EN 60950-1:2006+A11:2009+A1:2010+A12:2011)

IEC60950_1C - ATTACHMENT			
Clause	Requirement + Test	Result - Remark	Verdict
	Zx.3 Warning The warning shall be placed on the equipment, or on the packaging, or in the instruction manual and shall consist of the following: □ □ □ the symbol of Figure 1 with a minimum height of 5 mm; and □ □ □ the following wording, or similar: “To prevent possible hearing damage, do not listen at high volume levels for long periods.” **Figure 1 – Warning label (IEC 60417-6044)** Alternatively, the entire warning may be given through the equipment display during use, when the user is asked to acknowledge activation of the higher level.		N/A
	Zx.4 Requirements for listening devices (headphones and earphones)		N/A
	Zx.4.1 Wired listening devices with analogue input With 94 dBA sound pressure output $L_{Aeq,T}$, the input voltage of the fixed “programme simulation noise” described in EN 50332-2 shall be ≥ 75 mV. This requirement is applicable in any mode where the headphones can operate (active or passive), including any available setting (for example built-in volume level control). NOTE The values of 94 dBA – 75 mV correspond with 85dBA – 27 mV and 100 dBA – 150 mV.		N/A

Attachment 1 - European group differences and national differences (EN 60950-1:2006+A11:2009+A1:2010+A12:2011)

IEC60950_1C - ATTACHMENT			
Clause	Requirement + Test	Result - Remark	Verdict
	Zx.4.2 Wired listening devices with digital input With any playing device playing the fixed "programme simulation noise" described in EN 50332-1 (and respecting the digital interface standards, where a digital interface standard exists that specifies the equivalent acoustic level), the acoustic output $L_{Aeq,T}$ of the listening device shall be ≤ 100 dBA. This requirement is applicable in any mode where the headphones can operate, including any available setting (for example built-in volume level control, additional sound feature like equalization, etc.). NOTE An example of a wired listening device with digital input is a USB headphone.		N/A
	Zx.4.3 Wireless listening devices In wireless mode: □ □ with any playing and transmitting device playing the fixed programme simulation noise described in EN 50332-1; and □ □ respecting the wireless transmision standards, where an air interface standard exists that specifies the equivalent acoustic level; and □ □ with volume and sound settings in the listening device (for example built-in volume level control, additional sound feature like equalization, etc.) set to the combination of positions that maximize the measured acoustic output for the abovementioned programme simulation noise, the acoustic output $L_{Aeq,T}$ of the listening device shall be ≤ 100 dBA. NOTE An example of a wireless listening device is a Bluetooth headphone.		N/A
	Zx.5 Measurement methods Measurements shall be made in accordance with EN 50332-1 or EN 50332-2 as applicable. Unless stated otherwise, the time interval T shall be 30 s. NOTE Test method for wireless equipment provided without listening device should be defined.		N/A

Attachment 1 - European group differences and national differences (EN 60950-1:2006+A11:2009+A1:2010+A12:2011)

IEC60950_1C - ATTACHMENT			
Clause	Requirement + Test	Result - Remark	Verdict
2.7.1	Replace the subclause as follows: Basic requirements To protect against excessive current, short-circuits and earth faults in PRIMARY CIRCUITS, protective devices shall be included either as integral parts of the equipment or as parts of the building installation, subject to the following, a), b) and c): a) except as detailed in b) and c), protective devices necessary to comply with the requirements of 5.3 shall be included as parts of the equipment; b) for components in series with the mains input to the equipment such as the supply cord, appliance coupler, r.f.i. filter and switch, short-circuit and earth fault protection may be provided by protective devices in the building installation;		P
	c) it is permitted for PLUGGABLE EQUIPMENT TYPE B or PERMANENTLY CONNECTED EQUIPMENT, to rely on dedicated overcurrent and short-circuit protection in the building installation, provided that the means of protection, e.g. fuses or circuit breakers, is fully specified in the installation instructions. If reliance is placed on protection in the building installation, the installation instructions shall so state, except that for PLUGGABLE EQUIPMENT TYPE A the building installation shall be regarded as providing protection in accordance with the rating of the wall socket outlet.		N/A
2.7.2	This subclause has been declared ‘void’.		N/A
3.2.3	Delete the NOTE in Table 3A, and delete also in this table the conduit sizes in parentheses.		P
3.2.5.1	Replace “60245 IEC 53” by “H05 RR-F”; “60227 IEC 52” by “H03 VV-F or H03 VVH2-F”; “60227 IEC 53” by “H05 VV-F or H05 VVH2-F2”. In Table 3B, replace the first four lines by the following: Up to and including 6 | 0,75 [a)] | Over 6 up to and including 10| (0,75) [b)] 1,0 | Over 10 up to and including 16| (1,0) [c)] 1,5 | In the conditions applicable to Table 3B delete the words “in some countries” in condition [a)]. In NOTE 1, applicable to Table 3B, delete the second sentence.		P

Attachment 1 - European group differences and national differences (EN 60950-1:2006+A11:2009+A1:2010+A12:2011)

IEC60950_1C - ATTACHMENT			
Clause	Requirement + Test	Result - Remark	Verdict
3.3.4	In Table 3D, delete the fourth line: conductor sizes for 10 to 13 A, and replace with the following: Over 10 up to and including 16 | 1,5 to 2,5 | 1,5 to 4 | Delete the fifth line: conductor sizes for 13 to 16 A		N/A
4.3.13.6 (A1:2010)	Replace the existing NOTE by the following: NOTE Z1 Attention is drawn to: 1999/519/EC: Council Recommendation on the limitation of exposure of the general public to electromagnetic fields 0 Hz to 300 GHz, and 2006/25/EC: Directive on the minimum health and safety requirements regarding the exposure of workers to risks arising from physical agents (artifical optical radiation).		N/A
	Standards taking into account mentioned Recommendation and Directive which demonstrate compliance with the applicable EU Directive are indicated in the OJEC.		N/A
Annex H	Replace the last paragraph of this annex by: At any point 10 cm from the surface of the OPERATOR ACCESS AREA, the dose rate shall not exceed 1 µSv/h (0,1 mR/h) (see NOTE). Account is taken of the background level. Replace the notes as follows: NOTE These values appear in Directive 96/29/Euratom. Delete NOTE 2.		N/A
Bibliography	Additional EN standards.		—

ZA	**NORMATIVE REFERENCES TO INTERNATIONAL PUBLICATIONS WITH THEIR CORRESPONDING EUROPEAN PUBLICATIONS**	—

ZB ANNEX (normative) SPECIAL NATIONAL CONDITIONS (EN)			
1.2.4.1	In **Denmark**, certain types of Class I appliances (see 3.2.1.1) may be provided with a plug not establishing earthing conditions when inserted into Danish socket-outlets.		N/A
1.2.13.14	In **Norway** and **Sweden**, for requirements see 1.7.2.1 and 7.3 of this annex.		N/A

Attachment 1 - European group differences and national differences (EN 60950-1:2006+A11:2009+A1:2010+A12:2011)

IEC60950_1C - ATTACHMENT			
Clause	Requirement + Test	Result - Remark	Verdict
1.5.7.1	In **Finland, Norway** and **Sweden**, resistors bridging BASIC INSULATION in CLASS I PLUGGABLE EQUIPMENT TYPE A must comply with the requirements in 1.5.7.1. In addition when a single resistor is used, the resistor must withstand the resistor test in 1.5.7.2.		N/A
1.5.8	In **Norway**, due to the IT power system used (see annex V, Figure V.7), capacitors are required to be rated for the applicable line-to-line voltage (230 V).		N/A
1.5.9.4	In **Finland**, **Norway** and **Sweden**, the third dashed sentence is applicable only to equipment as defined in 6.1.2.2 of this annex.		N/A

Attachment 1 - European group differences and national differences (EN 60950-1:2006+A11:2009+A1:2010+A12:2011)

IEC60950_1C - ATTACHMENT			
Clause	Requirement + Test	Result - Remark	Verdict
1.7.2.1	In **Finland**, **Norway** and **Sweden**, CLASS I PLUGGABLE EQUIPMENT TYPE A intended for connection to other equipment or a network shall, if safety relies on connection to protective earth or if surge suppressors are connected between the network terminals and accessible parts, have a marking stating that the equipment must be connected to an earthed mains socket-outlet. The marking text in the applicable countries shall be as follows: In Finland: "Laite on liitettävä suojakoskettimilla varustettuun pistorasiaan" In Norway: “Apparatet må tilkoples jordet stikkontakt” In Sweden: “Apparaten skall anslutas till jordat uttag” In **Norway** and **Sweden**, the screen of the cable distribution system is normally not earthed at the entrance of the building and there is normally no equipotential bonding system within the building. Therefore the protective earthing of the building installation need to be isolated from the screen of a cable distribution system. It is however accepted to provide the insulation external to the equipment by an adapter or an interconnection cable with galvanic isolator, which may be provided by e.g. a retailer. The user manual shall then have the following or similar information in Norwegian and Swedish language respectively, depending on in what country the equipment is intended to be used in: “Equipment connected to the protective earthing of the building installation through the mains connection or through other equipment with a connection to protective earthing – and to a cable distribution system using coaxial cable, may in some circumstances create a fire hazard. Connection to a cable distribution system has therefore to be provided through a device providing electrical isolation below a certain frequency range (galvanic isolator, see EN 60728-11).”		N/A

Attachment 1 - European group differences and national differences (EN 60950-1:2006+A11:2009+A1:2010+A12:2011)

IEC60950_1C - ATTACHMENT			
Clause	Requirement + Test	Result - Remark	Verdict
	NOTE In Norway, due to regulation for installations of cable distribution systems, and in Sweden, a galvanic isolator shall provide electrical insulation below 5 MHz. The insulation shall withstand a dielectric strength of 1,5 kV r.m.s., 50 Hz or 60 Hz, for 1 min. Translation to Norwegian (the Swedish text will also be accepted in Norway): “Utstyr som er koplet til beskyttelsesjord via nettplugg og/eller via annet jordtilkoplet utstyr – og er tilkoplet et kabel-TV nett, kan forårsake brannfare. For å unngå dette skal det ved tilkopling av utstyret til kabel-TV nettet installeres en galvanisk isolator mellom utstyret og kabel- TV nettet.” Translation to Swedish: ”Utrustning som är kopplad till skyddsjord via jordat vägguttag och/eller via annan utrustning och samtidigt är kopplad till kabel-TV nät kan i vissa fall medföra risk för brand. För att undvika detta skall vid anslutning av utrustningen till kabel-TV nät galvanisk isolator finnas mellan utrustningen och kabel-TV nätet.”		
1.7.5	In **Denmark**, socket-outlets for providing power to other equipment shall be in accordance with the Heavy Current Regulations, Section 107-2-D1, Standard Sheet DK 1-3a, DK 1-5a or DK 1-7a, when used on Class I equipment. For STATIONARY EQUIPMENT the socket-outlet shall be in accordance with Standard Sheet DK 1-1b or DK 1-5a. For **CLASS II EQUIPMENT** the socket outlet shall be in accordance with Standard Sheet DKA 1-4a.		N/A
2.2.4	In **Norway**, for requirements see 1.7.2.1, 6.1.2.1 and 6.1.2.2 of this annex.		N/A
2.3.2	In **Finland**, **Norway** and **Sweden** there are additional requirements for the insulation. See 6.1.2.1 and 6.1.2.2 of this annex.		N/A
2.3.4	In **Norway**, for requirements see 1.7.2.1, 6.1.2.1 and 6.1.2.2 of this annex.		N/A
2.6.3.3	In the **United Kingdom**, the current rating of the circuit shall be taken as 13 A, not 16 A.		N/A

Attachment 1 - European group differences and national differences (EN 60950-1:2006+A11:2009+A1:2010+A12:2011)

IEC60950_1C - ATTACHMENT			
Clause	Requirement + Test	Result - Remark	Verdict
2.7.1	In the **United Kingdom**, to protect against excessive currents and short-circuits in the PRIMARY CIRCUIT of DIRECT PLUG-IN EQUIPMENT, tests according to 5.3 shall be conducted, using an external protective device rated 30 A or 32 A. If these tests fail, suitable protective devices shall be included as integral parts of the DIRECT PLUG-IN EQUIPMENT, so that the requirements of 5.3 are met.		N/A
2.10.5.13	In **Finland**, **Norway** and **Sweden**, there are additional requirements for the insulation, see 6.1.2.1 and 6.1.2.2 of this annex.		N/A
3.2.1.1	In **Switzerland**, supply cords of equipment having a RATED CURRENT not exceeding 10 A shall be provided with a plug complying with SEV 1011 or IEC 60884-1 and one of the following dimension sheets: SEV 6532-2.1991 Plug Type 15 3P+N+PE 250/400 V, 10 A SEV 6533-2.1991 Plug Type 11 L+N 250 V, 10 A SEV 6534-2.1991 Plug Type 12 L+N+PE 250 V, 10 A In general, EN 60309 applies for plugs for currents exceeding 10 A. However, a 16 A plug and socket-outlet system is being introduced in Switzerland, the plugs of which are according to the following dimension sheets, published in February 1998: SEV 5932-2.1998: Plug Type 25 , 3L+N+PE 230/400 V, 16 A SEV 5933-2.1998:Plug Type 21, L+N, 250 V, 16A SEV 5934-2.1998: Plug Type 23, L+N+PE 250 V, 1		N/A

Attachment 1 - European group differences and national differences (EN 60950-1:2006+A11:2009+A1:2010+A12:2011)

IEC60950_1C - ATTACHMENT			
Clause	Requirement + Test	Result - Remark	Verdict
3.2.1.1	In **Denmark**, supply cords of single-phase equipment having a rated current not exceeding13 A shall be provided with a plug according to the Heavy Current Regulations, Section 107-2-D1. CLASS I EQUIPMENT provided with socket-outlets with earth contacts or which are intended to be used in locations where protection against indirect contact is required according to the wiring rules shall be provided with a plug in accordance with standard sheet DK 2-1a or DK 2-5a. If poly-phase equipment and single-phase equipment having a RATED CURRENT exceeding 13 A is provided with a supply cord with a plug, this plug shall be in accordance with the Heavy Current Regulations, Section 107-2-D1 or EN 60309-2.		N/A
3.2.1.1	In **Spain**, supply cords of single-phase equipment having a rated current not exceeding 10 A shall be provided with a plug according to UNE 20315:1994. Supply cords of single-phase equipment having a rated current not exceeding 2,5 A shall be provided with a plug according to UNE-EN 50075:1993. CLASS I EQUIPMENT provided with socket-outlets with earth contacts or which are intended to be used in locations where protection against indirect contact is required according to the wiring rules, shall be provided with a plug in accordance with standard UNE 20315:1994. If poly-phase equipment is provided with a supply cord with a plug, this plug shall be in accordance with UNE-EN 60309-2.		N/A
3.2.1.1	In the **United Kingdom**, apparatus which is fitted with a flexible cable or cord and is designed to be connected to a mains socket conforming to BS 1363 by means of that flexible cable or cord and plug, shall be fitted with a ‘standard plug’ in accordance with Statutory Instrument 1768:1994 - The Plugs and Sockets etc. (Safety) Regulations 1994, unless exempted by those regulations. NOTE ‘Standard plug’ is defined in SI 1768:1994 and essentially means an approved plug conforming to BS 1363 or an approved conversion plug.		N/A

Attachment 1 - European group differences and national differences (EN 60950-1:2006+A11:2009+A1:2010+A12:2011)

IEC60950_1C - ATTACHMENT			
Clause	Requirement + Test	Result - Remark	Verdict
3.2.1.1	In **Ireland**, apparatus which is fitted with a flexible cable or cord and is designed to be connected to a mains socket conforming to I.S. 411 by means of that flexible cable or cord and plug, shall be fitted with a 13 A plug in accordance with Statutory Instrument 525:1997 - National Standards Authority of Ireland (section 28) (13 A Plugs and Conversion Adaptors for Domestic Use) Regulations 1997.		N/A
3.2.4	In **Switzerland**, for requirements see 3.2.1.1 of this annex.		N/A
3.2.5.1	In the **United Kingdom**, a power supply cord with conductor of 1,25 mm2 is allowed for equipment with a rated current over 10 A and up to and including 13 A.		N/A
3.3.4	In the **United Kingdom**, the range of conductor sizes of flexible cords to be accepted by terminals for equipment with a RATED CURRENT of over 10 A up to and including 13 A is: • 1,25 mm^2 to 1,5 mm^2 nominal cross-sectional area.		N/A
4.3.6	In the **United Kingdom**, the torque test is performed using a socket outlet complying with BS 1363 part 1:1995, including Amendment 1:1997 and Amendment 2:2003 and the plug part of DIRECT PLUG-IN EQUIPMENT shall be assessed to BS 1363: Part 1, 12.1, 12.2, 12.3, 12.9, 12.11, 12.12, 12.13, 12.16 and 12.17, except that the test of 12.17 is performed at not less than 125 °C. Where the metal earth pin is replaced by an Insulated Shutter Opening Device (ISOD), the requirements of clauses 22.2 and 23 also apply.		N/A
4.3.6	In **Ireland**, DIRECT PLUG-IN EQUIPMENT is known as plug similar devices. Such devices shall comply with Statutory Instrument 526:1997 - National Standards Authority of Ireland (Section 28) (Electrical plugs, plug similar devices and sockets for domestic use) Regulations, 1997.		N/A

Attachment 1 - European group differences and national differences (EN 60950-1:2006+A11:2009+A1:2010+A12:2011)

IEC60950_1C - ATTACHMENT			
Clause	Requirement + Test	Result - Remark	Verdict
5.1.7.1	In **Finland**, **Norway** and **Sweden** TOUCH CURRENT measurement results exceeding 3,5 mA r.m.s. are permitted only for the following equipment: • STATIONARY PLUGGABLE EQUIPMENT TYPE A that is intended to be used in a RESTRICTED ACCESS LOCATION where equipotential bonding has been applied, for example, in a telecommunication centre; and has provision for a permanently connected PROTECTIVE EARTHING CONDUCTOR; and is provided with instructions for the installation of that conductor by a SERVICE PERSON; • STATIONARY PLUGGABLE EQUIPMENT TYPE B; • STATIONARY PERMANENTLY CONNECTED EQUIPMENT.		N/A
6.1.2.1 (A1:2010)	In **Finland**, **Norway** and **Sweden**, add the following text between the first and second paragraph of the compliance clause: If this insulation is solid, including insulation forming part of a component, it shall at least consist of either - two layers of thin sheet material, each of which shall pass the electric strength test below, or - one layer having a distance through insulation of at least 0,4 mm, which shall pass the electric strength test below. Alternatively for components, there is no distance through insulation requirements for the insulation consisting of an insulating compound completely filling the casing, so that CLEARANCES and CREEPAGE DISTANCES do not exist, if the component passes the electric strength test in accordance with the compliance clause below and in addition - passes the tests and inspection criteria of 2.10.11 with an electric strength test of 1,5 kV multiplied by 1,6 (the electric strength test of 2.10.10 shall be performed using 1,5 kV), and - is subject to ROUTINE TESTING for electric strength during manufacturing, using a test voltage of 1,5 kV.		N/A

Attachment 1 - European group differences and national differences (EN 60950-1:2006+A11:2009+A1:2010+A12:2011)

IEC60950_1C - ATTACHMENT			
Clause	Requirement + Test	Result - Remark	Verdict
	It is permitted to bridge this insulation with an optocoupler complying with 2.10.5.4 b). It is permitted to bridge this insulation with a capacitor complying with EN 60384-14:2005, subclass Y2. A capacitor classified Y3 according to EN 60384-14:2005, may bridge this insulation under the following conditions: - the insulation requirements are satisfied by having a capacitor classified Y3 as defined by EN 60384-14, which in addition to the Y3 testing, is tested with an impulse test of 2,5 kV defined in EN 60950-1:2006, 6.2.2.1; - the additional testing shall be performed on all the test specimens as described in EN 60384-14: - the impulse test of 2,5 kV is to be performed before the endurance test in EN 60384-14, in the sequence of tests as described in EN 60384-14.		
6.1.2.2	In **Finland**, **Norway** and **Sweden**, the exclusions are applicable for PERMANENTLY CONNECTED EQUIPMENT, PLUGGABLE EQUIPMENT TYPE B and equipment intended to be used in a RESTRICTED ACCESS LOCATION where equipotential bonding has been applied, e.g. in a telecommunication centre, and which has provision for a permanently connected PROTECTIVE EARTHING CONDUCTOR and is provided with instructions for the installation of that conductor by a SERVICE PERSON.		N/A
7.2	In **Finland**, **Norway** and **Sweden**, for requirements see 6.1.2.1 and 6.1.2.2 of this annex. The term TELECOMMUNICATION NETWORK in 6.1.2 being replaced by the term CABLE DISTRIBUTION SYSTEM.		N/A
7.3	In **Norway** and **Sweden**, for requirements see 1.2.13.14 and 1.7.2.1 of this annex.		N/A
7.3	In **Norway**, for installation conditions see EN 60728-11:2005.		N/A

Attachment 2 – Photograph

Front view

Attachment 2 – Photograph

Rear view

Attachment 2 – Photograph

Inside view

Attachment 2 – Photograph

Power supply view 1



Attachment 2 – Photograph

Power supply view 2