

TEST REPORT

**CTK Co., Ltd.**

5 Dongbu-ro 221beon-gil, Cheoin-gu, Yongin-si,
Gyeonggi-do, Republic of Korea
Tel: +82-31-339-9970
Fax: +82-31-624-9501

REPORT No.:
CTK-2025-03137
Page (1) / (14) pages

1. Applicant

- Name : Hanwha Vision Co., Ltd.
- Address : 6, Pangyo-ro 319Beon-gil, Bundang-gu, Seongnam-si,
Gyeonggi-do, 13488 KOREA
- Date of Receipt : Feb. 25, 2022

2. Manufacturer

- Name : Hanwha Vision Co., Ltd.

3. Use of Report :

For submission to customer

4. Test sample / Model :

Network Thermal Camera / TNM-C4940TD

5. Date(s) of test :

Mar. 21, 2025 ~ Mar. 24, 2025

6. Test Standard (Method) used :

IEC 60529:1989 +A1:1999+A2:2013

7. Testing Environment :

Temperature: (25 ±10) °C, Humidity: (50 ±25) % R.H.

Pressure: (96 ±10) kPa

8. Test Results :

Refer to the test results

9. Location of Test :

☒ Permanent Testing Lab ☐ On Site Testing
(113, Yejik-ro, Cheoin-gu, Yongin-si, Gyeonggi-do, Republic of Korea)

The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This report cannot be reproduced or copied without the written consent of CTK.

Approval	Tested by	Technical Manager
	Name: HyungUk Jeon (Signature)	Name: HoHyun Lee (Signature)

Remark. This report is not related to KOLAS accreditation and relevant regulation.

Nov. 12, 2025

CTK Co., Ltd.



**CTK Co., Ltd.**

5 Dongbu-ro 221beon-gil, Cheoin-gu, Yongin-si,
Gyeonggi-do, Republic of Korea
Tel: +82-31-339-9970
Fax: +82-31-624-9501

REPORT No.:
CTK-2025-03137
Page (2) / (14) pages

Table of Contents

1. Testing laboratory	3
1.1 Testing laboratory information	3
1.2 Testing laboratory accreditation status.....	3
2. Product description and equipment information	4
2.1 Product description	4
2.2 Equipment information	4
2.3 Pre-test product images	5
2.4 Testing equipment images.....	6
2.5 Product appearance.....	8
3. Degrees of protection provided by enclosures (IP code)	9
3.1 Test date and environmental conditions	9
3.2 Test conditions and methods.....	9
3.3 Testing images	11
3.4 Test result.....	12
3.5 Post-test product images	13

**CTK Co., Ltd.**

5 Dongbu-ro 221beon-gil, Cheoin-gu, Yongin-si,
Gyeonggi-do, Republic of Korea
Tel: +82-31-339-9970
Fax: +82-31-624-9501

REPORT No.:
CTK-2025-03137
Page (3) / (14) pages

1. Testing laboratory

1.1 Testing laboratory information

Lab. Name	CTK Co., Ltd.
Representative	Young Joseph Seungwon
Address	5 Dongbu-ro 221beon-gil, Cheoin-gu, Yongin-si, Gyeonggi-do, Republic of Korea
Tel.	+82-31-339-9970
Fax.	+82-31-624-9501
E-Mail	all.youngin@element.com
Website	www.elementkorea.kr

1.2 Testing laboratory accreditation status

Country	Classification	Accreditation Number	Logo
International	KOLAS	TESTING NO. KT119	

**CTK Co., Ltd.**

5 Dongbu-ro 221beon-gil, Cheoin-gu, Yongin-si,
Gyeonggi-do, Republic of Korea
Tel: +82-31-339-9970
Fax: +82-31-624-9501

REPORT No.:
CTK-2025-03137
Page (4) / (14) pages

2. Product description and equipment information

2.1 Product description

Product Name	Model Name	Quantity	Comment
Network Thermal Camera	TNM-C4940TD	1 EA	–

2.2 Model description

Basic Model	TNM-C4940TD		
Series model	TNM-C4950TD, TNM-C4960TD, TNM-C4940TDR, TNM-C4942TDR, TNM-C4952TD, TNM-C4962TD		
Model differences	TNM-C4950TD, TNM-C4960TD, TNM-C4952TD, TNM-C4962TD	Use of the same external shape and materials (case, finishing material, PCB, cable, etc.), differences in SW.	
	TNM-C4940TDR, TNM-C4942TDR	differences in SW.	

2.3 Equipment information

Testing equipment	Model Name	Manufacturer	Manufacturing Number	Next Cal. Date
Stop Watch	NONE	Casio	612Q01R-1	Feb. 21, 2024
Aneroid Barometer	BAROMEX	SATO	84682	Feb. 02, 2024
Thermo/Humidity meter	Smart600	ZOGLAB	SMART1706010741A	Apr. 03, 2024
Push Pull Gage	FB30K	Imada	83805	Feb. 03, 2024
Test wire (1.0 mm)	TRP-02	ED&D	S1-J15	-
Dust Chamber	NONE	JFM	S3-IP36	Apr. 27, 2024
Waterproof test apparatus	IPX3-6	Kingpo	S3-IP37	-
Steel measuring meter	10 m	KOMELON	S3-D01	Nov. 11, 2024



CTK Co., Ltd.

5 Dongbu-ro 221beon-gil, Cheoin-gu, Yongin-si,
Gyeonggi-do, Republic of Korea
Tel: +82-31-339-9970
Fax: +82-31-624-9501

REPORT No.:
CTK-2025-03137
Page (5) / (14) pages

2.4 Pre-test product images

2.4.1 Test sample





CTK Co., Ltd.

5 Dongbu-ro 221beon-gil, Cheoin-gu, Yongin-si,
Gyeonggi-do, Republic of Korea
Tel: +82-31-339-9970
Fax: +82-31-624-9501

REPORT No.:
CTK-2025-03137
Page (6) / (14) pages

2.5 Testing equipment images

2.5.1 Test equipment (1)



Stop Watch



Aneroid Barometer



Thermo/Humidity meter



Push Pull Gage



Test Rod Probe Ø1.0



Dust Chamber



CTK Co., Ltd.

5 Dongbu-ro 221beon-gil, Cheoin-gu, Yongin-si,
Gyeonggi-do, Republic of Korea
Tel: +82-31-339-9970
Fax: +82-31-624-9501

REPORT No.:
CTK-2025-03137
Page (7) / (14) pages

2.5.2 Test equipment



Waterproof test apparatus



Steel measuring meter




CTK Co., Ltd.

5 Dongbu-ro 221beon-gil, Cheoin-gu, Yongin-si,
Gyeonggi-do, Republic of Korea
Tel: +82-31-339-9970
Fax: +82-31-624-9501

REPORT No.:
CTK-2025-03137
Page (8) / (14) pages

2.6 Product appearance

Enclosure dimensions [unit : mm]



**CTK Co., Ltd.**

5 Dongbu-ro 221beon-gil, Cheoin-gu, Yongin-si,
Gyeonggi-do, Republic of Korea
Tel: +82-31-339-9970
Fax: +82-31-624-9501

REPORT No.:
CTK-2025-03137
Page (9) / (14) pages

3. Degrees of protection provided by enclosures (IP code)

3.1 Test date and environmental conditions

3.1.1 Test date: Apr. 21, 2022 ~ Apr. 24, 2022

3.1.2 Measured Environmental Conditions

Item	Temperature (°C)	Humidity (% R.H.)	Pressure (kPa)
Measurement	27.6	67.4	89.1

3.2 Test conditions and methods

3.2.1 Test standard: IEC 60529:1989+A1:1999+A2:2013

3.2.2 Arrangement of the IP code

	IP	6	6
Code letters (International protection)	←		
First characteristic numeral (numerals 0 to 6, for letter X)	←		
Second characteristic numeral (numerals 0 to 8, for letter X)	←		

3.2.2.1 Degree of protection against access to hazardous parts indicated by the first characteristic numeral

First characteristic numeral	Degree of protection	Application
6	Protected against access to hazardous parts with a wire. The access probe of 1.0 mmØ, shall not penetrate. Test force: 1 N ± 10 %	☒

NOTE In the case of the first characteristic numerals 3, 4, 5 and 6, protection against access to hazardous parts is satisfied if adequate clearance is kept. The adequate clearance should be specified by the relevant product committee in accordance with 12.3.

Due to the simultaneous requirement specified in table 2, the definition "shall not penetrate" is given in table 1.

**CTK Co., Ltd.**

5 Dongbu-ro 221beon-gil, Cheoin-gu, Yongin-si,
Gyeonggi-do, Republic of Korea
Tel: +82-31-339-9970
Fax: +82-31-624-9501

REPORT No.:
CTK-2025-03137
Page (10) / (14) pages

3.2.2.2 Degree of protection against solid foreign objects indicated by the first characteristic numeral

First characteristic numeral	Degree of protection	Application
6	In Dust Testing Equipment, the test sample must have no ingress of dust after testing atmospheric pressure present condition for 8 h. (The talcum powder must pass through a calibrated sieve with a 50 µm wire mesh, spaced at 75 µm intervals in a square pattern. Additionally, the bulk density of the talcum powder should be 2 kg/m³) Products in volume: 10 884.75 cm³ → 10.884 L Target intake volume (Products in volume 80) : 870.780 L Suction volume (Max product in volume 60) ...: 653.085 LPH → 10.884 LPM Actual Suction volume: 10.884 L Suction pressure (Up to 2 kPa): 2 kPa Test time (Up to 8 time): 8 시간	☒
¹⁾ The full diameter of the object probe shall not pass through an opening of the enclosure. Due to the simultaneous requirement specified in table 2, the definition “shall not penetrate” is given in table 1.		

3.2.2.3 Degree of protection against water indicated by the second characteristic numeral

Second characteristic numeral	Degrees of protection	Application
6	The product must not be harmed in any direction even strong jet water. Water jet hose nozzle Fig.6, Nozzle 12.5 mm diameter Water flow rate: 100 l/min ± 5 % : 100 LPM Distance: 2.5 m to 3 m: 3 m Duration of test: 1 min/m² at least 3 min: 3 min	☒

3.3 Testing images

3.3.1 Evidence of test setting (1)



Dust test



Water test

**CTK Co., Ltd.**

5 Dongbu-ro 221beon-gil, Cheoin-gu, Yongin-si,
Gyeonggi-do, Republic of Korea
Tel: +82-31-339-9970
Fax: +82-31-624-9501

REPORT No.:
CTK-2025-03137
Page (12) / (14) pages

3.4 Test result

3.4.1 Test result table

IP code	Evaluation Criteria	Test Results	Remark
IP 6X	No ingress of Probe	Normal	-
	No ingress of dust	Normal	
IP X6	No ingress of water	Normal	

※ Refer to the product photos after the completion of testing in section 3.5.

3.5 Post-test product images

3.5.1 Product internal images after test [The first characteristic numeral test]



3.5.2 Product internal images after test [The second characteristic numeral test]



- End -