



Network

TNM-X6320A1WT1-M

Bi-spectrum AI Thermal Camera



Key Features

- ATEX and IECEx certified
- Electro-polished 316L stainless steel on all welded assemblies
- Camera station window in toughened glass

TNM-X6320A1WT1-M

Bi-spectrum AI Thermal Camera



Specifications

Video		Visible	Thermal
Imaging Device	Size	1/2.8"	
	Type	CMOS	Uncooled micro bolometer (384x288)
Resolution		1920x1080, 1280x1024, 1280x960, 1280x720, 1024x768, 800x600, 800x448, 720x576, 720x480, 640x480, 640x360, 320x240	768x576, 384x288
Max. Framerate	H.265/H.264	60fps/50fps(60Hz/50Hz)	8fps
	MJPEG	30fps	8fps
Spectral Range			8~14 μ m
NETD			$\leq$ 30mK
Pixel Size			17 μ m
Min. Illumination (Lux)	Color(1/30sec, 30IRE)	0.05	
	BW(1/30sec, 30IRE)	0.005	
Video Out		CVBS: 1.0 Vp-p / 75 Ω composite for installation	USB: Micro USB Type B

Lens

Focal Length (mm)		4.44~142.6	9.7
Zoom Ratio	Optical	32x	
	Digital	32x	
Max Aperture Ratio (F number)	Wide	1.6	1.0
	Tele	4.4	
Angular Field of View	Horizontal	64.66°~2.29°	38°
	Vertical	38.08°~1.30°	29°
	Diagonal		47°
iFoV			1.8 mRad
Min. Object Distance		1.5m(4.92ft)	2.8m(9.19ft)
Focus Control		Auto, Oneshot AF	Fixed
Lens Type		DC auto iris	

Operational

Direction Indicator		Support	
Day & Night		Auto(ICR)	
Backlight Compensation		BLC, HLC, WDR, SSDR	
Wide Dynamic Range (dB)		120	
Digital Noise Reduction		SSNR V	
Digital Image Stabilization		Support	
Defog		Support	
Motion Detection	Quantity	8ea	8ea
	Shape	8point Polygonal zones	8point Polygonal zones
Privacy Masking	Quantity	32ea	6ea
	Shape	Rectangular zones	Rectangular zones
	Color / Option	Gray, Green, Red, Blue, Black, White, Mosaic	Gray, Black, White
Gain Control		Low, Middle, High, Off	
White Balance		ATW, AWC, Manual, Indoor, Outdoor, Mercury, Sodium	
Electronic Shutter	Mode	Minimum, Maximum, Anti flicker	
	Speed Range	2~1/12,000sec	
Video Rotation		Flip, Mirror	Flip, Mirror, Hallway view(90°/270°)
Serial Interface		RS-485(Samsung-T, Pelco-D/P, Panasonic, Bosch, AD, GE, Vicon, Honeywell)	RS-485
Alarm Interface	In/Out	Input 1ea, Output 1ea	2 configurable I/O ports
Alarm Triggers		Analytics, Network disconnect, Alarm input	Analytics, Network disconnect, Alarm input, Time schedule, MQTT subscription
Alarm Events When Alarm Trigger Occurred		File upload(image): e-mail/FTP, Notification: e-mail, Recording: SD/SDHC/SDXC or NAS recording at event triggers, Alarm output, Handover: PTZ preset	File upload(image): e-mail/FTP, Notification: e-mail, Recording: SD/SDHC/SDXC or NAS recording at event triggers, Alarm output, Handover: PTZ preset, MQTT: publication
Audio In		Selectable(mic in/line in)	Selectable(mic in/line in)
Audio Out		Line out	Line out
Color Palettes			Whitehot, Blackhot, Rainbow, Rainbow2, Sepia, Red, Iron, Custom

Analytics

Classified Object Type		Person, Vehicle
Thumbnail		BestShot

Analytics

Analytics Events	Based on AI Engine		Object detection, Virtual line(Crossing/Direction), Virtual area(Loitering/Intrusion/Enter/Exit), Motion detection
	Normal	Defocus detection, Motion detection, Tampering, Fog detection, Face detection, Audio detection, Sound classification, Virtual area(Loitering, Intrusion, Enter/Exit, Appear/Disappear)	Motion detection, Tampering, Audio detection, Sound classification, Shock detection, Virtual area(Appear/Disappear), Temperature detection, Tank level detection, Temperature change detection

Radiometry

Temperature Detect Range			-40°C~550°C
Temperature Accuracy			±2°C(≤150°C), ±15%(>150°C)
Temperature Detection ROI Zones	Quantity		10ea
	Shape / Option		Polygonal
Hybrid Pallettes			Support
Spot Temperature Reading			Support
ROI Condition Monitoring			Above, Below, Increase, Decrease

Network

Ethernet		Metal shielded RJ-45(10/100BASE-T)	Metal shielded RJ-45(10/100/1000BASE-T)
Video Compression		H.265/H.264: Main/Baseline/High, MJPEG	H.265/H.264: Main/Baseline/High, MJPEG
Audio Compression		G.711 u-law /G.726 selectable,G.726(ADPCM) 8kHz,G.711 8kHz, G.726: 16kbps,24kbps,32kbps,40kbps, AAC-LC: 48kbps at 16kHz	G.711 u-law /G.726 selectable,G.726(ADPCM) 8kHz,G.711 8kHz, G.726: 16kbps,24kbps,32kbps,40kbps, AAC-LC: 48kbps at 16kHz
Smart Codec		Manual, WiseStream II	Manual, WiseStream II
Bitrate Control		H.265/H.264: CBR or VBR, MJPEG: VBR	H.265/H.264: CBR or VBR, MJPEG: VBR
Streaming	Unicast	Up to 20 users	Up to 20 users
	Multicast	Support	Support
	Multiple Streaming	Up to 10 profiles	Up to 10 profiles
Protocol		IPv4, IPv6, TCP/IP, UDP/IP, RTP(UDP), RTP(TCP), RTCP, RTSP, NTP, HTTP, HTTPS, SSL/TLS, DHCP, FTP, SMTP, ICMP, IGMP, SNMPv1/v2c/v3(MIB-2), ARP, DNS, DDNS, QoS, UPnP, Bonjour, LLDP, SRTP(TCP, UDP Unicast), PIM-SM	IPv4, IPv6, TCP/IP, UDP/IP, RTP(UDP), RTP(TCP), RTCP, RTSP, NTP, HTTP, HTTPS, SSL/TLS, DHCP, FTP, SMTP, ICMP, IGMP, SNMPv1/v2c/v3(MIB-2), ARP, DNS, DDNS, QoS, UPnP, Bonjour, LLDP, CDP, SRTP(TCP, UDP Unicast), MQTT
Application Programming Interface	ONVIF	S, G, T	S, G, T, M
	Others	SUNAPI(HTTP API), Hanwha Vision Open Platform	SUNAPI(HTTP API), Hanwha Vision Open Platform
Direct Cloud Connection		Optional (needs gateway)	Support

Security

OS / Firmware Protect	Encrypted firmware	Encrypted firmware, Secure boot, Signed firmware
-----------------------	--------------------	--

Security

User authentication	Digest authentication	Digest authentication, Prevent brute-force attack
Network authentication	IEEE 802.1X(EAP-TLS, EAP-LEAP, EAP-PEAP, MSCHAPv2)	IEEE 802.1X(EAP-TLS, EAP-LEAP, EAP-PEAP, MSCHAPv2)
Secure Communication	HTTPS, WSS(WebSocket Secure), SRTP	HTTPS, WSS(WebSocket Secure), SRTP
Access Control	IP-based access control	IP-based access control
Data Protect	Encryption credentials	Encryption credentials
Audit	Access / System / Event Log management	Access / System / Event Log management
Device ID	Device certificate(Hanwha Vision Root CA)	Device certificate(Hanwha Vision Root CA)
Secure Storage		TPM(Trusted platform module), SDcard partition encrypt(AES-256)
Security Certificate		TPM 2.0 with FIPS 140-2 level2

General

Memory	RAM	1GB	2GB
	Flash	256MB	512MB
Edge Storage	Micro SD/SDHC/SDXC	Max. 256GB x 1slot	Max. 1TB x 1slot

Environmental & Electrical

Operating Condition	Temperature	-40°C~+60°C(-40°F~+140°F)
Input Voltage		24VAC

Mechanical

Color	Silver
Material	Stainless(STS316L)
Product Dimensions	419x641x457

Certifications & Standards

Environment	IEC 60529 IP66, IEC 60529 IP67, II 2 G Ex db IIB+H2 II, 2 D Ex tb IIIC IECEX ATEX certified, INMETRO, Class I II III Division 1 Groups B, C, D, E, F, G, cFMus Approved
-------------	---

DORI (EN62676-4 standard)

Detect (25PPM/ 8PPF)	Wide	60.7m(199.1ft)	
	Tele	1921.3m(6303.4ft)	
Observe (63PPM/ 19PPF)	Wide	24.3m(79.6ft)	
	Tele	768.5m(2521.4ft)	
Recognize (125PPM/ 38PPF)	Wide	12.1m(39.8ft)	
	Tele	384.3m(1260.7ft)	
Identify (250PPM/ 76PPF)	Wide	6.1m(19.9ft)	
	Tele	192.1m(630.3ft)	