



TEST REPORT



Report No. : KES-EM262107

Page 1 / 71

KES Co., Ltd.

#3002, #3503, #3701, 40, Simin-daero365beon-gil, Dongan-gu, Anyang-si, Gyeonggi-do, 14057, Republic of Korea
Tel : +82-31-425-6200, Fax : +82-31-341-3838

1. Client

- Name : Hanwha Vision Co., Ltd.
- Address : 6, Pangyo-ro 319beon-gil, Bundang-gu, Seongnam-si, Gyeonggi-do, Republic of Korea

2. Sample Description

- Product item : NETWORK CAMERA
- Model name : TNO-A45080R
- Variant model : -
- Manufacturer etc. : HANWHA VISION VIETNAM COMPANY LIMITED
- Manufacturer address : Lot O-2, Que Vo Industrial Zone Extended Area, Nam Son Ward, Bac Ninh Province, Vietnam
- Manufacturer etc. : D-TECH CO.,LTD.
- Manufacturer address : 173-25, Saneop-ro, Gwonseon-gu, Suwon-si, Gyeonggi-do, Korea (Suwon Industrial Complex)

3. Date of test

: 2026. 06. 16. ~ 2026. 06. 20.

4. Location of Test

- Address : Permanent Testing Lab
- Address : 473-21, Gayeo-ro, Yeoju-si, Gyeonggi-do, 12658, Republic of Korea

5. Test method used

: EN 55032:2015+A1:2020, EN 50130-4:2011+A1:2014,
: EN IEC 61000-3-2:2019, EN 61000-3-3:2013+A2:2021

6. Test result



: PASS

The results shown in this test report refer only to the sample(s) tested unless otherwise stated.

This test report cannot be reproduced and copied without permission without the written consent of KES Co., Ltd.

This laboratory is not accredited for the test results marked *.

This test report is not related to KOLAS accreditation.

Affirmation	Tested by	Technical Manager by
	Name : SeongMin Jang  [장성민]2026/07/03	Name : DongHun Jang  [장동훈]2026/07/03

2026. 07. 03.

KES Co., Ltd.

**REPORT REVISION HISTORY**

Date	Test Report No.	Revision History
2026. 07. 03.	KES-EM262107	Issued

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd. This document may be altered or revised by KES Co., Ltd. personnel only, and shall be noted in the revision section of the document. Any alteration of this document not carried out by KES Co., Ltd. will constitute fraud and shall nullify the document.

Use of uncertainty of measurement for decisions on conformity (decision rule):

- ☒ No decision rule is specified by the standard, when comparing the measurement result with the applicable limit according to the specification in that standard. The decisions on conformity are made without applying the measurement uncertainty("simple acceptance" decision rule, previously known as "accuracy method").
- ☐ Other (to be specified, for example when required by the standard or client)



TABLE OF CONTENTS

1	Laboratory Information	4
1.1	Test Location	4
1.2	Laboratory Accreditations and Listings	4
2	Test Summary	5
2.1	Class and Voltage	5
2.2	Summary of Test Results	5
2.3	Remarks when standards applied	6
2.4	Variant Model Differences	6
2.5	Device Modifications	6
3	General Product Description	7
4	EUT Setup and Operation Mode	9
4.1	EUT Configuration	9
4.2	System Configuration	9
4.3	External I/O Cabling	10
4.4	EUT Operating Mode(s)	11
4.5	Test operating S/W	11
4.6	Configuration	12
5	General Performance Criteria	13
6	Test Item	15
6.1	Conducted Emissions at Mains Power Ports	15
6.2	Conducted Emissions at Telecommunication Ports	18
6.3	Radiated Emissions(Below 1 GHz)	21
6.4	Radiated Emissions(Above 1 GHz)	24
6.5	Harmonic Current Emissions	27
6.6	Voltage Fluctuations and Flicker	31
6.7	Electrostatic Discharge	33
6.8	Continuous RF electromagnetic field disturbances	39
6.9	Electrical Fast Transients/Bursts	42
6.10	Surge	45
6.11	Continuous Induced RF Disturbances	48
6.12	Voltage Dips and Interruptions	51
7	Test Setup Photos and EUT Photographs	53
7.1	Test Setup Photos	53
7.2	EUT Photographs	67
7.3	Label	71



1 Laboratory Information

1.1 Test Location

Category	Details
Address	473-21, Gayeo-ro, Yeosu-si, Gyeonggi-do, 12658, Republic of Korea
Telephone Number	031-883-5092
Facsimile Number	031-883-5169

The measurement facility is located at 473-21, Gayeo-ro, Yeosu-si, Gyeonggi-do, 12658, Republic of Korea. The sites are constructed in conformance with the requirements of ANSI C63.4a-2017 and CISPR 16-1-4:2019

1.2 Laboratory Accreditations and Listings

Country	Agency	Scope of Accreditation	Logo
KOREA	RRA	EMI (3 m & 10 m Semi-Anechoic Chamber and conducted test site) EMS (ESD, RS, EFT/Burst, Surge, CS, Magnetic, Dips and interruptions)	 KR0100
International	KOLAS	EMI (3 m & 10 m Semi-Anechoic Chamber and conducted test site) EMS (ESD, RS, EFT/Burst, Surge, CS, Magnetic, Dips and interruptions)	 KT489
USA	FCC	3 m & 10 m Semi-Anechoic Chamber Conducted test site to perform FCC Part 15/18 measurements.	 KR0100
Canada	ISED	3 m & 10 m Semi-Anechoic Chamber and Conducted test site	 23298
JAPAN	VCCI	EMI (3 m & 10 m Semi-Anechoic Chamber and conducted test site)	 C-20136, T-20137, R-20181, G-20176
Europe	TÜV SÜD	EMI (3 m & 10 m Semi-Anechoic Chamber and conducted test site) EMS (ESD, RS, EFT/Burst, Surge, CS, Magnetic, Dips and interruptions)	 CARAT 001633 0008



2 Test Summary

2.1 Class and Voltage

Test Class	Test Voltage
Class A	AC 230 V, 50 Hz, PoE

2.2 Summary of Test Results

Regulation
EMC Directive 2014/30/EU, EMC Regulations SI 2016/1091

Test Item	Test Standard		Test Result	Remark
Conducted Emissions at Mains Power Ports	EN 55032:2015+A1:2020		PASS	NOTE 1
Conducted Emissions at Telecommunication Ports			PASS	-
Radiated Emissions(Below 1 GHz)			PASS	-
Radiated Emissions(Above 1 GHz)			PASS	-
Harmonic Current Emissions	EN IEC 61000-3-2:2019		PASS	NOTE 1
Voltage Fluctuations and Flicker	EN 61000-3-3:2013+A2:2021		PASS	NOTE 1
Electrostatic Discharge	EN 50130-4:2011+A1:2014	EN 61000-4-2:2009	PASS	-
Continuous RF electromagnetic field disturbances		EN IEC 61000-4-3:2020	PASS	-
Electrical Fast Transients/Bursts		EN 61000-4-4:2012	PASS	NOTE 1
Surge		EN 61000-4-5 :2014+A1:2017	PASS	NOTE 1
Continuous Induced RF Disturbances		EN IEC 61000-4-6:2023	PASS	NOTE 1
Voltage Dips and Interruptions		EN IEC 61000-4-11:2020	PASS	NOTE 1

* N/A: Not Applicable

(NOTE 1) PoE Power Mode is powered by the PoE port, PoE port is considered to be wired network port, so power-related test items are excluded.



2.3 Remarks when standards applied

- When the SFP port was connected during the Mode 2 test, the RJ-45 (Data) port did not operate, so the port was excluded during the test.

2.4 Variant Model Differences

N/A

2.5 Device Modifications

N/A





3 General Product Description

Division		Specificity
Internal maximum operating frequency		1 400 MHz
Video		
Imaging Device	Size	Diagonal 28.3mm 1.8"
	Type	CMOS
Resolution		45MP Mode : 8192x5552, 7792x5280, 7392x5008, 6752x4576, 5936x4024, 4512x3056, 4096x2776, 3456x2344, 2880x1952, 2240x1520, 1440x976, 1216x824, 800x544 32M Mode : 7680x4320, 7424x4176, 7680x3840, 6400x4800, 6144x3456, 5120x2880, 4096x3072, 3840x2160, 3200x2400, 3328x1872, 2688x1512, 2560x1440, 1920x1080, 1664x1088, 1408x1088 8192x5552(45MP)
Max. Resolution		45.48MP
Max. Resolution(MP)		
Max. Framerate	H.265/H.264	Max 25fps(Max 15fps@45MP, Max 25fps@33.2MP)
	MJPEG	Max 25fps(Max 1fps@45fps, 1fps@8K)
Min. Illumination(Lux)	Color(1/30sec, 30IRE)	0.08
	BW(1/30sec, 30IRE)	0.008
Lens		
Focal Length (Zoom Ratio)		12-51mm(4.2x)
Zoom Ratio	Optical	4.2x
Max. Focal Length		51mm
Min. Focal Length		12mm
Zoom Ratio		4.2x
Focal Type		Motorized varifocal
Max. Aperture Ratio	Wide	1.6
	Tele	3.8
Angular Field of View	Horizontal	89.6°~21.1°
	Vertical	61.1°~14.2°
	Diagonal	107.3°~25.4°
Min. Object Distance		1.8m(Wide)~2.2m(Tele)
Focus Control		Simple focus
Lens Type		P-iris
Pan / Tilt / Rotate		
Pan / Tilt / Rotate Range	Pan	±180°
	Tilt	0~90°
	Rotate	-90~270°
Operational		
Day & Night		Auto(ICR)
Backlight Compensation		BLC, SSDR, DWDR
Digital Noise Reduction		SSNR.V., WiseNR II(Based on AI engine)(revision)
Digital Image Stabilization		Support
Defog		Support
Motion Detection	Quantity	8ea
	Shape	8point polygonal zones
Privacy Masking	Quantity	16ea
	Shape	4point polygonal zones
	Color/Option	gray/green/red/blue/black/white/purple/yellow
Gain Control		Low / Middle / High
White Balance		ATW / AWC / Manual / Indoor / Outdoor
LDC		Support
Electronic Shutter Speed	Mode	Minimum, Maximum, Anti flicker, Prefer shutter control(Based on AI engine)
	Speed Range	1/5~1/12,000sec
Video Rotation		Flip, Mirror, Halfway view(90°/270°)
Alarm Interface	In/Out	2 configurable I/O ports
Alarm Triggers		Analytics, Network disconnection, Alarm input, Time schedule, MQTT subscription, Day/Night, Storage disruption, Case tampering
Alarm Events When Alarm Trigger Occurred		- File upload(image): e-mail/FTP/SFTP - File upload(video clip): FTP/SFTP - Notification: e-mail - Recording: SD/SDHC/SDXC or NAS recording at event triggers - Alarm output - Handover: PTZ preset, send message by HTTP/HTTPS/TCP - Audio clip playback(WAV, MP3) - MQTT: publication
Audio In		Selectable(mic in/line in)
Audio Out		Line out
Light Type		IR LED
Light Viewable Length	IR	WiseIR 60m
IR Wavelength		850nm



Analytics		
Classified Object Type		Person, Face, Vehicle, License plate
Attributes	Person	Gender, Clothing top/bottom color, Bag
	Vehicle	Type(car/bus/truck/motorcycle/bicycle), Color
	Face	Age, Gender, Mask, Glasses
Sunukaruty Search		IP-based access control, MAC-based access control, Auto logout
Thumbnail		BestShot
Analytics Events	Based on AI Engine	Motion detection, Object detection, Virtual line(Crossing/Direction), Virtual area(Loitering/Intrusion/ Enter/Exit/Appear/Disappear)
	Normal	Defocus detection, Tampering, Shock detection, Virtual area(Appear/Disappear)
Business Intelligence		People/Vehicle/Crowd counting, Queue management, Heatmap
Network		
Ethernet		Metal shielded RJ-45(10/100/1000 BASE-T), SFP slot(100/1000Mbps)
Video Compression		H.265/H.264: Main/High, MJPEG
Audio Compression		G.711(PCM): 8kHz(64kbps)
		G.726(ADPCM): 8kHz(16/24/32/40kbps)
		AAC-LC: 16kHz(48kbps)
		OPUS: 16kHz(64kbps)
Smart Codec		Manual(Sea area), WiseStream(Based on AI engine)
Bitrate Control		H.264/H.265: CBR or VBR
Streaming	Unicast	Up to 20 users
	Multicast	Support
	Multiple Streaming	Up to 3 profiles
Protocol		IPv4, IPv6, TCP/IP, UDP/IP, RTP(UDP), RTP(TCP), RTCP, RTSP, NTP, HTTP, HTTPS, SSL/TLS, DHCP, FTP/SFTP, SMTP, ICMP, IGMP, SNMPv1/v2c/v3(MIB-2), ARP, DNS, DDNS, QoS, UPnP, Bonjour, LLDP, SRTP(TCP, UDP Unicast), CDP, MQTT, Syslog
Application Programming Interface	ONVIF	S, G, T, M
	Others	SUNAPI(HTTP API), Hanwha Vision Open Platform
Security		
OS / Firmware Protect		Secure boot, Signed firmware, Firmware encryption
User authentication		Digest Authentication, Prevent brute-force attack
Network authentication		802.1X Authentication(EAP-TLS, EAP-LEAP, EAP-PEAP MSCHAPv2), 802.1AE(MACsec)
Secure Communication		HTTPS, SRTP, WSS(Websocket secure)
Access Control		IP-based access control, MAC-based access control, Auto logout
Data Protect		Authentication information encryption, ZIP compression encryption
Audit		User Access/System/Event log management
Device ID		Device Certificate(Hanwha vision Root CA)
Secure Storage		Secure element, SDcard partition encrypt
Security Certificate		ETSI EN 303 645, Secure element/FIPS 140-3 level3, CC EAL6+
General		
Edge Storage	Micro SD/SDHC/SDXC	Max 1TB x 1slot
Memory	RAM	8GB
	FLASH	16GB
Environmental & Electrical		
Operating Condition	Temperature	-40°C~+55°C(-40°F~+131°F)
	Humidity	0~100%RH(Condensing)
	Others	Humidity control with AIR vent
Storage Condition	Temperature	-50°C~+60°C(-58°F~+140°F)
	Humidity	0~95% RH (non-condensing)
Input Voltage		PoE+ (IEEE802.3at, Class4)
		PoE++(IEEE802.3bt, Class6)
		12VDC
Power Consumption	PoE++	Max. 39.4W, typical 19.0W
	12VDC	Max. 37.3W, typical 18.4W
WisePower		Support
Mechanical		
Color		White/Black
Material		Aluminum/Plastic
RAL Code		RAL9003
Product Dimensions		120mm * 120mm * 350mm
Product Weight		4.05Kg



4 EUT Setup and Operation Mode

4.1 EUT Configuration

Product Name	Model Number	Serial Number	Manufacturer	Remarks
NETWORK CAMERA	TNO-A45080R	-	HANWHA VISION VIETNAM COMPANY LIMITED	EUT
PoE Injector	PT-PSE109GBRO- AH-S	-	Dongguan PROCET Network Technology Co.,Ltd	-
AC/DC Adaptor	FJ-SW1205000	-	SHENZHEN FUJIA APPLIANCE CO., LTD.	-
Laptop	NT350XCR	-	Samsung Electronics Vietnam Co., Ltd.	-
Laptop Adaptor	A13-040N2A	-	Chicony Power Technology Co., Ltd.	-
Micro SD card #1	-	-	SanDisk	32 GB
Micro SD card #2	-	-	SanDisk	32 GB
Earphone	-	-	-	-
LED Alarm	PRO-SL	-	SENSOR PRO	-
Button Alarm	-	-	-	-
Smartphone	SM-N960N	-	SAMSUNG	-
Optical module #1	FTRJ8519P1BNL	-	Finisar	-
Optical module #2	FTRJ8519P1BNL	-	Finisar	-

4.2 System Configuration

Product Name	Model Number	Serial Number	Manufacturer	Remarks
-	-	-	-	-



4.3 External I/O Cabling

Mode 1

Start		End		Cable Spec.	
Description	I/O Port	Description	I/O Port	Length	Shield
EUT	RJ-45(PoE)	PoE Injector	RJ-45(PoE)	3.5	U
	Micro SD card slot	Micro SD Card #1	Micro SD card slot	-	-
	Micro SD card slot	Micro SD Card #2	Micro SD card slot	-	-
	Alarm OUT	LED Alarm	Alarm IN	3.2	U
	Alarm IN	Button Alarm	Alarm OUT	3.5	U
	SPEAKER	Earphone	Line	1.2	U
	MIC	Smartphone	3.5 mm	1.7	U
	SFP	Optical module #2	SFP	-	-
Optical module #2	SFP	Optical module #1	SFP	2.9	U
Optical module #1	SFP	PoE Injector	SFP	-	-
PoE Injector	RJ-45(LAN)	Laptop	RJ-45	1.3	U
Laptop	DC Jack	Laptop Adaptor	Line	1.5	U

Mode 2

Start		End		Cable Spec.	
Description	I/O Port	Description	I/O Port	Length	Shield
EUT	DC IN	AC/DC Adaptor	Line	1.5	U
	RJ-45(LAN)	Laptop	RJ-45(LAN)	3.5	U
	Micro SD card slot	Micro SD Card #1	Micro SD card slot	-	-
	Micro SD card slot	Micro SD Card #2	Micro SD card slot	-	-
	Alarm OUT	LED Alarm	Alarm IN	3.2	U
	Alarm IN	Button Alarm	Alarm OUT	3.5	U
	SPEAKER	Earphone	Line	1.2	U
	MIC	Smartphoen	3.5 mm	1.7	U
Laptop	DC Jack	Laptop Adaptor	Line	1.5	U

* Unshielded=U, Shielded=S



4.4 EUT Operating Mode(s)


Category	Mode	Operating
Mode 1	PoE	1. After accessing the webpage of the Laptop, check whether the image of the EUT is output normally and verify that the network is operating normally through the ping test. 2. Press Button Alarm to verify that LED Alarm is operating normally. 3. Checked if the 1 kHz tone sound played on the smartphone is output to the earphone normally. 4. Checked the LINK LED on the PoE Injector connected to the EUT for the SFP connection to function properly. 5. After the test, I checked if it was recorded normally on Micro SD cards #1 and #2.
Mode 2	DC 12 V	1. After accessing the webpage of the Laptop, check whether the image of the EUT is output normally and verify that the network is operating normally through the ping test. 2. Press Button Alarm to verify that LED Alarm is operating normally. 3. Checked if the 1 kHz tone sound played on the smartphone is output to the earphone normally. 4. After the test, I checked if it was recorded normally on Micro SD cards #1 and #2.

4.5 Test operating S/W


Name	Version	Manufacture Company
Web Page	-	Hanwha Vision Co., Ltd.



4.6 Configuration



Mode 1



Mode 2



5 General Performance Criteria

Criteria for compliance was based on the following guidelines:

EN 50130-4 Alarm systems-Part 4: Electromagnetic compatibility Product family standard: Immunity requirements for components of fire, intruder and social alarm systems

The variety and the diversity of the apparatus within the scope of this document makes it difficult to define precise criteria for the evaluation of the immunity test results.

If as a result of the application of the tests defined in this standard, the apparatus becomes dangerous or unsafe then the apparatus shall be deemed to have failed the test.

A functional description and a definition of performance by the manufacture and noted in the test report, based on the following criteria:

Electrostatic discharge

There shall be no damage, malfunction or change of status due to the conditioning.

Flickering of an indicator during the application of discharge is permissible, providing that is no residual change in the EUT or any change in outputs, which could be interpreted by associated equipment as a change.

Radiated electromagnetic fields

There shall be no damage, malfunction or change of status due to the conditioning.

Flickering of an indicator during the application of discharge is permissible, providing which could be interpreted by associated equipment as a change, and no such Flickering of indicators occurs at a field strength of 3 V/m.

For components of CCTV systems, where the picture is allowed at 10 V/m, providing.

- (a) there is no permanent damage or change to EUT
(e.g. no corruption of memory or changes to programmable setting etc.)
- (b) at 3 V/m, any deterioration of the picture is so minor that the system could still be used; and
- (c) there is no observable deterioration of the picture at 1 V/m.

Fast transient burst / slow high energy voltage surge

There shall be no damage, malfunction or change of status due to the conditioning.

Flickering of an indicator during the application of discharge is permissible, providing

That there is no residual is permissible, providing that there is no residual change in the EUT or any change in outputs, which could be interpreted by associated equipment as a change.

**Conducted RF immunity**

There shall be no damage, malfunction or change of status due to the conditioning.

Flickering of an indicator during the application of discharge is permissible, providing

That there is no residual is permissible, providing that there is no residual change in the EUT or any

change in outputs, which could be interpreted by associated equipment as a change,

and no such flickering of indicators oeuvres at $U = 130 \text{ dB}\mu\text{V}$.

For component of CCTV systems, where the status is monitored by observing the TV picture,

then deterioration of the picture is allowed at $U = 140 \text{ dB}\mu\text{V}$, providing:

(a) there is no permanent damage or change to the EUT

(e.g. no corruption of memory or changes to programmable settings etc.)

(b) at $U = 130 \text{ dB}\mu\text{V}$, any deterioration of the picture is so minor that the system could still be used; and

(c) there in no observable deterioration of the picture at $U = 120 \text{ dB}\mu\text{V}$.

Voltage dip/interruption / Voltage variation

There shall be no damage, malfunction or change of status due to the conditioning.

Flickering of an indicator during the conditioning is permissible, providing that there is no residual

change in the EUT or any change in outputs, which could be interpreted by associated equipment

as a change. The EUT shall meet the acceptance criteria for the functional test, after the conditioning.

◆ Calculation**- Conducted Emissions**

QuasiPeak[dBuV] / CAverage [dBuV] = Reading Value[dBuV] + Corr. [dB]

QuasiPeak / CAverage : The Final Value

Reading Value : Not shown in the table.

Corr. : Correction values (LISN FACTOR + (Cable Loss + Pulse Limiter FACTOR))

- Radiated Emissions(Below 1 GHz)

Result(QP) [dB($\mu\text{V}/\text{m}$)] = (Reading(QP)[dB(μV)] + c.f[dB(1/m)])

Margin(QP)[dB] = Limit[dB($\mu\text{V}/\text{m}$)] - Result(QP) [dB($\mu\text{V}/\text{m}$)]

Reading(QP) : Reading value, Result(QP) : Reading value + Factor value

Limit(QP) : Limit value, c.f : (ANT Factor + Cable Loss - Preamp Factor), Margin: Margin value

- Radiated Emissions(Above 1 GHz)

Result(PK/CAV) [dB($\mu\text{V}/\text{m}$)] = (Reading(PK/CAV)[dB(μV)] + c.f[dB(1/m)])

Margin(PK/CAV)[dB] = Limit[dB($\mu\text{V}/\text{m}$)] - Result(PK/CAV) [dB($\mu\text{V}/\text{m}$)]

Reading(PK/CAV) : Reading value, Result(PK/CAV) : Reading value + Factor value

Limit(PK/CAV) : Limit value, c.f : (ANT Factor + Cable Loss - Preamp Factor), Margin: Margin value



6 Test Item

6.1 Conducted Emissions at Mains Power Ports

6.1.1 Test Equipment

Equipment Name	Model Number	Manufacturer	Serial No.	Cal. Date	Next Cal. Date	Used
SHIELD ROOM #6	-	DYMSTEC	-	-	-	■
EMC32 Measurement Software	EMC32	R&S	9.12.00	-	-	■
EMI TEST RECEIVER	ESR3	Rohde & Schwarz	101783	2025-11-03	2026-11-03	■
LISN	ENV216	Rohde & Schwarz	101787	2025-09-04	2026-09-04	■
ARTIFICIAL MAINS NETWORK	ESH2-Z5	Rohde & Schwarz	100450	2025-11-03	2026-11-03	■
PULSE LIMITER	ESH3-Z2	Rohde & Schwarz	101915	2025-11-03	2026-11-03	■

6.1.2 Test Location : SHIELD ROOM #6

6.1.3 Test Conditions :

Temperature	Relative Humidity
(24.0 ~ 24.2) °C	(50.7 ~ 50.8) % R.H.




6.1.4 Test Result

- Test Date : 2026-06-16
- Test Mode : Mode 2

Test Report

1 / 1

Test Description: Conducted Emission
Job No.: KES-EM262107
Phase: L
Mode: Mode 2
Operator Name: KES



Final_Result

Frequency (MHz)	QuasiPeak (dBμV)	CAverage (dBμV)	Limit (dBμV)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Line	Corr. (dB)
0.155000	—	29.70	66.00	36.30	1000.0	9.000	L1	19.4
0.155000	48.42	—	79.00	30.58	1000.0	9.000	L1	19.4
0.600000	—	25.79	60.00	34.21	1000.0	9.000	L1	19.5
0.600000	33.10	—	73.00	39.90	1000.0	9.000	L1	19.5
0.905000	—	19.50	60.00	40.50	1000.0	9.000	L1	19.5
0.905000	25.38	—	73.00	47.62	1000.0	9.000	L1	19.5
3.300000	—	13.89	60.00	46.11	1000.0	9.000	L1	19.7
3.300000	23.54	—	73.00	49.46	1000.0	9.000	L1	19.7
24.115000	—	34.52	60.00	25.48	1000.0	9.000	L1	20.3
24.115000	40.34	—	73.00	32.66	1000.0	9.000	L1	20.3
24.330000	—	34.78	60.00	25.22	1000.0	9.000	L1	20.3
24.330000	40.43	—	73.00	32.57	1000.0	9.000	L1	20.3




○ Test Date : 2026-06-16

● Test Mode : Mode 2

Test Report

1 / 1

Test Description: Conducted Emission
Job No.: KES-EM262107
Phase: N
Mode: Mode 2
Operator Name: KES



Final_Result

Frequency (MHz)	QuasiPeak (dB μV)	CAverage (dB μV)	Limit (dB μV)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Line	Corr. (dB)
0.150000	—	29.54	66.00	36.46	1000.0	9.000	N	19.4
0.150000	48.79	—	79.00	30.21	1000.0	9.000	N	19.4
0.165000	—	31.84	66.00	34.16	1000.0	9.000	N	19.4
0.165000	47.33	—	79.00	31.67	1000.0	9.000	N	19.4
1.045000	—	22.90	60.00	37.10	1000.0	9.000	N	19.5
1.045000	28.58	—	73.00	44.42	1000.0	9.000	N	19.5
3.475000	—	18.20	60.00	41.80	1000.0	9.000	N	19.7
3.475000	26.08	—	73.00	46.92	1000.0	9.000	N	19.7
24.150000	—	35.21	60.00	24.79	1000.0	9.000	N	20.5
24.150000	40.79	—	73.00	32.21	1000.0	9.000	N	20.5
24.410000	—	35.52	60.00	24.48	1000.0	9.000	N	20.5
24.410000	40.80	—	73.00	32.20	1000.0	9.000	N	20.5

6.1.5 Remark

Complies with the test requirements.



6.2 Conducted Emissions at Telecommunication Ports

6.2.1 Test Equipment

Equipment Name	Model Number	Manufacturer	Serial No.	Cal. Date	Next Cal. Date	Used
SHIELD ROOM #6	-	DYMSTEC	-	-	-	■
EMC32 Measurement Software	EMC32	R&S	9.12.00	-	-	■
EMI TEST RECEIVER	ESR3	Rohde & Schwarz	101783	2025-11-03	2026-11-03	■
LISN	ENV216	Rohde & Schwarz	101787	2025-09-04	2026-09-04	■
ARTIFICIAL MAINS NETWORK	ESH2-Z5	Rohde & Schwarz	100450	2025-11-03	2026-11-03	■
PULSE LIMITER	ESH3-Z2	Rohde & Schwarz	101915	2025-11-03	2026-11-03	■
8-WIRE ISN CAT6	ENY81-CAT6	Rohde & Schwarz	101666	2026-02-24	2027-02-24	■

6.2.2 Test Location : SHIELD ROOM #6

6.2.3 Test Conditions :

Temperature	Relative Humidity
(24.0 ~ 24.3) °C	(50.7 ~ 50.9) % R.H.




6.2.4 Test Result

- Test Date : 2026-06-16
- Test Mode : Mode 1

Test Report

1 / 1

Test Description: Telecommunication Emission
Job No.: KES-EM262107
Mode : Mode 1
Speed : 1 000 Mbps
Operator Name: KES



Final_Result

Frequency (MHz)	QuasiPeak (dB μV)	CAverage (dB μV)	Limit (dB μV)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Line	Corr. (dB)
0.750000	—	38.28	74.00	35.72	1000.0	9.000	Single Line	19.3
0.750000	54.88	—	87.00	32.12	1000.0	9.000	Single Line	19.3
0.805000	—	39.23	74.00	34.77	1000.0	9.000	Single Line	19.3
0.805000	53.29	—	87.00	33.71	1000.0	9.000	Single Line	19.3
0.880000	—	37.25	74.00	36.75	1000.0	9.000	Single Line	19.3
0.880000	50.25	—	87.00	36.75	1000.0	9.000	Single Line	19.3
0.905000	—	35.66	74.00	38.34	1000.0	9.000	Single Line	19.3
0.905000	49.70	—	87.00	37.30	1000.0	9.000	Single Line	19.3
11.605000	—	38.63	74.00	35.37	1000.0	9.000	Single Line	19.6
11.605000	47.94	—	87.00	39.06	1000.0	9.000	Single Line	19.6
11.690000	—	39.12	74.00	34.88	1000.0	9.000	Single Line	19.6
11.690000	48.64	—	87.00	38.36	1000.0	9.000	Single Line	19.6



Report No. : KES-EM262107


Page 20 / 71

- Test Date : 2026-06-16
- Test Mode : Mode 2

Test Report

1 / 1

Test Description: Telecommunication Emission
Job No.: KES-EM262107
Mode : Mode 2
Speed : 1 000 Mbps
Operator Name: KES



Final_Result

Frequency (MHz)	QuasiPeak (dB μV)	CAverage (dB μV)	Limit (dB μV)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Line	Corr. (dB)
0.755000	50.82	—	87.00	36.18	1000.0	9.000	Single Line	19.3
0.755000	—	47.09	74.00	26.91	1000.0	9.000	Single Line	19.3
1.505000	50.95	—	87.00	36.05	1000.0	9.000	Single Line	19.3
1.505000	—	46.01	74.00	27.99	1000.0	9.000	Single Line	19.3
1.510000	51.66	—	87.00	35.34	1000.0	9.000	Single Line	19.3
1.510000	—	47.09	74.00	26.91	1000.0	9.000	Single Line	19.3
3.015000	—	41.77	74.00	32.23	1000.0	9.000	Single Line	19.3
3.015000	47.13	—	87.00	39.87	1000.0	9.000	Single Line	19.3
20.040000	—	40.07	74.00	33.93	1000.0	9.000	Single Line	19.8
20.040000	45.75	—	87.00	41.25	1000.0	9.000	Single Line	19.8
20.505000	—	39.05	74.00	34.95	1000.0	9.000	Single Line	19.8
20.505000	44.64	—	87.00	42.36	1000.0	9.000	Single Line	19.8

6.2.5 Remark

Complies with the test requirements.



6.3 Radiated Emissions(Below 1 GHz)

6.3.1 Test Equipment

Equipment Name	Model Number	Manufacturer	Serial No.	Cal. Date	Next Cal. Date	Used
SEMI ANECHOIC CHAMBER #4(10 m)	-	DYMSTEC	-	-	-	■
EP5/RE Software	EP5/RE	TOYO	6.0.0	-	-	■
EMI TEST RECEIVER	ESU26	Rohde & Schwarz	100551	2026-02-12	2027-02-12	■
AMPLIFIER	SCU 01	Rohde & Schwarz	100574	2026-04-24	2027-04-24	■
TRILOG-BROADBAND ANTENNA	VULB9163	Schwarzbeck	715	2024-11-08	2026-11-08	■

6.3.2 Test Location : SEMI ANECHOIC CHAMBER #4(10 m) Measurement Distance : □ 3 m, ■ 10 m


6.3.3 Test Conditions :

Temperature	Relative Humidity
(24.3 ~ 24.6) °C	(57.7 ~ 58.0) % R.H.



6.3.4 Test Result

- Test Date : 2026-06-16
- Test Mode : Mode 1



Final Result

No.	Frequency [MHz]	(P)	Reading QP [dB(uV)]	c.f [dB(1/m)]	Result QP [dB(uV/m)]	Limit QP [dB(uV/m)]	Margin QP [dB]	Height [cm]	Angle [deg]	Remark
1	44.550	V	51.2	-21.5	29.7	40.0	10.3	108.0	218.0	
2	94.020	V	48.9	-22.8	26.1	40.0	13.9	112.0	2.0	
3	110.510	H	44.9	-22.6	22.3	40.0	17.7	387.0	294.0	
4	374.956	V	53.7	-14.5	39.2	47.0	7.8	103.0	2.0	
5	750.346	H	31.2	-5.3	25.9	47.0	21.1	356.0	241.0	
6	888.935	H	30.4	-2.6	27.8	47.0	19.2	400.0	279.0	


※ The data is the result measured by the detector in Quasi-Peak mode on the Peak graph.



Report No. : KES-EM262107

Page 23 / 71

- Test Date : 2026-06-16
- Test Mode : Mode 2



※ The data is the result measured by the detector in Quasi-Peak mode on the Peak graph.

6.3.5 Remark

Complies with the test requirements.



6.4 Radiated Emissions(Above 1 GHz)

6.4.1 Test Equipment

Equipment Name	Model Number	Manufacturer	Serial No.	Cal. Date	Next Cal. Date	Used
SEMI ANECHOIC CHAMBER #5	-	SY Corporation	-	-	-	■
ES10/RE Software	ES10/RE	TOYO	2022.01.000	-	-	■
EMI TEST RECEIVER	ESU26	Rohde & Schwarz	100552	2026-02-12	2027-02-12	■
PREAMPLIFIER	8449B	HP	3008A00538	2026-04-29	2027-04-29	■
HORN ANTENNA	BBHA 9120D	SCHWARZBEC K	9120D-1802	2025-11-05	2026-11-05	■
ATTENUATOR	8491B	HP	23094	2026-02-12	2027-02-12	■

6.4.2 Test Location : SEMI ANECHOIC CHAMBER #5


6.4.3 Test Conditions :

Temperature	Relative Humidity
(25.4 ~ 25.7) °C	(47.0 ~ 47.2) % R.H.



6.4.4 Test Result

- Test Date : 2026-06-17
- Test Mode : Mode 1



Final Result

No.	Frequency [MHz]	Pol	Reading AV [dB(μV)]	Reading PK [dB(μV)]	c.f. [dB(1/m)]	Result AV [dB(μV/m)]	Result PK [dB(μV/m)]	Limit AV [dB(μV/m)]	Limit PK [dB(μV/m)]	Margin AV [dB]	Margin PK [dB]	Height [cm]	Angle [deg]	Remark
1	1812.854	H	33.3	45.4	2.7	36.0	48.1	60.0	80.0	24.0	31.9	100.0	9.7	
2	2698.588	V	30.4	43.6	6.0	36.4	49.6	60.0	80.0	23.6	30.4	100.0	70.0	
3	3583.714	V	29.7	44.2	7.7	37.4	51.9	60.0	80.0	22.6	28.1	100.0	134.0	
4	4768.713	H	28.5	38.7	12.1	40.6	50.8	60.0	80.0	19.4	29.2	100.0	105.6	
5	4957.777	H	28.4	38.6	12.8	41.2	51.4	60.0	80.0	18.8	28.6	100.0	359.8	
6	5758.703	V	27.2	39.1	14.0	41.2	53.1	60.0	80.0	18.8	26.9	100.0	19.2	

- ※ The data is the result of measured by the detector in PK and CISPR Average on the Peak graph.
- ※ The Average of the test data is the cispr average result.




Report No. : KES-EM262107

Page 26 / 71

○ Test Date : 2026-06-17

● Test Mode : Mode 2



Final Result

No.	Frequency [MHz]	Pol	Reading AV [dB(μV)]	Reading PK [dB(μV)]	c.f. [dB(1/m)]	Result AV [dB(μV/m)]	Result PK [dB(μV/m)]	Limit AV [dB(μV/m)]	Limit PK [dB(μV/m)]	Margin AV [dB]	Margin PK [dB]	Height [cm]	Angle [deg]	Remark
1	1062.346	V	35.8	48.0	-1.0	34.8	47.0	60.0	80.0	25.2	33.0	100.0	290.5	
2	1124.169	V	33.0	46.8	-0.7	32.3	46.1	60.0	80.0	27.7	33.9	100.0	290.5	
3	2606.473	H	31.0	42.4	5.7	36.7	48.1	60.0	80.0	23.3	31.9	100.0	345.2	
4	3446.034	V	29.4	44.4	7.5	36.9	51.9	60.0	80.0	23.1	28.1	100.0	100.7	
5	4672.564	H	28.3	39.9	11.7	40.0	51.6	60.0	80.0	20.0	28.4	100.0	127.2	
6	5740.011	H	27.0	38.9	14.0	41.0	52.9	60.0	80.0	19.0	27.1	100.0	0.1	

✘ The data is the result of measured by the detector in PK and CISPR Average on the Peak graph.

✘ The Average of the test data is the cispr average result.

6.4.5 Remark

Complies with the test requirements.



6.5 Harmonic Current Emissions

6.5.1 Test Equipment

Equipment Name	Model Number	Manufacturer	Serial No.	Cal. Date	Next Cal. Date	Used
SHIELD ROOM #7	-	DYMSTEC	-	-	-	■
net.control Software	net.control	EM TEST	2.1.4	-	-	■
DIGITAL POWER ANALYZER (Harmonic)	DPA 500N	EM TEST	V1024106759	2026-04-06	2027-04-06	■
POWER SOURCE	ACS 500N6	EM TEST	V1024106760	-	-	■

6.5.2 Test Location : SHIELD ROOM #7

6.5.3 Test Conditions :

Temperature	Relative Humidity
(24.9 ~ 25.1) °C	(48.0 ~ 48.2) % R.H.

6.5.4 Classification of Equipment for Harmonic Current Emissions

- Limits for Class A equipment
- Limits for Class B equipment
- Limits for Class C equipment(Rated Power > 25 W)
- Limits for Class C equipment(Rated Power ≥ 5 W and ≤ 25 W)
- Limits for Class D equipment

**6.5.5 Test Result**

- Test Date : 2026-06-17
- Test Mode : Mode 2

Maximum harmonic current results

Hn	I _{eff} [A]	% of Limit	Limit [A]	Result
1	0.126			
2	0.004	0.244	1.620	n/a
3	0.117	3.379	3.450	PASS
4	0.006	0.883	0.645	PASS
5	0.112	6.575	1.710	PASS
6	0.005	1.123	0.450	PASS
7	0.107	9.264	1.155	PASS
8	0.005	1.425	0.345	n/a
9	0.099	16.565	0.600	PASS
10	0.005	1.717	0.276	n/a
11	0.091	18.388	0.495	PASS
12	0.004	1.896	0.230	n/a
13	0.083	26.198	0.315	PASS
14	0.004	2.242	0.197	n/a
15	0.073	32.247	0.225	PASS
16	0.004	2.280	0.173	n/a
17	0.062	31.109	0.199	PASS
18	0.004	2.303	0.153	n/a
19	0.052	29.064	0.178	PASS
20	0.003	2.401	0.138	n/a
21	0.042	26.106	0.161	PASS
22	0.003	2.488	0.125	n/a
23	0.033	22.431	0.147	PASS
24	0.003	2.475	0.115	n/a
25	0.025	18.781	0.135	PASS
26	0.003	2.500	0.106	n/a
27	0.019	15.181	0.125	PASS
28	0.002	2.507	0.099	n/a
29	0.014	11.900	0.116	PASS
30	0.002	2.429	0.092	n/a
31	0.011	9.868	0.109	PASS
32	0.002	2.461	0.086	n/a
33	0.010	9.365	0.102	PASS
34	0.002	2.396	0.081	n/a
35	0.010	10.028	0.096	PASS
36	0.002	2.372	0.077	n/a
37	0.010	10.566	0.091	PASS
38	0.002	2.324	0.073	n/a
39	0.009	10.892	0.087	PASS
40	0.002	2.225	0.069	n/a

Harmonic currents less than 0.6% of the input current measured under the test conditions, or less than 5 mA, whichever is greater, are disregarded.



Test Data - Harmonics (continued)

Average harmonic current results

Hn	I _{eff} [A]	% of Limit	Limit [A]	Result
1	0.125			
2	0.003	0.321	1.080	n/a
3	0.116	5.041	2.300	PASS
4	0.005	1.121	0.430	n/a
5	0.112	9.812	1.140	PASS
6	0.004	1.475	0.300	n/a
7	0.107	13.859	0.770	PASS
8	0.004	1.860	0.230	n/a
9	0.098	24.587	0.400	PASS
10	0.004	2.231	0.184	n/a
11	0.090	27.352	0.330	PASS
12	0.004	2.523	0.153	n/a
13	0.082	39.130	0.210	PASS
14	0.004	2.973	0.131	n/a
15	0.072	48.105	0.150	PASS
16	0.003	3.034	0.115	n/a
17	0.061	46.365	0.132	PASS
18	0.003	3.096	0.102	n/a
19	0.051	43.224	0.118	PASS
20	0.003	3.234	0.092	n/a
21	0.042	25.837	0.161	PASS
22	0.003	3.295	0.084	n/a
23	0.032	22.120	0.147	PASS
24	0.003	3.317	0.077	n/a
25	0.025	18.434	0.135	PASS
26	0.002	3.346	0.071	n/a
27	0.019	14.877	0.125	PASS
28	0.002	3.368	0.066	n/a
29	0.014	11.616	0.116	PASS
30	0.002	3.295	0.061	n/a
31	0.011	9.712	0.109	PASS
32	0.002	3.321	0.058	n/a
33	0.009	9.227	0.102	PASS
34	0.002	3.241	0.054	n/a
35	0.010	9.864	0.096	PASS
36	0.002	3.235	0.051	n/a
37	0.010	10.472	0.091	PASS
38	0.002	3.164	0.048	n/a
39	0.009	10.761	0.087	PASS
40	0.001	2.966	0.046	n/a

Note: Harmonic currents less than 0.6 % of the input current measured under the test conditions, or less than 5 mA, whichever is greater, are disregarded.

* Application of limits for average is 100% except for odd harmonics from 21 to 39, where 150% applies.



6.5.6 Remark

Complies with the test requirements.





6.6 Voltage Fluctuations and Flicker

6.6.1 Test Equipment

Equipment Name	Model Number	Manufacturer	Serial No.	Cal. Date	Next Cal. Date	Used
SHIELD ROOM #7	-	DYMSTEC	-	-	-	■
net.control Software	net.control	EM TEST	2.1.4	-	-	■
DIGITAL POWER ANALYZER (Flicker)	DPA 500N	EM TEST	V1024106759	2026-04-06	2027-04-06	■
POWER SOURCE	ACS 500N6	EM TEST	V1024106760	-	-	■

6.6.2 Test Location : SHIELD ROOM #7

6.6.3 Test Conditions :

Temperature	Relative Humidity
(24.9 ~ 25.2) °C	(48.0 ~ 48.2) % R.H.



6.6.4 Test Result

- Test Date : 2026-06-17
- Test Mode : Mode 2

Flicker Measurements					
	P _{lt}	Max P _{st}	Max D _c	Max D _{max}	Max T _{max}
Line 1:	0.028	0.028	0	< 0.2	0
Limits:	0.65	1	3.3	4	0.5
Results:	PASS	PASS	PASS	PASS	PASS

6.6.5 Remark

Complies with the test requirements.



6.7 Electrostatic Discharge

6.7.1 Test Equipment

Equipment Name	Model Number	Manufacturer	Serial No.	Cal. Date	Next Cal. Date	Used
SHIELD ROOM #6	-	DYMSTEC	-	-	-	■
ESD SIMULATOR	ESS-S3011A	NoiseKen	ESS2589132	2026-05-22	2027-05-22	■
HCP	-	KES	-	-	-	■
VCP	-	Noise Ken	-	-	-	■

6.7.2 Test Location : SHIELD ROOM #6

6.7.3 Test Conditions :

Temperature	Relative Humidity
Temperature(15 ~ 35) °C	(24.0 ~ 24.5) °C
Relative Humidity(30 ~ 60) % R.H.	(50.7 ~ 50.9) % R.H.
Atmospheric Pressure(86 ~ 106) kPa	(100.1 ~ 100.2) kPa


6.7.4 Test Specifications :

Discharge Factor	: 1 s
Discharge Impedance	: 330 Ω / 150 pF
Kind of Discharge	: Direct Discharge - Contact Discharge, Air Discharge Indirect Discharge - HCP, VCP
Polarity	: Positive and Negative
Number of Discharge	: 10 at all locations for Contact Discharge, 10 at all locations for Air Discharge
Performance Criteria	: Complied
Discharge Voltage	:


Type	Direct Discharge		Indirect Discharge	
	Contact Discharge	Air Discharge	Horizontal Coupling Plane	Vertical Coupling Plane
Test Voltage	-	± 2 kV	-	-
	± 6 kV	± 4 kV	± 6 kV	± 6 kV
	-	± 8 kV	-	-




6.7.5 Location of Discharge




<Location of Discharge-1> Mode 1




<Location of Discharge-2> Mode 1




<Location of Discharge-3> Mode 1



<Location of Discharge-4> Mode 2



<Location of Discharge-5> Mode 2



<Location of Discharge-6> Mode 2

**6.7.6 Test Result**

○ Test Date : 2026-06-16

● Test Mode : Mode 1

○ Indirect Discharge

No.	Test Point	Discharge Method	Observations	Remarks
1	HCP Contact	Contact Discharge	Complied	-
2	VCP Contact	Contact Discharge	Complied	-

○ Direct Discharge

No.	Test Point	Discharge Method	Observations	Remarks
1	Enclosure 1	Air Discharge	Complied	-
2	Enclosure 2	Contact Discharge	Complied	-
3	Screws	Contact Discharge	Complied	-
4	Lens	Air Discharge	Complied	-
5	Ports	Contact Discharge	Complied	-

○ Test Date : 2026-06-16

● Test Mode : Mode 2

○ Indirect Discharge

No.	Test Point	Discharge Method	Observations	Remarks
1	HCP Contact	Contact Discharge	Complied	-
2	VCP Contact	Contact Discharge	Complied	-

○ Direct Discharge

No.	Test Point	Discharge Method	Observations	Remarks
1	Enclosure 1	Air Discharge	Complied	-
2	Enclosure 2	Contact Discharge	Complied	-
3	Screws	Contact Discharge	Complied	-
4	Lens	Air Discharge	Complied	-
5	Ports	Contact Discharge	Complied	-



6.7.7 Remark

No loss of performance of function.





6.8 Continuous RF electromagnetic field disturbances

6.8.1 Test Equipment

Equipment Name	Model Number	Manufacturer	Serial No.	Cal. Date	Next Cal. Date	Used
SEMI ANECHOIC CHAMBER #3	-	DYMSTEC	-	-	-	■
TEPTO-EMS-X	TEPTO-EMS-X	Tsj	1.1.0.39	-	-	■
SIGNAL GENERATOR	SMCV100B	Rohde & Schwarz	108002	2026-04-07	2027-04-07	■
BROADBAND AMPLIFIER	HDR1000-80M1GAIII	RAD Co.,Ltd	260352-00	-	-	■
BROADBAND AMPLIFIER	SX250	PRANA	2511-02705	-	-	■
POWER METER	LSPM 1.0+	LUMILOOP	179	2026-04-08	2027-04-08	■
DIRECTIONAL COUPLER	C5027-727	WERLATONE	139036	2026-04-07	2027-04-07	■
DIRECTIONAL COUPLER	C10761-20	WERLATONE	139080	2026-04-07	2027-04-07	■
STACKED DOUBLE LOG-PER- ANTENNA	STPL9128 E	SCHWARZBEC K	9128ES-121	-	-	■
DOUBLE RIDGED HORN ANTENNA	SAS-571	A.H. SYSTEM,INC	781	2026-03-06	2027-03-06	■

6.8.2 Test Location : SEMI ANECHOIC CHAMBER #3

6.8.3 Test Conditions :

Temperature	Relative Humidity
(22.4 ~ 22.9) °C	(49.3 ~ 49.5) % R.H.



6.8.4 Test Specifications :

Antenna Polarization	:	Horizontal & Vertical unless indicated otherwise
Antenna Distance	:	3 m
Field Strength	:	10 V/m (rms)
Frequency Range	:	80 MHz ~ 2.7 GHz
Modulation	:	AM 80 %, 1 kHz, Sine wave PM 1 Hz (0.5 s ON : 0.5 s OFF)
Dwell Time	:	3 s
Frequency Step	:	1 %
Application method	:	4
Performance Criteria	:	Complied

**6.8.5 Test Result**

- Test Date : 2026-06-20
- Test Mode : Mode 1
- Enclosure Port

Side Exposed	Observations	
	Horizontal	Vertical
Front	Complied	Complied
Rear	Complied	Complied
Right	Complied	Complied
Left	Complied	Complied

- Test Date : 2026-06-20
- Test Mode : Mode 2
- Enclosure Port

Side Exposed	Observations	
	Horizontal	Vertical
Front	Complied	Complied
Rear	Complied	Complied
Right	Complied	Complied
Left	Complied	Complied

6.8.6 Remark

No loss of performance of function.



6.9 Electrical Fast Transients/Bursts

6.9.1 Test Equipment

Equipment Name	Model Number	Manufacturer	Serial No.	Cal. Date	Next Cal. Date	Used
SHIELD ROOM #7	-	DYMSTEC	-	-	-	■
iec.control Software	iec.control	EM TEST	5.4.8	-	-	■
ULTRA COMPACT SIMULATOR	UCS 500N7	EM TEST	P1608172950	2025-11-05	2026-11-05	■
MOTOR VARIAC	MV 2616	EM TEST	P1552169719	2025-11-05	2026-11-05	■
CAPACITIVE COUPLING CLAMP	HFK	EM TEST	P1633183115	2025-11-05	2026-11-05	■

6.9.2 Test Location : SHIELD ROOM #7

6.9.3 Test Conditions :

Temperature	Relative Humidity
(25.0 ~ 25.2) °C	(48.0 ~ 48.2) % R.H.

6.9.4 Test Specifications :

Pulse Amplitude & Polarity	: Input a.c power ports ± 2.0 kV Other supply and Signal ports ± 1 kV
Repetition Rate	: 100 kHz
Impulse Rise Time	: 5 ns ± 30 %
Impulse Period	: 50 ns ± 30 %
Burst Duration	: 15 ms ± 20 %
Burst Period	: 300 ms ± 20 %
Duration of Test Voltage	: 1 min
Application Method	: a.c / d.c power ports (Coupling / Decoupling Network) Other than a.c / d.c power poerts (Capacitive Coupling Clamp)
Performance Criteria	: Complied



6.9.5 Test Result

○ Test Date : 2026-06-17

● Test Mode : Mode 1

○ Input a.c power ports

Mode of Application	Observations	
	(+) Burst	(-) Burst
N/A	-	-

○ Input d.c power ports

Mode of Application	Observations	
	(+) Burst	(-) Burst
N/A	-	-

○ Signal ports and telecommunication ports

Mode of Application	Observations	
	(+) Burst	(-) Burst
RJ-45(PoE)	Complied	Complied
Alarm IN	Complied	Complied
Alarm OUT	Complied	Complied



○ Test Date : 2026-06-17

● Test Mode : Mode 2

○ Input a.c power ports

Mode of Application	Observations	
	(+) Burst	(-) Burst
L-N	Complied	Complied

○ Input d.c power ports

Mode of Application	Observations	
	(+) Burst	(-) Burst
N/A	-	-

○ Signal ports and telecommunication ports

Mode of Application	Observations	
	(+) Burst	(-) Burst
RJ-45(LAN)	Complied	Complied
Alarm IN	Complied	Complied
Alarm OUT	Complied	Complied

6.9.6 Remark

No loss of performance of function.



6.10 Surge

6.10.1 Test Equipment

Equipment Name	Model Number	Manufacturer	Serial No.	Cal. Date	Next Cal. Date	Used
SHIELD ROOM #7	-	DYMSTEC	-	-	-	■
iec.control Software	iec.control	EM TEST	5.4.8	-	-	■
ULTRA COMPACT SIMULATOR	UCS 500N7	EM TEST	P1608172950	2025-11-05	2026-11-05	■
MOTOR VARIAC	MV 2616	EM TEST	P1552169719	2025-11-05	2026-11-05	■
CDN	CNV 508N1	EM TEST	P1610176296	2025-11-05	2026-11-05	■

6.10.2 Test Location : SHIELD ROOM #7

6.10.3 Test Conditions :

Temperature	Relative Humidity
(24.8 ~ 25.2) °C	(48.0 ~ 48.2) % R.H.

6.10.4 Test Specifications :

Surge	: Input a.c power ports	Line to Line ±0.5 kV, ±1.0 kV
		Line to Ground ±0.5 kV, ±1.0 kV, ±2.0 kV
	Other supply / Signal lines	Line to Ground ±0.5 kV, ±1.0 kV
Input a.c / Other supply / Signal lines		
Open-Circuit Voltage Waveform	: 1.2/50 μs	
Short-Circuit Current Waveform	: 8/20 μs	
Number of Applications	: Apply 5 surges for each polarity	
Phase Angle	: 0° ~ 270° (input a.c. power port)	
Polarity	: Positive and Negative	
Repetition Rate	: 1 surge per 30 s	
Performance Criteria	: Complied	

**6.10.5 Test Result**

○ Test Date : 2026-06-17

● Test Mode : Mode 1

○ Input a.c power ports

Mode of Application	Observations	
	(+) Surge	(-) Surge
N/A	-	-

○ Signal ports and telecommunication ports

Mode of Application	Coupling Method	Observations	
		(+) Surge	(-) Surge
RJ-45(PoE)	CDN	Complied	Complied
	LINE	Complied	Complied
Alarm IN	CDN	Complied	Complied
	LINE	Complied	Complied
Alarm OUT	CDN	Complied	Complied
	LINE	Complied	Complied



○ Test Date : 2026-06-17

● Test Mode : Mode 2

○ Input a.c power ports

Mode of Application	Observations	
	(+) Surge	(-) Surge
L-N	Complied	-

○ Signal ports and telecommunication ports

Mode of Application	Coupling Method	Observations	
		(+) Surge	(-) Surge
RJ-45(LAN)	CDN	Complied	Complied
	LINE	Complied	Complied
Alarm IN	CDN	Complied	Complied
	LINE	Complied	Complied
Alarm OUT	CDN	Complied	Complied
	LINE	Complied	Complied

6.10.6 Remark

No loss of performance of function.



6.11 Continuous Induced RF Disturbances

6.11.1 Test Equipment

Equipment Name	Model Number	Manufacturer	Serial No.	Cal. Date	Next Cal. Date	Used
SHIELD ROOM #7	-	DYMSTEC	-	-	-	■
icd.control Software	icd.control	EM TEST	8.0.0	-	-	■
TEST SYSTEM FOR CONDUCTED AND RADIATED	NSG4070	TESEQ	65585	2025-11-03	2026-11-03	■
ATTENUATOR	ATT 6/80	EM TEST	P1614178148	2025-11-03	2026-11-03	■
CDN	CDN M016	TESEQ	43694	2025-11-03	2026-11-03	■
CDN	CDN M016	TESEQ	43697	2025-11-03	2026-11-03	■
CDN	CDN T8 RJ45	SCHWARZBECK	00103	2025-07-07	2026-07-07	■
EM CLAMP	KEMZ 801A	TESEQ	44099	2025-11-05	2026-11-05	■

6.11.2 Test Location : SHIELD ROOM #7

6.11.3 Test Conditions :

Temperature	Relative Humidity
(23.3 ~ 23.7)°C	(48.0 ~ 48.3) % R.H.

6.11.4 Test Specifications

Frequency range and Voltage Level	: 0.15 MHz ~ 100 MHz : 10 V(r.m.s)
Modulation	: AM 80 %, 1 kHz, Sine wave PM 1 Hz (0.5 s ON : 0.5 s OFF)
Dwell Time	: 3 s
Frequency Step	: 1 %
Performance Criteria	: Complied

**6.11.5 Test Result**

○ Test Date : 2026-06-17

● Test Mode : Mode 1

○ Input a.c power ports

Coupling Location (Line Stressed)	Coupling Method	Observations
N/A	CDN	-

○ Input d.c power ports

Coupling Location (Line Stressed)	Coupling Method	Observations
N/A	-	-

○ Signal ports and telecommunication ports

Coupling Location (Line Stressed)	Coupling Method	Observations
RJ-45(PoE)	CDN	Complied
Alarm IN	Clamp	Complied
Alarm OUT	Clamp	

○ Test Date : 2026-06-17

● Test Mode : Mode 2

○ Input a.c power ports

Coupling Location (Line Stressed)	Coupling Method	Observations
L-N	CDN	Complied

○ Input d.c power ports

Coupling Location (Line Stressed)	Coupling Method	Observations
N/A	-	-

○ Signal ports and telecommunication ports

Coupling Location (Line Stressed)	Coupling Method	Observations
RJ-45(LAN)	CDN	Complied
Alarm IN	Clamp	Complied
Alarm OUT	Clamp	Complied



Report No. : KES-EM262107

Page 50 / 71

6.11.6 Remark

No loss of performance of function.





6.12 Voltage Dips and Interruptions

6.12.1 Test Equipment

Equipment Name	Model Number	Manufacturer	Serial No.	Cal. Date	Next Cal. Date	Used
SHIELD ROOM #7	-	DYMSTEC	-	-	-	■
iec.control Software	iec.control	EM TEST	5.4.8	-	-	■
ULTRA COMPACT SIMULATOR	UCS 500N7	EM TEST	P1608172950	2025-11-05	2026-11-05	■
MOTOR VARIAC	MV 2616	EM TEST	P1552169719	2025-11-05	2026-11-05	■

6.12.2 Test Location : SHIELD ROOM #7

6.12.3 Test Conditions :

Temperature	Relative Humidity
(24.9 ~ 25.2) °C	(47.9 ~ 48.0) % R.H.

6.12.4 Test Specifications

Instantaneous peak overshoot/undershoot of the actual voltage	: Less than 5 %
Voltage Rise Time, Voltage Fall Time	: Between 1 μs and 5 μs
Test Voltage Frequency Deviation for Voltage Dips	: with in ± 2 %
EUT Voltage	: AC 230 V, 50 Hz
Number of Applications	: 3 cycles
Test Interval	: 10 s
Performance Criteria	: Complied

Voltage Dips and Interruptions	Duration [in period]
20 % Voltage reduction	250 T
30 % Voltage reduction	25 T
60 % Voltage reduction	10 T
100 % Voltage reduction	250 T

Voltage Variations	Supply Voltage
Supply Voltage max (Umax)	Unom a + 10 %
Supply Voltage min (Umin)	Unom a - 15 %



6.12.5 Test Result

- Test Date: 2026-06-17
- Test Mode: Mode 2

○ Voltage Dips and Short Interruptions

Depth	Duration [in period]	Observations
20 % Voltage reduction	250 T	Complied
30 % Voltage reduction	25 T	Complied
60 % Voltage reduction	10 T	Complied
100 % Voltage reduction	250 T	Degradation

○ Voltage variations

Voltage Variations	Supply Voltage	Observations
Supply voltage max ($U_{\max} = U_{\text{nom}} + 10\%$)	253 V	Complied
Supply voltage min ($U_{\min} = U_{\text{nom}} - 15\%$)	195.5 V	Complied

U_{nom} = Nominal mains voltage, $U_{\max}$ = (Maximum U_{nom}) + 10 %, $U_{\min}$ = (Minimum U_{nom}) – 15 %.


6.12.6 Remark

Degradation : During the test(100%, 250cycle), EUT was turned off but after the test, it was recovered without operator's intervention




7 Test Setup Photos and EUT Photographs


7.1 Test Setup Photos



<Conducted Emissions at Mains Power Ports - Front> Mode 2




<Conducted Emissions at Mains Power Ports - Rear> Mode 2



<Conducted Emissions at Telecommunication Ports - Front>Mode 1



<Conducted Emissions at Telecommunication Ports - Rear> Mode 1




<Conducted Emissions at Telecommunication Ports - Front>Mode 2




<Conducted Emissions at Telecommunication Ports - Rear> Mode 2




<Radiated Emissions(Below 1 GHz) - Front> Mode 1




<Radiated Emissions(Below 1 GHz) - Rear> Mode 1




<Radiated Emissions(Below 1 GHz) - Front> Mode 2




<Radiated Emissions(Below 1 GHz) - Rear> Mode 2




<Radiated Emissions(Above 1 GHz) - Front> Mode 1



<Radiated Emissions(Above 1 GHz) - Rear> Mode 1



<Radiated Emissions(Above 1 GHz) - Front> Mode 2




<Radiated Emissions(Above 1 GHz) - Rear> Mode 2



<Harmonic Current Emissions and Voltage Fluctuations and Flicker> Mode 2




<Electrostatic Discharge> Mode 1




<Electrostatic Discharge> Mode 2




<Continuous RF electromagnetic field disturbances> Mode 1



<Continuous RF electromagnetic field disturbances> Mode 2



<Electrical Fast Transients/Bursts> Mode 1



<Electrical Fast Transients/Bursts> Mode 2




<Surge> Mode 1



<Surge> Mode 2



<Continuous Induced RF Disturbances> Mode 1



<Continuous Induced RF Disturbances> Mode 2



<Voltage Dips and Interruptions> Mode 2



7.2 EUT Photographs



<EUT External Photographs - Top>




<EUT External Photographs - Bottom>



<Components>




<Port-1>



<Port-2>



<Port-3>



<EUT Internal Photographs>



7.3 Label



Name : Hanwha Vision Co., Ltd.
Product item : NETWORK CAMERA
Model name : TNO-A45080R

The End.

