



Network

Bullet

TNO-A45090R

Ultra High Resolution 45MP T AI Camera



Key Features

- 45MP Image Resolution
- 50~150mm Focal Length
- 3.0x Optical Zoom
- AI Analytics Person and Vehicle Detection
- Compact & Lightweight (13.8" × 4.7", 8.93 lbs)
- Dual Model Lineup (TNO-A45080R: 12-51mm, TNO-A45090R: 50-150mm)
- Low Light Performance with 1/1.4" Sensor
- IR Distance Up to 200m
- Flexible Power & Connectivity Options(PoE+, PoE, 12V DC, SFP)
- Multi-View (1 Original + Up to 4 ROI Channels)

TNO-A45090R

Ultra High Resolution 45MP T AI Camera



Specifications

Video		
Imaging Device	Size	Diagonal 23.1mm 1.4"
	Type	CMOS
Resolution Mode	45MP	8192x5552, 7792x5280, 7392x5008, 6752x4576, 5936x4024, 4512x3056, 4096x2776, 3456x2344, 2880x1952, 2240x1520, 1440x976, 1216x824, 800x544, 640x436
	8K	7680x4320, 7424x4176, 7680x3840, 6400x4800, 6144x3456, 5120x2880, 4096x3072, 3840x2160, 3200x2400, 3328x1872, 2688x1512, 2560x1440, 1920x1080, 1600x1200, 640x480
	Virtual Channel (Supports 1 to 4 Channels)	3840x2160, 3328x1872, 3200x2400, 2688x1512, 2560x1440, 1920x1080, 1600x1200
Max. Framerate	H.265/H.264	15fps@45MP(45MP mode) / 25fps@33MP(8K mode)
	MJPEG	25fps/1fps@45MP(45MP mode) / 1fps@33MP(8K mode)
Min. Illumination (Lux)	Color(1/30sec, 30IRE)	0.12
	BW(1/30sec, 30IRE)	0.012
Video Out		USB: USB Type C. Preview and installation ONLY. Requires WiFi dongle.
Lens		
Focal Length (mm)		50-150
Zoom Ratio	Optical	3.0
Max Aperture Ratio (F number)	Wide	2.3
	Tele	3.5
Angular Field of View	Horizontal	21.3°(Wide)~7.2°(Tele)
	Vertical	14.6°(Wide)~4.9°(Tele)
	Diagonal	25.4°(Wide)~8.6°(Tele)
Min. Object Distance		2m(Wide)~3m(Tele)
Focus Control		Simple focus
Lens Type		P iris(IR corrected)
Pan / Tilt / Rotate		
Pan / Tilt / Rotate Range	Pan	0°~350°
	Tilt	0~90°
	Rotate	0°~350°

Operational

Day & Night		Auto(ICR)
Backlight Compensation		BLC, SSDR
Digital Noise Reduction		WiseNR II (Based on AI engine), SSNR V
Digital Image Stabilization		Support
Defog		Support
Motion Detection	Quantity	8ea
	Shape	8point Polygonal zones
Privacy Masking	Quantity	4ea
	Shape	Polygonal zones
	Color / Option	Gray, Green, Red, Blue, Black, White, Mosaic
Gain Control		Low, Middle, High, Off
White Balance		ATW, AWC, Manual, Indoor, Outdoor
LDC		Support
Electronic Shutter	Mode	Minimum, Maximum, Anti flicker, Prefer shutter control(Based on AI engine)
	Speed Range	1/5~1/12,000sec
Digital PTZ		Support
Video Rotation		Flip, Mirror, Hallway view(90°/270°)
Alarm Interface	In/Out	2 configurable I/O ports
	Others	Support extra alarm I/O via optional I/O box
Alarm Triggers		Analytics, Network disconnect, Alarm input, Time schedule, MQTT subscription, Case tampering, Day/Night, Storage disruption
Alarm Events When Alarm Trigger Occurred		File upload(image): e-mail/FTP/SFTP, File upload(video clip): FTP/SFTP, Notification: e-mail, Recording: SD/SDHC/SDXC or NAS recording at event triggers,Alarm output, Handover: PTZ preset,send message by HTTP/HTTPS/TCP,Audio clip playback, MQTT: publication
Audio In		Selectable(mic in/line in)
Audio Out		Line out
Light Type		IR LED
Light Viewable Length	IR	200m(656.2ft)
IR Wavelength		850nm

Analytics

Classified Object Type		Person, Face, Vehicle, License plate
Attributes	Person	Upper/Lower clothes color, Gender, Bag
	Vehicle	Type(car, bus, truck, motorcycle, bicycle), Color
	Face	Age, Gender, Face mask, Glasses
Thumbnail		BestShot

Analytics

Analytics Events	Based on AI Engine	Object detection, Virtual line(Crossing/Direction), Motion detection, Virtual area(Loitering/Intrusion/Enter/Exit/Appear/Disappear)
	Normal	Defocus detection, Tampering, Audio detection, Shock detection
Business Intelligence	Based on AI Engine	People counting, Queue management, Heatmap, Vehicle counting, Crowd counting

Network

Ethernet		Metal shielded RJ-45(10/100/1000BASE-T), SFP
Video Compression		H.265: Main, H.264: Main/High,MJPEG
Audio Compression		G.711(PCM): 8kHz(64kbps), G.726(ADPCM): 8kHz(16/24/32/40kbps), AAC-LC: 16kHz(48kbps), OPUS: 16kHz(64kbps)
Smart Codec		Manual, WiseStream(Based on AI engine)
Bitrate Control		H.265/H.264: CBR or VBR, MJPEG: VBR
Streaming	Unicast	Up to 20 users
	Multicast	Support
	Multiple Streaming	Up to 3 profiles
Protocol		IPv4, IPv6, TCP/IP, UDP/IP, RTP(UDP), RTP(TCP), RTCP, RTSP, NTP, HTTP, HTTPS, SSL/TLS, DHCP, FTP, SFTP, SMTP, ICMP, IGMPv2, SNMPv1/v2c/v3(MIB-2), ARP, DNS, DDNS, QoS, UPnP, Bonjour, LLDP, CDP, SRTP(TCP, UDP Unicast), MQTT, Syslog
Application Programming Interface	ONVIF	S, G, T, M
	Others	SUNAPI(HTTP API), Hanwha Vision Open Platform

Security

OS / Firmware Protect		Encrypted firmware, Secure boot, Signed firmware
User authentication		Digest authentication, Prevent brute-force attack
Network authentication		IEEE 802.1X(EAP-TLS, EAP-LEAP, EAP-PEAP, MSCHAPv2)
Secure Communication		HTTPS, WSS(WebSocket Secure), SRTP
Access Control		IP-based access control, MAC-based access control, Auto logout
Data Protect		Encryption credentials, Encrypt compress for live recording file export
Audit		Access / System / Event Log management
Device ID		Device certificate(Hanwha Vision Root CA)
Secure Storage		TPM(Trusted platform module), SDcard partition encrypt(AES-256), Secure element
Supply Chain Security		SBOM
Security Certificate		Secure element(FIPS 140-3 level3, CC EAL6+), Consumer IoT Security Standard (ETSI EN 303 645)

General

Memory	RAM	8GB
	Flash	16GB eMMC

General

Edge Storage	Micro SD/SDHC/SDXC	Max. 1TB x 2slot(Total 2TB)
--------------	--------------------	-----------------------------

Environmental & Electrical

Operating Condition	Temperature	-40°C~+55°C(-40°F~+131°F)
	Humidity	0~100% RH(condensing)
	Others	Humidity control with AIR vent
Storage Condition	Temperature	-50°C~+60°C(-58°F~+140°F)
	Humidity	0~95% RH(non-condensing)
Input Voltage		PoE+(IEEE802.3at, Class4), PoE++(IEEE802.3bt type3, Class6), 12VDC
Power Consumption	PoE	PoE++: Max. 39.4W, typical 19.0W PoE+: Max. 24.2W, typical 19.0W
	12VDC	Max. 37.3W, typical 18.4W
WisePower		Power mode, Power monitoring

Mechanical

Color	White, Black
Material	Aluminum, Plastic
RAL Code	RAL9003
Product Dimensions	120x120x350mm(4.72"x4.72"x13.78")
Product Weight	4050g(8.93lb)
Compatible Gang Box	Single, Double, 4" Octagon, Square

Certifications & Standards

EMC	FCC 47 CFR 15 Subpart B Class A,CE/UKCA - EN55032 Class A,EN 50130-4,EN 61000-3-2,EN 61000-3-3,KS C 9832 Class A,KS C 9835,IC Regulation ICES-003 Issue 7 Class A,FCC - IC Regulation ICES 003 Issue 7, RCM - EN IEC 63000:2018 Class A, VCCI - EN IEC 63000:2018 Class A
Safety	UL 62368-1, CAN/CSA C22.2 NO. 62368-1, IEC 62471
Environment	IEC/EN 63000, IEC 60529 IP66, IEC 60529 IP67, IEC 62262 IK10, NEMA 250 type 4X, IEC 60068-2-1, IEC 60068-2-2, IEC 60068-2-6, IEC 60068-2-14, IEC 60068-2-27, IEC 60068-2-78

AI Detection Distance

Person(1.8m/5.9ft)	Wide	Up to 312.2m(1024.3ft)
	Tele	Up to 934.9m(3067.3ft)
Vehicle(1.45m/4.8ft)	Wide	Up to 404.3m(1326.4ft)
	Tele	Up to 1210.3m(3970.8ft)

DORI (EN62676-4 standard)

Detect (25PPM/ 8PPF)	Wide	871.3m(2858.48ft)
	Tele	2604.2m(8543.84ft)

DORI (EN62676-4 standard)

Observe (63PPM/ 19PPF)	Wide	348.5m(1143.39ft)
	Tele	1041.7m(3417.54ft)
Recognize (125PPM/ 38PPF)	Wide	174.3m(571.70ft)
	Tele	520.8m(1708.77ft)
Identify (250PPM/ 76PPF)	Wide	87.1m(285.85ft)
	Tele	260.4m(854.38ft)

TNO-A45090R

Ultra High Resolution 45MP T AI Camera



CAD

Unit: mm [inch]

