

# TEST REPORT

**CTK Co., Ltd.**

5 Dongbu-ro 221beon-gil, Cheoin-gu, Yongin-si,  
Gyeonggi-do, Republic of Korea  
Tel: +82-31-339-9970  
Fax: +82-31-624-9501

REPORT No.:  
CTK-2025-02417  
Page (1) / (17) pages

**1. Applicant**

- Name : Hanwha Vision Co., Ltd.
- Address : 6, Pangyo-ro 319Beon-gil, Bundang-gu, Seongnam-si,  
Gyeonggi-do, 13488 KOREA
- Date of Receipt : Jul. 04, 2025

**2. Manufacturer**

- Name : Hanwha Vision Co., Ltd.

**3. Use of Report :**

For submission to customer

**4. Test sample / Model :**

NETWORK CAMERA / TNP-A9430RW

**5. Date(s) of test :**

Aug. 09, 2025 ~ Aug. 10, 2025

**6. Test Standard (Method) used :**

IEC 60529:1989 +A1:1999+A2:2013

**7. Testing Environment :**

Temperature: (25 ±10) °C, Humidity: (50 ±25) % R.H.

Pressure: (96 ±10) kPa

**8. Test Results :**

Refer to the test results

☒ Permanent Testing Lab ☐ On Site Testing

**9. Location of Test :**

(5 Dongbu-ro 221beon-gil, Cheoin-gu, Yongin-si, Gyeonggi-do, Republic of Korea)

113, Yejik-ro, Cheoin-gu, Yongin-si, Gyeonggi-do Republic of Korea

The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This report cannot be reproduced or copied without the written consent of CTK.

|  |                                             |                                                   |
|--|---------------------------------------------|---------------------------------------------------|
|  | Tested by<br>Name: HyungUk Jeon (Signature) | Technical Manager<br>Name: HoHyun Lee (Signature) |
|--|---------------------------------------------|---------------------------------------------------|

Remark. This report is not related to KOLAS accreditation and relevant regulation.

Sep. 04, 2025

**CTK Co., Ltd.**



**CTK Co., Ltd.**

5 Dongbu-ro 221beon-gil, Cheoin-gu, Yongin-si,  
Gyeonggi-do, Republic of Korea  
Tel: +82-31-339-9970  
Fax: +82-31-624-9501

REPORT No.:  
CTK-2025-02417  
Page (2) / (17) pages

## Table of Contents

|                                                                 |    |
|-----------------------------------------------------------------|----|
| 1. Testing laboratory .....                                     | 3  |
| 1.1 Testing laboratory information .....                        | 3  |
| 1.2 Testing laboratory accreditation status.....                | 3  |
| 2. Product description and equipment information .....          | 4  |
| 2.1 Product description .....                                   | 4  |
| 2.2 Equipment information .....                                 | 4  |
| 2.3 Pre-test product images .....                               | 5  |
| 2.4 Testing equipment images.....                               | 6  |
| 2.5 Product appearance.....                                     | 7  |
| 3. Degrees of protection provided by enclosures (IP code) ..... | 8  |
| 3.1 Test date and environmental conditions .....                | 8  |
| 3.2 Test conditions and methods.....                            | 8  |
| 3.3 Testing images .....                                        | 10 |
| 3.4 Test result.....                                            | 12 |
| 3.5 Post-test product images .....                              | 14 |

**CTK Co., Ltd.**

5 Dongbu-ro 221beon-gil, Cheoin-gu, Yongin-si,  
Gyeonggi-do, Republic of Korea  
Tel: +82-31-339-9970  
Fax: +82-31-624-9501

REPORT No.:  
CTK-2025-02417  
Page (3) / (17) pages

## 1. Testing laboratory

### 1.1 Testing laboratory information

|                |                                                                               |
|----------------|-------------------------------------------------------------------------------|
| Lab. Name      | CTK Co., Ltd.                                                                 |
| Representative | Young Joseph Seungwon                                                         |
| Address        | 5 Dongbu-ro 221beon-gil, Cheoin-gu, Yongin-si, Gyeonggi-do, Republic of Korea |
| Tel.           | +82-31-339-9970                                                               |
| Fax.           | +82-31-624-9501                                                               |
| E-Mail         | <a href="mailto:all.youngin@element.com">all.youngin@element.com</a>          |
| Website        | <a href="http://www.elementkorea.kr">www.elementkorea.kr</a>                  |

### 1.2 Testing laboratory accreditation status

| Country       | Classification | Accreditation Number | Logo                                                                                  |
|---------------|----------------|----------------------|---------------------------------------------------------------------------------------|
| International | KOLAS          | TESTING<br>NO. KT119 |  |

**CTK Co., Ltd.**

5 Dongbu-ro 221beon-gil, Cheoin-gu, Yongin-si,  
Gyeonggi-do, Republic of Korea  
Tel: +82-31-339-9970  
Fax: +82-31-624-9501

REPORT No.:  
CTK-2025-02417  
Page (4) / (17) pages

## 2. Product description and equipment information

### 2.1 Product description

| Product Name   | Model Name  | Quantity | Comment |
|----------------|-------------|----------|---------|
| NETWORK CAMERA | TNP-A9430RW | –        | –       |

### 2.2 Model description

|                         |                                                                                                                  |
|-------------------------|------------------------------------------------------------------------------------------------------------------|
| Basic Model .....       | TNP-A9430RW                                                                                                      |
| Series model .....      | TNP-A7430RW, TNP-A6650RW, TNP-A9430RWB, TNP-A7430RWB,<br>TNP-A6650RWB                                            |
| Model differences ..... | Use of the same external shape and materials (case, finishing<br>material, PCB, cable, etc.), differences in SW. |

### 2.3 Equipment information

| Testing equipment     | Model Name | Manufacturer | Manufacturing Number | Next Cal. Date |
|-----------------------|------------|--------------|----------------------|----------------|
| Stop Watch            | NONE       | Casio        | 612Q01R-1            | 2027-01-15     |
| Push Pull Gage        | FB30K      | Imada        | 83805                | 2026-01-16     |
| Test Rod Probe Ø1.0   | TRP-02     | ED&D         | S1-J15               | 2027-05-16     |
| Immersion tank        | -          | -            | -                    | -              |
| Dust Chamber          | NONE       | JFM          | S5-IP02              | 2026-02-14     |
| Steel measuring meter | 5.5 m      | KOMELON      | 225851               | 2026-01-16     |



## CTK Co., Ltd.

5 Dongbu-ro 221beon-gil, Cheoin-gu, Yongin-si,  
Gyeonggi-do, Republic of Korea  
Tel: +82-31-339-9970  
Fax: +82-31-624-9501

REPORT No.:  
CTK-2025-02417  
Page (5) / (17) pages

## 2.4 Pre-test product images

### 2.4.1 Test sample #1



Top



Bottom



Front



Rear



Left side



Right side



## 2.5 Testing equipment images

### 2.5.1 Test equipment (1)



Stop Watch



Push Pull Gage



Test Rod Probe Ø1.0



Immersion tank



Dust Chamber



Steel measuring meter








## CTK Co., Ltd.

5 Dongbu-ro 221beon-gil, Cheoin-gu, Yongin-si,  
Gyeonggi-do, Republic of Korea  
Tel: +82-31-339-9970  
Fax: +82-31-624-9501

REPORT No.:  
CTK-2025-02417  
Page (7) / (17) pages

## 2.6 Product appearance

Enclosure dimensions [unit : mm]



**CTK Co., Ltd.**

5 Dongbu-ro 221beon-gil, Cheoin-gu, Yongin-si,  
Gyeonggi-do, Republic of Korea  
Tel: +82-31-339-9970  
Fax: +82-31-624-9501

REPORT No.:  
CTK-2025-02417  
Page (8) / (17) pages

### 3. Degrees of protection provided by enclosures (IP code)

#### 3.1 Test date and environmental conditions

3.1.1 Test date: Aug. 09, 2025 ~ Aug. 10, 2025

3.1.2 Measured Environmental Conditions

| Item        | Temperature (°C) | Humidity (% R.H.) | Pressure (kPa) |
|-------------|------------------|-------------------|----------------|
| Measurement | 27.6             | 67.4              | 89.1           |

#### 3.2 Test conditions and methods

3.2.1 Test standard: IEC 60529:1989+A1:1999+A2:2013

3.2.2 Arrangement of the IP code

|                                                               |    |   |   |
|---------------------------------------------------------------|----|---|---|
|                                                               | IP | 6 | 8 |
| Code letters (International protection)                       | ←  |   |   |
| First characteristic numeral (numerals 0 to 6, for letter X)  | ←  |   |   |
| Second characteristic numeral (numerals 0 to 8, for letter X) | ←  |   |   |

##### 3.2.2.1 Degree of protection against access to hazardous parts indicated by the first characteristic numeral

| First characteristic numeral | Degree of protection                                                                                                                    | Application                         |
|------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------|
| 6                            | Protected against access to hazardous parts with a wire.<br>The access probe of 1.0 mmØ, shall not penetrate.<br>Test force: 1 N ± 10 % | <input checked="" type="checkbox"/> |

NOTE In the case of the first characteristic numerals 3, 4, 5 and 6, protection against access to hazardous parts is satisfied if adequate clearance is kept. The adequate clearance should be specified by the relevant product committee in accordance with 12.3.

Due to the simultaneous requirement specified in table 2, the definition “shall not penetrate” is given in table 1.

##### 3.2.2.2 Degree of protection against solid foreign objects indicated by the first characteristic numeral





# CTK Co., Ltd.

5 Dongbu-ro 221beon-gil, Cheoin-gu, Yongin-si,  
Gyeonggi-do, Republic of Korea  
Tel: +82-31-339-9970  
Fax: +82-31-624-9501

REPORT No.:  
CTK-2025-02417  
Page (9) / (17) pages

| First characteristic numeral                                                                                                                                                                                                           | Degree of protection                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          | Application                         |
|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------|
| 6                                                                                                                                                                                                                                      | <p>In Dust Testing Equipment, the test sample must have no ingress of dust after testing atmospheric pressure present condition for 8 h.</p> <p>(The talcum powder must pass through a calibrated sieve with a 50 µm wire mesh, spaced at 75 µm intervals in a square pattern. Additionally, the bulk density of the talcum powder should be 2 kg/m³)</p> <p>Products in volume .....: <b>24 122.733 cm³ → 24.122 L</b></p> <p>Target intake volume (Products in volume 80) : <b>1 929.818 L</b></p> <p>Suction volume (Max product in volume 60) ...: <b>1 447.363 LPH → 24.122 LPM</b></p> <p>Actual Suction volume .....: <b>24.012 L</b></p> <p>Suction pressure (Up to 2 kPa) .....: <b>2 kPa</b></p> <p>Test time (Up to 8 time) .....: <b>8 hr</b></p> | <input checked="" type="checkbox"/> |
| <p><sup>1)</sup> The full diameter of the object probe shall not pass through an opening of the enclosure.<br/>Due to the simultaneous requirement specified in table 2, the definition “shall not penetrate” is given in table 1.</p> |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |                                     |

## 3.2.2.3 Degree of protection against water indicated by the second characteristic numeral

| Second characteristic numeral | Degrees of protection                                                                                                                                                                                                                                                                                                                                                                                                                         | Application                         |
|-------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------|
| 8                             | <p>Unless there is a relevant product standard, the test conditions are subject to agreement between manufacturer and user, but they shall be more severe than those prescribed in IP X7 and they shall take account of the condition that the enclosure will be continuously immersed in actual use.</p> <p>the lowest point of enclosures located below the surface of the water:<br/><b>2 m</b></p> <p>Duration of test: <b>24 min</b></p> | <input checked="" type="checkbox"/> |



## CTK Co., Ltd.

5 Dongbu-ro 221beon-gil, Cheoin-gu, Yongin-si,  
Gyeonggi-do, Republic of Korea  
Tel: +82-31-339-9970  
Fax: +82-31-624-9501

REPORT No.:  
CTK-2025-02417  
Page (10) / (17) pages

### 3.3 Testing images

#### 3.3.1 Evidence of test setting (1)



Probe test photo\_1



Probe test photo\_2



Probe test photo\_3



Probe test photo\_4



Probe test photo\_5



Probe test photo\_6



## CTK Co., Ltd.

5 Dongbu-ro 221beon-gil, Cheoin-gu, Yongin-si,  
Gyeonggi-do, Republic of Korea  
Tel: +82-31-339-9970  
Fax: +82-31-624-9501

REPORT No.:  
CTK-2025-02417  
Page (11) / (17) pages

### 3.3.2 Evidence of test setting (2)



IP(6X)



IP(6X)



### 3.3.3 Evidence of test setting (3)



IP(X8)



IP(X8)

**CTK Co., Ltd.**

5 Dongbu-ro 221beon-gil, Cheoin-gu, Yongin-si,  
Gyeonggi-do, Republic of Korea  
Tel: +82-31-339-9970  
Fax: +82-31-624-9501

REPORT No.:  
CTK-2025-02417  
Page (13) / (17) pages

**3.4 Test result****3.4.1 Test result table**

| IP code | Evaluation Criteria | Test Results | Remark |
|---------|---------------------|--------------|--------|
| IP 6X   | No ingress of Probe | Normal       | -      |
|         | No ingress of dust  | Normal       |        |
| IP X8   | No ingress of water | Normal       |        |

※ Refer to the product photos after the completion of testing in section 3.5.








## CTK Co., Ltd.

5 Dongbu-ro 221beon-gil, Cheoin-gu, Yongin-si,  
Gyeonggi-do, Republic of Korea  
Tel: +82-31-339-9970  
Fax: +82-31-624-9501

REPORT No.:  
CTK-2025-02417  
Page (14) / (17) pages

### 3.5 Post-test product images

#### 3.5.1 Product internal images after test [The first characteristic numeral test]










## CTK Co., Ltd.

5 Dongbu-ro 221beon-gil, Cheoin-gu, Yongin-si,  
Gyeonggi-do, Republic of Korea  
Tel: +82-31-339-9970  
Fax: +82-31-624-9501

REPORT No.:  
CTK-2025-02417  
Page (15) / (17) pages

### 3.5.2 Product internal images after test [The first characteristic numeral test]







## CTK Co., Ltd.

5 Dongbu-ro 221beon-gil, Cheoin-gu, Yongin-si,  
Gyeonggi-do, Republic of Korea  
Tel: +82-31-339-9970  
Fax: +82-31-624-9501




REPORT No.:  
CTK-2025-02417  
Page (16) / (17) pages

### 3.5.3 Product internal images after test [The second characteristic numeral test]





### 3.5.4 Product internal images after test [The second characteristic numeral test]



- End -