

Network

TNS-9060IBC

Câmera BCR de Sensor Duplo

Key Features

- IP67, IK66, IK10 Rated
- 35mm Focal Length
- Dual Sensor Color + mono
- 4K Image Resolution
- Sensor duplo Cor + mono
- 35mm Campo de Visão Amplo
- Classificação IP67, IP66, IK10
- Pesquisa de localização com AI lê de forma confiável códigos 1D em esteiras transportadoras movendo-se a até 2m/s
- Elimina erros manuais, aumenta a velocidade e fornece rastreabilidade completa para reduzir devoluções
- Lê código 1D e código 2D em múltiplas orientações e suporta alta capacidade de armazenamento de dados para workflows

Design and specifications are subject to change without notice. The latest product information / specification can be found at HanwhaVision.com
Hanwha Vision is formerly known as Hanwha Techwin.

© Hanwha Vision CO., LTD. All rights reserved.

TNS-9060IBC

Câmera BCR de Sensor Duplo



Specifications

Video		MONO	COLOR
Imaging Device	Size	1"	
	Type	CMOS	
Resolution		4096x2160	4096x2160, 640x360
Max. Framerate	H.265/H.264	20fps/20fps(60Hz/50Hz)	
Pixel Size		3.45㎛	

Lens		
Focal Length (mm)		35mm
Max Aperture Ratio (F number)	Wide	F8.0
Angular Field of View	Horizontal	21.5°
	Vertical	11.5°
	Diagonal	24.2°
Min. Object Distance		0.2m (0.66ft)
Focus Control		Manual
Lens Type		Manual
Mount Type		C mount

Operational		
Digital Noise Reduction		SSNR
Gain Control		Manual
White Balance		AWC, Manual
Electronic Shutter	Mode	Global shutter mode
	Speed Range	1/30~1/10,000s (33.3ms~100㎲)
Video Rotation		Flip, Mirror
Alarm Interface	In/Out	Output 1ea
LED	Color	White(M12 5pin connector)
	Color Temperature	5700K
	Quantity	48EA

Design and specifications are subject to change without notice. The latest product information / specification can be found at HanwhaVision.com
Hanwha Vision is formerly known as Hanwha Techwin.

© Hanwha Vision CO., LTD. All rights reserved.

Analytics

Barcode Type	1D Code	Code128, CODE39, CODE93, Codabar, ITF(Interleaved 2 of 5), UPC, EAN
	2D Code	QRcode, DataMatrix, Maxicode, PDF417

Network

Ethernet		M12 8pin connector(10/100/1000BASE-T)
Video Compression		H.265/H.264: Main/High, MJPEG
Streaming	Unicast	Up to 6 users
	Multicast	Support
Protocol		IPv4, IPv6, TCP/IP, UDP/IP, RTP(UDP), RTP(TCP), RTCP, RTSP, NTP, HTTP, HTTPS, SSL/TLS, DHCP, FTP, SMTP, ICMP, IGMPv2, SNMPv1/v2c/v3(MIB-2), ARP, DNS, DDNS, QoS, UPnP, Bonjour, SRTP(TCP, UDP Unicast), MQTT
Application Programming Interface	ONVIF	M
	Others	SUNAPI(HTTP API), Hanwha Vision Open Platform

Security

OS / Firmware Protect	Encrypted firmware, Secure boot, Signed firmware
User authentication	Digest authentication, Prevent brute-force attack
Network authentication	IEEE 802.1X(EAP-TLS, EAP-LEAP, EAP-PEAP, MSCHAPv2)
Secure Communication	HTTPS, WSS(WebSocket Secure), SRTP
Access Control	IP-based access control
Data Protect	Encryption credentials, Encrypt compress for live recording file export
Audit	Access / System / Event Log management
Device ID	Device certificate(Hanwha Vision Root CA)
Secure Storage	HTPM(Hanwha Trusted Platform Module)

General

Memory	RAM	4GB
	Flash	512MB

Environmental & Electrical

Operating Condition	Temperature	-40°C~+55°C(-40°F~+131°F)
	Humidity	0~95% RH(non-condensing)
	Others	+74°C(+165°F)(Max) based on NEMA-TS 2(2.2.7), Start up should be done at above -30°C
Storage Condition	Temperature	-40°C~+60°C(-40°F~+140°F)
	Humidity	0~95% RH(non-condensing)
Input Voltage		24VDC, M12 12pin connector
Power Consumption	24VDC	Max 35.4W, Typical 13.7W * Max: LED On Typical: LED Off

Design and specifications are subject to change without notice. The latest product information / specification can be found at HanwhaVision.com
Hanwha Vision is formerly known as Hanwha Techwin.

© Hanwha Vision CO., LTD. All rights reserved.

Mechanical

Color	Black
Material	Aluminum
RAL Code	RAL9005
Product Dimensions	Camera: 218x104.1x127.1mm LED: 255.8x73.8x49.8mm Total: 255.8x181x127.1mm(with install bracket)
Product Weight	Camera: 1897g LED: 996g Total: 3438g(with install bracket)

Certifications & Standards

EMC	FCC 47 CFR 15 Subpart B Class A, ICES-3(A)/NMB-3(A), CE/UKCA - EN55032 Class A, EN 50130-4, EN 61000-3-2, EN 61000-3-3, KS C 9832 Class A, KS C 9835
Safety	UL 62368-1, CAN/CSA C22.2 NO. 62368-1
Environment	IEC 60529 IP66, IEC 60529 IP67, IEC 62262 IK10, NEMA TS-2 2.2.9 (shock resistance), IEC 60068-2-6, IEC 60068-2-27

Design and specifications are subject to change without notice. The latest product information / specification can be found at HanwhaVision.com
Hanwha Vision is formerly known as Hanwha Techwin.

© Hanwha Vision CO., LTD. All rights reserved.


TNS-9060IBC

Câmera BCR de Sensor Duplo



CAD

Unit: mm [inch]



Design and specifications are subject to change without notice. The latest product information / specification can be found at HanwhaVision.com
Hanwha Vision is formerly known as Hanwha Techwin.

© Hanwha Vision CO., LTD. All rights reserved.