



Network

TNV-8011C

5MP Anti-ligature Corner-mount Camera



Key Features

- Anti-ligature design for corrections and behavioral health facilities
- 5 Megapixel (2592 x 1944) resolution
- 30fps @ all resolutions (H.265/H.264)
- 0.1 lux @ F2.3 (Color), 0.02 lux @ F2.3 (B/W)
- Built-in 2.3mm fixed lens
- H.265, H.264, MJPEG triple codec support, Multiple streaming
- Day & Night, WDR (120dB)
- Video & audio analytics
- microSD/SDHC/SDXC memory slot (Maximum 128GB)
- Hallway view, WiseStream II support
- PoE, IK10

TNV-8011C

5MP Anti-ligature Corner-mount Camera



Specifications

Video		
Imaging Device	Size	1/2.8"
	Type	CMOS
Resolution		2592x1944, 1920x1080, 1280x960, 1280x720, 800x600, 800x448, 720x576, 720x480, 640x480, 640x360
Max. Framerate	H.265/H.264	30fps/25fps(60Hz/50Hz)
	MJPEG	15fps
Min. Illumination (Lux)	Color(1/30sec, 30IRE)	0.1
	BW(1/30sec, 30IRE)	0.02
Video Out		CVBS: 1.0 Vp-p / 75Ω composite for installation, USB: Micro USB Type B. Preview and installation ONLY. Requires WiFi dongle.

Lens		
Focal Length (mm)		2.3
Max Aperture Ratio (F number)	Wide	2.3
Angular Field of View	Horizontal	131°
	Vertical	93.4°
	Diagonal	174°
Focus Control		Fixed

Operational		
Day & Night		Auto(ICR)
Backlight Compensation		BLC, WDR, SSDR
Wide Dynamic Range (dB)		120
Digital Noise Reduction		SSNR
Digital Image Stabilization		Support
Defog		Support
Motion Detection	Quantity	4ea
	Shape	8point Polygonal zones
Privacy Masking	Quantity	6ea
	Shape	Rectangular zones

Operational

Gain Control		Low, Middle, High
White Balance		ATW, AWC, Manual, Indoor, Outdoor, Mercury, Sodium
LDC		Support
Electronic Shutter	Mode	Minimum, Maximum, Anti flicker
	Speed Range	2~1/12,000sec
Video Rotation		Flip, Mirror, Hallway view(90°/270°)
Alarm Interface	In/Out	Input 1ea, Output 1ea
Alarm Triggers		Analytics, Network disconnect, Alarm input
Alarm Events When Alarm Trigger Occurred		File upload(image): e-mail/FTP, Notification: e-mail, Recording: SD/SDHC/SDXC or NAS recording at event triggers, Alarm output
Audio In		Selectable(mic in/line in)
Audio Out		Line out

Analytics

Analytics Events	Normal	Defocus detection, Motion detection, Tampering, Audio detection, Virtual area(Intrusion/Enter/Exit), Virtual line(Crossing, Direction)
------------------	--------	--

Network

Ethernet		RJ-45(10/100BASE-T)
Video Compression		H.265: Main, H.264: Main/Baseline/High, MJPEG
Audio Compression		G.711 u-law /G.726 selectable, G.726(ADPCM) 8kHz, G.711 8kHz, G.726: 16kbps, 24kbps, 32kbps, 40kbps
Smart Codec		Manual, WiseStream II
Bitrate Control		H.265/H.264: CBR or VBR, MJPEG: VBR
Streaming	Unicast	Up to 6 users
	Multicast	Support
	Multiple Streaming	Up to 3 profiles
Protocol		IPv4, IPv6, TCP/IP, UDP/IP, RTP(UDP), RTP(TCP), RTCP, RTSP, NTP, HTTP, HTTPS, SSL/TLS, DHCP, FTP, SMTP, ICMP, IGMPv2, SNMPv1/v2c/v3(MIB-2), ARP, DNS, DDNS, QoS, UPnP, Bonjour, SRTP(TCP, UDP Unicast), PIM-SM
Application Programming Interface	Others	SUNAPI(HTTP API), Hanwha Vision Open Platform

Security

OS / Firmware Protect		Encrypted firmware
User authentication		Digest authentication
Network authentication		IEEE 802.1X(EAP-TLS, EAP-LEAP)
Secure Communication		HTTPS, SRTP
Access Control		IP-based access control

Security

Audit	Access / System / Event Log management
Device ID	Device certificate(Hanwha Vision Root CA)
Secure Storage	SDcard partition encrypt(AES-256)

General

Memory	RAM	512MB
	Flash	256MB
Edge Storage	Micro SD/SDHC/SDXC	Max. 128GB x 1slot

Environmental & Electrical

Operating Condition	Temperature	-10°C~+55°C(+14°F~+131°F)
	Humidity	0~95% RH(non-condensing)
Storage Condition	Temperature	-50°C~+60°C(-58°F~+140°F)
	Humidity	0~95% RH(non-condensing)
Input Voltage		PoE(IEEE802.3af, Class2)
Power Consumption	PoE	Max 6.49W, typical 4.6W

Mechanical

Color	White
Material	Aluminum
RAL Code	RAL9003
Product Dimensions	170(W)x165(H)x78.8(D)mm(6.69x6.49x3.10")
Product Weight	830g(1.83lb)

Certifications & Standards

EMC	FCC 47 CFR 15 Subpart B Class A, CE/UKCA - EN55032 Class A, EN 50130-4, EN 61000-3-2, EN 61000-3-3, VCCI CISPR 32 Class A, RCM AS-NZS CISPR 32 Class A
Environment	IEC/EN 63000, IEC 60529 IP66, ISO 20653 IP6K9K, IEC 62262 IK10

DORI (EN62676-4 standard)

Detect (25PPM/ 8PPF)	Wide	23.6m(77.51ft)
Observe (63PPM/ 19PPF)	Wide	9.4m(31.00ft)
Recognize (125PPM/ 38PPF)	Wide	4.7m(15.50ft)
Identify (250PPM/ 76PPF)	Wide	2.4m(7.75ft)


TNV-8011C

5MP Anti-ligature Corner-mount
Camera



CAD

Unit: mm [inch]



Compatible Devices



SBC-170CW



SBC-170C



SBC-170CB