



Network

XNB-6001

2МП сетевая камера с выносным видеомодулем



Key Features

- Макс. разрешение 2 Мп (1920 x 1080)
- Поддержка кодеков H.265, H.264, MJPEG, многоканальная передача видео
- До 60 кад/с при 2 Мп (H.265 / H.264)
- WDR (120 дБ), функция Defog, цифровая стабилизация изображения, WiseStreamII
- Обнаружение внешнего воздействия, праздного шатания, направления движения, тумана
- Обнаружение аудио, цифровое автоматическое слежение, тепловая карта
- Управление очередями, определение лица, подсчет людей
- Обнаружение движения, передача данных на PTZ камеру
- Слот для карты памяти (макс. 256 гб), функция обзора коридоров
- Коррекция искажения объектива, технология PoE / 12 В пост. тока, поддержка двусторонней передачи аудио

XNB-6001

2МП сетевая камера с выносным видеомодулем



Specifications

Video		
Resolution		1920x1080, 1280x1024, 1280x960, 1280x720, 1024x768, 800x600, 800x448, 720x576, 720x480, 640x480, 640x360, 320x240
Max. Framerate	H.265/H.264	60fps/50fps(60Hz/50Hz)
	MJPEG	30fps
Video Out		CVBS: 1.0 Vp-p / 75Ω composite for installation, USB: Micro USB Type B. Preview and installation ONLY. Requires WiFi dongle.
Lens		
Optional Lens		SLA-T1080F, SLA-T2480, SLA-T2480V, SLA-T4680, SLA-T4680V
Operational		
Day & Night		Auto(Electrical)
Backlight Compensation		BLC, HLC, WDR, SSDR
Wide Dynamic Range (dB)		120
Digital Noise Reduction		SSNR V
Digital Image Stabilization		Support
Defog		Support
Motion Detection	Quantity	8ea
	Shape	8point Polygonal zones
Privacy Masking	Quantity	32ea
	Shape	4point Quadrangle zones
	Color / Option	Gray, Green, Red, Blue, Black, White, Mosaic
Gain Control		Low, Middle, High
White Balance		ATW, AWC, Manual, Indoor, Outdoor
LDC		Support
Electronic Shutter	Mode	Minimum, Maximum, Anti flicker
	Speed Range	2~1/12,000sec
Video Rotation		Flip, Mirror, Hallway view(90°/270°)
Alarm Interface	In/Out	Input 1ea, Output 1ea
Alarm Triggers		Analytics, Network disconnect, Alarm input

Operational

Alarm Events When Alarm Trigger Occurred	File upload(image): e-mail/FTP, Notification: e-mail, Recording: SD/SDHC/SDXC or NAS recording at event triggers,Alarm output, Handover: PTZ preset
Audio In	Selectable(mic in/line in)
Audio Out	Line out

Analytics

Analytics Events	Normal	Defocus detection, Motion detection, Tampering, Fog detection, Face detection, Virtual area(Lotering, Intrusion, Enter/Exit, Appear/Disappear), Virtual line(Crossing, Direction) , Digital auto tracking
------------------	--------	--

Network

Ethernet		RJ-45(10/100BASE-T)
Video Compression		H.265/H.264: Main/Baseline/High, MJPEG
Audio Compression		G.711 u-law /G.726 selectable,G.726(ADPCM) 8kHz,G.711 8kHz, G.726: 16kbps,24kbps,32kbps,40kbps, AAC-LC: 48kbps at 16kHz
Smart Codec		Manual, WiseStream II
Bitrate Control		H.265/H.264: CBR or VBR, MJPEG: VBR
Streaming	Unicast	Up to 20 users
	Multicast	Support
	Multiple Streaming	Up to 10 profiles
Protocol		IPv4, IPv6, TCP/IP, UDP/IP, RTP(UDP), RTP(TCP), RTCP, RTSP, NTP, HTTP, HTTPS, SSL/TLS, DHCP, FTP, SMTP, ICMP, IGMP, SNMPv1/v2c/v3(MIB-2), ARP, DNS, DDNS, QoS, UPnP, Bonjour, LLDP, SRTP(TCP, UDP Unicast), PIM-SM
Application Programming Interface	ONVIF	S, G, T
	Others	SUNAPI(HTTP API), Hanwha Vision Open Platform
Direct Cloud Connection		Optional (needs gateway)

Security

OS / Firmware Protect	Encrypted firmware, Secure boot, Signed firmware
User authentication	Digest authentication
Network authentication	IEEE 802.1X(EAP-TLS, EAP-LEAP)
Secure Communication	HTTPS, SRTP
Access Control	IP-based access control
Data Protect	Encryption credentials, Encrypt compress for live recording file export
Audit	Access / System / Event Log management
Secure Storage	SDcard partition encrypt(AES-256)

General

Memory	RAM	1GB
	Flash	256MB
Edge Storage	Micro SD/SDHC/SDXC	Max. 256GB x 1slot

Environmental & Electrical

Operating Condition	Temperature	-10°C~+55°C(+14°F~+131°F)
	Humidity	0~90% RH(non-condensing)
Storage Condition	Temperature	-30°C~+60°C(-22°F~+140°F)
	Humidity	0~90% RH(non-condensing)
Input Voltage		PoE(IEEE802.3af, Class3), 12VDC
Power Consumption	PoE	Max. 6.5W
	12VDC	Max. 6W

Mechanical

Color	Ivory
Material	Plastic
Product Dimensions	131.1(W)x28(H)x86(D)mm(5.16x1.1x3.39")
Product Weight	245g(0.54lb)

Compatible lenses



Video		SLA-T2480	SLA-T1080F	SLA-T2480V	SLA-T4680V	SLA-T4680
Imaging Device	Size					
	Type					
Min. Illumination (Lux)	Color(1/30sec, 30IRE)					
	BW(1/30sec, 30IRE)					
Lens						
Max. Aperture Ratio (F number)	Wide					
	Tele					
Angular Field of View	Horizontal					
	Vertical					
	Diagonal					
Pan / Tilt / Rotate						
Pan / Tilt / Rotate Range	Pan					
	Tilt					
	Rotate					
Operational						
Environmental & Electrical						
Operating Condition	Temperature					
	Humidity					
	Others					
Storage Condition	Temperature					
	Humidity					
Mechanical						
Certification & Standards						


XNB-6001

2МП сетевая камера с выносным видеомодулем



CAD

Unit: mm [inch]



XNB-6001
UNIT : mm[inch]

