



## EMC TEST REPORT For RCM

Test Report No. : KES-EM-21T0613  
Date of Issue : Jul. 19, 2021  
Product name : NETWORK CAMERA  
Model/Type No. : XNB-6003  
Variant Model : -  
Applicant : Hanwha Techwin Co., Ltd.  
Applicant Address : 6, Pangyo-ro 319Beon-gil, Bundang-gu, Seongnam-si,  
Gyeonggi-do, Republic of Korea  
Manufacturer : 1. HANWHA TECHWIN SECURITY VIETNAM CO.,LTD.  
2. D-TECH CO.,LTD.  
Manufacturer Address : 1. Lot O-2, Que Vo Industrial Zone extended area,  
Nam Son commune, Bac Ninh city, Bac Ninh province, Vietnam  
2. 173-25, Saneop-ro, Gwonseon-gu, Suwon-si, Gyeonggi- do,  
Korea (Suwon Industrial Complex)  
Date of Receipt : Jun. 03, 2021  
Test date : Jul. 07, 2021 ~ Jul. 13, 2021  
Test Results : ☒ **In Compliance** ☐ **Not in Compliance**

Tested by

Dong Hyun, Won  
EMC Test Engineer

Reviewed by

Dong-Hun, Jang  
EMC Technical Manager

This test report is not related to KS Q ISO/IEC 17025 and KOLAS.

**KES Co., Ltd.**

3701, 40, Simin-daero 365beon-gil,  
Dongan-gu, Anyang-si, Gyeonggi-do, 14057, Korea  
Tel: +82-31-425-6200 / Fax: +82-31-424-0450  
www.kes.co.kr

Report No.:

KES-EM-21T0613

Page (2) of (39)

---

**REPORT REVISION HISTORY**

| Date          | Test Report No. | Revision History |
|---------------|-----------------|------------------|
| Jul. 19, 2021 | KES-EM-21T0613  | Issued           |
|               |                 |                  |
|               |                 |                  |
|               |                 |                  |
|               |                 |                  |
|               |                 |                  |
|               |                 |                  |
|               |                 |                  |
|               |                 |                  |
|               |                 |                  |

***This report shall not be reproduced except in full, without the written approval of KES Co., Ltd. This document may be altered or revised by KES Co., Ltd. personnel only, and shall be noted in the revision section of the document. Any alteration of this document not carried out by KES Co., Ltd. will constitute fraud and shall nullify the document.***

---

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.  
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.  
The authenticity of the test report, contact shchoi@kes.co.kr



## TABLE OF CONTENTS

|                                                      |                                                             |    |
|------------------------------------------------------|-------------------------------------------------------------|----|
| 1.0                                                  | General Product Description.....                            | 4  |
| 1.1                                                  | Test Voltage & Frequency .....                              | 7  |
| 1.2                                                  | Variant Model Differences .....                             | 7  |
| 1.3                                                  | Device Modifications .....                                  | 7  |
| 1.4                                                  | Equipment Under Test.....                                   | 7  |
| 1.5                                                  | Support Equipments .....                                    | 8  |
| 1.6                                                  | External I/O Cabling .....                                  | 9  |
| 1.7                                                  | EUT Operating Mode(s) .....                                 | 10 |
| 1.8                                                  | Configuration.....                                          | 11 |
| 1.9                                                  | Remarks when standards applied .....                        | 12 |
| 1.10                                                 | Calibration Details of Equipment Used for Measurement ..... | 12 |
| 1.11                                                 | Test Facility .....                                         | 12 |
| 1.12                                                 | Laboratory Accreditations and Listings .....                | 12 |
| 2.0                                                  | Test Regulations.....                                       | 13 |
| 2.1                                                  | Conducted Emissions at Mains Power Ports .....              | 15 |
| 2.2                                                  | Conducted Emissions at Telecommunication Ports.....         | 16 |
| 2.3                                                  | Radiated Electric Field Emissions(Below 1 GHz) .....        | 17 |
| 2.4                                                  | Radiated Electric Field Emissions(Above 1 GHz) .....        | 18 |
| APPENDIX A – TEST DATA.....                          |                                                             | 19 |
| Conducted Emissions at Mains Power Ports.....        |                                                             | 19 |
| Conducted Emissions at Telecommunication Ports ..... |                                                             | 21 |
| Radiated Electric Field Emissions(Below 1 GHz) ..... |                                                             | 23 |
| Radiated Electric Field Emissions(Above 1 GHz).....  |                                                             | 25 |
| Test Setup Photos and Configuration .....            |                                                             | 27 |
| Conducted Emissions at Mains Power Ports.....        |                                                             | 27 |
| Conducted Emissions at Telecommunication Ports ..... |                                                             | 28 |
| Radiated Electric Field Emissions(Below 1 GHz) ..... |                                                             | 30 |
| Radiated Electric Field Emissions(Above 1 GHz).....  |                                                             | 32 |
| EUT External Photographs .....                       |                                                             | 34 |
| EUT Internal Photographs .....                       |                                                             | 35 |



## KES Co., Ltd.

3701, 40, Simin-daero 365beon-gil,  
Dongan-gu, Anyang-si, Gyeonggi-do, 14057, Korea  
Tel: +82-31-425-6200 / Fax: +82-31-424-0450  
www.kes.co.kr

Report No.:  
KES-EM-21T0613  
Page (4) of (39)

## 1.0 General Product Description

### Main Specifications of EUT are:

|                             | XNB-6003                                                                                                                                                                                                                                                                                                                                               |
|-----------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Video</b>                |                                                                                                                                                                                                                                                                                                                                                        |
| Imaging Device              | 1/2.8" progressive CMOS                                                                                                                                                                                                                                                                                                                                |
| Resolution                  | 1920x1080, 1280x1024, 1280x960, 1280x720, 1024x768, 800x600, 800x448, 720x576, 720x480, 640x480, 640x360, 320x240                                                                                                                                                                                                                                      |
| Max. Framerate              | H.265/H.264: Max. 120fps/100fps(60Hz/50Hz)(WDR off)<br>Max. 60fps/50fps(60Hz/50Hz)(WDR on)<br>MJPEG: Max. 30fps/25fps(60Hz/50Hz)                                                                                                                                                                                                                       |
| NETD                        | None                                                                                                                                                                                                                                                                                                                                                   |
| Pixel Size                  | None                                                                                                                                                                                                                                                                                                                                                   |
| Min. Illumination           | (TBD)<br>Color: 0.011Lux(F1.4, 1/30sec, 30IRE)<br>B/W : 0.0011Lux(F1.4, 1/30sec, 30IRE), 0Lux(IR LED on), 30/25fps<br><br>Color: 0.022Lux(F1.4, 1/60sec, 30IRE)<br>B/W : 0.0022Lux(F1.4, 1/60sec, 30IRE), 0Lux(IR LED on), 60/50fps<br><br>Color: 0.022Lux(F1.4, 1/60sec, 30IRE)<br>B/W : 0.0022Lux(F1.4, 1/60sec, 30IRE), 0Lux(IR LED on), 120/100fps |
| Video Out                   | CVBS: 1.0 Vp-p / 75Ω composite, 720x480(N), 720x576(P) for installation<br>USB: Micro USB Type B, 1280x720 for installation                                                                                                                                                                                                                            |
| Video Transmission Distance | None                                                                                                                                                                                                                                                                                                                                                   |
| <b>Lens</b>                 |                                                                                                                                                                                                                                                                                                                                                        |
| Focal Length (Zoom Ratio)   | None                                                                                                                                                                                                                                                                                                                                                   |
| Max. Aperture Ratio         | None                                                                                                                                                                                                                                                                                                                                                   |
| Angular Field of View       | None                                                                                                                                                                                                                                                                                                                                                   |
| Min. Object Distance        | None                                                                                                                                                                                                                                                                                                                                                   |
| Focus Control               | Simple focus                                                                                                                                                                                                                                                                                                                                           |
| Lens Type                   | DC auto iris, P-iris, Manual, I-CS                                                                                                                                                                                                                                                                                                                     |
| Mount Type                  | C mount, CS mount                                                                                                                                                                                                                                                                                                                                      |
| Optional Lens               | None                                                                                                                                                                                                                                                                                                                                                   |
| <b>Pan / Tilt / Rotate</b>  |                                                                                                                                                                                                                                                                                                                                                        |
| Pan / Tilt / Rotate Range   | None                                                                                                                                                                                                                                                                                                                                                   |
| Pan Range                   | None                                                                                                                                                                                                                                                                                                                                                   |
| Pan Speed                   | None                                                                                                                                                                                                                                                                                                                                                   |
| Tilt Range                  | None                                                                                                                                                                                                                                                                                                                                                   |
| Tilt Speed                  | None                                                                                                                                                                                                                                                                                                                                                   |
| Rotate Range                | None                                                                                                                                                                                                                                                                                                                                                   |
| Sequence                    | None                                                                                                                                                                                                                                                                                                                                                   |
| Preset Accuracy             | None                                                                                                                                                                                                                                                                                                                                                   |
| <b>Operational</b>          |                                                                                                                                                                                                                                                                                                                                                        |
| Camera Title                | Displayed up to 85 characters                                                                                                                                                                                                                                                                                                                          |
| Direction Indicator         | None                                                                                                                                                                                                                                                                                                                                                   |
| Day & Night                 | Auto(ICR)                                                                                                                                                                                                                                                                                                                                              |
| Backlight Compensation      | BLC, HLC, WDR, SSDR                                                                                                                                                                                                                                                                                                                                    |
| Wide Dynamic Range          | extremeWDR (150dB)                                                                                                                                                                                                                                                                                                                                     |
| Digital Noise Reduction     | WiseNR II (Based on AI engine), SSNR V                                                                                                                                                                                                                                                                                                                 |
| Digital Image Stabilization | Support(built-in gyro sensor)                                                                                                                                                                                                                                                                                                                          |
| Defog                       | Support                                                                                                                                                                                                                                                                                                                                                |
| Motion Detection            | 8ea, 8point Polygonal zones                                                                                                                                                                                                                                                                                                                            |

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.  
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.  
The authenticity of the test report, contact shchoi@kes.co.kr



## KES Co., Ltd.

3701, 40, Simin-daero 365beon-gil,  
Dongan-gu, Anyang-si, Gyeonggi-do, 14057, Korea  
Tel: +82-31-425-6200 / Fax: +82-31-424-0450  
www.kes.co.kr

Report No.:

KES-EM-21T0613

Page (5) of (39)

|                           |                                                                                                                                                                                                                                                                                                                                                                              |
|---------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Privacy Masking           | 32ea, Quadrangle zones<br>- Color : Gray, Green, Red, Blue, Black, White<br>- Mosaic                                                                                                                                                                                                                                                                                         |
| Gain Control              | Support                                                                                                                                                                                                                                                                                                                                                                      |
| White Balance             | ATW / Narrow ATW / AWC / Manual / Indoor / Outdoor                                                                                                                                                                                                                                                                                                                           |
| LDC                       | Support (Fill/stretch mode)                                                                                                                                                                                                                                                                                                                                                  |
| Electronic Shutter Speed  | Minimum / Maximum / Anti flicker (2~1/12,000sec)<br>Auto prefer shutter control(Based on AI engine)                                                                                                                                                                                                                                                                          |
| Digital PTZ               | Support                                                                                                                                                                                                                                                                                                                                                                      |
| Video Rotation            | Flip, Mirror, Hallway view(90°/270°)                                                                                                                                                                                                                                                                                                                                         |
| Analytics                 | - Analytics events based on AI engine(NPU) : Object detection<br>(Person/Face/Vehicle(car/truck/bus/bicycle/motorcycle)/Licence plate), IVA (Virtual line/Area, Enter/Exit, Loitering, direction, intrusion)<br>- Analytics events : Defocus detection, Motion detection, Tampering, Fog detection, Audio detection, Sound classification, Shock detection, Appear/Disappear |
| Business Intelligence     | Based on AI engine(NPU) : People counting, Queue management, Heatmap                                                                                                                                                                                                                                                                                                         |
| Serial Interface          | RS-485(Samsung-T, Pelco-D/P, Panasonic, Bosch, AD, GE, Vicon, Honeywell)                                                                                                                                                                                                                                                                                                     |
| Alarm I/O                 | 2 configurable I/O ports                                                                                                                                                                                                                                                                                                                                                     |
| Alarm Triggers            | Analytics, Network disconnect, Alarm input, App event, Time schedule                                                                                                                                                                                                                                                                                                         |
| Alarm Events              | When alarm trigger occurred<br>- File upload(image) : e-mail/FTP<br>- Notification : e-mail<br>- Recording : SD/SDHC/SDXC or NAS recording at event triggers<br>- Alarm output<br>- Handover(PTZ preset, Send message by HTTP/HTTPS/TCP)<br>- Audio clip playback<br>- PTZ preset                                                                                            |
| Audio In                  | Selectable(mic in/line in/Built-in MIC)<br>Supply voltage: 2.5VDC(4mA), Input impedance: 2K Ohm                                                                                                                                                                                                                                                                              |
| Audio Out                 | Line out, Max.output level: 1Vrms                                                                                                                                                                                                                                                                                                                                            |
| IR Viewable Length        | None                                                                                                                                                                                                                                                                                                                                                                         |
| IR Illuminator (Optional) | None                                                                                                                                                                                                                                                                                                                                                                         |
| Water Removal             | None                                                                                                                                                                                                                                                                                                                                                                         |
| Auto Tracking             | None                                                                                                                                                                                                                                                                                                                                                                         |
| Coaxial Protocol          | None                                                                                                                                                                                                                                                                                                                                                                         |
| Color Palettes            | None                                                                                                                                                                                                                                                                                                                                                                         |
| <b>Radiometry</b>         |                                                                                                                                                                                                                                                                                                                                                                              |
| Temperature Detect Range  | None                                                                                                                                                                                                                                                                                                                                                                         |
| Temperature Accuracy      | None                                                                                                                                                                                                                                                                                                                                                                         |
| Temperature Detection     | None                                                                                                                                                                                                                                                                                                                                                                         |
| Additional                | None                                                                                                                                                                                                                                                                                                                                                                         |
| <b>Network</b>            |                                                                                                                                                                                                                                                                                                                                                                              |
| Ethernet                  | Metal shielded RJ-45(10/100/1000BASE-T)                                                                                                                                                                                                                                                                                                                                      |
| Video Compression         | H.265/H.264: Main/High, MJPEG                                                                                                                                                                                                                                                                                                                                                |
| Audio Compression         | G.711 u-law /G.726 Selectable<br>G.726(ADPCM) 8KHz, G.711 8KHz<br>G.726: 16Kbps, 24Kbps, 32Kbps, 40Kbps<br>AAC-LC: 48Kbps at 16KHz                                                                                                                                                                                                                                           |
| Smart Codec               | Manual(5ea area), WiseStreamⅡ, WiseStreamⅢ(Based on AI engine)                                                                                                                                                                                                                                                                                                               |

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.  
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.  
The authenticity of the test report, contact shchoi@kes.co.kr



# KES Co., Ltd.

3701, 40, Simin-daero 365beon-gil,  
Dongan-gu, Anyang-si, Gyeonggi-do, 14057, Korea  
Tel: +82-31-425-6200 / Fax: +82-31-424-0450  
www.kes.co.kr

Report No.:  
KES-EM-21T0613  
Page (6) of (39)

|                                       |                                                                                                                                                                                                                                                                                                                                                                |
|---------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Video Quality Adjustment              | H.264/H.265: Target bitrate level control<br>MJPEG: Target bitrate level control                                                                                                                                                                                                                                                                               |
| Bitrate Control                       | H.264/H.265: CBR or VBR<br>MJPEG: VBR                                                                                                                                                                                                                                                                                                                          |
| Streaming                             | Unicast(20 users) / Multicast<br>Multiple streaming(Up to 10 profiles, 3 virtual channel support)                                                                                                                                                                                                                                                              |
| Protocol                              | IPv4, IPv6, TCP/IP, UDP/IP, RTP(UDP), RTP(TCP), RTCP, RTSP, NTP, HTTP, HTTPS, SSL/TLS, DHCP, FTP, SMTP, ICMP, IGMP, SNMPv1/v2c/v3(MIB-2), ARP, DNS, DDNS, QoS, UPnP, Bonjour, LLDP, SRTP (TCP, UDP Unicast)                                                                                                                                                    |
| Security                              | TPM 2.0 (TPM 1.40-2 level 2)<br>HTTPS(SSL) Login Authentication<br>Digest Login Authentication<br>IP Address Filtering<br>User access log<br>802.1X Authentication(EAP-TLS, EAP-LEAP, EAP-PEAP MSCHAPv2)<br>Device Certificate(Hanwha Techwin Root CA, pre-installed)<br>Secure by default certificate(TBD)<br>Secure OS/Boot/Storage, Verify firmware forgery |
| Application Programming Interface     | ONVIF Profile S/G/T<br>SUNAPI(HTTP API)<br>Wisenet open platform                                                                                                                                                                                                                                                                                               |
| <b>General</b>                        |                                                                                                                                                                                                                                                                                                                                                                |
| Webpage Language                      | English, Korean, Chinese, French, Italian, Spanish, German, Japanese, Russian, Swedish, Portuguese, Czech, Polish, Turkish, Dutch, Greek, Hungarian                                                                                                                                                                                                            |
| Web Viewer                            | None                                                                                                                                                                                                                                                                                                                                                           |
| Edge Storage                          | Micro SD/SDHC/SDXC 2slot Max. 1TB (512GB * 2)                                                                                                                                                                                                                                                                                                                  |
| Memory                                | 2GB RAM, 512MB Flash                                                                                                                                                                                                                                                                                                                                           |
| <b>Environmental &amp; Electrical</b> |                                                                                                                                                                                                                                                                                                                                                                |
| Operating Temperature / Humidity      | -10 °C ~ 55°C(-14°F ~ +131°F)<br>less than 95%RH(non-condensing)                                                                                                                                                                                                                                                                                               |
| Storage Temperature / Humidity        | -50°C ~ +60°C(-58°F ~ +140°F) / Less than 90% RH                                                                                                                                                                                                                                                                                                               |
| Certification                         | None                                                                                                                                                                                                                                                                                                                                                           |
| Input Voltage                         | PoE(IEEE802.3af, Class3), 12VDC(TBD)                                                                                                                                                                                                                                                                                                                           |
| Power Consumption                     | TBD<br>Power redundancy failover(TBD)                                                                                                                                                                                                                                                                                                                          |
| <b>Mechanical</b>                     |                                                                                                                                                                                                                                                                                                                                                                |
| Color / Material                      | Black / Aluminum                                                                                                                                                                                                                                                                                                                                               |
| RAL Code                              | None                                                                                                                                                                                                                                                                                                                                                           |
| Product Dimensions / Weight           | 81(W)x67(H)x165(D)mm(3.19x2.64x6.48"), 0.88kg(1.94 lb) (TBD)                                                                                                                                                                                                                                                                                                   |
| Compatible Conduit hole / Gangbox     | None                                                                                                                                                                                                                                                                                                                                                           |
| Hanging Mount (Dome)                  | None                                                                                                                                                                                                                                                                                                                                                           |
| Skin Cover (Dome)                     | None                                                                                                                                                                                                                                                                                                                                                           |
| Weather Cap (Dome)                    | None                                                                                                                                                                                                                                                                                                                                                           |
| Power Module                          | None                                                                                                                                                                                                                                                                                                                                                           |
| Backbox                               | None                                                                                                                                                                                                                                                                                                                                                           |
| <b>DORI (EN62676-4 standard)</b>      |                                                                                                                                                                                                                                                                                                                                                                |
| Detect (25PPM/ 8PPF)                  | None                                                                                                                                                                                                                                                                                                                                                           |
| Observe (63PPM/ 19PPF)                | None                                                                                                                                                                                                                                                                                                                                                           |
| Recognize (125PPM/ 38PPF)             | None                                                                                                                                                                                                                                                                                                                                                           |
| Identify (250PPM/ 76PPF)              | None                                                                                                                                                                                                                                                                                                                                                           |

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.  
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.  
The authenticity of the test report, contact shchoi@kes.co.kr



## 1.1 Test Voltage & Frequency

Unless indicated otherwise on the individual data sheet or test results, the test voltage and frequency was as indicated below.

☒ AC 240 V, 50 Hz      ☒ PoE

## 1.2 Variant Model Differences

Not applicable

## 1.3 Device Modifications

Not applicable

## 1.4 Equipment Under Test

| Description    | Model Number | Serial Number | Manufacturer                                   | Remarks |
|----------------|--------------|---------------|------------------------------------------------|---------|
| NETWORK CAMERA | XNB-6003     | -             | HANWHA TECHWIN<br>SECURITY VIETNAM<br>CO.,LTD. | EUT     |

**KES Co., Ltd.**

3701, 40, Simin-daero 365beon-gil,  
Dongan-gu, Anyang-si, Gyeonggi-do, 14057, Korea  
Tel: +82-31-425-6200 / Fax: +82-31-424-0450  
www.kes.co.kr

Report No.:  
KES-EM-21T0613  
Page (8) of (39)

## 1.5 Support Equipments

| Description        | Model Number         | Serial Number             | Manufacturer                                   | Remarks |
|--------------------|----------------------|---------------------------|------------------------------------------------|---------|
| Lens               | -                    | -                         | -                                              | -       |
| AC / DC Adapter    | 2ACB022F             | -                         | Channel Well Technology (Guangzhou) Co., Ltd.  | -       |
| PoE Adapter        | PT-PSE109GBRO-AH     | -                         | Dongguan PROCET Network Technology Co.,Ltd     | -       |
| Notebook           | P89F                 | P89F004                   | Wistron Infocom (Chengdu) Company Limited      | -       |
| Notebook Adapter   | LA240PM190           | 0D0X04-LOC00-0AR-4104-A02 | Lite-On Technology (Changzhou) Co., Ltd.       | -       |
| Controller         | SPC-1010             | C60E67WD601003            | SamSung Techwin Co.,Ltd.                       | -       |
| Controller Adapter | RS-AB1000            | -                         | Dongguan Jinhuasheng Power Technology Co.,Ltd. | -       |
| Alarm              | SLE-0001 DO          | C64167JDB601268 F         | -                                              | -       |
| Button Alarm       | SIP-1201DD D0        | -                         | SAMSUNG TECHWIN CO., LTD.                      | -       |
| Speaker            | BR1000A Cuve Black 2 | -                         | DONGGUAN EDIFIER TECHNOLOGY Co., Ltd           | -       |
| MIC                | CMK-303              | -                         | CAMAC                                          | -       |
| Smart Phone        | SM-J500N0            | -                         | Samsung Electronics Co., Ltd.                  | -       |
| Micro SD Card      | -                    | -                         | Sandisk                                        | 32 GB   |

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.  
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.  
The authenticity of the test report, contact shchoi@kes.co.kr

**KES Co., Ltd.**

3701, 40, Simin-daero 365beon-gil,  
Dongan-gu, Anyang-si, Gyeonggi-do, 14057, Korea  
Tel: +82-31-425-6200 / Fax: +82-31-424-0450  
www.kes.co.kr

Report No.:  
KES-EM-21T0613  
Page (9) of (39)

## 1.6 External I/O Cabling

### ■ DC 12 V Mode

| Start                   |           | END                |           | Cable Spec. |        |
|-------------------------|-----------|--------------------|-----------|-------------|--------|
| Description             | I/O Port  | Description        | I/O Port  | Length      | Shield |
| NETWORK CAMERA<br>(EUT) | IRIS      | Lens               | IRIS      | 0.2         | U      |
|                         | 2 Pin     | AC / DC Adapter    | 2 Pin     | 1.4         | U      |
|                         | RJ-45     | Notebook           | RJ-45     | 4.0         | S      |
|                         | RS-485    | Controller         | RS-485    | 4.0         | U      |
|                         | Alarm OUT | Alarm              | Alarm IN  | 3.0         | U      |
|                         | Alarm IN  | Button Alarm       | Alarm OUT | 3.0         | U      |
|                         | 3.5 mm    | Speaker            | 3.5 mm    | 1.4         | U      |
|                         | 3.5 mm    | MIC                | 3.5 mm    | 1.7         | S      |
|                         | Slot      | Micro SD Card      | Slot      | -           | -      |
| Notebook                | DC Jack   | Notebook Adapter   | DC Jack   | 2.0         | S      |
|                         | 3.5 mm    | Smart Phone        | 3.5 mm    | 1.8         | U      |
| Controller              | DC Jack   | Controller Adapter | DC Jack   | 2.2         | U      |

\* Unshielded=U, Shielded=S

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.  
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.  
The authenticity of the test report, contact shchoi@kes.co.kr



■ PoE Mode

| Start                |           | END                |           | Cable Spec. |        |
|----------------------|-----------|--------------------|-----------|-------------|--------|
| Description          | I/O Port  | Description        | I/O Port  | Length      | Shield |
| NETWORK CAMERA (EUT) | IRIS      | Lens               | IRIS      | 0.2         | U      |
|                      | RJ-45     | PoE Adapter        | RJ-45     | 4.0         | S      |
|                      | RS-485    | Controller         | RS-485    | 4.0         | U      |
|                      | Alarm OUT | Alarm              | Alarm IN  | 3.0         | U      |
|                      | Alarm IN  | Button Alarm       | Alarm OUT | 3.0         | U      |
|                      | 3.5 mm    | Speaker            | 3.5 mm    | 1.4         | U      |
|                      | 3.5 mm    | MIC                | 3.5 mm    | 1.7         | S      |
|                      | Slot      | Micro SD Card      | Slot      | -           | -      |
| Notebook             | RJ-45     | PoE Adapter        | RJ-45     | 2.5         | S      |
|                      | DC Jack   | Notebook Adapter   | DC Jack   | 2.0         | S      |
|                      | 3.5 mm    | Smart Phone        | 3.5 mm    | 1.8         | U      |
| Controller           | DC Jack   | Controller Adapter | DC Jack   | 2.2         | U      |

\* Unshielded=U, Shielded=S

## 1.7 EUT Operating Mode(s)

| Test Mode    | operating                 |
|--------------|---------------------------|
| DC 12 V Mode | EUT Monitoring, Ping Test |
| PoE Mode     |                           |


| EUT Test operating S/W |         |                          |
|------------------------|---------|--------------------------|
| Name                   | Version | Manufacture Company      |
| Web Viewer             | -       | Hanwha Techwin Co., Ltd. |

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.  
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.  
The authenticity of the test report, contact shchoi@kes.co.kr


## 1.8 Configuration

■ AC Main  
 □ DC Main

### ■ DC 12 V Mode



### ■ PoE Mode



## 1.9 Remarks when standards applied

USB port and VIDEO port was excluded from the test as it is an unused port.

## 1.10 Calibration Details of Equipment Used for Measurement

Test equipment and test accessories are calibrated on regular basis. The maximum time between calibrations is one year or what is recommended by the manufacturer, whichever is less.

## 1.11 Test Facility

The measurement facility is located at 473-21 Gayeo-ro, Yeoju-si, Gyeonggi-do, 12658, Korea. The sites are constructed in conformance with the requirements of ANSI C63.4:2014 and CISPR 16-1-4:2019

## 1.12 Laboratory Accreditations and Listings

| Country       | Agency  | Scope of Accreditation                                                                                                                                                                                     | Logo                                                                                                                           |
|---------------|---------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------|
| KOREA         | RRA     | EMI (3 m & 10 m Semi-Anechoic Chamber ,<br>10 m Open Area and conducted test site)<br>EMS (ESD, RS, EFT/Burst, Surge, CS,<br>Magnetic, Dips and interruptions)                                             | <br>KR0100                                  |
| International | KOLAS   | EMI (3 m & 10 m Semi-Anechoic Chamber ,<br>and conducted test site)<br>EMS (ESD, RS, EFT/Burst, Surge, CS,<br>Magnetic, Dips and interruptions)                                                            | <br>KT489                                 |
| USA           | FCC     | 3 m & 10 m Semi-Anechoic Chamber, 10 m<br>Open Area and Conducted test site to<br>perform FCC Part 15/18 measurements.                                                                                     | <br>KR0100                                |
| Canada        | ISED    | 3 m & 10 m Semi-Anechoic Chamber and<br>Conducted test site                                                                                                                                                | <br>23298-1                               |
| JAPAN         | VCCI    | Mains Ports Conducted Interference<br>Measurement, Telecommunication Ports<br>Conducted Disturbance Measurement and<br>Radiation 10 meter site, Facility for<br>measuring radiated disturbance above 1 GHz | <br>R-20056, C-20036,<br>T-20040, G-20057 |
| Europe        | TÜV SÜD | EMI (3 m & 10 m Semi-Anechoic Chamber ,<br>10 m Open Area and conducted test site)<br>EMS (ESD, RS, EFT/Burst, Surge, CS,<br>Magnetic, Dips and interruptions)                                             | <br>CARAT 001633 0004                     |



## 2.0 Test Regulations

The emissions tests were performed according to following regulations:

☐ **EMC – Directive 2014/30/EU**

☐ EN 61000-6-3:2011

☐ EN 61000-6-1:2007

☐ EN 61000-6-4:2007 +A1:2011

☐ EN 61000-6-2:2005

☐ EN 55011:2007 +A1:2010

☐ Group 1  
☐ Class A

☐ Group 2  
☐ Class B

☐ EN 55014-1:2006 +A2:2011

☐ EN 55014-2:1997 +A2:2008

☐ EN 55015:2013

☐ EN 55032:2015

☐ Class A

☐ Class B

☐ EN 55024:2010

☐ EN 50130-4:2011 +A1:2014

☐ EN 61000-3-2:2014

☐ EN 61000-3-3:2013

☐ EN 61326-1:2013



**KES Co., Ltd.**

3701, 40, Simin-daero 365beon-gil,  
Dongan-gu, Anyang-si, Gyeonggi-do, 14057, Korea  
Tel: +82-31-425-6200 / Fax: +82-31-424-0450  
www.kes.co.kr

Report No.:  
KES-EM-21T0613  
Page (14) of (39)

- 
- |                                                                |                                             |                                  |
|----------------------------------------------------------------|---------------------------------------------|----------------------------------|
| <input type="checkbox"/> <b>VCCI-CISPR 32:2016</b>             | <input type="checkbox"/> Class A            | <input type="checkbox"/> Class B |
| <input checked="" type="checkbox"/> <b>AS/NZS CISPR32:2015</b> | <input checked="" type="checkbox"/> Class A | <input type="checkbox"/> Class B |
| <br>                                                           |                                             |                                  |
| <input type="checkbox"/> <b>47 CFR Part 15, Subpart B</b>      |                                             |                                  |
| <input type="checkbox"/> CISPR 22:2009 +A1:2010                | <input type="checkbox"/> Class A            | <input type="checkbox"/> Class B |
| <input type="checkbox"/> ANSI C63.4-2009                       |                                             |                                  |
| <br>                                                           |                                             |                                  |
| <input type="checkbox"/> <b>IC Regulation ICES-003 : 2016</b>  |                                             |                                  |
| <input type="checkbox"/> CAN/CSA CISPR 22-10                   | <input type="checkbox"/> Class A            | <input type="checkbox"/> Class B |
| <input type="checkbox"/> ANSI C63.4-2014                       |                                             |                                  |
| <br>                                                           |                                             |                                  |
| <input type="checkbox"/> <b>RE– Directive 2014/53/EU</b>       |                                             |                                  |
| <br>                                                           |                                             |                                  |
| <input type="checkbox"/> EN 301 489-1 V1.9.2                   |                                             |                                  |
| <input type="checkbox"/> Equipment for fixed use               |                                             |                                  |
| <input type="checkbox"/> Equipment for vehicular use           |                                             |                                  |
| <input type="checkbox"/> Equipment for portable use            |                                             |                                  |
| <br>                                                           |                                             |                                  |
| <input type="checkbox"/> EN 301 489-3 V1.6.1                   |                                             |                                  |
| <input type="checkbox"/> EN 301 489-17 V2.2.1                  |                                             |                                  |
| <input type="checkbox"/> EN 60945:2002                         |                                             |                                  |

---

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.  
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.  
The authenticity of the test report, contact shchoi@kes.co.kr



## 2.1 Conducted Emissions at Mains Power Ports

### Test Date

Jul. 07, 2021

### Test Location

Electro wave Shieldroom #6

### Test Equipment

| Used                                | Description       | Model Number | Manufacturer | Serial Number | Cal. Due     |
|-------------------------------------|-------------------|--------------|--------------|---------------|--------------|
| <input checked="" type="checkbox"/> | EMI Test S/W      | EMC32        | R & S        | 9.12.00       | -            |
| <input checked="" type="checkbox"/> | EMI TEST RECEIVER | ESR3         | R & S        | 101783        | 01, 15, 2022 |
| <input checked="" type="checkbox"/> | LISN              | ENV216       | R & S        | 101787        | 12, 29, 2021 |
| <input checked="" type="checkbox"/> | LISN              | ESH2-Z5      | R & S        | 100450        | 12, 29, 2021 |
| <input checked="" type="checkbox"/> | PULSE LIMITER     | ESH3-Z2      | R & S        | 101915        | 12, 29, 2021 |

### Test Conditions

Temperature: (24,9 ± 0,2) °C

Relative Humidity: (46,8 ± 0,1) % R.H.

### Frequency Range of Measurement

150 kHz to 30 MHz

### Instrument Settings

IF Band Width: 9 kHz

### Test Results

The requirements are:

- ☒ PASS  
☐ NOT PASS  
☐ NOT APPLICABLE

### Remarks

See Appendix A for test data.



## 2.2 Conducted Emissions at Telecommunication Ports

### Test Date

Jul. 07, 2021

### Test Location

Electro wave Shieldroom #6

### Test Equipment

| Used                                | Description       | Model Number | Manufacturer | Serial Number | Cal. Due     |
|-------------------------------------|-------------------|--------------|--------------|---------------|--------------|
| <input checked="" type="checkbox"/> | EMI Test S/W      | EMC32        | R & S        | 9.12.00       | -            |
| <input checked="" type="checkbox"/> | EMI TEST RECEIVER | ESR3         | R & S        | 101783        | 01, 15, 2022 |
| <input checked="" type="checkbox"/> | LISN              | ENV216       | R & S        | 101787        | 12, 29, 2021 |
| <input checked="" type="checkbox"/> | LISN              | ESH2-Z5      | R & S        | 100450        | 12, 29, 2021 |
| <input checked="" type="checkbox"/> | PULSE LIMITER     | ESH3-Z2      | R & S        | 101915        | 12, 29, 2021 |
| <input checked="" type="checkbox"/> | ISN               | ISN S8       | SCHWARZBECK  | ISN-S8-0019   | 03, 10, 2022 |

### Test Conditions

Temperature: (24,9 ± 0,2) °C

Relative Humidity: (46,8 ± 0,1) % R.H.

### Frequency Range of Measurement

150 kHz to 30 MHz

### Instrument Settings

IF Band Width: 9 kHz

### Test Results

The requirements are:

- ☒ PASS  
☐ NOT PASS  
☐ NOT APPLICABLE

### Remarks

- See Appendix A for test data.

- For Ethernet interfaces, measurements are required at the highest data rate supported by the interface.



## 2.3 Radiated Electric Field Emissions(Below 1 GHz)

### Test Date

Jul. 13, 2021

### Test Location

☐ OPEN AREA TEST SITE #2      ☒ SEMI ANECHOIC CHAMBER #4(10m)

### Test Equipment

| Used                                | Description              | Model Number | Manufacturer     | Serial Number | Cal. Due     |
|-------------------------------------|--------------------------|--------------|------------------|---------------|--------------|
| <input checked="" type="checkbox"/> | EMI Test S/W             | EP5/RE       | TOYO Corporation | 6.0.0         | -            |
| <input checked="" type="checkbox"/> | EMI TEST RECEIVER        | ESU26        | R & S            | 100551        | 04, 01, 2022 |
| <input checked="" type="checkbox"/> | AMPLIFIER                | SCU 01       | R & S            | 100603        | 11, 25, 2021 |
| <input checked="" type="checkbox"/> | TRILOG-BROADBAND ANTENNA | VULB9163     | Schwarzbeck      | 715           | 12, 08, 2022 |
| <input checked="" type="checkbox"/> | ATTENUATOR               | 8491A        | HP               | 32173         | 03, 10, 2022 |

### Test Conditions

Temperature: (24,7 ± 0,2) °C  
Relative Humidity: (46,6 ± 0,1) % R.H.

### Frequency Range of Measurement

30 MHz to 1 GHz

### Instrument Settings

IF Band Width: 120 kHz

### Test Results

The requirements are:

☒ PASS  
☐ NOT PASS  
☐ NOT APPLICABLE

### Remarks

See Appendix A for test data.



## 2.4 Radiated Electric Field Emissions(Above 1 GHz)

### Test Date

Jul. 12, 2021

### Test Location

SEMI ANECHOIC CHAMBER #3

### Test Equipment

| Used                                | Description                | Model Number | Manufacturer     | Serial Number | Cal. Due     |
|-------------------------------------|----------------------------|--------------|------------------|---------------|--------------|
| <input checked="" type="checkbox"/> | EMI Test S/W               | EP5/RE       | TOYO Corporation | 6.0.0         | -            |
| <input checked="" type="checkbox"/> | EMI TEST RECEIVER          | ESR7         | R & S            | 101190        | 08, 05, 2021 |
| <input checked="" type="checkbox"/> | PREAMPLIFIER               | 8449B        | AGILENT          | 2008A01967    | 04, 07, 2022 |
| <input type="checkbox"/>            | ATTENUATOR                 | 8491A        | HP               | 35496         | 03, 10, 2022 |
| <input checked="" type="checkbox"/> | DOUBLE RIDGED HORN ANTENNA | SAS-571      | A.H.SYSTEM,INC   | 781           | 03, 11, 2022 |

### Test Conditions

Temperature: (25,1 ± 0,2) °C

Relative Humidity: (46,8 ± 0,2) % R.H.

### Frequency Range of Measurement

1 GHz to 6 GHz

### Instrument Settings

IF Band Width: 1 MHz

### Test Results

The requirements are:

- ☒ PASS  
☐ NOT PASS  
☐ NOT APPLICABLE

### Remarks

See Appendix A for test data.

## APPENDIX A – TEST DATA


### Conducted Emissions at Mains Power Ports

■ DC 12 V Mode

HOT LINE

### Common Information

|                   |                    |
|-------------------|--------------------|
| Test Description: | Conducted Emission |
| Model No.:        | XNB-6003           |
| Phase:            |                    |
| Mode:             | DC_H               |
| Operator Name:    | KES                |



### Final Result

| Frequency (MHz) | QuasiPeak (dBμV) | CAverage (dBμV) | Limit (dBμV) | Margin (dB) | Meas. Time (ms) | Bandwidth (kHz) | Line | Corr. (dB) |
|-----------------|------------------|-----------------|--------------|-------------|-----------------|-----------------|------|------------|
| 0.155000        | ---              | 36.92           | 66.00        | 29.08       | 1000.0          | 9.000           | L1   | 19.4       |
| 0.155000        | 50.97            | ---             | 79.00        | 28.03       | 1000.0          | 9.000           | L1   | 19.4       |
| 4.795000        | ---              | 28.24           | 60.00        | 31.76       | 1000.0          | 9.000           | L1   | 19.7       |
| 4.795000        | 34.09            | ---             | 73.00        | 38.91       | 1000.0          | 9.000           | L1   | 19.7       |
| 4.825000        | ---              | 28.26           | 60.00        | 31.74       | 1000.0          | 9.000           | L1   | 19.7       |
| 4.825000        | 34.06            | ---             | 73.00        | 38.94       | 1000.0          | 9.000           | L1   | 19.7       |
| 6.085000        | ---              | 27.80           | 60.00        | 32.20       | 1000.0          | 9.000           | L1   | 19.5       |
| 6.085000        | 34.21            | ---             | 73.00        | 38.79       | 1000.0          | 9.000           | L1   | 19.5       |
| 6.170000        | ---              | 28.23           | 60.00        | 31.77       | 1000.0          | 9.000           | L1   | 19.5       |
| 6.170000        | 34.21            | ---             | 73.00        | 38.79       | 1000.0          | 9.000           | L1   | 19.5       |

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.  
 The results shown in this test report refer only to the sample(s) tested unless otherwise stated.  
 The authenticity of the test report, contact shchoi@kes.co.kr



## KES Co., Ltd.


3701, 40, Simin-daero 365beon-gil,  
Dongan-gu, Anyang-si, Gyeonggi-do, 14057, Korea  
Tel: +82-31-425-6200 / Fax: +82-31-424-0450  
www.kes.co.kr

Report No.:  
KES-EM-21T0613  
Page (20) of (39)

### NEUTRAL LINE

## Common Information

Test Description: Conducted Emission  
Model No.: XNB-6003  
Phase:  
Mode: DC\_N  
Operator Name: KES



## Final Result

| Frequency (MHz) | QuasiPeak (dBμV) | CAverage (dBμV) | Limit (dBμV) | Margin (dB) | Meas. Time (ms) | Bandwidth (kHz) | Line | Corr. (dB) |
|-----------------|------------------|-----------------|--------------|-------------|-----------------|-----------------|------|------------|
| 0.150000        | ---              | 32.04           | 66.00        | 33.96       | 1000.0          | 9.000           | N    | 19.4       |
| 0.150000        | 48.09            | ---             | 79.00        | 30.91       | 1000.0          | 9.000           | N    | 19.4       |
| 3.170000        | ---              | 27.66           | 60.00        | 32.34       | 1000.0          | 9.000           | N    | 20.1       |
| 3.170000        | 33.38            | ---             | 73.00        | 39.62       | 1000.0          | 9.000           | N    | 20.1       |
| 4.735000        | ---              | 27.02           | 60.00        | 32.98       | 1000.0          | 9.000           | N    | 19.7       |
| 4.735000        | 33.29            | ---             | 73.00        | 39.71       | 1000.0          | 9.000           | N    | 19.7       |
| 5.780000        | ---              | 28.00           | 60.00        | 32.00       | 1000.0          | 9.000           | N    | 19.5       |
| 5.780000        | 33.90            | ---             | 73.00        | 39.10       | 1000.0          | 9.000           | N    | 19.5       |
| 5.820000        | ---              | 27.91           | 60.00        | 32.09       | 1000.0          | 9.000           | N    | 19.5       |
| 5.820000        | 33.77            | ---             | 73.00        | 39.23       | 1000.0          | 9.000           | N    | 19.5       |

### ◆ Calculation

QuasiPeak[dBuV] / CAverage [dBuV] = Reading Value[dBuV] + Corr. [dB]

QuasiPeak / CAverage : The Final Value

Reading Value : Not shown in the table.

Corr. : Correction values (LISN FACTOR + (Cable Loss + Pulse Limiter FACTOR))

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.  
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.  
The authenticity of the test report, contact shchoi@kes.co.kr



## KES Co., Ltd.

3701, 40, Simin-daero 365beon-gil,  
Dongan-gu, Anyang-si, Gyeonggi-do, 14057, Korea  
Tel: +82-31-425-6200 / Fax: +82-31-424-0450  
www.kes.co.kr

Report No.:  
KES-EM-21T0613  
Page (21) of (39)


## Conducted Emissions at Telecommunication Ports

■ DC 12 V Mode

[1 000 Mbps]

### Common Information

Test Description: Telecommunication Emission  
Model No.: XNB-6003  
Mode :  
Speed : DC\_ 1 000 Mbps  
Operator Name: KES



### Final\_Result

| Frequency (MHz) | QuasiPeak (dBμV) | CAverage (dBμV) | Limit (dBμV) | Margin (dB) | Meas. Time (ms) | Bandwidth (kHz) | Line        | Corr. (dB) |
|-----------------|------------------|-----------------|--------------|-------------|-----------------|-----------------|-------------|------------|
| 0.566000        | ---              | 22.32           | 74.00        | 51.68       | 1000.0          | 9.000           | Single Line | 19.7       |
| 0.566000        | 33.75            | ---             | 87.00        | 53.25       | 1000.0          | 9.000           | Single Line | 19.7       |
| 0.738000        | ---              | 26.16           | 74.00        | 47.84       | 1000.0          | 9.000           | Single Line | 19.8       |
| 0.738000        | 30.65            | ---             | 87.00        | 56.35       | 1000.0          | 9.000           | Single Line | 19.8       |
| 4.766000        | ---              | 36.99           | 74.00        | 37.01       | 1000.0          | 9.000           | Single Line | 19.5       |
| 4.766000        | 43.49            | ---             | 87.00        | 43.51       | 1000.0          | 9.000           | Single Line | 19.5       |
| 5.118000        | ---              | 37.31           | 74.00        | 36.69       | 1000.0          | 9.000           | Single Line | 19.5       |
| 5.118000        | 43.61            | ---             | 87.00        | 43.39       | 1000.0          | 9.000           | Single Line | 19.5       |
| 8.350000        | ---              | 43.78           | 74.00        | 30.22       | 1000.0          | 9.000           | Single Line | 19.5       |
| 8.350000        | 51.05            | ---             | 87.00        | 35.95       | 1000.0          | 9.000           | Single Line | 19.5       |

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.  
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.  
The authenticity of the test report, contact shchoi@kes.co.kr



## KES Co., Ltd.

3701, 40, Simin-daero 365beon-gil,  
Dongan-gu, Anyang-si, Gyeonggi-do, 14057, Korea  
Tel: +82-31-425-6200 / Fax: +82-31-424-0450  
www.kes.co.kr


Report No.:  
KES-EM-21T0613  
Page (22) of (39)

### ■ PoE Mode

[1 000 Mbps]

## Common Information

Test Description: Telecommunication Emission  
Model No.: XNB-6003  
Mode :  
Speed : PoE\_ 1 000 Mbps  
Operator Name: KES



## Final Result

| Frequency (MHz) | QuasiPeak (dBμV) | CAverage (dBμV) | Limit (dBμV) | Margin (dB) | Meas. Time (ms) | Bandwidth (kHz) | Line        | Corr. (dB) |
|-----------------|------------------|-----------------|--------------|-------------|-----------------|-----------------|-------------|------------|
| 0.434000        | ---              | 55.02           | 75.18        | 20.16       | 1000.0          | 9.000           | Single Line | 19.6       |
| 0.434000        | 56.03            | ---             | 88.18        | 32.15       | 1000.0          | 9.000           | Single Line | 19.6       |
| 1.218000        | ---              | 38.88           | 74.00        | 35.12       | 1000.0          | 9.000           | Single Line | 20.0       |
| 1.218000        | 40.10            | ---             | 87.00        | 46.90       | 1000.0          | 9.000           | Single Line | 20.0       |
| 4.362000        | ---              | 29.68           | 74.00        | 44.32       | 1000.0          | 9.000           | Single Line | 19.6       |
| 4.362000        | 40.34            | ---             | 87.00        | 46.66       | 1000.0          | 9.000           | Single Line | 19.6       |
| 7.054000        | ---              | 37.86           | 74.00        | 36.14       | 1000.0          | 9.000           | Single Line | 19.3       |
| 7.054000        | 47.13            | ---             | 87.00        | 39.87       | 1000.0          | 9.000           | Single Line | 19.3       |
| 7.058000        | ---              | 37.72           | 74.00        | 36.28       | 1000.0          | 9.000           | Single Line | 19.3       |
| 7.058000        | 47.29            | ---             | 87.00        | 39.71       | 1000.0          | 9.000           | Single Line | 19.3       |

### ◆ Calculation

QuasiPeak[dBuV] / CAverage [dBuV] = Reading Value[dBuV] + Corr. [dB]

QuasiPeak / CAverage : The Final Value

Reading Value : Not shown in the table.


Corr. : Correction values (ISN FACTOR + (Cable Loss + Pulse Limiter FACTOR))

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.  
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.  
The authenticity of the test report, contact shchoi@kes.co.kr



## Radiated Electric Field Emissions(Below 1 GHz)

### ■ DC 12 V Mode




### Final Result

| No. | Frequency<br>[MHz] | (P) | Reading<br>QP<br>[dB(uV)] | c.f<br>[dB(1/m)] | Result<br>QP<br>[dB(uV/m)] | Limit<br>QP<br>[dB(uV/m)] | Margin<br>QP<br>[dB] | Height<br>[cm] | Angle<br>[deg] | Remark |
|-----|--------------------|-----|---------------------------|------------------|----------------------------|---------------------------|----------------------|----------------|----------------|--------|
| 1   | 125.000            | H   | 55.3                      | -24.8            | 30.5                       | 40.0                      | 9.5                  | 368.0          | 146.0          |        |
| 2   | 125.011            | V   | 50.0                      | -24.8            | 25.2                       | 40.0                      | 14.8                 | 119.0          | 126.0          |        |
| 3   | 249.996            | V   | 57.4                      | -19.1            | 38.3                       | 47.0                      | 8.7                  | 125.0          | 168.0          |        |
| 4   | 250.012            | H   | 57.5                      | -19.1            | 38.4                       | 47.0                      | 8.6                  | 394.0          | 47.0           |        |
| 5   | 532.703            | H   | 32.0                      | -10.9            | 21.1                       | 47.0                      | 25.9                 | 400.0          | 24.0           |        |
| 6   | 594.055            | V   | 38.9                      | -8.6             | 30.3                       | 47.0                      | 16.7                 | 150.0          | 320.0          |        |



## PoE Mode



## Final Result

| No. | Frequency [MHz] | (P) | Reading QP [dB(uV)] | c.f [dB(1/m)] | Result QP [dB(uV/m)] | Limit QP [dB(uV/m)] | Margin QP [dB] | Height [cm] | Angle [deg] | Remark |
|-----|-----------------|-----|---------------------|---------------|----------------------|---------------------|----------------|-------------|-------------|--------|
| 1   | 58.979          | V   | 44.5                | -21.8         | 22.7                 | 40.0                | 17.3           | 115.0       | 224.0       |        |
| 2   | 69.164          | H   | 50.1                | -24.6         | 25.5                 | 40.0                | 14.5           | 356.0       | 159.0       |        |
| 3   | 198.901         | H   | 43.7                | -20.8         | 22.9                 | 40.0                | 17.1           | 364.0       | 112.0       |        |
| 4   | 201.933         | V   | 41.7                | -20.7         | 21.0                 | 40.0                | 19.0           | 100.0       | 286.0       |        |
| 5   | 398.721         | V   | 42.2                | -14.3         | 27.9                 | 47.0                | 19.1           | 148.0       | 185.0       |        |
| 6   | 598.420         | H   | 32.7                | -8.6          | 24.1                 | 47.0                | 22.9           | 389.0       | 221.0       |        |

## ◆ Calculation

Result(QP) [dB(μV/m)] = (Reading(QP)[dB(μV)] + c.f[dB(1/m)])

Margin(QP)[dB] = Limit[dB(μV/m)] - Result(QP) [dB(μV/m)]

Reading(QP) : Reading value, Result(QP) : Reading value + Factor value

Limit(QP) : Limit value, c.f : (ANT Factor + Cable Loss - Preamp Factor), Margin: Margin value




## KES Co., Ltd.

3701, 40, Simin-daero 365beon-gil,  
Dongan-gu, Anyang-si, Gyeonggi-do, 14057, Korea  
Tel: +82-31-425-6200 / Fax: +82-31-424-0450  
www.kes.co.kr

Report No.:  
KES-EM-21T0613  
Page (25) of (39)

## Radiated Electric Field Emissions(Above 1 GHz)

### ■ DC 12 V Mode



#### Final Result

| No. | Frequency [MHz] | (P) | Reading PK [dB(uV)] | Reading CAV [dB(uV)] | c.f [dB(1/m)] | Result PK [dB(uV/m)] | Result CAV [dB(uV/m)] | Limit PK [dB(uV/m)] | Limit AV [dB(uV/m)] | Margin PK [dB] | Margin CAV [dB] | Height [cm] | Angle [deg] | Remark |
|-----|-----------------|-----|---------------------|----------------------|---------------|----------------------|-----------------------|---------------------|---------------------|----------------|-----------------|-------------|-------------|--------|
| 1   | 1625.310        | V   | 54.5                | 47.5                 | -4.9          | 49.6                 | 42.6                  | 76.0                | 56.0                | 26.4           | 13.4            | 100.0       | 18.1        |        |
| 2   | 1625.550        | H   | 51.1                | 41.1                 | -4.9          | 46.2                 | 36.2                  | 76.0                | 56.0                | 29.8           | 19.8            | 100.0       | 50.7        |        |
| 3   | 1752.917        | H   | 43.1                | 29.5                 | -3.5          | 39.6                 | 26.0                  | 76.0                | 56.0                | 36.4           | 30.0            | 100.0       | 24.2        |        |
| 4   | 2179.763        | V   | 43.7                | 27.8                 | -0.6          | 43.1                 | 27.2                  | 76.0                | 56.0                | 32.9           | 28.8            | 100.0       | 112.1       |        |
| 5   | 2665.660        | H   | 50.6                | 41.6                 | 0.9           | 51.5                 | 42.5                  | 76.0                | 56.0                | 24.5           | 13.5            | 100.0       | 61.7        |        |
| 6   | 5332.410        | V   | 42.2                | 31.0                 | 8.3           | 50.5                 | 39.3                  | 80.0                | 60.0                | 29.5           | 20.7            | 100.0       | 13.6        |        |

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.  
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.  
The authenticity of the test report, contact shchoi@kes.co.kr




## KES Co., Ltd.

3701, 40, Simin-daero 365beon-gil,  
Dongan-gu, Anyang-si, Gyeonggi-do, 14057, Korea  
Tel: +82-31-425-6200 / Fax: +82-31-424-0450  
www.kes.co.kr

Report No.:  
KES-EM-21T0613  
Page (26) of (39)

### ■ PoE Mode



### ◆ Calculation

Result(PK/CAV) [dB( $\mu$ V/m)] = (Reading(PK/CAV)[dB( $\mu$ V)] + c.f[dB(1/m)])

Margin(PK/CAV)[dB] = Limit[dB( $\mu$ V/m)] - Result(PK/CAV) [dB( $\mu$ V/m)]

Reading(PK/CAV) : Reading value, Result(PK/CAV) : Reading value + Factor value

Limit(QP) : Limit value, c.f : (ANT Factor + Cable Loss - Preamp Factor), Margin: Margin value

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.  
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.  
The authenticity of the test report, contact shchoi@kes.co.kr

## Test Setup Photos and Configuration

### Conducted Emissions at Mains Power Ports

#### ■ DC 12 V Mode



This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.  
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.  
The authenticity of the test report, contact shchoi@kes.co.kr

## Conducted Emissions at Telecommunication Ports

### ■ DC 12 V Mode



This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.  
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.  
The authenticity of the test report, contact shchoi@kes.co.kr

■ PoE Mode




This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.  
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.  
The authenticity of the test report, contact shchoi@kes.co.kr

## Radiated Electric Field Emissions(Below 1 GHz)

### ■ DC 12 V Mode




This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.  
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.  
The authenticity of the test report, contact shchoi@kes.co.kr

**■ PoE Mode**

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.  
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.  
The authenticity of the test report, contact shchoi@kes.co.kr

## Radiated Electric Field Emissions(Above 1 GHz)

### ■ DC 12 V Mode



This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.  
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.  
The authenticity of the test report, contact shchoi@kes.co.kr

■ PoE Mode



This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.  
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.  
The authenticity of the test report, contact shchoi@kes.co.kr

## EUT External Photographs

(Top)




(Bottom)



This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.  
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.  
The authenticity of the test report, contact shchoi@kes.co.kr

## EUT Internal Photographs

(Internal View)



This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.  
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.  
The authenticity of the test report, contact shchoi@kes.co.kr

## EUT Internal View – Board

(Top)




(Bottom)




This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.  
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.  
The authenticity of the test report, contact shchoi@kes.co.kr

## EUT Internal View – Main Board

(Top)




(Bottom)




This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.  
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.  
The authenticity of the test report, contact shchoi@kes.co.kr

## EUT Internal View – Lens Board

(Top)




(Bottom)




This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.  
 The results shown in this test report refer only to the sample(s) tested unless otherwise stated.  
 The authenticity of the test report, contact shchoi@kes.co.kr

## EUT Internal View –Power Board

(Top)



(Bottom)



This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.  
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.  
The authenticity of the test report, contact shchoi@kes.co.kr