



TEST REPORT



Report No. : KES-EM252066

Page 1 / 68

KES Co., Ltd.

#3002, #3503, #3701, 40, Simin-daero365beon-gil, Dongan-gu, Anyang-si, Gyeonggi-do, 14057, Republic of Korea
Tel : +82-31-425-6200, Fax : +82-31-341-3838

1. Client

Applicant : Hanwha Vision Co., Ltd.
Applicant Address : 6, Pangyo-ro 319Beon-gil, Bundang-gu, Seongnam-si, Gyeonggi-do, Republic of Korea

2. Sample Description

Product name : NETWORK CAMERA
Model/Type No. : XNB-A8004
Variant Model : -
Manufacturer : 1. HANWHA VISION VIETNAM COMPANY LIMITED
2. D-TECH CO.,LTD.
Manufacturer Address : 1. Lot O-2, Que Vo Industrial Zone Extended Area, Nam Son Ward, Bac Ninh Province, Vietnam
2. 173-25, Saneop-ro, Gwonseon-gu, Suwon-si, Gyeonggi- do, Korea (Suwon Industrial Complex)

3. Date of Receipt : Jun. 09, 2025

4. Test date : Jul. 16, 2025 ~ Jul. 18, 2025

5. Date of Issue : Aug. 19, 2025

6. Test Results : In Compliance

Tested by

Reviewed by

Seong Jun, Park
EMC Test Engineer

Dong Hun, Jang
EMC Technical Manager

This test report is not related to KS Q ISO/IEC 17025 and KOLAS.

KES-QP16-F01(00-23-01-01)

KES Co., Ltd.

The authenticity of this test report can be found on the verification page of our website (www.kes.co.kr).

**REPORT REVISION HISTORY**

Date	Test Report No.	Revision History
Aug. 19, 2025	KES-EM252066	Issued

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd. This document may be altered or revised by KES Co., Ltd. personnel only, and shall be noted in the revision section of the document. Any alteration of this document not carried out by KES Co., Ltd. will constitute fraud and shall nullify the document.



TABLE OF CONTENTS

1.0	General Product Description.....	4
1.1	Test Voltage & Frequency.....	5
1.2	Variant Model Differences.....	5
1.3	Device Modifications.....	5
1.4	Equipment Under Test.....	5
1.5	Support Equipments.....	5
1.6	External I/O Cabling.....	6
1.7	EUT Operating Mode(s).....	6
1.8	Configuration.....	8
1.9	Remarks when standards applied.....	9
1.10	Calibration Details of Equipment Used for Measurement.....	9
1.11	Test Facility.....	9
1.12	Laboratory Accreditations and Listings.....	10
2.0	Test Regulations.....	11
2.1	Conducted Emissions at Mains Power Ports.....	12
2.2	Conducted Emissions at Telecommunication Ports.....	13
2.3	Radiated Electric Field Emissions(Below 1 GHz).....	14
2.4	Radiated Electric Field Emissions(Above 1 GHz).....	15
2.5	Harmonic Current Emissions.....	16
2.6	Voltage Fluctuations and Flicker.....	17
3.0	Criteria for compliance.....	18
3.1	Electrostatic Discharge.....	20
3.2	Radiated Electric Field Immunity.....	23
3.3	Electrical Fast Transients/Bursts.....	26
3.4	Surge Transients.....	29
3.5	Conducted Disturbance.....	33
3.6	Voltage Dips and Short Interruptions.....	35
APPENDIX A – TEST DATA.....		37
Conducted Emissions at Mains Power Ports.....		37
Conducted Emissions at Telecommunication Ports.....		39
Radiated Electric Field Emissions(Below 1 GHz).....		41
Radiated Electric Field Emissions(Above 1 GHz).....		43
Harmonic Current Emissions and Voltage Fluctuations and Flicker.....		45
Test Setup Photos and Configuration.....		48
Conducted Emissions at Mains Power Ports.....		48
Conducted Emissions at Telecommunication Ports.....		49
Radiated Electric Field Emissions(Below 1 GHz).....		51
Radiated Electric Field Emissions(Above 1 GHz).....		51
Harmonic Current Emissions and Voltage Fluctuations and Flicker.....		53
Electrostatic Discharge.....		56
Radiated Electric Field Immunity.....		56
Electrical Fast Transients/Bursts.....		57
Surge Transients.....		59
Conducted Disturbance.....		60
Voltage Dips and Short Interruptions.....		61
EUT External Photographs.....		61
EUT Internal Photographs.....		63



1.0 General Product Description

Main Specifications of EUT are:

XNB-A8004		
Video		
Imaging Device	Size	1/2.8"
	Type	CMOS
Resolution	2560x1920, 2560x1440, 1920x1080, 1600x1200, 1280x960, 1280x720, 1024x768, 800x600, 640x480, 640x360, 320x240, 320x180	
Max. Framerate	H.265/H.264	30fps/25fps(60Hz/50Hz)
	MJPEG	30fps@5MP Max. 5fps)
Video Out	USB: Micro USB Type C	
Lens		
Focus Control	Simple focus	
Lens Type	DC auto iris, P iris(IR corrected), Manual, I-CS	
Mount Type	C mount, CS mount	
Operational		
Day & Night	Auto(ICR)	
Backlight Compensation	BLC, HLC, WDR, SDR	
Wide Dynamic Range (dB)	120	
Digital Noise Reduction	WiseNRⅡ(Based on AI engine), SSNRV	
Digital Image Stabilization	Support	
Defog	Support	
Motion Detection	Quantity	8ea
	Shape	8point Polygonal zones
Privacy Masking	Quantity	32ea
	Shape	8point Polygonal zones
	Color / Option	Gray, Green, Red, Blue, Black, White, Mosaic, Purple, Yellow
	Dynamic Privacy Masking: Color / Option	Gray, Green, Red, Blue, Black, White, Mosaic, Purple, Yellow
Gain Control	Off, Max gain, Manual	
White Balance	ATW, NarrowATW, AWC, Manual, Indoor, Outdoor	
LDC	Support/Fill/stretch mode)	
Electronic Shutter	Mode	Minimum, Maximum, Anti flicker, Prefer shutter control(Based on AI engine)
	Speed Range	2~1/30,000sec
Video Rotation	Flip, Mirror, Hallway view(90°/270°)	
Serial Interface	RS-485(Samsung-T, Pelco-D/P, Panasonic, Bosch, AD, GE, Vicon, Honeywell)	
Alarm Interface	In/Out	2 configurable I/O ports
	Others	Support extra alarm I/O via optional I/O box
	Analytics, Network disconnect, Alarm input, Time schedule, MQTT subscription, Day/Night, Storage disruption	
Alarm Triggers	File upload(image): e-mail/FTP/SFTP, File upload(video clip): FTP/SFTP, Notification: e-mail, Recording: SD/SDHC/SDXC or NAS recording at event triggers, Alarm output, Handover: PTZ preset, send message by HTTP/HTTPS/TCP, Audio clip playback, MQTT: publication, SIP: call generation	
Alarm Events When Alarm Trigger Occurred		
Audio In	Selectable(mic in/line in), Built-in mic	
Audio Out	Line out	

Analytics		
Classified Object Type		Person, Face, Vehicle, License plate
Attributes	Person	Upper/Lower clothes color, Gender, Bag
	Vehicle	Type(car, bus, truck, motorcycle, bicycle), Color
Re-ID	Face	Age, Gender, Face mask, Glasses
	Person	BestShot
Thumbnail		BestShot
Analytics Events	Based on AI Engine	Object detection, Virtual line(Crossing/Direction), Motion detection, Face mask detection, Social distancing detection, Slip & fall detection, Virtual area(Looting/Intrusion/Enter/Exit/Appear/Disappear)
	Normal	Defocus detection, Tampering, Audio detection, Shock detection
Business Intelligence	Based on AI Engine	People counting, Queue management, Heatmap, Vehicle counting, Crowd counting
Network		
Ethernet		Metal shielded RJ-45(10/100BASE-T)
Video Compression		H.265/H.264: Main/Baseline/High, MJPEG
Audio Compression		G.711(PCM): 8KHz(64kbps), G.726(ADPCM): 8KHz(16/24/32/40kbps), AAC-LC: 16KHz(48kbps), OPUS: 48KHz(64kbps)
Smart Codec		WiseStream(Based on AI engine)
Bitrate Control		H.265/H.264: CBR or VBR, MJPEG: VBR
Streaming	Unicast	Up to 20 users
	Multicast	Support
Protocol	Multiple Streaming	Up to 5 profiles, 3 virtual channel support
		IPv4, IPv6, TCP/IP, UDP/IP, RTP/UDP, RTSP(TCP), RTSP, RTP, NTP, HTTP, HTTPS, SSL/TLS, DHCP, FTP, SFTP, ICMP, IGMP, SNMPv1/v2c/v3(MIB-2), ARP, DNS, DDNS, QoS, UPnP, Bonjour, LLDP, CDP, SRTP(TCP, UDP Unicast), MQTT, SMTP(StartTLS), SIP, Syslog
SIP support (VoIP, Peer-to-peer, SIP/PBX Integration)		Tested with Cisco, Grandstream, Yealink VoIP phones and Asterisk PBX software
Application Programming Interface	ONVIF	S, G, T, M
	Others	SUNAPI(HTTP API), Hanwha Vision Open Platform
	OnCloud(미사용 필독)	OnCloud edge recording, compatible with Hanwha SD cards up to 1TB
Direct Cloud Connection		Support
Security		
OS / Firmware Protect		Encrypted firmware, Secure boot, Signed firmware
User authentication		Digest authentication, Prevent brute-force attack
Network authentication		IEEE 802.1X(EAP-TLS, EAP-LEAP, EAP-PEAP, MSCHAPv2)
Secure Communication		HTTPS, WSS(WebSocket Secure), SRTP, 802.1AE(MACsec)
Access Control		IP-based access control, MAC-based access control, Auto logout
Data Protect		Encryption credentials, Encrypt compress for live recording file export
Audit		Access / System / Event Log management
Device ID		Device certificate(Hanwha Vision Root CA)
Secure Storage		SDcard partition encrypt(AES-256), Secure element
Supply Chain Security		SBOM
Security Certificate		Secure element(RPS 140-3 level3, CC EAL6+), ETSI EN 303 645, IEC 62443-4-1

General		
Memory	RAM	4GB
	Flash	8GB eMMC
Edge Storage	Micro SD/SDHC/SDXC	Max. 1TB x 2slot(Total 2TB)
	SSD	None
Environmental & Electrical		
Operating Condition	Temperature	-10℃~+55℃(+14℉~+131℉)
	Humidity	0~95% RH(non-condensing)
Storage Condition	Temperature	-50℃~+60℃(-58℉~+140℉)
	Humidity	0~90% RH(non-condensing)
Input Voltage	PoE(IEEE802.3af, Class3), 12VDC	
Power Consumption	PoE	Max. 8.9W, typical 7.5W
	12VDC	Max. 8.1W, typical 6.7W
Wisepower	Power monitoring, ECO mode	
Power Redundance	Support	
Fallover		
Mechanical		
Color	Black	
Material	Aluminum	
Material Management	Declaration	RoHS(EU RoHS directive 2011/65/EU and IEC/EN 63000:2018), REACH(Regulation (EC) No. 1907/2006), Conflict mineral policy(Section 1502 of US Dodd Frank Act)
	Recycle Rate	None
RAL Code	RAL9005	
Product Dimensions	81(W)x67(H)x165(D)mm(3.19x2.64x6.48")	
Product Weight	851g(1.88lb)	
Certifications & Standards		
EMC	FCC 47 CFR 15 Subpart B Class A, ICES-3(A)/NMB-3(A), CE/UKCA - EN55032 Class A, EN 50130-4, EN 61000-3-2, EN 61000-3-3, VCCI CISPR 32 Class A, RCM AS-NZS CISPR 32 Class A, KS C 9832 Class A, KS C 9835	
Safety	UL 62368-1, CAN/CSA C22.2 NO. 62368-1, IEC 62471	
Environment	IEC 60068-2-1, IEC 60068-2-2, IEC 60068-2-6, IEC 60068-2-14, IEC 60068-2-27, IEC 60068-2-78	



1.1 Test Voltage & Frequency

Unless indicated otherwise on the individual data sheet or test results, the test voltage and frequency was as indicated below.

☒ AC 230 V, 50 Hz ☒ PoE

1.2 Variant Model Differences

Not applicable

1.3 Device Modifications

Not applicable

1.4 Equipment Under Test

Description	Model Number	Serial Number	Manufacturer	Remarks
NETWORK CAMERA	XNB-A8004	-	HANWHA VISION VIETNAM COMPANY LIMITED	EUT

1.5 Support Equipments

Description	Model Number	Serial Number	Manufacturer	Remarks
Adapter	FSP060-DIBAN2	-	FSP GROUP INC.	-
PoE Injector	PT-PSE106GBR-AH-S	-	Dongguan PROCET Network Technology Co., Ltd	-
Notebook	NT500R5W	-	Samsung Eelcotronics Co., Ltd.	-
Notebook Adapter	PA-1400-96	-	LITE-ON TECHNOLOGY CHANGZHOU CO.,LTD	-
Micro SD Card 1	-	-	SanDisk	-
Micro SD Card 2	-	-	SanDisk	-
LED Alarm	PRO-SL	-	SENSOR PRO	-
Button Alarm	-	-	-	-
Earphone	-	-	-	-
Smartphone	SM-N950N	-	Samsung Eelcotronics Co., Ltd.	-
Controller	SPC-1010	-	SamSung Techwin Co.,Ltd.	-



1.6 External I/O Cabling

■ mode 1

Start		END		Cable Spec.	
Description	I/O Port	Description	I/O Port	Length	Shield
NETWORK CAMERA (EUT)	2 Pin	Adapter	2 Pin	1.6	U
	Micro SD Card Slot	Micro SD Card 1	Micro SD Card Slot	-	-
	Micro SD Card Slot	Micro SD Card 2	Micro SD Card Slot	-	-
	RJ-45 (LAN)	Notebook	RJ-45 (LAN)	3.1	U
	Alarm IN (2 PIN)	Button Alarm	Alarm OUT	3.1	U
	Alarm OUT (2 PIN)	LED Alarm	Alarm IN	3.1	U
	RS-485 (2 PIN)	Controller	2 Pin	3.1	U
	Audio IN	Smartphone	3.5 mm	1.0	U
	Audio OUT	Earphone	3.5 mm	1.4	U
	Ground	Ground	Ground	1.5	-
Notebook	DC Jack	Notebook Adapter	DC Jack	1.6	U

* Unshielded=U, Shielded=S

■ mode 2

Start		END		Cable Spec.	
Description	I/O Port	Description	I/O Port	Length	Shield
NETWORK CAMERA (EUT)	RJ-45 (PoE)	PoE Injector	RJ-45 (PoE)	3.1	U
	Micro SD Card Slot	Micro SD Card 1	Micro SD Card Slot	-	-
	Micro SD Card Slot	Micro SD Card 2	Micro SD Card Slot	-	-
	Alarm IN (2 PIN)	Button Alarm	Alarm OUT	3.1	U
	Alarm OUT (2 PIN)	LED Alarm	Alarm IN	3.1	U
	RS-485 (2 PIN)	Controller	2 Pin	3.1	U
	Audio IN	Smartphone	3.5 mm	1.0	U
	Audio OUT	Earphone	3.5 mm	1.4	U
	Ground	Ground	Ground	1.5	-
Notebook	DC Jack	Notebook Adapter	DC Jack	1.6	U

* Unshielded=U, Shielded=S



1.7 EUT Operating Mode(s)


Test mode		Normal operating
mode 1	Adapter	- IP from the test equipment to the laptop was tested by Ping Test on the laptop. - The test was conducted by checking whether the camera image was output normally in the Web Viewer. - After the test, I checked whether the video was recorded normally on the Micro SD Card.
mode 2	PoE	

EUT Test operating S/W		
Name	Version	Manufacture Company
Web Viewer	-	HANWHA VISION VIETNAM COMPANY LIMITED




1.8 Configuration

■ mode 1




■ mode 2





1.9 Remarks when standards applied

USB C Type ports are not used and have not been tested.



1.10 Calibration Details of Equipment Used for Measurement

Test equipment and test accessories are calibrated on regular basis. The maximum time between calibrations is one year or what is recommended by the manufacturer, whichever is less.

1.11 Test Facility

The measurement facility is located at 473-21, Gayeo-ro, Yeoju-si, Gyeonggi-do, 12658, Korea, Republic of. The sites are constructed in conformance with the requirements of ANSI C63.4a-2017 and CISPR 16-1-4:2019



1.12 Laboratory Accreditations and Listings

Country	Agency	Scope of Accreditation	Logo
KOREA	RRA	EMI (3 m & 10 m Semi-Anechoic Chamber and conducted test site) EMS (ESD, RS, EFT/Burst, Surge, CS, Magnetic, Dips and interruptions)	 KR0100
International	KOLAS	EMI (3 m & 10 m Semi-Anechoic Chamber and conducted test site) EMS (ESD, RS, EFT/Burst, Surge, CS, Magnetic, Dips and interruptions)	 KT489
USA	FCC	3 m & 10 m Semi-Anechoic Chamber Conducted test site to perform FCC Part 15/18 measurements.	 KR0100
Canada	ISED	3 m & 10 m Semi-Anechoic Chamber and Conducted test site	 23298
JAPAN	VCCI	EMI (3 m & 10 m Semi-Anechoic Chamber and conducted test site)	 C-20136, T-20137, R-20181, G-20176
Europe	TÜV SÜD	EMI (3 m & 10 m Semi-Anechoic Chamber and conducted test site) EMS (ESD, RS, EFT/Burst, Surge, CS, Magnetic, Dips and interruptions)	 CARAT 001633 0008



2.0 Test Regulations

The emissions tests were performed according to following regulations:

☒ **EMC – Directive 2014/30/EU**

☒ EN 55032:2015/A1:2020

☒ Class A

☐ Class B

☒ EN 50130-4:2011/A1:2014

☒ EN IEC 61000-3-2:2019

☒ EN 61000-3-3:2013/A2:2021

☒ **EMC – Regulations 2016**

☒ EN 55032:2015/A1:2020

☒ Class A

☐ Class B

☒ EN 50130-4:2011/A1:2014

☒ EN IEC 61000-3-2:2019

☒ EN 61000-3-3:2013/A2:2021



2.1 Conducted Emissions at Mains Power Ports

Test Date

Jul. 17, 2025

Test Location

Electro wave Shieldroom #6

Test Equipment

Used	Description	Model Number	Manufacturer	Serial Number	Cal. Due
☒	EMI Test SW	EMC32	R & S	9.12.00	-
☒	EMI TEST RECEIVER	ESR3	R & S	101783	11, 06, 2025
☒	LISN	ENV216	R & S	101786	01, 09, 2026
☒	ARTIFICIAL MAINS NETWORK	ESH2-Z5	R & S	100450	11, 06, 2025
☒	PULSE LIMITER	ESH3-Z2	R & S	101915	11, 06, 2025

Test Conditions

Temperature: (23,8 ± 0,1) °C

Relative Humidity: (46,2 ± 0,1) % R.H.

Frequency Range of Measurement

150 kHz to 30 MHz

Instrument Settings

IF Band Width: 9 kHz

Test Results

The requirements are:

- ☒ PASS
☐ NOT PASS
☐ NOT APPLICABLE

RemarksSee Appendix A for test data.



2.2 Conducted Emissions at Telecommunication Ports

Test Date

Jul. 17, 2025

Test Location

Electro wave Shieldroom #6

Test Equipment

Used	Description	Model Number	Manufacturer	Serial Number	Cal. Due
☒	EMI Test S/W	EMC32	R & S	9.12.00	-
☒	EMI TEST RECEIVER	ESR3	R & S	101783	11, 06, 2025
☒	LISN	ENV216	R & S	101786	01, 09, 2026
☒	ARTIFICIAL MAINS NETWORK	ESH2-Z5	R & S	100450	11, 06, 2025
☒	PULSE LIMITER	ESH3-Z2	R & S	101915	11, 06, 2025
☒	8-WIRE ISN CAT3,5	ENY81	R & S	100174	11, 12, 2025

Test Conditions

Temperature: (23,8 ± 0,1) °C

Relative Humidity: (46,2 ± 0,1) % R.H.

Frequency Range of Measurement

150 kHz to 30 MHz

Instrument Settings

IF Band Width: 9 kHz

Test Results

The requirements are:

- ☒ PASS
☐ NOT PASS
☐ NOT APPLICABLE

RemarksSee Appendix A for test data.



2.3 Radiated Electric Field Emissions(Below 1 GHz)

Test Date

Jul. 16, 2025

Test Location☒ SEMI ANECHOIC CHAMBER #4(10m)**Test Equipment**

Used	Description	Model Number	Manufacturer	Serial Number	Cal. Due
☒	EMI Test S/W	EP5/RE	TOYO Corporation	6.0.0	-
☒	EMI TEST RECEIVER	ESW8	R & S	101319	03, 24, 2026
☒	AMPLIFIER	SCU 01	R & S	100603	11, 06, 2025
☒	BILOG ANTENNA	VULB 9168	SCHWARZBECK	9168-461	05, 09, 2026
☒	ATTENUATOR	6806.17.A	HUBER+SUHNER	-	02, 13, 2026

Test Conditions

Temperature: (24,0 ± 0,1) °C

Relative Humidity: (47,5 ± 0,1) % R.H.

Frequency Range of Measurement

30 MHz to 1 GHz

Instrument Settings

IF Band Width: 120 kHz

Test Results

The requirements are:

- ☒ PASS
☐ NOT PASS
☐ NOT APPLICABLE

RemarksSee Appendix A for test data.



2.4 Radiated Electric Field Emissions(Above 1 GHz)

Test Date

Jul. 18, 2025

Test Location

SEMI ANECHOIC CHAMBER #5

Test Equipment

Used	Description	Model Number	Manufacturer	Serial Number	Cal. Due
☒	EMI Test SW	ES10/RE	TOYO Corporation	2022.01.000	-
☒	EMI TEST RECEIVER	ESU26	Rohde & Schwarz	100552	02, 13, 2026
☒	HORN ANTENNA	BBHA 9120D	SCHWARZBECK	9120D-1802	11, 04, 2025
☒	PREAMPLIFIER	8449B	HP	3008A00899	03, 05, 2026
☒	ATTENUATOR	8491B	HP	23094	02, 13, 2026

Test Conditions

Temperature: (23,5 ± 0,1) °C

Relative Humidity: (46,6 ± 0,1) % R.H.

Frequency Range of Measurement

1 GHz to 6 GHz

Instrument Settings

IF Band Width: 1 MHz

Test Results

The requirements are:

- ☒ PASS
☐ NOT PASS
☐ NOT APPLICABLE

Remarks

- See Appendix A for test data.
- The Average of the test data is the cispr average result.



2.5 Harmonic Current Emissions

Test Date

Jul. 18, 2025

Test Location

Electro wave Shieldroom #7

Test Equipment

Used	Description	Model Number	Manufacturer	Serial Number	Cal. Due
☒	EMI Test SW	net.control	EM TEST	2.1.4	-
☒	DIGITAL POWER ANALYZER	DPA 500N	EM TEST	V1024106759	03, 31, 2026
☒	POWER SOURCE	ACS 500N6	EM TEST	V1024106760	-

Test Conditions

Temperature: (23,5 ± 0,1) °C

Relative Humidity: (46,7 ± 0,1) % R.H.

Classification of Equipment for Harmonic Current Emissions

- ☒ Class A
☐ Class B
☐ Class C(Below 25 W)
☐ Class C(Above 25 W)
☐ Class D

Test Results

The requirements are:

- ☒ PASS
☐ NOT PASS
☐ NOT APPLICABLE

RemarksSee Appendix A for test data.The LAN port is regarded as a wired communication network port and power-related ports are not tested.



2.6 Voltage Fluctuations and Flicker

Test Date

Jul. 18, 2025

Test Location

Electro wave Shieldroom #7

Test Equipment

Used	Description	Model Number	Manufacturer	Serial Number	Cal. Due
☒	EMI Test SW	net.control	EM TEST	2.1.4	-
☒	DIGITAL POWER ANALYZER	DPA 500N	EM TEST	V1024106759	03, 31, 2026
☒	POWER SOURCE	ACS 500N6	EM TEST	V1024106760	-

Test Conditions

Temperature: (23,5 ± 0,1) °C

Relative Humidity: (46,7 ± 0,1) % R.H.

Test Results

The requirements are:

- ☒ PASS
☐ NOT PASS
☐ NOT APPLICABLE

RemarksSee Appendix A for test data.The LAN port is regarded as a wired communication network port and power-related ports are not tested.



3.0 Criteria for compliance

Criteria for compliance was based on the following guidelines:

EN 50130-4:2011/A1 :2014 Alarm systems-Part 4: Electromagnetic compatibility Product family standard: Immunity requirements for components of fire, intruder and social alarm systems

The variety and the diversity of the apparatus within the scope of this document makes it difficult to define precise criteria for the evaluation of the immunity test results.

If as a result of the application of the tests defined in this standard, the apparatus becomes dangerous or unsafe then the apparatus shall be deemed to have failed the test.

A functional description and a definition of performance by the manufacture and noted in the test report, based on the following criteria:

Electrostatic discharge

There shall be no damage, malfunction or change of status due to the conditioning.

Flickering of an indicator during the application of discharge is permissible, providing that is no residual change in the EUT or any change in outputs, which could be interpreted by associated equipment as a change.

Radiated electromagnetic fields

There shall be no damage, malfunction or change of status due to the conditioning.

Flickering of an indicator during the application of discharge is permissible, providing which could be interpreted by associated equipment as a change, and no such

Flickering of indicators occurs at a field strength of 3 V/m.

For components of CCTV systems, where the picture is allowed at 10 V/m, providing.

- (a) there is no permanent damage or change to EUT
(e.g. no corruption of memory or changes to programmable setting etc.)
- (b) at 3 V/m, any deterioration of the picture is so minor that the system could still be used; and
- (c) there is no observable deterioration of the picture at 1 V/m.



Fast transient burst / slow high energy voltage surge

There shall be no damage, malfunction or change of status due to the conditioning.

Flickering of an indicator during the application of discharge is permissible, providing

That there is no residual is permissible, providing that there is no residual change in the EUT or any change in outputs, which could be interpreted by associated equipment as a change.

Conducted RF immunity

There shall be no damage, malfunction or change of status due to the conditioning.

Flickering of an indicator during the application of discharge is permissible, providing

That there is no residual is permissible, providing that there is no residual change in the EUT or any change in outputs, which could be interpreted by associated equipment as a change, and no such flickering of indicators oeuvres at $U = 130 \text{ dB}\mu\text{V}$.

For component of CCTV systems, where the status is monitored by observing the TV picture, then deterioration of the picture is allowed at $U = 140 \text{ dB}\mu\text{V}$, providing:

- (a) there is no permanent damage or change to the EUT
(e.g. no corruption of memory or changes to programmable settings etc.)
- (b) at $U = 130 \text{ dB}\mu\text{V}$, any deterioration of the picture is so minor that the system could still be used; and
- (c) there in no observable deterioration of the picture at $U = 120 \text{ dB}\mu\text{V}$.

Voltage dip/interruption / Voltage variation

There shall be no damage, malfunction or change of status due to the conditioning.

Flickering of an indicator during the conditioning is permissible, providing that there is no residual change in the EUT or any change in outputs, which could be interpreted by associated equipment as a change. The EUT shall meet the acceptance criteria for the functional test, after the conditioning.



3.1 Electrostatic Discharge

Reference Standard

EN 61000-4-2

Test Date

Jul. 16, 2025

Test Location

EMS-ESD: Electro wave Shieldroom #6

Test Equipment

Used	Description	Model Number	Manufacturer	Serial Number	Cal. Due
☒	ESD SIMULATOR	ESS-2000	Noise Ken	ESS01Z0454	01, 21, 2026
☒	HCP	-	KES	-	-
☒	VCP	-	Noise Ken	-	-

Test Conditions

Temperature: (23,6 ± 0,1) °C
Relative Humidity: (46,1 ± 0,1) % R.H.
Atmospheric Pressure: (99,2 ± 0,0) kPa

Test Specifications

Discharge Factor: ≥ 1 s
Discharge Impedance: 330 ohm / 150 pF
Kind of Discharge: Air, Contact (direct and indirect)
Polarity: Positive and Negative
Number of Discharge: 10 at all locations for Air discharge
10 at all locations for Contact discharge


Discharge Voltage:	Contact	Air	HCP	VCP
	☐ 2 kV	☒ 2 kV	☐ 2 kV	☐ 2 kV
	☐ 4 kV	☒ 4 kV	☐ 4 kV	☐ 4 kV
	☒ 6 kV	☐ 6 kV	☒ 6 kV	☒ 6 kV
	☐ 8 kV	☒ 8 kV	☐ 8 kV	☐ 8 kV
	☐ 15 kV	☐ 15 kV	☐ 15 kV	☐ 15 kV

Notes: HCP: Horizontal coupling plane
VCP: Vertical coupling plane



Required Performance Criteria: ☒ Complied



Location of Discharge:



■ mode 1, mode 2



**Test Data**

■ mode 1

No.	Test Point	Discharge Method	Observations	Remarks
1	HCP Contact	Contact Discharge	Complied	-
2	VCP Contact	Contact Discharge	Complied	-

Direct Discharge

No.	Test Point	Discharge Method	Observations	Remarks
1	Enclosure	Contact Discharge	Complied	-
2	Ports	Air Discharge	Complied	-
3	Screw	Contact Discharge	Complied	-

■ mode 2

No.	Test Point	Discharge Method	Observations	Remarks
1	HCP Contact	Contact Discharge	Complied	-
2	VCP Contact	Contact Discharge	Complied	-

Direct Discharge

No.	Test Point	Discharge Method	Observations	Remarks
1	Enclosure	Contact Discharge	Complied	-
2	Ports	Air Discharge	Complied	-
3	Screw	Contact Discharge	Complied	-

Note: "Blank" = Not performed

Observations:

Complied – No degradation of function

Test Results

- ☒ PASS Required Performance Criteria
☐ NOT PASS Required Performance Criteria

Remarks

- PASS Required Performance Criteria



3.2 Radiated Electric Field Immunity

Reference Standard

EN IEC 61000-4-3

Test Date

Jul. 17, 2025

Test LocationEMS-RS: ☐ SEMI ANECHOIC CHAMBER #2☒ SEMI ANECHOIC CHAMBER #3**Test Equipment**

Used	Description	Model Number	Manufacturer	Serial Number	Cal. Due
☒	EMS Test S/W	EMC32	R & S	10.10.02	-
☒	SIGNAL GENERATOR	SMB 100A	Rohde & Schwarz	108252	07, 29, 2025
☒	HIGH POWER DUAL AMP	SSA532	SUNGSAN	SSA532-001	-
☒	POWER METER	E4419B	Agilent	GB40203000	02, 13, 2026
☒	AVERAGE POWER SENSOR	E9301A	Agilent	MY52170007	02, 13, 2026
☒	AVERAGE POWER SENSOR	E9301A	Agilent	MY41498669	02, 13, 2026
☒	STACKED DOUBLE LOG-PER- ANTENNA	STPL9128 E	Schwarzbeck	9128ES-121	-
☒	DOUBLE RIDGED HORN ANTENNA	SAS-571	A.H.SYSTEM,INC	781	03, 05, 2026

Test Conditions

Temperature: (24,5 ± 0,1) °C
Relative Humidity: (46,0 ± 0,1) % R.H.
Atmospheric Pressure: (100,0 ± 0,1) kPa



Test Specifications

Antenna Polarization: Horizontal & vertical unless indicated otherwise

Antenna Distance: ☒ 3 m

Field Strength: ☐ 1 V/m ☐ 3 V/m
☒ 10 V/m

Frequency Range: ☐ 80 MHz to 1 GHz ☐ 1,4 GHz to 2,7 GHz
☒ 80 MHz to 2,7 GHz

Modulation: ☒ AM, 80 %, 1 kHz sine wave
☒ PM, 1 Hz (0,5 s ON : 0,5 s OFF)

Frequency step: ☒ 1 % step

Dwell Time: ☐ 1 s ☒ 3 s

of Sides Radiated: ☒ 4

Required Performance Criteria: ☒ Complied

**Test Data**

■ mode 1

Side Exposed	Observations	
	Horizontal	Vertical
Front	Complied	Complied
Right	Complied	Complied
Back	Complied	Complied
Left	Complied	Complied

■ mode 2

Side Exposed	Observations	
	Horizontal	Vertical
Front	Complied	Complied
Right	Complied	Complied
Back	Complied	Complied
Left	Complied	Complied

Note: "Blank" = Not performed

Observations:

Complied – No degradation of function

Test Results

- ☒ PASS Required Performance Criteria
☐ NOT PASS Required Performance Criteria

Remarks

PASS Required Performance Criteria



3.3 Electrical Fast Transients/Bursts

Reference Standard

EN 61000-4-4

Test Date

Jul. 18, 2025

Test Location

EMS-EFT: Electro wave Shieldroom #7

Test Equipment

Used	Description	Model Number	Manufacturer	Serial Number	Cal. Due
☒	EMS Test S/W	iec.control	EM TEST	5.4.8	-
☒	ULTRA COMPACT SIMULATOR	UCS 500N7	EM TEST	P1608172950	11, 06, 2025
☒	MOTOR VARIAC	MV2616	EM TEST	P1552169719	11, 07, 2025
☒	CAPACITIVE COUPLING CLAMP	HFK	EM TEST	P1633183115	11, 06, 2025

Test Conditions

Temperature: (23,5 ± 0,1) °C
Relative Humidity: (46,7 ± 0,1) % R.H.
Atmospheric Pressure: (100,3 ± 0,1) kPa

Test Specifications

Pulse Amplitude & Polarity: ☐ ± 1.0 kV ☒ ± 2.0 kV
(AC Power Lines) ☐ ± 4.0 kV

Pulse Amplitude & Polarity: ☐ ± 0.5 kV ☒ ± 1.0 kV
(Other supply / Signal Lines) ☐ ± 2.0 kV

Burst Period: ☒ 300 ms ☐ 2 s

Repetition Rate: ☐ 5 klz ☒ 100 klz

Duration of Test Voltage: ☒ ≥ 1 min

Required Performance Criteria: ☒ Complied

**Test Data**

■ mode 1

☒ Input a.c. power ports – Coupling/Decoupling Network used

Mode of Application	Observations	
	(+) Burst (kV)	(-) Burst (kV)
L	Complied	Complied
N	Complied	Complied
L – N	Complied	Complied

☐ Input d.c. power ports – Coupling/Decoupling Network used

Mode of Application	Observations	
	(+) Burst (kV)	(-) Burst (kV)
-	-	-

☒ Signal ports and telecommunication ports – Coupling Clamp used

Mode of Application	Observations	
	(+) Burst (kV)	(-) Burst (kV)
RJ-45 (LAN)	Complied	Complied
Alarm IN	Complied	Complied
Alarm OUT	Complied	Complied
Controller	Complied	Complied



☒ mode 2

☐ Input a.c. power ports – Coupling/Decoupling Network used

Mode of Application	Observations	
	(+) Burst (kV)	(-) Burst (kV)
-	-	-

☐ Input d.c. power ports – Coupling/Decoupling Network used

Mode of Application	Observations	
	(+) Burst (kV)	(-) Burst (kV)
-	-	-

☒ Signal ports and telecommunication ports – Coupling Clamp used

Mode of Application	Observations	
	(+) Burst (kV)	(-) Burst (kV)
RJ-45 (PoE)	Complied	Complied
Alarm IN	Complied	Complied
Alarm OUT	Complied	Complied
Controller	Complied	Complied

Note: “Blank” = Not performed

Observations:

Complied – No degradation of function

Test Results

☒ PASS Required Performance Criteria

☐ NOT PASS Required Performance Criteria

Remarks

PASS Required Performance Criteria



3.4 Surge Transients

Reference Standard

EN 61000-4-5

Test Date

Jul. 18, 2025

Test Location

EMS-Surge: Electro wave Shieldroom #7

Test Equipment

Used	Description	Model Number	Manufacturer	Serial Number	Cal. Due
☒	EMS Test S/W	iec.control	EM TEST	5.4.8	-
☒	ULTRA COMPACT SIMULATOR	UCS 500N7	EM TEST	P1608172950	11, 07, 2025
☒	MOTOR VARIAC	MV2616	EM TEST	P1552169719	11, 07, 2025

Test Conditions

Temperature: (23.5 ± 0.1) °C
Relative Humidity: (46.7 ± 0.1) % R.H.
Atmospheric Pressure: (100.3 ± 0.1) kPa

**Test Specifications****AC Power Lines**

Source Impedance: 12 ohm for common Mode and 2 ohm for differential Mode

Surge Amplitude :

Common Mode☐ (0,5 / 1,0 / 2,0) kVDifferential Mode☒ (0,5 / 1,0) kV

Number of Surges:

☒ 5 surges per angle

Angle:

☒ 0°, 90°, 180°, 270° (input a.c. power port)

Polarity:

☒ Positive & Negative

Repetition Rate:

☐ 1 surge per min☒ 1 surge per 30 sec.

Required Performance Criteria:

☒ Complied**Other supply / Signal Lines**

Source Impedance:

42 ohm for common Mode

Surge Amplitude:

Common Mode☒ (0,5 / 1,0) kV

Number of Surges:

☒ 5 Surges

Polarity:

☒ Positive & Negative

Repetition Rate:

☒ 1 surge per min☐ 1 surge per 30 sec.

Required Performance Criteria:

☒ Complied

**Test Data**

■ mode 1

☒ Line to Line – Differential Mode

Mode of Application	Observations	
	(+) Surge (kV)	(-) Surge (kV)
L - N	Complied	Complied

☐ Line to Earth – Common Mode

Mode of Application	Observations	
	(+) Surge (kV)	(-) Surge (kV)
-	-	-

Signal Lines☒ Line to Earth – Common Mode

Mode of Application	Coupling Method	Observations	
		(+) Surge (kV)	(-) Surge (kV)
RJ-45 (LAN)	CDN	Complied	Complied
	LINE	Complied	Complied

☒ mode 2☐ Line to Line – Differential Mode

Mode of Application	Observations	
	(+) Surge (kV)	(-) Surge (kV)
-	-	-

☐ Line to Earth – Common Mode

Mode of Application	Observations	
	(+) Surge (kV)	(-) Surge (kV)
-	-	-

Signal Lines☒ Line to Earth – Common Mode

Mode of Application	Coupling Method	Observations	
		(+) Surge (kV)	(-) Surge (kV)
RJ-45 (PoE)	CDN	Complied	Complied
	LINE	Complied	Complied

Note: "Blank" = Not performed

Observations:

Complied – No degradation of function

Test Results☒ PASS Required Performance Criteria☐ NOT PASS Required Performance Criteria**Remarks**PASS Required Performance Criteria



3.5 Conducted Disturbance

Reference Standard

EN 61000-4-6

Test Date

Jul. 16, 2025

Test Location

EMS-CS: Electro wave Shieldroom #7

Test Equipment

Used	Description	Model Number	Manufacturer	Serial Number	Cal. Due
☒	EMS Test S/W	icd.control	EM TEST	8.0.0	-
☒	TEST SYSTEM FOR CONDUCTED AND RADIATED	NSG4070	TESEQ	65585	11, 18, 2025
☒	ATTENUATOR	ATT 6/80	EM TEST	P1614178148	11, 06, 2025
☒	CDN	CDN M016	TESEQ	43694	11, 07, 2025
☒	CDN	CDN M016	TESEQ	43697	11, 07, 2025
☒	CDN	CDN T8RJ45	EM TEST	0909-09	07, 29, 2025
☒	EM CLAMP	KEMZ 801A	TESEQ	44099	11, 08, 2025

Test Conditions

Temperature: (23,1 ± 0,1) °C
Relative Humidity: (46,0 ± 0,1) % R.H.
Atmospheric Pressure: (100,1 ± 0,1) kPa

Test Specifications

Frequency range: ☒ 150 kHz to 100 MHz ☐ 150 kHz to 80 MHz

Voltage Level: ☐ 1 Vrms ☐ 3 Vrms
☒ 10 Vrms

Modulation: ☒ AM, 80 %, 1 kHz sine wave
☒ PM, 1 Hz (0,5 s ON : 0,5 s OFF)

Frequency step: ☒ 1 % step

Dwell Time: ☐ 1 s ☒ 3 s

Required Performance Criteria: ☒ Complied

**Test Data**

■ mode 1

☒ Input a.c. power ports

Coupling Location (Line Stressed)	Coupling Method	Observations
L – N	CDN	Complied

☐ Input d.c. power ports

Coupling Location (Line Stressed)	Coupling Method	Observations
-	-	-

☒ Signal ports and telecommunication ports

Coupling Location (Line Stressed)	Coupling Method	Observations
RJ-45 (LAN)	CDN	Complied
Alarm IN	Clamp	Complied
Alarm OUT	Clamp	Complied
Controler	Clamp	Complied

■ mode 2

☐ Input a.c. power ports

Coupling Location (Line Stressed)	Coupling Method	Observations
-	-	-

☐ Input d.c. power ports

Coupling Location (Line Stressed)	Coupling Method	Observations
-	-	-

☒ Signal ports and telecommunication ports

Coupling Location (Line Stressed)	Coupling Method	Observations
RJ-45 (PoE)	CDN	Complied
Alarm IN	Clamp	Complied
Alarm OUT	Clamp	Complied
Controler	Clamp	Complied

Notes: CDN = Coupling Decoupling Network
"blank" = Not performed

Observations:

Complied – No degradation of function

Test Results☒ PASS Required Performance Criteria☐ NOT PASS Required Performance Criteria**Remarks**

PASS Required Performance Criteria



3.6 Voltage Dips and Short Interruptions

Reference Standard

EN IEC 61000-4-11

Test Date

Jul. 18, 2025

Test Location

EMS-Voltage dip: Electro wave Shieldroom #7

Test Equipment

Used	Description	Model Number	Manufacturer	Serial Number	Cal. Due
☒	EMS Test S/W	iec.control	EM TEST	5.4.8	-
☒	ULTRA COMPACT SIMULATOR	UCS 500N7	EM TEST	P1608172950	11, 07, 2025
☒	MOTOR VARIAC	MV2616	EM TEST	P1552169719	11, 07, 2025

Test Conditions

Temperature: (23,5 ± 0,1) °C
Relative Humidity: (46,7 ± 0,1) % R.H.
Atmospheric Pressure: (100,3 ± 0,1) kPa

**Test Specifications & Observations/Remarks**

■ mode 1

- Voltage Dips and Short Interruptions

<u>Test Level</u>	<u>Duration [in period/ms (50 Hz)]</u>	<u>Results</u>
☒ 20 % dip	☒ 250 / 5 000	<u>Complied</u>
☒ 30 % dip	☒ 25 / 500	<u>Complied</u>
☒ 60 % dip	☒ 10 / 200	<u>Complied</u>
☒ 100 % dip	☒ 250 / 5 000	<u>Complied</u>

- Voltage variations

☒ Unom + 10 %	☒ 253.0 V (ac)	<u>Complied</u>
☒ Unom - 15 %	☒ 195.5 V (ac)	<u>Complied</u>

Observations:

Complied – No degradation of function

Degradation - See "Remarks "

Test Results

- ☒ PASS Required Performance Criteria
☐ NOT PASS Required Performance Criteria
☐ NOT APPLICABLE

RemarksPASS Required Performance CriteriaDuring the test(100%, 250cycle), EUT was turned off but after the test, it was recovered without operator's intervention.N/A : EUT doesn't have any power port and the RJ-45 port is regarded as a wired communication network port.



APPENDIX A – TEST DATA

Conducted Emissions at Mains Power Ports

■ mode 1

[HOT]

Test Description:

Conducted Emission

Job No.:

KES-EM252066

Phase:


L

Mode:

Mode 1

Operator Name:

KES




Final_Result

Frequency (MHz)	QuasiPeak (dB μV)	CAverage (dB μV)	Limit (dB μV)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Line	Corr. (dB)
0.200000	---	36.23	66.00	29.77	1000.0	9.000	L1	19.5
0.200000	47.87	---	79.00	31.13	1000.0	9.000	L1	19.5
0.910000	---	23.08	60.00	36.92	1000.0	9.000	L1	19.6
0.910000	27.72	---	73.00	45.28	1000.0	9.000	L1	19.6
5.120000	---	22.36	60.00	37.64	1000.0	9.000	L1	19.9
5.120000	27.81	---	73.00	45.19	1000.0	9.000	L1	19.9
8.045000	---	24.21	60.00	35.79	1000.0	9.000	L1	20.0
8.045000	29.09	---	73.00	43.91	1000.0	9.000	L1	20.0
12.810000	---	26.62	60.00	33.38	1000.0	9.000	L1	20.2
12.810000	29.94	---	73.00	43.06	1000.0	9.000	L1	20.2



[NEUTRAL]

Test Description: Conducted Emission
Job No.: KES-EM252066
Phase: N
Mode: Mode 1
Operator Name: KES



Final_Result

Frequency (MHz)	QuasiPeak (dBμV)	CAverage (dBμV)	Limit (dBμV)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Line	Corr. (dB)
0.175000	---	39.05	66.00	26.95	1000.0	9.000	N	19.5
0.175000	50.72	---	79.00	28.28	1000.0	9.000	N	19.5
0.185000	---	37.40	66.00	28.60	1000.0	9.000	N	19.5
0.185000	49.65	---	79.00	29.35	1000.0	9.000	N	19.5
4.920000	---	22.93	60.00	37.07	1000.0	9.000	N	19.9
4.920000	28.78	---	73.00	44.22	1000.0	9.000	N	19.9
5.035000	---	23.05	60.00	36.95	1000.0	9.000	N	19.9
5.035000	28.88	---	73.00	44.12	1000.0	9.000	N	19.9
5.535000	---	23.29	60.00	36.71	1000.0	9.000	N	19.9
5.535000	29.10	---	73.00	43.90	1000.0	9.000	N	19.9
12.810000	---	26.59	60.00	33.41	1000.0	9.000	N	20.1
12.810000	29.94	---	73.00	43.06	1000.0	9.000	N	20.1

◆ Calculation

QuasiPeak[dBμV] / CAverage [dBμV] = Reading Value[dBμV] + Corr. [dB]

QuasiPeak / CAverage : The Final Value

Reading Value : Not shown in the table.


Corr. : Correction values (LISN FACTOR + (Cable Loss + Pulse Limiter FACTOR))

**Conducted Emissions at Telecommunication Ports**

■ mode 1

[100 Mbps]

Test Description: Telecommunication Emission
Job No.: KES-EM252066
Mode : Mode 1
Speed : 100 Mbps
Operator Name: KES

**Final_Result**


Frequency (MHz)	QuasiPeak (dBμV)	CAverage (dBμV)	Limit (dBμV)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Line	Corr. (dB)
0.365000	---	31.43	76.61	45.18	1000.0	9.000	Single Line	19.5
0.365000	40.19	---	89.61	49.42	1000.0	9.000	Single Line	19.5
0.420000	---	22.63	75.45	52.82	1000.0	9.000	Single Line	19.5
0.420000	36.57	---	88.45	51.88	1000.0	9.000	Single Line	19.5
5.025000	---	36.72	74.00	37.28	1000.0	9.000	Single Line	19.5
5.025000	41.51	---	87.00	45.49	1000.0	9.000	Single Line	19.5
26.610000	---	54.12	74.00	19.88	1000.0	9.000	Single Line	20.1
26.610000	57.33	---	87.00	29.67	1000.0	9.000	Single Line	20.1
28.685000	---	54.70	74.00	19.30	1000.0	9.000	Single Line	20.2
28.685000	57.68	---	87.00	29.32	1000.0	9.000	Single Line	20.2



■ mode 2

[100 Mbps]

Test Description: Telecommunication Emission
Job No.: KES-EM252066
Mode : Mode 2
Speed : 100 Mbps
Operator Name: KES



Final_Result

Frequency (MHz)	QuasiPeak (dB μ V)	CAverage (dB μ V)	Limit (dB μ V)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Line	Corr. (dB)
0.195000	---	75.49	81.82	6.33	1000.0	9.000	Single Line	19.7
0.195000	75.54	---	94.82	19.28	1000.0	9.000	Single Line	19.7
1.270000	---	48.56	74.00	25.44	1000.0	9.000	Single Line	19.4
1.270000	52.56	---	87.00	34.44	1000.0	9.000	Single Line	19.4
1.470000	---	50.43	74.00	23.57	1000.0	9.000	Single Line	19.4
1.470000	53.80	---	87.00	33.20	1000.0	9.000	Single Line	19.4
26.610000	---	53.79	74.00	20.21	1000.0	9.000	Single Line	20.1
26.610000	56.56	---	87.00	30.44	1000.0	9.000	Single Line	20.1

◆ Calculation

QuasiPeak[dBuV] / CAverage [dBuV] = Reading Value[dBuV] + Corr. [dB]


QuasiPeak / CAverage : The Final Value

Reading Value : Not shown in the table.

Corr. : Correction values (ISN FACTOR + (Cable Loss + Pulse Limiter FACTOR))

**Radiated Electric Field Emissions(Below 1 GHz)**


■ mode 1

**Final Result**

No.	Frequency [MHz]	(P)	Reading QP [dB(uV)]	c.f [dB(1/m)]	Result QP [dB(uV/m)]	Limit QP [dB(uV/m)]	Margin QP [dB]	Height [cm]	Angle [deg]	Remark
1	42.974	V	48.3	-21.5	26.8	40.0	13.2	197.0	271.0	
2	96.203	V	54.5	-25.5	29.0	40.0	11.0	225.0	93.0	
3	184.958	V	50.5	-21.2	29.3	40.0	10.7	199.0	345.0	
4	232.730	H	43.1	-20.5	22.6	47.0	24.4	279.0	292.0	
5	701.968	H	38.6	-4.9	33.7	47.0	13.3	392.0	357.0	
6	969.566	V	35.7	-0.3	35.4	47.0	11.6	159.0	203.0	



■ mode 2



Final Result

No.	Frequency [MHz]	(P)	Reading QP [dB(μV)]	c.f [dB(1/m)]	Result QP [dB(μV/m)]	Limit QP [dB(μV/m)]	Margin QP [dB]	Height [cm]	Angle [deg]	Remark
1	40.670	V	54.7	-21.8	32.9	40.0	7.1	169.0	354.0	
2	87.958	V	54.7	-26.2	28.5	40.0	11.5	299.0	81.0	
3	191.505	V	51.4	-21.7	29.7	40.0	10.3	156.0	336.0	
4	249.948	V	46.2	-19.4	26.8	47.0	20.2	190.0	355.0	
5	602.058	V	35.2	-7.0	28.2	47.0	18.8	209.0	37.0	
6	701.968	H	39.9	-4.9	35.0	47.0	12.0	395.0	155.0	

◆ Calculation

Result(QP) [dB(μV/m)] = (Reading(QP)[dB(μV)] + c.f[dB(1/m)])


Margin(QP)[dB] = Limit[dB(μV/m)] - Result(QP) [dB(μV/m)]

Reading(QP) : Reading value, Result(QP) : Reading value + Factor value

Limit(QP) : Limit value, c.f : (ANT Factor + Cable Loss - Preamp Factor), Margin: Margin value

**Radiated Electric Field Emissions(Above 1 GHz)**


■ mode 1

**Final Result**

No.	Frequency	Pol	Reading	Reading	c.f	Result	Result	Limit	Limit	Margin	Margin	Height	Angle	Remark
	[MHz]		AV	PK		AV	PK	AV	PK	[dB]	[dB]	[cm]	[deg]	
1	1515.211	V	29.9	44.5	1.2	31.1	45.7	56.0	76.0	24.9	30.3	100.0	133.3	
2	2452.370	V	29.2	45.0	4.8	34.0	49.8	56.0	76.0	22.0	26.2	100.0	278.6	
3	2715.367	H	28.3	44.2	5.6	33.9	49.8	56.0	76.0	22.1	26.2	100.0	13.8	
4	4705.487	V	28.1	42.6	11.5	39.6	54.1	60.0	80.0	20.4	25.9	100.0	189.5	
5	5052.213	H	25.5	39.8	12.7	38.2	52.5	60.0	80.0	21.8	27.5	100.0	4.0	
6	5704.459	H	27.2	41.0	13.9	41.1	54.9	60.0	80.0	18.9	25.1	100.0	26.5	



■ mode 2



◆ Calculation

$$\text{Result(PK/CAV)} [\text{dB}(\mu\text{V/m})] = (\text{Reading(PK/CAV)} [\text{dB}(\mu\text{V})] + \text{c.f} [\text{dB}(1/\text{m})])$$
$$\text{Margin(PK/CAV)} [\text{dB}] = \text{Limit} [\text{dB}(\mu\text{V/m})] - \text{Result(PK/CAV)} [\text{dB}(\mu\text{V/m})]$$

Reading(PK/CAV) : Reading value, Result(PK/CAV) : Reading value + Factor value

Limit(PK/CAV) : Limit value, c.f : (ANT Factor + Cable Loss - Preamp Factor), Margin: Margin value

**Harmonic Current Emissions and Voltage Fluctuations and Flicker**

■ mode 1

Average harmonic current results

Hn	I _{eff} [A]	% of Limit	Limit [A]	Result
1	0.051			
2	0.002	0.228	1.080	n/a
3	0.045	1.938	2.300	PASS
4	0.003	0.708	0.430	n/a
5	0.045	3.966	1.140	PASS
6	0.003	1.000	0.300	n/a
7	0.044	5.679	0.770	PASS
8	0.003	1.246	0.230	n/a
9	0.040	10.079	0.400	PASS
10	0.003	1.559	0.184	n/a
11	0.038	11.515	0.330	PASS
12	0.003	1.813	0.153	n/a
13	0.035	16.803	0.210	PASS
14	0.003	2.091	0.131	n/a
15	0.032	21.244	0.150	PASS
16	0.003	2.271	0.115	n/a
17	0.029	21.712	0.132	PASS
18	0.003	2.490	0.102	n/a
19	0.026	21.581	0.118	PASS
20	0.002	2.683	0.092	n/a
21	0.022	13.923	0.161	PASS
22	0.002	2.892	0.084	n/a
23	0.019	12.988	0.147	PASS
24	0.002	3.076	0.077	n/a
25	0.016	11.891	0.135	PASS
26	0.002	3.214	0.071	n/a
27	0.014	10.966	0.125	PASS
28	0.002	3.377	0.066	n/a
29	0.011	9.481	0.116	PASS
30	0.002	3.497	0.061	n/a
31	0.009	8.399	0.109	PASS
32	0.002	3.639	0.058	n/a
33	0.008	7.527	0.102	PASS
34	0.002	3.663	0.054	n/a
35	0.007	6.984	0.096	PASS
36	0.002	3.746	0.051	n/a
37	0.006	6.895	0.091	PASS
38	0.002	3.831	0.048	n/a
39	0.006	6.619	0.087	PASS
40	0.002	3.748	0.046	n/a

NONE: Current limits are disabled because rated power is less than 75W. (Active input Power: 28.772 W)

* Application of limits for average is 100% except for odd harmonics from 21 to 39, where 150% applies.



Test Data - Harmonics (continued)

Maximum harmonic current results

Hn	I _{eff} [A]	% of Limit	Limit [A]	Result
1	0.053			
2	0.003	0.200	1.620	n/a
3	0.047	1.366	3.450	PASS
4	0.004	0.628	0.645	n/a
5	0.048	2.790	1.710	PASS
6	0.004	0.865	0.450	n/a
7	0.046	3.986	1.155	PASS
8	0.004	1.118	0.345	n/a
9	0.042	7.064	0.600	PASS
10	0.004	1.372	0.276	n/a
11	0.040	8.053	0.495	PASS
12	0.004	1.583	0.230	n/a
13	0.037	11.711	0.315	PASS
14	0.004	1.840	0.197	n/a
15	0.033	14.767	0.225	PASS
16	0.003	1.993	0.173	n/a
17	0.030	15.004	0.199	PASS
18	0.003	2.174	0.153	n/a
19	0.026	14.861	0.178	PASS
20	0.003	2.343	0.138	n/a
21	0.023	14.342	0.161	PASS
22	0.003	2.486	0.125	n/a
23	0.019	13.280	0.147	PASS
24	0.003	2.645	0.115	n/a
25	0.016	12.167	0.135	PASS
26	0.003	2.812	0.106	n/a
27	0.014	11.153	0.125	PASS
28	0.003	2.920	0.099	n/a
29	0.011	9.683	0.116	PASS
30	0.003	3.040	0.092	n/a
31	0.009	8.631	0.109	PASS
32	0.003	3.079	0.086	n/a
33	0.008	7.765	0.102	PASS
34	0.003	3.163	0.081	n/a
35	0.007	7.428	0.096	PASS
36	0.003	3.278	0.077	n/a
37	0.007	7.469	0.091	PASS
38	0.002	3.246	0.073	n/a
39	0.006	7.292	0.087	PASS
40	0.002	3.170	0.069	n/a

NONE: Current limits are disabled because rated power is less than 75W.(Active input Power: 28.772 W)

* Application of limits for average is 100% except for odd harmonics from 21 to 39, where 150% applies.



Report No. : KES-EM252066

Page 47 / 68

Test Data - Voltage Fluctuations

■ mode 1

Maximum Flicker results

Flicker Measurements					
	Plt	Max Pst	Max Dc	Max Dmax	Max Tmax
Line 1:	0.028	0.028	0	< 0.2	0
Limits:	0.65	1	3.3	4	0.5
Results:	PASS	PASS	PASS	PASS	PASS





Test Setup Photos and Configuration

Conducted Emissions at Mains Power Ports


■ mode 1






Conducted Emissions at Telecommunication Ports

■ mode 1







■ mode 2







Radiated Electric Field Emissions(Below 1 GHz)

■ mode 1







■ mode 2






Radiated Electric Field Emissions(Above 1 GHz)

■ mode 1





■ mode 2





Harmonic Current Emissions and Voltage Fluctuations and Flicker

■ mode 1






Report No. : KES-EM252066

Page 56 / 68

Electrostatic Discharge

■ mode 1



■ mode 2



KES-QP16-F01(00-23-01-01)


KES Co., Ltd.

The authenticity of this test report can be found on the verification page of our website (www.kes.co.kr).




Radiated Electric Field Immunity

■ mode 1



■ mode 2





Electrical Fast Transients/Bursts

■ mode 1




■ mode 2





Surge Transients

■ mode 1



■ mode 2





Conducted Disturbance

■ mode 1



■ mode 2





Voltage Dips and Short Interruptions

■ mode 1





EUT External Photographs

(Top)




(Bottom)





EUT Internal Photographs


(Internal View)






EUT Internal View – Board 1

(Top)




(Bottom)






EUT Internal View – Board 2

(Top)




(Bottom)






EUT Internal View – Board 3

(Top)



(Bottom)





EUT Internal View – Speaker

(Top)



(Bottom)





Label and Location



<u>NETWORK CAMERA</u> Model No : XNB-A8004 Manufacturer : HANWHA VISION VIETNAM COMPANY LIMITED Made in Vietnam	UK CA CE
--	--

The End.