



Network

Dome

# XND-8081REV

5MP IR PoE Extender Dome Camera



## Key Features

- Max. 5MP resolution
- PoE Extender (Main cam, extension cam)
- PoE out :Max. 12.95W@80m
- 3.9~9.4mm(2.4x) motorized varifocal
- 0.07Lux@F1.3 (Color), 0Lux (B/W, IR LED on)
- IR viewable length 50m
- Day & Night (ICR), WDR (120dB)
- Hallway View, WiseStreamII Support
- Video & audio analytics, Audio playback
- Business Intelligence(People counting, Queue management, Heatmap)
- DIS and shock detection with built-in gyro sensor
- Modular structure, PoE+ in/PoE out
- IP52, IK10

## Compatible Devices



SBP-300LMW



SBP-300WMW1



SBP-300KMW



SBP-300BW



SBP-300PMW



SBP-300WMW



SPB-IND85W



SBC-160B



SBP-300NBW



SBP-300CMW



SBP-167HMW

## XND-8081REV

5MP IR PoE Extender Dome Camera



### Specifications

| Video                         |                       |                                                                                                                                                    |
|-------------------------------|-----------------------|----------------------------------------------------------------------------------------------------------------------------------------------------|
| Imaging Device                | Size                  | 1/1.8"                                                                                                                                             |
|                               | Type                  | CMOS                                                                                                                                               |
| Resolution                    |                       | 2560x1920, 2560x1440, 1920x1080, 1600x1200, 1280x1024, 1280x960, 1280x720, 1024x768, 800x600, 800x448, 720x576, 720x480, 640x640, 640x360, 320x240 |
| Max. Framerate                | H.265/H.264           | 30fps/25fps(60Hz/50Hz)                                                                                                                             |
|                               | MJPEG                 | 30fps                                                                                                                                              |
| Min. Illumination (Lux)       | Color(1/30sec, 30IRE) | 0.07                                                                                                                                               |
|                               | BW(1/30sec, 30IRE)    | 0.007                                                                                                                                              |
| Video Out                     |                       | CVBS: 1.0 Vp-p / 75Ω composite for installation,<br>USB: Micro USB Type B. Preview and installation ONLY. Requires WiFi dongle.                    |
| Lens                          |                       |                                                                                                                                                    |
| Focal Length (mm)             |                       | 3.9~9.4                                                                                                                                            |
| Zoom Ratio                    | Optical               | 2.4x                                                                                                                                               |
| Max Aperture Ratio (F number) | Wide                  | 1.3                                                                                                                                                |
| Angular Field of View         | Horizontal            | 92.1°~38.7°                                                                                                                                        |
|                               | Vertical              | 67.2°~29.0°                                                                                                                                        |
|                               | Diagonal              | 119.9°~48.6°                                                                                                                                       |
| Min. Object Distance          |                       | 0.5m(1.64ft)                                                                                                                                       |
| Focus Control                 |                       | Simple focus                                                                                                                                       |
| Lens Type                     |                       | DC auto iris, P iris(IR corrected)                                                                                                                 |
| Pan / Tilt / Rotate           |                       |                                                                                                                                                    |
| Pan / Tilt / Rotate Range     | Pan                   | 0°~360°                                                                                                                                            |
|                               | Tilt                  | -45°~85°                                                                                                                                           |
|                               | Rotate                | 0°~355°                                                                                                                                            |
| Operational                   |                       |                                                                                                                                                    |
| Day & Night                   |                       | Auto(ICR)                                                                                                                                          |
| Backlight Compensation        |                       | BLC, HLC, WDR, SSDR                                                                                                                                |

## Operational

|                                          |                |                                                                                                                                     |
|------------------------------------------|----------------|-------------------------------------------------------------------------------------------------------------------------------------|
| Wide Dynamic Range (dB)                  |                | 120                                                                                                                                 |
| Digital Noise Reduction                  |                | SSNR V                                                                                                                              |
| Digital Image Stabilization              |                | Support(built-in gyro sensor)                                                                                                       |
| Defog                                    |                | Support                                                                                                                             |
| Motion Detection                         | Quantity       | 8ea                                                                                                                                 |
|                                          | Shape          | 8point Polygonal zones                                                                                                              |
| Privacy Masking                          | Quantity       | 32ea                                                                                                                                |
|                                          | Shape          | Rectangular zones                                                                                                                   |
|                                          | Color / Option | Gray, Green, Red, Blue, Black, White, Mosaic                                                                                        |
| Gain Control                             |                | Low, Middle, High                                                                                                                   |
| White Balance                            |                | ATW, AWC, Manual, Indoor, Outdoor                                                                                                   |
| LDC                                      |                | Support                                                                                                                             |
| Electronic Shutter                       | Mode           | Minimum, Maximum, Anti flicker                                                                                                      |
|                                          | Speed Range    | 2~1/12,000sec                                                                                                                       |
| Video Rotation                           |                | Flip, Mirror, Hallway view(90°/270°)                                                                                                |
| Alarm Interface                          | In/Out         | Input 1ea, Output 1ea                                                                                                               |
| Alarm Triggers                           |                | Analytics, Network disconnect, Alarm input                                                                                          |
| Alarm Events When Alarm Trigger Occurred |                | File upload(image): e-mail/FTP,<br>Notification: e-mail,<br>Recording: SD/SDHC/SDXC or NAS recording at event triggers,Alarm output |
| Audio In                                 |                | Selectable(mic in/line in)                                                                                                          |
| Audio Out                                |                | Line out                                                                                                                            |
| Light Type                               |                | IR LED                                                                                                                              |
| Light Viewable Length                    | IR             | 50m(164.04ft)                                                                                                                       |
| IR Wavelength                            |                | 850nm                                                                                                                               |

## Analytics

|                       |        |                                                                                                                                                                                                                                                  |
|-----------------------|--------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Analytics Events      | Normal | Defocus detection, Motion detection, Tampering, Fog detection, Face detection, Audio detection, Sound classification, Virtual area(Lotering, Intrusion, Enter/Exit, Appear/Disappear), Virtual line(Crossing, Direction) , Digital auto tracking |
| Business Intelligence | Normal | People counting, Queue management, Heatmap                                                                                                                                                                                                       |

## Network

|                   |                                                                                                                               |
|-------------------|-------------------------------------------------------------------------------------------------------------------------------|
| Ethernet          | Metal shielded RJ-45(10/100BASE-T)                                                                                            |
| Video Compression | H.265/H.264: Main/Baseline/High, MJPEG                                                                                        |
| Audio Compression | G.711 u-law /G.726 selectable,G.726(ADPCM) 8kHz,G.711 8kHz,<br>G.726: 16kbps,24kbps,32kbps,40kbps,<br>AAC-LC: 48kbps at 16kHz |
| Smart Codec       | Manual, WiseStream II                                                                                                         |

## Network

|                                   |                    |                                                                                                                                                                                                              |
|-----------------------------------|--------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Bitrate Control                   |                    | H.265/H.264: CBR or VBR,<br>MJPEG: VBR                                                                                                                                                                       |
| Streaming                         | Unicast            | Up to 20 users                                                                                                                                                                                               |
|                                   | Multicast          | Support                                                                                                                                                                                                      |
|                                   | Multiple Streaming | Up to 10 profiles                                                                                                                                                                                            |
| Protocol                          |                    | IPv4, IPv6, TCP/IP, UDP/IP, RTP(UDP), RTP(TCP), RTCP, RTSP, NTP, HTTP, HTTPS, SSL/TLS, DHCP, FTP, SMTP, ICMP, IGMP, SNMPv1/v2c/v3(MIB-2), ARP, DNS, DDNS, QoS, UPnP, Bonjour, SRTP(TCP, UDP Unicast), PIM-SM |
| Application Programming Interface | ONVIF              | S, G, T                                                                                                                                                                                                      |
|                                   | Others             | SUNAPI(HTTP API), Hanwha Vision Open Platform                                                                                                                                                                |

## Security

|                        |                                           |
|------------------------|-------------------------------------------|
| User authentication    | Digest authentication                     |
| Network authentication | IEEE 802.1X(EAP-TLS, EAP-LEAP)            |
| Secure Communication   | HTTPS                                     |
| Access Control         | IP-based access control                   |
| Audit                  | Access / System / Event Log management    |
| Device ID              | Device certificate(Hanwha Vision Root CA) |

## General

|              |                    |                                 |
|--------------|--------------------|---------------------------------|
| Memory       | RAM                | 1GB                             |
|              | Flash              | 256MB                           |
| Edge Storage | Micro SD/SDHC/SDXC | Max. 256GB x 2slot(Total 512GB) |

## Environmental & Electrical

|                     |             |                                                                |
|---------------------|-------------|----------------------------------------------------------------|
| Operating Condition | Temperature | -25°C~+60°C(-13°F~+140°F)                                      |
|                     | Humidity    | 0~90% RH(non-condensing)                                       |
| Storage Condition   | Temperature | -50°C~+60°C(-58°F~+140°F)                                      |
|                     | Humidity    | 0~90% RH(non-condensing)                                       |
| Input Voltage       |             | PoE(IEEE802.3af, Class3)                                       |
| Power Consumption   | PoE         | Max 25.5 W (Main CAM + Extension CAM) Typical 10.2W (Main CAM) |

## Mechanical

|                    |                        |
|--------------------|------------------------|
| Color              | White                  |
| Material           | Aluminum               |
| RAL Code           | RAL9003                |
| Product Dimensions | Ø160x125mm(6.30x4.92") |
| Product Weight     | 1.45kg(3.20 lb)        |

## Certifications & Standards

|             |                                |
|-------------|--------------------------------|
| Environment | IEC 60529 IP52, IEC 62262 IK10 |
|-------------|--------------------------------|

**DORI (EN62676-4 standard)**

|                           |      |                 |
|---------------------------|------|-----------------|
| Detect (25PPM/ 8PPF)      | Wide | 49.4m(162.07ft) |
|                           | Tele | 146m(479.00ft)  |
| Observe (63PPM/ 19PPF)    | Wide | 19.7m(64.63ft)  |
|                           | Tele | 58m(190.29ft)   |
| Recognize (125PPM/ 38PPF) | Wide | 9.9m(32.48ft)   |
|                           | Tele | 29m(95.14ft)    |
| Identify (250PPM/ 76PPF)  | Wide | 4.9m(16.08ft)   |
|                           | Tele | 15m(49.21ft)    |

XND-8081REV  
5MP IR PoE Extender Dome Camera



CAD

Unit: mm [inch]

