



Network

Fisheye

XNF-8010RW

X series 6 MP sensor 360° Indoor IR Fisheye (branco)

Key Features

- Resolução de 2048 x 2048, 30fps
- Codec H.265, H.264, MJPEG suportado
- Modo de visualização variável (Fisheye, Panorama único, Panorama duplo, Visualização quádrupla)
- Desempenho dewarping a bordo, PTZ digital (8x), Áudio bidirecional
- True WDR (120dB), suporte WiseStream II
- Detecção de adulteração, Loitering, Detecção direcional, Detecção de áudio, Classificação de som, Heatmap, Contagem de pessoas, Gestão de filas
- Detecção de movimento, Handover
- Slots de memória dupla SD / SDHC / SDXC (Capacidade máxima total de 512GB), 12V DC / PoE
- Comprimento visível de IR 15m (49,21ft)

XNF-8010RW

X series 6 MP sensor 360° Indoor IR Fisheye (branco)



Specifications

Video		
Imaging Device	Size	1/1.8"
	Type	CMOS
Resolution		2048x2048, 2048x1536, 2048x1024, 2048x512, 1920x960, 1920x480, 1600x1200, 1280x1280, 1280x960, 1280x640, 1280x320, 1080x1080, 1024x768, 960x960, 800x600, 768x768, 720x720, 704x576, 704x352, 704x176, 640x640, 640x480, 640x160, 480x480
Max. Framerate	H.265/H.264	30fps
	MJPEG	15fps
Min. Illumination (Lux)	Color(1/30sec, 30IRE)	0.1
	BW(1/30sec, 30IRE)	0.01
Video Out		CVBS: 1.0 Vp-p / 75Ω composite for installation, USB: Micro USB Type B. Preview and installation ONLY. Requires WiFi dongle.
Lens		
Focal Length (mm)		1.6
Max Aperture Ratio (F number)	Wide	1.6
Angular Field of View	Horizontal	192°
	Vertical	192°
	Diagonal	192°
Min. Object Distance		0.3m (0.98ft)
Focus Control		Simple focus, Manual
Lens Type		Fixed iris
Operational		
Day & Night		Auto(ICR)
Backlight Compensation		BLC, HLC, WDR
Wide Dynamic Range (dB)		120
Digital Noise Reduction		SSNR V
Digital Image Stabilization		Support
Defog		Support

Operational

Motion Detection	Quantity	8ea
	Shape	8point Polygonal zones
Privacy Masking	Quantity	32ea
	Shape	Polygonal zones
	Color / Option	Gray, Green, Red, Blue, Black, White, Mosaic
Gain Control		Low, Middle, High, Off
White Balance		ATW, AWC, Manual, Indoor, Outdoor
Electronic Shutter	Mode	Minimum, Maximum, Anti flicker
	Speed Range	2~1/12,000sec
Digital PTZ		Support
Video Rotation		Flip, Mirror
Alarm Interface	In/Out	Input 1ea, Output 1ea
Alarm Triggers		Analytics, Network disconnect, Alarm input
Alarm Events When Alarm Trigger Occurred		File upload(image): e-mail/FTP, Notification: e-mail, Recording: SD/SDHC/SDXC or NAS recording at event triggers, Alarm output
Audio In		Selectable(mic in/line in), Built-in mic
Audio Out		Line out
Light Type		IR LED
Light Viewable Length	IR	15m(49.21ft)

Analytics

Analytics Events	Normal	Tampering, Audio detection, Sound classification, Virtual area(Lotering, Intrusion, Enter/Exit, Appear/Disappear), Virtual line(Crossing, Direction)
Business Intelligence	Normal	People counting, Queue management, Heatmap

Network

Ethernet		RJ-45(10/100BASE-T)
Video Compression		H.265/H.264: Main/Baseline/High, MJPEG
Audio Compression		G.711 u-law /G.726 selectable,G.726(ADPCM) 8kHz,G.711 8kHz, G.726: 16kbps,24kbps,32kbps,40kbps, AAC-LC: 48kbps at 16kHz
Smart Codec		Manual, WiseStream II
Bitrate Control		H.265/H.264: CBR or VBR, MJPEG: VBR
Streaming	Unicast	Up to 20 users
	Multicast	Support
	Multiple Streaming	Up to 10 profiles

Network

Protocol		IPv4, IPv6, TCP/IP, UDP/IP, RTP(UDP), RTP(TCP), RTCP, RTSP, NTP, HTTP, HTTPS, SSL/TLS, DHCP, FTP, SMTP, ICMP, IGMP, SNMPv1/v2c/v3(MIB-2), ARP, DNS, DDNS, QoS, UPnP, Bonjour, SRTP(TCP, UDP Unicast), PPPoE, SIP 2.0(RFC 3261 and companion RFCs), PIM-SM
Application Programming Interface	ONVIF	S, G
	Others	SUNAPI(HTTP API), Hanwha Vision Open Platform
Direct Cloud Connection		Optional (needs gateway)

Security

User authentication	Digest authentication
Network authentication	IEEE 802.1X(EAP-TLS, EAP-LEAP)
Secure Communication	HTTPS
Access Control	IP-based access control
Data Protect	Encryption credentials
Audit	Access / System / Event Log management

General

Edge Storage	Micro SD/SDHC/SDXC	Max. 256GB x 2slot(Total 512GB)
--------------	--------------------	---------------------------------

Environmental & Electrical

Operating Condition	Temperature	-10°C~+55°C(+14°F~+131°F)
	Humidity	0~90% RH(non-condensing)
Storage Condition	Temperature	-50°C~+60°C(-58°F~+140°F)
	Humidity	0~90% RH(non-condensing)
Input Voltage		PoE(IEEE802.3af, Class3), 12VDC
Power Consumption	PoE	Max. 12W
	12VDC	Max. 11W

Mechanical

Color	White
Material	Aluminum
RAL Code	RAL9003
Product Dimensions	Ø146 x 54.8mm (Ø5.75" x 2.16")
Product Weight	730g (1.61 lb)