



TEST REPORT



Report No. : KES-EM253473

Page 1 / 70

KES Co., Ltd.

#3002, #3503, #3701, 40, Simin-daero365beon-gil, Dongan-gu, Anyang-si, Gyeonggi-do, 14057, Republic of Korea
Tel : +82-31-425-6200, Fax : +82-31-341-3838

1. Client

Applicant : Hanwha Vision Co., Ltd
Applicant Address : 6, Pangyo-ro 319Beon-gil, Bundang-gu, Seongnam-si, Gyeonggi-do, Republic of Korea

2. Sample Description

Product name : NETWORK CAMERA
Model/Type No. : XNF-A9014RV
Variant Model : XNF-A8014RV
Manufacturer : 1. HANWHA VISION VIETNAM COMPANY LIMITED
2. D-TECH CO.,LTD.
Manufacturer Address : 1. Lot O-2, Que Vo Industrial Zone extended Area, Nam Son Ward, Bac Ninh Province, Vietnam
2. 173-25, Saneop-ro, Gwonseon-gu, Suwon-si, Gyeonggi-do, Korea (Suwon Industrial Complex)

3. Date of Receipt : Sep. 30, 2025

4. Test date : Oct. 03, 2025 ~ Oct. 05, 2025

5. Date of Issue : Nov. 14, 2025

6. Test Results : In Compliance

Tested by

Reviewed by

Seong Min, Jang
EMC Test Engineer

Dong Hun, Jang
EMC Technical Manager

This test report is not related to KS Q ISO/IEC 17025 and KOLAS.

KES-QP16-F01(00-23-01-01)

KES Co., Ltd.

The authenticity of this test report can be found on the verification page of our website (www.kes.co.kr).

**REPORT REVISION HISTORY**

Date	Test Report No.	Revision History
Nov. 14, 2025	KES-EM253473	Issued

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd. This document may be altered or revised by KES Co., Ltd. personnel only, and shall be noted in the revision section of the document. Any alteration of this document not carried out by KES Co., Ltd. will constitute fraud and shall nullify the document.



TABLE OF CONTENTS

1.0 General Product Description	4
1.1 Test Voltage & Frequency	7
1.2 Variant Model Differences	7
1.3 Device Modifications	7
1.4 Equipment Under Test	7
1.5 System Configuration	7
1.6 Support Equipments	7
1.7 External I/O Cabling	8
1.8 EUT Operating Mode(s)	9
1.9 Configuration	10
1.10 Remarks When Standards Applied	11
1.11 Calibration Details of Equipment Used for Measurement	11
1.12 Test Facility	11
1.13 Laboratory Accreditations and Listings	11
2.0 Test Regulations	12
2.1 Conducted Emissions at Mains Power Ports	13
2.2 Conducted Emissions at Telecommunication Ports	14
2.3 Radiated Electric Field Emissions(Below 1 GHz)	15
2.4 Radiated Electric Field Emissions(Above 1 GHz)	16
2.5 Harmonic Current Emissions	17
2.6 Voltage Fluctuations and Flicker	18
3.0 Criteria for Compliance	19
3.1 Electrostatic Discharge	20
3.2 Radio-frequency Electromagnetic Field	24
3.3 Fast Transients	27
3.4 Surges	30
3.5 Conducted Disturbance	34
3.6 Power Frequency Magnetic Field Immunity	37
APPENDIX A – TEST DATA	40
Conducted Emissions at Mains Power Ports	40
Conducted Emissions at Telecommunication Ports	42
Radiated Electric Field Emissions(Below 1 GHz)	44
Radiated Electric Field Emissions(Above 1 GHz)	46
Harmonic Current Emissions and Voltage Fluctuations and Flicker	48
Test Setup Photos and Configuration	51
Conducted Emissions at Mains Power Ports	51
Conducted Emissions at Telecommunication Ports	52
Radiated Electric Field Emissions(Below 1 GHz)	54
Radiated Electric Field Emissions(Above 1 GHz)	56
Harmonic Current Emissions and Voltage Fluctuations and Flicker	58
Electrostatic Discharge	59
Radio-frequency Electromagnetic Field	60
Fast Transients	61
Surges	62
Conducted Disturbance	63
Power Frequency Magnetic Field Immunity	64
EUT External Photographs	68
EUT Internal Photographs	69



1.0 General Product Description

Main Specifications of EUT are:

	XNF-A9014RV
Video	
Imaging Device	1/1.6" CMOS
Resolution	Original view: 3536x3536, 3008x3008, 2560x2560, 1600x1600, 1280x1280, 800x800, 640x640, 480x480, 160x160 Double panorama: 3584x1792, 2560x1280, 1920x960, 1280x640, 1024x512, 640x320 Single panorama: 3584x896, 2560x640, 1920x480, 1280x320, 1024x256, 640x160 Quad view: 3584x2688, 2560x1920, 1792x1344, 1280x960, 1024x768, 800x600, 640x480 Q1/Q2/Q3/Q4: 1792x1344, 1280x960, 1024x768, 800x600, 640x480, 320x240
Max. Framerate	Original view: Max.30fps@3536x3536 Double panorama: Max.30fps@3584x1792 Single panorama: Max.30fps@3584x896 Quad view: Max.30fps@3584x2688 Q1/Q2/Q3/Q4(4:3): Max.30fps@1792x1344 MJPEG: Max.5fps
NETD	None
Pixel Size	None
Min. Illumination	Color: 0.02Lux (F1.8, 1/30sec) (TBD) BW: 0.001Lux (F1.8, 1/30sec) (TBD)
Video Out	None
Video Transmission Distance	None
Lens	
Focal Length (Zoom Ratio)	1.76mm fixed focal
Optical Zoom	None
Max. Aperture Ratio	F1.8
Angular Field of View	H: 185° / V: 185° / D: 185°
Min. Object Distance	0.5m(1.64ft)
Focus Control	None
Lens Type	None
Mount Type	None
Optional Lens	None
Pan / Tilt / Rotate	
Pan / Tilt / Rotate	Digital Rotation
Operational	
Camera Title	Displayed up to 85 characters
Direction Indicator	None
Day & Night	Auto(ICR)
Backlight Compensation	BLC, HLC, WDR, SDR
Wide Dynamic Range	120dB
Digital Noise Reduction	SSNR V, WiseNR II (Based on AI engine/AI-ISP)
Digital Image Stabilization	Support
Defog	Support
Motion Detection	8ea, 8point polygonal zones
Privacy Masking	32ea, 8point polygonal zones - Color: gray/green/red/blue/black/white - Mosaic
Gain Control	Off / Max Gain / Manual
White Balance	ATW / NarrowATW / AWC / Manual / Indoor / Outdoor
LDC	None
Electronic Shutter Speed	Minimum / Maximum / Anti flicker(2~1/30,000sec) Prefer shutter control(Based on AI engine)
Digital PTZ	Support
Video Rotation	Flip, mirror



Analytics	Classified object type: Person/Vehicle Attributes: Person(Upper/lower clothes color), Vehicle(Color) Support BestShot Analytics events based on AI engine - Motion detection, Object detection, Virtual line(Crossing/Direction), Virtual area(Loitering/Intrusion/Enter/Exit/Appear/Disappear), Sound classification(To be released) Analytics events - Defocus detection, Tampering, Shock detection, Audio detection
Business Intelligence	Based on AI engine: People/Vehicle/Crowd counting, Queue management, Heatmap
Serial Interface	None
Alarm I/O	2 configurable I/O ports *Support extra alarm I/O via optional I/O box
Alarm Triggers	Analytics, Network disconnection, Alarm input, App event, Time schedule, MQTT subscription, Day/Night change, SD/NAS disruption, Case open tempering
Alarm Events	When alarm trigger occurred - File upload(image): e-mail/FTP/SFTP - File upload(video clip): FTP/SFTP - Notification: e-mail - Recording: SD/SDHC/SDXC or NAS recording at event triggers - Alarm output - Handover: PTZ preset, send message by HTTP/HTTPS/TCP - Audio clip playback(WAV, MP3) - MQTT: publication - SIP(TBD)
Audio Streaming	None
Audio In	Selectable(mic in/line in). Built-in 3 mic with noise reduction
Audio Out	Line out
Light Type	IR LED
Light Viewable Length	WiseIR up to 15m(49.21ft)
IR Viewable Length	None
IR Illuminator (Optional)	None
IR Radiation angle	None
IR LED	None
IR Wavelength	850nm
IR Operation	None
Water Removal	None
Auto Tracking	None
Coaxial Protocol	None
Color Palettes	None
Network	
Ethernet	Metal shielded RJ-45(10/100BASE-T)
Video Compression	H.265/H.264: Main/Baseline/High MJPEG
Audio Compression	G.711(PCM): 8kHz(64Kbps) G.726(ADPCM): 8kHz(16/24/32/40Kbps) AAC-LC: 16/32/44.1/48kHz(48Kbps) OPUS: 8/16/48kHz
Smart Codec	WiseStream(Based on AI engine)
Video Quality Adjustment	None
Bitrate Control	H.264/H.265: CBR or VBR MJPEG: VBR
Streaming	Unicast(20 users) / Multicast Multiple streaming (Up to 5 profiles)
Protocol	IPv4, IPv6, TCP/IP, UDP/IP, RTP(UDP), RTP(TCP), RTCP, RTSP, NTP, HTTP, HTTPS, SSL/TLS, DHCP, FTP/SFTP, SMTP(StartTLS), ICMP, IGMP, SNMPv1/v2c/v3(MIB-2), ARP, DNS, DDNS, QoS, UPnP, Bonjour, LLDP, SRTP(TCP, UDP Unicast), CDP, MQTT, Syslog, SIP(TBD)
SIP support (VoIP, Peer-to-peer)	Support(TBD)

KES-QP16-FU1(00-23-01-01)

KES Co., Ltd.

The authenticity of this test report can be found on the verification page of our website (www.kes.co.kr).



Security	None
Application Programming Interface	ONVIF Profile S/G/T/M SUNAPI(HTTP API) Hanwha Vision Open Platform - WiseAI application included - Cloud connector application included - Sound classification(Based on AI engine) application (To be released)
Security	
OS / Firmware Protect	Encrypted Firmware, Secure boot, Signed Firmware
User authentication	Digest Authentication, Prevent brute-force attack
Network authentication	802.1X Authentication(EAP-TLS, EAP-LEAP, EAP-PEAP MSCHAPv2), 802.1AE(MACsec)
Secure Communication	HTTPS, SRTP, WSS(Websocket secure)
Access Control	IP-based access control, MAC-based access control, Auto logout
Data Protect	Encryption Credentials, Encrypt compress for live recording file export
Audit	Access / System / Event Log management
Device ID	Device Certificate(Hanwha vision Root CA)
Secure Storage	Secure element, SDcard partition encrypt
Security Certificate	ETSI EN 303 645, Secure element(FIPS 140-3 level3, CC EAL6+)
General	
Webpage Language	English, Korean, Simplified Chinese, Traditional Chinese, French, Italian, Spanish, German, Japanese, Russian, Portuguese, Czech, Polish, Turkish, Dutch, Hungarian, Greek
Web Viewer	None
Edge Storage	Micro SD/SDHC/SDXC 1slot Max. 1TB
Edge Storage(OnCloud)	Micro SD/SDHC/SDXC 1slot Max. 1TB * Hanwha Vision branded microSD cards have been certified and recommended for OnCloud edge recording.
Memory	4GB RAM, 8GB eMMC
Environmental & Electrical	
Operating Temperature / Humidity	-40°C~+55°C (-40°F ~ +131°F) 0~100%RH(Condensing) In PoE+ mode, IR illuminator will turn off if the temperature is higher than 50°C
Storage Temperature / Humidity	-50°C~+60°C(-58°F~+140°F) / 0~95% RH
Wind Load	None
EPA(Effective Projected Area)	0.009m ²
Input Voltage	WisePower(PoE(IEEE802.3af, class3)/PoE+(IEEE802.3at type2, Class4)), 12VDC
Power Consumption	PoE+: Max. 19.8W, typical 10.5W for 15m IR LED distance 12VDC: Max 20.0W, typical 10.9W PoE: Max. 11.2W, typical 7.7W for 10m IR LED distance 12VDC: Max 11.3W, typical 7.9W Support Wisepower - Power monitoring(Max/Current/Avg.) - Power logging
Mechanical	
RAL Code	RAL9003
Product Dimensions / Weight	Ø160x75mm(6.23x2.95") / 1020g
Compatible Conduit hole / Gang	single, double, 4" octagon, 4" square



1.1 Test Voltage & Frequency

Unless indicated otherwise on the individual data sheet or test results, the test voltage and frequency was as indicated below.

☒ AC 230 V, 50 Hz

1.2 Variant Model Differences

Simple derivations due to SW differences Add Model
(Basic models, circuits, hardware No changes. Same inside.)

1.3 Device Modifications

Not applicable

1.4 Equipment Under Test

Description	Model Number	Serial Number	Manufacturer	Remarks
NETWORK CAMERA	XNF-A9014RV	-	HANWHA VISION VIETNAM COMPANY LIMITED	EUT

1.5 System Configuration

Description	Model Number	Serial Number	Manufacturer	Remarks
-	-	-	-	-

1.6 Support Equipments

Description	Model Number	Serial Number	Manufacturer	Remarks
Adaptor	2ACB022F	-	Channel Well Technology (Guangzhou) Co., Ltd.	-
PoE Injector	PT-PSE109GBRO-A	-	Dongguan PROCET Network Technology Co.,Ltd	-
LED Alarm	-	-	-	-
Button Alarm	-	-	-	-
Headset	K550	-	Britz®	-
Micro SD Card	-	-	Sandisk	8 GB
Laptop	LG15N54	506NZGK000615	LG	-
Laptop Adaptor	PA-1650-43(65W)	OF58U63849302Y609	LG	-



1.7 External I/O Cabling

■ Mode 1

Start		END		Cable Spec.	
Description	I/O Port	Description	I/O Port	Length	Shield
NETWORK CAMERA (EUT)	DC 12 V	Adaptor	2 Pin	0.8	U
	PoE	Laptop	RJ-45	3.2	U
	Micro SD Card Slot	Micro SD Card	Micro SD Card Slot	-	-
	Alarm OUT	LED Alarm	Alarm IN	3.1	U
	Alarm IN	Button Alarm	Alarm OUT	3.3	U
	MIC	Headset	3.5 mm	2.0	U
	SPEAKER				
Laptop	DC Jack	Laptop Adaptor	DC Jack	1.5	U

* Unshielded=U, Shielded=S

■ Mode 2

Start		END		Cable Spec.	
Description	I/O Port	Description	I/O Port	Length	Shield
NETWORK CAMERA (EUT)	PoE	PoE Injector	RJ-45	3.2	U
	Micro SD Card Slot	Micro SD Card	Micro SD Card Slot	-	-
	Alarm OUT	LED Alarm	Alarm IN	3.1	U
	Alarm IN	Button Alarm	Alarm OUT	3.3	U
	MIC	Headset	3.5 mm	2.0	U
	SPEAKER				
Laptop	DC Jack	Laptop Adaptor	DC Jack	1.5	U

* Unshielded=U, Shielded=S



1.8 EUT Operating Mode(s)


Test mode	Test Voltage	Test No.	operating
Mode 1	DC 12 V	1	- Check the network behavior of the EUT with the laptop's ping test - View images of the camera through the Web Viewer - Play the 1 kHz tone through the Web Viewer to see the sound output with the headset - When the alarm is pressed, make sure the button alarm is working - After testing, check the recording with Micro SD Card
Mode 2	PoE	2	

EUT Test operating S/W		
Name	Version	Manufacture Company
Web Viewer	-	HANWHA VISION VIETNAM COMPANY LIMITED




1.9 Configuration

■ Mode 1



■ Mode 2



**1.10 Remarks When Standards Applied**

N/A

1.11 Calibration Details of Equipment Used for Measurement

Test equipment and test accessories are calibrated on regular basis. The maximum time between calibrations is one year or what is recommended by the manufacturer, whichever is less.

1.12 Test Facility

The measurement facility is located at 473-21, Gayeo-ro, Yeosu-si, Gyeonggi-do, 12658, Korea, Republic of. The sites are constructed in conformance with the requirements of ANSI C63.4a-2017 and CISPR 16-1-4:2019

1.13 Laboratory Accreditations and Listings

Country	Agency	Scope of Accreditation	Logo
KOREA	RRA	EMI (3 m & 10 m Semi-Anechoic Chamber and conducted test site) EMS (ESD, RS, EFT/Burst, Surge, CS, Magnetic, Dips and interruptions)	 KR0100
International	KOLAS	EMI (3 m & 10 m Semi-Anechoic Chamber and conducted test site) EMS (ESD, RS, EFT/Burst, Surge, CS, Magnetic, Dips and interruptions)	 KT489
USA	FCC	3 m & 10 m Semi-Anechoic Chamber Conducted test site to perform FCC Part 15/18 measurements.	 KR0100
Canada	ISED	3 m & 10 m Semi-Anechoic Chamber and Conducted test site	 23298
JAPAN	VCCI	EMI (3 m & 10 m Semi-Anechoic Chamber and conducted test site)	 C-20136, T-20137, R-20181, G-20176
Europe	TÜV SÜD	EMI (3 m & 10 m Semi-Anechoic Chamber and conducted test site) EMS (ESD, RS, EFT/Burst, Surge, CS, Magnetic, Dips and interruptions)	 CARAT 001633 0008



2.0 Test Regulations

The emissions tests were performed according to following regulations:

☒ **EMC – Directive 2014/30/EU**

☒ EN 50121-4:2016/A1:2019

☒ EN IEC 61000-3-2:2019

☒ EN 61000-3-3:2013/A2:2021

☒ **EMC – Regulations 2016**

☒ EN 50121-4:2016/A1:2019

☒ EN IEC 61000-3-2:2019

☒ EN 61000-3-3:2013/A2:2021



2.1 Conducted Emissions at Mains Power Ports

Test Date

Oct. 03, 2025

Test Location

Electro wave Shieldroom #6

Test Equipment

Used	Description	Model Number	Manufacturer	Serial Number	Cal. Due
☒	EMI Test S/W	EMC32	R & S	9.12.00	-
☒	EMI TEST RECEIVER	ESR3	R & S	101783	11. 06, 2025
☒	LISN	ENV216	R & S	101786	01. 09, 2026
☒	PULSE LIMITER	ESH3-Z2	R & S	101915	11. 06, 2025

Test Conditions

Temperature: (25,7 ± 0,2) °C

Relative Humidity: (56,0 ± 0,1) % R.H.

Frequency Range of Measurement

150 kHz to 30 MHz

Instrument Settings

IF Band Width: 9 kHz

Test Results

The requirements are:

- ☒ PASS
☐ NOT PASS
☐ NOT APPLICABLE

RemarksSee Appendix A for test data.



2.2 Conducted Emissions at Telecommunication Ports

Test Date

Oct. 03, 2025

Test Location

Electro wave Shieldroom #6

Test Equipment

Used	Description	Model Number	Manufacturer	Serial Number	Cal. Due
☒	EMI Test S/W	EMC32	R & S	9.12.00	-
☒	EMI TEST RECEIVER	ESR3	R & S	101783	11. 06, 2025
☒	LISN	ENV216	R & S	101786	01. 09, 2026
☒	PULSE LIMITER	ESH3-Z2	R & S	101915	11. 06, 2025
☒	8-WIRE ISN CAT3,5	ENY81	R & S	100174	11. 12, 2025

Test Conditions

Temperature: (25,7 ± 0,2) °C
Relative Humidity: (56,0 ± 0,2) % R.H.

Frequency Range of Measurement

150 kHz to 30 MHz

Instrument Settings

IF Band Width: 9 kHz

Test Results

The requirements are:

- ☒ PASS
☐ NOT PASS
☐ NOT APPLICABLE

RemarksSee Appendix A for test data.



2.3 Radiated Electric Field Emissions(Below 1 GHz)

Test Date

Oct. 04, 2025

Test Location☒ SEMI ANECHOIC CHAMBER #4(10 m)**Test Equipment**

Used	Description	Model Number	Manufacturer	Serial Number	Cal. Due
☒	EMI Test S/W	EP5/RE	TOYO Corporation	6.0.0	-
☒	EMI TEST RECEIVER	ESU26	R & S	100551	02. 13, 2026
☒	AMPLIFIER	SCU 01	R & S	100603	11. 06, 2025
☒	BILOG ANTENNA	VULB9168	Schwarzbeck	715	05. 09, 2026
☒	ATTENUATOR	6806.17.A	HUBER+SUHNER	-	02. 13, 2026

Test Conditions

Temperature: (23,2 ± 0,3) °C
Relative Humidity: (56,4 ± 0,2) % R.H.

Frequency Range of Measurement

30 MHz to 1 GHz

Instrument Settings

IF Band Width: 120 kHz

Test Results

The requirements are:

- ☒ PASS
☐ NOT PASS
☐ NOT APPLICABLE

RemarksSee Appendix A for test data.



2.4 Radiated Electric Field Emissions(Above 1 GHz)

Test Date

Oct. 04, 2025

Test Location

SEMI ANECHOIC CHAMBER #5

Test Equipment

Used	Description	Model Number	Manufacturer	Serial Number	Cal. Due
☒	EMI Test S/W	ES10/RE	TOYO Corporation	2022.01.000	-
☒	EMI TEST RECEIVER	ESU26	Rohde & Schwarz	100552	02. 13, 2026
☒	HORN ANTENNA	BBHA 9120D	SCHWARZBECK	9120D-1802	11. 04, 2025
☒	PREAMPLIFIER	8449B	HP	3008A00538	04. 30, 2026
☒	ATTENUATOR	8491B	HP	23094	02. 13, 2026

Test Conditions

Temperature: (23,8 ± 0,2) °C
Relative Humidity: (55,8 ± 0,1) % R.H.

Frequency Range of Measurement

1 GHz to 6 GHz

Instrument Settings

IF Band Width: 1 MHz

Test Results

The requirements are:

- ☒ PASS
☐ NOT PASS
☐ NOT APPLICABLE

RemarksSee Appendix A for test data.



2.5 Harmonic Current Emissions

Test Date

Oct. 04, 2025

Test Location

Electro wave Shieldroom #7

Test Equipment

Used	Description	Model Number	Manufacturer	Serial Number	Cal. Due
☒	EMI Test S/W	net.control	EM TEST	2.1.4	-
☒	DIGITAL POWER ANALYZER	DPA 500N	EM TEST	V1024106759	03. 31, 2026
☒	POWER SOURCE	ACS 500N6	EM TEST	V1024106760	-

Test Conditions

Temperature: (24,4 ± 0,1) °C

Relative Humidity: (58,6 ± 0,1) % R.H.

Classification of Equipment for Harmonic Current Emissions

- ☒ Class A
- ☐ Class B
- ☐ Class C(Below 25 W)
- ☐ Class C(Above 25 W)
- ☐ Class D

Test Results

The requirements are:

- ☒ PASS
- ☐ NOT PASS
- ☐ NOT APPLICABLE

Remarks- See Appendix A for test data.



2.6 Voltage Fluctuations and Flicker

Test Date

Oct. 04, 2025

Test Location

Electro wave Shieldroom #7

Test Equipment

Used	Description	Model Number	Manufacturer	Serial Number	Cal. Due
☒	EMI Test S/W	net.control	EM TEST	2.1.4	-
☒	DIGITAL POWER ANALYZER	DPA 500N	EM TEST	V1024106759	03. 31, 2026
☒	POWER SOURCE	ACS 500N6	EM TEST	V1024106760	-

Test Conditions

Temperature: (24,4 ± 0,3) °C
Relative Humidity: (58,6 ± 0,1) % R.H.

Test Results

The requirements are:

- ☒ PASS
☐ NOT PASS
☐ NOT APPLICABLE

Remarks- See Appendix A for test data.



3.0 Criteria for Compliance

Criteria for compliance was based on the following guidelines:

General performance criteria

The general principles (performance criteria) for the evaluation of the immunity test results are the following.

Performance criteria A

The apparatus shall continue to operate as intended during and after the test. No degradation of performance or loss of function is allowed below a performance level specified by the manufacturer, when the apparatus is used as intended. The performance level may be replaced by a permissible loss of performance. If the minimum performance level or the permissible performance loss is not specified by the manufacturer, either of these may be derived from the product description and documentation and what the user may reasonably expect from the apparatus if used as intended.

Performance criteria B

The apparatus shall continue to operate as intended after the test. No degradation of performance or loss of function is allowed below a performance level specified by the manufacturer, when the apparatus is used as intended. The performance level may be replaced by a permissible loss of performance. During the test, degradation of performance is however allowed. No change of actual operating state or stored data is allowed. If the minimum performance level or the permissible performance loss is not specified by the manufacturer, either of these may be derived from the product description and documentation and what the user may reasonably expect from the apparatus if used as intended.

Performance criteria C

Temporary loss of function is allowed, provided the function is self-recoverable or can be restored by the operation of the controls.



3.1 Electrostatic Discharge

Reference Standard

EN 61000-4-2:2009

Test Date

Oct. 03, 2025

Test Location

EMS-ESD: Electro wave Shieldroom#7

Test Equipment

Used	Description	Model Number	Manufacturer	Serial Number	Cal. Due
☒	ESD SIMULATOR	ESS-2000	Noise Ken	ESS01Z0454	01. 21, 2026
☒	HCP	-	KES	-	-
☒	VCP	-	Noise Ken	-	-

Test Conditions

Temperature: (25,7 ± 0,2) °C
Relative Humidity: (56,0 ± 0,1) % R.H.
Atmospheric Pressure: (100,1 ± 0,1) kPa

Test Specifications

Discharge Factor: ≥ 1 s

Discharge Impedance: 330 ohm / 150 pF

Kind of Discharge: Air, Contact (direct and indirect)

Polarity: Positive and Negative

Number of Discharge: ■ 10 at all locations for Air discharge
■ 10 at all locations for Contact discharge

Discharge Voltage:	Contact	Air	HCP	VCP
	☐ 2 kV	☒ 2 kV	☐ 2 kV	☐ 2 kV
	☐ 4 kV	☒ 4 kV	☐ 4 kV	☐ 4 kV
	☒ 6 kV	☐ 6 kV	☒ 6 kV	☒ 6 kV
	☐ 8 kV	☒ 8 kV	☐ 8 kV	☐ 8 kV
	☐ 15 kV	☐ 15 kV	☐ 15 kV	☐ 15 kV


Notes: HCP: Horizontal Coupling Plane

VCP: Vertical Coupling Plane


Required Performance Criteria: ☒ B



Location of Discharge:




■ Mode 1





■ Mode 2



**Test Data**

■ Mode 1

Indirect Discharge

No.	Test Point	Discharge Method	Observations	Remarks
1	HCP Contact	Contact Discharge	A	-
2	VCP Contact	Contact Discharge	A	-

Direct Discharge

No.	Test Point	Discharge Method	Observations	Remarks
1	Enclosure 1	Contact Discharge	A	-
2	Enclosure 2	Air Discharge	A	-
3	Port 1	Contact Discharge	A	-
4	Port 2	Air Discharge	A	-

■ Mode 2

Indirect Discharge

No.	Test Point	Discharge Method	Observations	Remarks
1	HCP Contact	Contact Discharge	A	-
2	VCP Contact	Contact Discharge	A	-

Direct Discharge

No.	Test Point	Discharge Method	Observations	Remarks
1	Enclosure 1	Contact Discharge	A	-
2	Enclosure 2	Air Discharge	A	-
3	Port 1	Contact Discharge	A	-
4	Port 2	Air Discharge	A	-

Note: "Blank" = Not performed

Observations:

- A – No response observed from EUT
- B – Unit shuts down then automatically restarts when full voltage is restored.
- C – Unit shuts down then manually restarts when full voltage is restored or Loss of function.

Test Results

- ☒ Test result reference
- ☐ NOT APPLICABLE

Remarks

During the test, There are no degradation of performance was found.



3.2 Radio-frequency Electromagnetic Field

Reference Standard

EN IEC 61000-4-3:2020

Test Date

Oct. 05, 2025

Test LocationEMS-RS: ☒ SEMI ANECHOIC CHAMBER #3 ☐ SEMI ANECHOIC CHAMBER #4(10 m)**Test Equipment**

Used	Description	Model Number	Manufacturer	Serial Number	Cal. Due
☒	EMS Test S/W	EMC32	R & S	10.10.02	-
☒	SIGNAL GENERATOR	SMB 100A	Rohde & Schwarz	108252	07. 28, 2026
☒	HIGH POWER DUAL AMP	SSA532	SUNGSAN	SSA532-001	-
☒	POWER METER	E4419B	Agilent	GB40203000	02. 13, 2026
☒	AVERAGE POWER SENSOR	E9301A	Agilent	MY52170007	02. 13, 2026
☒	AVERAGE POWER SENSOR	E9301A	Agilent	MY41498669	02. 13, 2026
☒	STACKED DOUBLE LOG-PER- ANTENNA	STPL9128 E	Schwarzbeck	9128ES-121	-
☒	DOUBLE RIDGED HORN ANTENNA	SAS-571	A.H.SYSTEM,INC	781	03. 05, 2026

Test Conditions

Temperature: (24,5 ± 0,3) °C
Relative Humidity: (57,3 ± 0,2) % R.H.
Atmospheric Pressure: (99,9 ± 0,1) kPa



Test Specifications

Antenna Polarization: Horizontal & Vertical unless indicated otherwise

Antenna Distance: ☒ 3 m

Frequency Range: ☒ 80 MHz to 800 MHz [10V/m]
[Field Strength] ☒ 800 MHz to 1 GHz [20 V/m]
☒ 1,4 GHz to 2,0 GHz [10 V/m]
☒ 2,0 GHz to 2,7 GHz [5 V/m]
☒ 5,1 GHz to 6,0 GHz [3 V/m]

Modulation: ☒ 80 % AM, 1 kHz sine wave

Frequency Step: ☒ 1 % step

Dwell Time: ☐ 1 s ☒ 3 s

of Sides Radiated: ☒ 4

Required Performance Criteria: ☒ A

**Test Data**

■ Mode 1

Side Exposed	Observations	
	Horizontal	Vertical
Front	A	A
Right	A	A
Back	A	A
Left	A	A

■ Mode 2

Side Exposed	Observations	
	Horizontal	Vertical
Front	A	A
Right	A	A
Back	A	A
Left	A	A

Note: "Blank" = Not performed

Observations:

- A – No response observed from EUT
- B – Unit shuts down then automatically restarts when full voltage is restored.
- C – Unit shuts down then manually restarts when full voltage is restored or Loss of function.

Test Results

- ☒ Test result reference
- ☐ NOT APPLICABLE

Remarks

During the test, There are no degradation of performance was found.



3.3 Fast Transients

Reference Standard

EN 61000-4-4:2012

Test Date

Oct. 04, 2025

Test Location

EMS-EFT: Electro wave Shieldroom #7

Test Equipment

Used	Description	Model Number	Manufacturer	Serial Number	Cal. Due
☒	EMS Test S/W	iec.control	EM TEST	5.4.8	-
☒	ULTRA COMPACT SIMULATOR	UCS 500N7	EM TEST	P1608172950	11. 06, 2025
☒	MOTOR VARIAC	MV2616	EM TEST	P1552169719	11. 07, 2025
☒	CAPACITIVE COUPLING CLAMP	HFK	EM TEST	P1633183115	11. 06, 2025

Test Conditions

Temperature: (24,4 ± 0,2) °C
Relative Humidity: (58,6 ± 0,1) % R.H.
Atmospheric Pressure: (100,2 ± 0,1) kPa

Test Specifications

Pulse Amplitude & Polarity: ☒ ± 2.0 kV ☐ ± 4.0 kV
(Power Lines)

Pulse Amplitude & Polarity: ☒ ± 2.0 kV ☐ ± 4.0 kV
(Signal Lines)

Pulse Amplitude & Polarity: ☐ ± 1.0 kV
(Earth Lines)

Burst Period: ☒ 300 ms

Repetition Rate: ☒ 5 kHz

Duration of Test Voltage: ☒ ≥ 1 min

Required Performance Criteria: ☒ A

**Test Data**

■ Mode 1

☒ Input a.c. power ports – Coupling/Decoupling Network used

Mode of Application	Observations	
	(+) Burst (kV)	(-) Burst (kV)
L	A	A
N	A	A
L – N	A	A

☐ Input d.c. power ports – Coupling/Decoupling Network used

Mode of Application	Observations	
	(+) Burst (kV)	(-) Burst (kV)
-	-	-

☒ Signal ports and telecommunication ports – Coupling Clamp used

Mode of Application	Observations	
	(+) Burst (kV)	(-) Burst (kV)
PoE	A	A
Alarm IN, Alarm OUT	A	A

☐ Earth ports – Coupling Clamp used

Mode of Application	Observations	
	(+) Burst (kV)	(-) Burst (kV)
-	-	-

**■ Mode 2**☐ Input a.c. power ports – Coupling/Decoupling Network used

Mode of Application	Observations	
	(+) Burst (kV)	(-) Burst (kV)
-	-	-

☐ Input d.c. power ports – Coupling/Decoupling Network used

Mode of Application	Observations	
	(+) Burst (kV)	(-) Burst (kV)
-	-	-

☒ Signal ports and telecommunication ports – Coupling Clamp used

Mode of Application	Observations	
	(+) Burst (kV)	(-) Burst (kV)
PoE	A	A
Alarm IN, Alarm OUT	A	A

☐ Earth ports – Coupling Clamp used

Mode of Application	Observations	
	(+) Burst (kV)	(-) Burst (kV)
-	-	-

Note: “Blank” = Not performed

Observations:

A – No response observed from EUT

B – Unit shuts down then automatically restarts when full voltage is restored.

C – Unit shuts down then manually restarts when full voltage is restored or Loss of function.

Test Results☒ Test result reference☐ NOT APPLICABLE**Remarks**During the test, There are no degradation of performance was found.



3.4 Surges

Reference Standard

EN 61000-4-5:2014+A1:2017

Test Date

Oct. 04, 2025

Test Location

EMS-Surge: Electro wave Shieldroom #7

Test Equipment

Used	Description	Model Number	Manufacturer	Serial Number	Cal. Due
☒	EMS Test S/W	iec.control	EM TEST	5.4.8	-
☒	EMS Test S/W	iec.control	EM TEST	5.4.8	11. 07, 2025
☒	ULTRA COMPACT SIMULATOR	UCS 500N7	EM TEST	P1608172950	11. 07, 2025
☒	MOTOR VARIAC	MV2616	EM TEST	P1552169719	11. 08, 2025
☒	CDN	CNV 508N1	EM TEST	P1610176296	11. 08, 2025
☒	CDN	CNV 504N7.3	EM TEST	P1744207079	11, 08, 2025

Test Conditions

Temperature: (24,4 ± 0,2) °C
Relative Humidity: (58,6 ± 0,2) % R.H.
Atmospheric Pressure: (100,2 ± 0,1) kPa

**Test Specifications****AC Power Lines**

Source Impedance: 12 ohm for common mode and 2 ohm for differential mode

Surge Amplitude :
Common Mode
☐ (2,0) kV
Differential Mode
☒ (1,0) kVNumber of Surges: ☒ 5 surges per angle
Angle: ☒ 0°, 90°, 180°, 270° (input AC power port)
Polarity: ☒ Positive & Negative
Repetition Rate: ☒ 1 surge per min ☐ 1 surge per 30 sec.
Required Performance Criteria: ☒ B**DC Power Lines**Source Impedance: 42 ohm
Surge Amplitude: Common Mode
☐ (2,0) kV
Differential Mode
☐ (1,0) kVNumber of Surges: ☐ 5 Surges
Polarity: ☐ Positive & Negative
Repetition Rate: ☐ 1 surge per min ☐ 1 surge per 30 sec.
Required Performance Criteria: ☐ B**Signal Lines**Source Impedance: 42 ohm
Surge Amplitude: Common Mode
☐ (2,0) kV
Differential Mode
☒ (1,0) kVNumber of Surges: ☒ 5 Surges
Polarity: ☒ Positive & Negative
Repetition Rate: ☒ 1 surge per min ☐ 1 surge per 30 sec.
Required Performance Criteria: ☒ B

**Test Data**

■ Mode 1

☒ Line to Line – Differential Mode

Mode of Application	Observations	
	(+) Surge (kV)	(-) Surge (kV)
L – N	A	A

☐ Line to Earth – Common Mode

Mode of Application	Observations	
	(+) Surge (kV)	(-) Surge (kV)
-	-	-

Signal Lines☒ Line to Line – Differential Mode

Mode of Application	Observations	
	(+) Surge (kV)	(-) Surge (kV)
PoE	A	A

☐ Line to Earth – Common Mode

Mode of Application	Observations	
	(+) Surge (kV)	(-) Surge (kV)
-	-	-



☒ Mode 2

☐ Line to Line – Differential Mode

Mode of Application	Observations	
	(+) Surge (kV)	(-) Surge (kV)
-	-	-

☐ Line to Earth – Common Mode

Mode of Application	Observations	
	(+) Surge (kV)	(-) Surge (kV)
-	-	-

Signal Lines

☒ Line to Line – Differential Mode

Mode of Application	Observations	
	(+) Surge (kV)	(-) Surge (kV)
PoE	A	A

☐ Line to Earth – Common Mode

Mode of Application	Observations	
	(+) Surge (kV)	(-) Surge (kV)
-	-	-

Note: “Blank” = Not performed

Observations:

A – No response observed from EUT

B – Unit shuts down then automatically restarts when full voltage is restored.

C – Unit shuts down then manually restarts when full voltage is restored or Loss of function.

Test Results

☒ Test result reference

☐ NOT APPLICABLE

Remarks

During the test, There are no degradation of performance was found.



3.5 Conducted Disturbance

Reference Standard

EN 61000-4-6:2014

Test Date

Oct. 03, 2025

Test Location

EMS-CS: Electro wave Shieldroom #7

Test Equipment

Used	Description	Model Number	Manufacturer	Serial Number	Cal. Due
☒	EMS Test S/W	icd.control	EM TEST	8.0.0	-
☒	TEST SYSTEM FOR CONDUCTED AND RADIATED	NSG4070	TESEQ	65585	11. 18, 2025
☒	ATTENUATOR	ATT 6/80	EM TEST	P1614178148	11. 06, 2025
☒	CDN	CDN M016	TESEQ	43694	11. 07, 2025
☒	CDN	CDN T8 RJ45	SCHWARZBECK	00103	07. 07, 2026
☒	EM CLAMP	KEMZ 801A	TESEQ	44099	11. 08, 2025

Test Conditions

Temperature: (23,9 ± 0,2) °C
Relative Humidity: (58,3 ± 0,1) % R.H.
Atmospheric Pressure: (100,1 ± 0,1) kPa

Test Specifications

Frequency Range: ☒ 150 kHz to 80 MHz
Voltage Level: ☒ 10 Vrms
Modulation: ☒ 80 % AM, 1 kHz sine wave
Frequency Step: ☒ 1 % step
Dwell Time: ☐ 1 s ☒ 3 s
Required Performance Criteria: ☒ A

**Test Data**

■ Mode 1

☒ Input a.c. power ports

Coupling Location (Line Stressed)	Coupling Method	Observations
L – N	CDN	A

☐ Input d.c. power ports

Coupling Location (Line Stressed)	Coupling Method	Observations
-	-	-

☒ Signal ports and telecommunication ports

Coupling Location (Line Stressed)	Coupling Method	Observations
PoE	CDN	A
Alarm IN, Alarm OUT	Clamp	A

☐ Earth ports

Coupling Location (Line Stressed)	Coupling Method	Observations
-	-	-

☒ Mode 2☐ Input a.c. power ports

Coupling Location (Line Stressed)	Coupling Method	Observations
-	-	-

☐ Input d.c. power ports

Coupling Location (Line Stressed)	Coupling Method	Observations
-	-	-

☒ Signal ports and telecommunication ports

Coupling Location (Line Stressed)	Coupling Method	Observations
PoE	CDN	A
Alarm IN, Alarm OUT	Clamp	A

☐ Earth ports

Coupling Location (Line Stressed)	Coupling Method	Observations
-	-	-

Notes: CDN = Coupling Decoupling Network
"blank" = Not performed

Observations:

- A – No response observed from EUT
- B – Unit shuts down then automatically restarts when full voltage is restored.
- C – Unit shuts down then manually restarts when full voltage is restored or Loss of function.

Test Results

- ☒ Test result reference
- ☐ NOT APPLICABLE

Remarks

During the test, There are no degradation of performance was found.



3.6 Power Frequency Magnetic Field Immunity

Reference Standard

EN 61000-4-8:2010

Test Date

Oct. 04, 2025

Test Location

EMS-Magnetic: Electro wave Shieldroom #7

Test Equipment

Used	Description	Model Number	Manufacturer	Serial Number	Cal. Due
☒	EMS Test S/W	iec.control	EM TEST	5.4.8	-
☒	ULTRA COMPACT SIMULATOR	UCS 500N7	EM TEST	P1608172950	11. 08, 2025
☒	MOTOR VARIAC	MV2616	EM TEST	P1552169719	11. 07, 2025
☒	MAGNETIC FIELD COIL	MS 100N	EM TEST	P1536163691	11. 08, 2025
☒	CURRENT TRANSFORMER	MC 2630	EM TEST	P1629182219	11. 08, 2025
☒	CURRENT TRANSFORMER	MC 26100	EM TEST	P1550168963	02. 14, 2026

Test Conditions

Temperature: (24,4 ± 0,2) °C
Relative Humidity: (58,6 ± 0,2) % R.H.
Atmospheric Pressure: (100,2 ± 0,1) kPa



Test Specifications

Field Strength(Power Source):

☒ 100 A/m (ac)

☒ 300 A/m (dc)

Frequency (ac):

☒ 16.7 Hz

☒ 50 Hz

☐ 60 Hz

Frequency (dc):

☒ 0 Hz

Required Performance Criteria:

☒ A



**Test Data**

■ Mode 1

☒ Immersion method

Coil orientation	Observations
X	A
Y	A
Z	A

☐ Proximity method

Coil orientation	Observations
X	-
Y	-
Z	-

■ Mode 2

☒ Immersion method

Coil orientation	Observations
X	A
Y	A
Z	A

☐ Proximity method

Coil orientation	Observations
X	-
Y	-
Z	-

Note: "blank" = Not performed

Observations:

- A – No response observed from EUT
- B – Unit shuts down then automatically restarts when full voltage is restored.
- C – Unit shuts down then manually restarts when full voltage is restored or Loss of function.

Test Results☒ Test result reference☐ NOT APPLICABLE**Remarks**During the test, There are no degradation of performance was found.



APPENDIX A – TEST DATA

Conducted Emissions at Mains Power Ports

■ Mode 1

[HOT]

Test Description:

Conducted Emission

Job No.:

KES-EM253473

Phase:


L

Mode:

Mode 1

Operator Name:

KES



Final_Result

Frequency (MHz)	QuasiPeak (dBμV)	CAverage (dBμV)	Limit (dBμV)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Line	Corr. (dB)
0.160000	---	37.67	66.00	28.33	1000.0	9.000	L1	19.5
0.160000	52.47	---	79.00	26.53	1000.0	9.000	L1	19.5
0.930000	---	27.27	60.00	32.73	1000.0	9.000	L1	19.6
0.930000	32.40	---	73.00	40.60	1000.0	9.000	L1	19.6
0.940000	---	27.22	60.00	32.78	1000.0	9.000	L1	19.6
0.940000	32.16	---	73.00	40.84	1000.0	9.000	L1	19.6
7.985000	---	24.26	60.00	35.74	1000.0	9.000	L1	20.0
7.985000	29.51	---	73.00	43.49	1000.0	9.000	L1	20.0
16.230000	---	30.47	60.00	29.53	1000.0	9.000	L1	20.3
16.230000	31.88	---	73.00	41.12	1000.0	9.000	L1	20.3

**[NEUTRAL]**

Test Description:

Conducted Emission

Job No.:

KES-EM253473

Phase:


N

Mode:

Mode 1

Operator Name:

KES

**Final_Result**

Frequency (MHz)	QuasiPeak (dBμV)	CAverage (dBμV)	Limit (dBμV)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Line	Corr. (dB)
0.185000	---	37.21	66.00	28.79	1000.0	9.000	N	19.5
0.185000	49.37	---	79.00	29.63	1000.0	9.000	N	19.5
0.335000	---	40.76	66.00	25.24	1000.0	9.000	N	19.5
0.335000	47.80	---	79.00	31.20	1000.0	9.000	N	19.5
0.985000	---	26.25	60.00	33.75	1000.0	9.000	N	19.6
0.985000	31.09	---	73.00	41.91	1000.0	9.000	N	19.6
0.990000	---	26.38	60.00	33.62	1000.0	9.000	N	19.6
0.990000	31.18	---	73.00	41.82	1000.0	9.000	N	19.6
8.310000	---	24.08	60.00	35.92	1000.0	9.000	N	20.0
8.310000	29.26	---	73.00	43.74	1000.0	9.000	N	20.0
16.230000	---	30.59	60.00	29.41	1000.0	9.000	N	20.3
16.230000	32.57	---	73.00	40.43	1000.0	9.000	N	20.3

◆ Calculation

$$\text{QuasiPeak [dBμV]} / \text{CAverage [dBμV]} = \text{Reading Value [dBμV]} + \text{Corr. [dB]}$$

QuasiPeak / CAverage : The Final Value

Reading Value : Not shown in the table.


Corr. : Correction values (LISN FACTOR + (Cable Loss + Pulse Limiter FACTOR))

**Conducted Emissions at Telecommunication Ports**

■ Mode 1

[100 Mbps]

Test Description: Telecommunication Emission
Job No.: KES-EM253473
Mode : Mode 1
Speed : 100 Mbps
Operator Name: KES

**Final_Result**


Frequency (MHz)	QuasiPeak (dB μ V)	CAverage (dB μ V)	Limit (dB μ V)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Line	Corr. (dB)
0.330000	---	55.30	77.45	22.15	1000.0	9.000	Single Line	19.4
0.330000	62.39	---	90.45	28.06	1000.0	9.000	Single Line	19.4
0.345000	---	55.72	77.08	21.36	1000.0	9.000	Single Line	19.4
0.345000	63.62	---	90.08	26.46	1000.0	9.000	Single Line	19.4
3.485000	---	44.66	74.00	29.34	1000.0	9.000	Single Line	19.4
3.485000	48.99	---	87.00	38.01	1000.0	9.000	Single Line	19.4
3.500000	---	44.20	74.00	29.80	1000.0	9.000	Single Line	19.4
3.500000	49.22	---	87.00	37.78	1000.0	9.000	Single Line	19.4
16.230000	---	61.22	74.00	12.78	1000.0	9.000	Single Line	19.8
16.230000	62.08	---	87.00	24.92	1000.0	9.000	Single Line	19.8



■ Mode 2

[100 Mbps]

Test Description: Telecommunication Emission
Job No.: KES-EM253473
Mode : Mode 2
Speed : 100 Mbps
Operator Name: KES



Final_Result

Frequency (MHz)	QuasiPeak (dB μ V)	CAverage (dB μ V)	Limit (dB μ V)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Line	Corr. (dB)
0.180000	---	41.16	82.49	41.33	1000.0	9.000	Single Line	19.6
0.180000	41.32	---	95.49	54.17	1000.0	9.000	Single Line	19.6
0.795000	---	32.03	74.00	41.97	1000.0	9.000	Single Line	19.3
0.795000	36.69	---	87.00	50.31	1000.0	9.000	Single Line	19.3
2.275000	---	51.07	74.00	22.93	1000.0	9.000	Single Line	19.3
2.275000	56.08	---	87.00	30.92	1000.0	9.000	Single Line	19.3
2.320000	---	50.08	74.00	23.92	1000.0	9.000	Single Line	19.3
2.320000	54.50	---	87.00	32.50	1000.0	9.000	Single Line	19.3
13.480000	---	56.35	74.00	17.65	1000.0	9.000	Single Line	19.7
13.480000	58.00	---	87.00	29.00	1000.0	9.000	Single Line	19.7
13.555000	---	30.89	74.00	43.11	1000.0	9.000	Single Line	19.7
13.555000	63.19	---	87.00	23.81	1000.0	9.000	Single Line	19.7


◆ Calculation

QuasiPeak[dBuV] / CAverage [dBuV] = Reading Value[dBuV] + Corr. [dB]

QuasiPeak / CAverage : The Final Value

Reading Value : Not shown in the table.


Corr. : Correction values (ISN FACTOR + (Cable Loss + Pulse Limiter FACTOR))

**Radiated Electric Field Emissions(Below 1 GHz)****■ Mode 1****Final Result**

No.	Frequency [MHz]	(P)	Reading QP [dB(uV)]	c.f [dB(1/m)]	Result QP [dB(uV/m)]	Limit QP [dB(uV/m)]	Margin QP [dB]	Height [cm]	Angle [deg]	Remark
1	94.384	V	51.2	-25.8	25.4	40.0	14.6	101.0	111.0	
2	226.668	V	54.1	-20.9	33.2	40.0	6.8	100.0	149.0	
3	310.330	V	51.6	-16.7	34.9	47.0	12.1	102.0	349.0	
4	333.125	V	49.9	-16.0	33.9	47.0	13.1	105.0	146.0	
5	342.219	H	48.6	-15.7	32.9	47.0	14.1	201.0	93.0	
6	426.003	V	43.9	-12.5	31.4	47.0	15.6	101.0	146.0	



■ Mode 2



Final Result

No.	Frequency [MHz]	(P)	Reading QP [dB(μV)]	c.f [dB(1/m)]	Result QP [dB(μV/m)]	Limit QP [dB(μV/m)]	Margin QP [dB]	Height [cm]	Angle [deg]	Remark
1	43.701	V	48.7	-21.5	27.2	40.0	12.8	102.0	276.0	
2	162.405	V	49.6	-19.6	30.0	40.0	10.0	106.0	50.0	
3	226.668	V	53.8	-20.9	32.9	40.0	7.1	100.0	58.0	
4	296.750	V	51.4	-17.2	34.2	47.0	12.8	101.0	241.0	
5	334.823	V	50.7	-15.9	34.8	47.0	12.2	108.0	188.0	
6	360.649	V	50.3	-15.1	35.2	47.0	11.8	107.0	203.0	
7	433.763	H	46.7	-12.2	34.5	47.0	12.5	299.0	107.0	


◆ Calculation

Result(QP) [dB(μV/m)] = (Reading(QP)[dB(μV)] + c.f[dB(1/m)])

Margin(QP)[dB] = Limit[dB(μV/m)] - Result(QP) [dB(μV/m)]

Reading(QP) : Reading value, Result(QP) : Reading value + Factor value


Limit(QP) : Limit value, c.f : (ANT Factor + Cable Loss - Preamp Factor), Margin: Margin value

**Radiated Electric Field Emissions(Above 1 GHz)****Mode 1****Final Result**

No.	Frequency [MHz]	Pol	Reading AV [dB (μV)]	Reading PK [dB (μV)]	c.f [dB (1/m)]	Result AV [dB (μV/m)]	Result PK [dB (μV/m)]	Limit AV [dB (μV/m)]	Limit PK [dB (μV/m)]	Margin AV [dB]	Margin PK [dB]	Height [cm]	Angle [deg]
1	2588.146	V	29.4	42.7	5.3	34.7	48.0	56.0	76.0	21.3	28.0	100.0	277.3
2	2786.359	H	28.9	42.8	6.1	35.0	48.9	56.0	76.0	21.0	27.1	100.0	53.5
3	3567.012	V	28.9	42.7	7.7	36.6	50.4	60.0	80.0	23.4	28.6	100.0	200.7
4	4828.243	V	28.0	41.1	11.8	39.8	52.9	60.0	80.0	20.2	27.1	100.0	99.7
5	5299.741	H	26.3	40.6	13.1	39.4	53.7	60.0	80.0	20.6	26.3	100.0	265.9
6	5717.085	H	27.4	40.4	14.0	41.4	54.4	60.0	80.0	18.6	25.6	100.0	351.5



■ Mode 2



◆ Calculation

$$\text{Result(PK/CAV)} [\text{dB}(\mu\text{V/m})] = (\text{Reading(PK/CAV)} [\text{dB}(\mu\text{V})] + \text{c.f} [\text{dB}(1/\text{m})])$$
$$\text{Margin(PK/CAV)} [\text{dB}] = \text{Limit} [\text{dB}(\mu\text{V/m})] - \text{Result(PK/CAV)} [\text{dB}(\mu\text{V/m})]$$

Reading(PK/CAV) : Reading value, Result(PK/CAV) : Reading value + Factor value

Limit(PK/CAV) : Limit value, c.f : (ANT Factor + Cable Loss -Preamp Factor), Margin: Margin value

**Harmonic Current Emissions and Voltage Fluctuations and Flicker**

■ Mode 1

Average harmonic current results

Hn	I _{eff} [A]	% of Limit	Limit [A]	Result
1	0.042			
2	0.002	0.228	1.080	n/a
3	0.036	1.585	2.300	PASS
4	0.003	0.673	0.430	n/a
5	0.037	3.231	1.140	PASS
6	0.003	0.974	0.300	n/a
7	0.036	4.656	0.770	PASS
8	0.003	1.224	0.230	n/a
9	0.034	8.437	0.400	PASS
10	0.003	1.528	0.184	n/a
11	0.032	9.789	0.330	PASS
12	0.003	1.792	0.153	n/a
13	0.030	14.517	0.210	PASS
14	0.003	2.108	0.131	n/a
15	0.028	18.835	0.150	PASS
16	0.003	2.326	0.115	n/a
17	0.026	19.834	0.132	PASS
18	0.003	2.574	0.102	n/a
19	0.024	20.297	0.118	PASS
20	0.003	2.818	0.092	n/a
21	0.022	13.531	0.161	PASS
22	0.003	3.067	0.084	n/a
23	0.019	13.197	0.147	PASS
24	0.003	3.333	0.077	n/a
25	0.017	12.700	0.135	PASS
26	0.002	3.468	0.071	n/a
27	0.015	12.115	0.125	PASS
28	0.002	3.694	0.066	n/a
29	0.013	11.005	0.116	PASS
30	0.002	3.808	0.061	n/a
31	0.011	10.150	0.109	PASS
32	0.002	3.975	0.058	n/a
33	0.009	9.175	0.102	PASS
34	0.002	4.093	0.054	n/a
35	0.008	8.070	0.096	PASS
36	0.002	4.156	0.051	n/a
37	0.007	7.351	0.091	PASS
38	0.002	4.242	0.048	n/a
39	0.006	6.499	0.087	PASS
40	0.002	4.133	0.046	n/a

Note: Harmonic currents less than 0.6 % of the input current measured under the test conditions, or less than 5 mA, whichever is greater, are disregarded.

* Application of limits for average is 100% except for odd harmonics from 21 to 39, where 150% applies.



Test Data - Harmonics (continued)

Maximum harmonic current results

Hn	I _{eff} [A]	% of Limit	Limit [A]	Result
1	0.043			
2	0.003	0.215	1.620	n/a
3	0.038	1.094	3.450	PASS
4	0.004	0.545	0.645	n/a
5	0.038	2.204	1.710	PASS
6	0.003	0.770	0.450	n/a
7	0.037	3.169	1.155	PASS
8	0.003	1.008	0.345	n/a
9	0.034	5.730	0.600	PASS
10	0.003	1.232	0.276	n/a
11	0.033	6.594	0.495	PASS
12	0.003	1.487	0.230	n/a
13	0.031	9.783	0.315	PASS
14	0.003	1.744	0.197	n/a
15	0.029	12.670	0.225	PASS
16	0.003	1.947	0.173	n/a
17	0.026	13.340	0.199	PASS
18	0.003	2.207	0.153	n/a
19	0.024	13.658	0.178	PASS
20	0.003	2.374	0.138	n/a
21	0.022	13.717	0.161	PASS
22	0.003	2.605	0.125	n/a
23	0.020	13.337	0.147	PASS
24	0.003	2.828	0.115	n/a
25	0.017	12.869	0.135	PASS
26	0.003	2.944	0.106	n/a
27	0.015	12.362	0.125	PASS
28	0.003	3.133	0.099	n/a
29	0.013	11.154	0.116	PASS
30	0.003	3.226	0.092	n/a
31	0.011	10.385	0.109	PASS
32	0.003	3.396	0.086	n/a
33	0.010	9.320	0.102	PASS
34	0.003	3.421	0.081	n/a
35	0.008	8.259	0.096	PASS
36	0.003	3.479	0.077	n/a
37	0.007	7.538	0.091	PASS
38	0.003	3.453	0.073	n/a
39	0.006	6.820	0.087	PASS
40	0.002	3.450	0.069	n/a

Note: Harmonic currents less than 0.6 % of the input current measured under the test conditions, or less than 5 mA, whichever is greater, are disregarded.

* Application of limits for average is 100% except for odd harmonics from 21 to 39, where 150% applies.



Test Data - Voltage Fluctuations

Maximum Flicker results

■ Mode 1

Flicker Measurements					
	Plt	Max Pst	Max Dc	Max Dmax	Max Tmax
Line 1:	0.028	0.028	0	< 0.2	0
Limits:	0.65	1	3.3	4	0.5
Results:	PASS	PASS	PASS	PASS	PASS





Test Setup Photos and Configuration

Conducted Emissions at Mains Power Ports

■ Mode 1





Conducted Emissions at Telecommunication Ports

■ Mode 1







■ Mode 2







Radiated Electric Field Emissions(Below 1 GHz)

■ Mode 1







■ Mode 2







Radiated Electric Field Emissions(Above 1 GHz)

■ Mode 1





■ Mode 2





Harmonic Current Emissions and Voltage Fluctuations and Flicker

■ Mode 1





Electrostatic Discharge

■ Mode 1



■ Mode 2





Radio-frequency Electromagnetic Field

■ Mode 1



■ Mode 2






Fast Transients

■ Mode 1



■ Mode 2





Surges

■ Mode 1



■ Mode 2






Conducted Disturbance

■ Mode 1



■ Mode 2






Power Frequency Magnetic Field Immunity

■ Mode 1

[16.7 Hz (AC), 100 A/m]




[50 Hz (AC), 100 A/m]






[0 Hz (DC), 300 A/m]






■ Mode 2

[16.7 Hz (AC), 100 A/m]




[50 Hz (AC), 100 A/m]






[0 Hz (DC), 300 A/m]





EUT External Photographs

(Top)




(Bottom)





EUT Internal Photographs





Label



Name : Hanwha Vision Co., Ltd.
Product item : NETWORK CAMERA
Model name : XNF-A9014RV

The End.

