

TEST REPORT

**CTK Co., Ltd.**

5 Dongbu-ro 221beon-gil, Cheoin-gu, Yongin-si,
Gyeonggi-do, Republic of Korea
Tel: +82-31-339-9970
Fax: +82-31-624-9501

REPORT No.:

CTK-2025-03003

Page (1) / (28) pages

1. Applicant

- Name : Hanwha Vision Co., Ltd
◦ Address : 6, Pangyo-ro 319Beon-gil, Bundang-gu, Seongnam-si,
Gyeonggi-do, 13488 Republic of Korea
◦ Date of Receipt : Sep. 02, 2025

2. Manufacturer

- Name : Hanwha Vision Co., Ltd

3. Use of Report :

Quality control

4. Test sample / Model :

NETWORK CAMERA / XNF-A9014RV

5. Date(s) of test :

Oct. 10, 2025~ Oct. 17, 2025

6. Test Standard (Method) used :

NEMA 250-2014

Enclosures for Electrical Equipment (1000 Volts Maximum)

7. Testing Environment :

Temperature: (25 ±10) °C, Humidity: (50 ±25) % R.H.

Pressure: (96 ±10) kPa

8. Test Results :

Refer to the test results

9. Location of Test :☒ Permanent Testing Lab ☐ On Site Testing

(5 Dongbu-ro 221beon-gil, Cheoin-gu, Yongin-si, Gyeonggi-do, Republic of Korea)

The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This report cannot be reproduced or copied without the written consent of CTK.

Approval	Tested by	Technical Manager
	Name: HyungUk Jeon (Signature)	Name: HoHyun Lee (Signature)

Remark. This report is not related to KOLAS accreditation and relevant regulation.

Nov. 17, 2025

CTK Co., Ltd.

**CTK Co., Ltd.**

5 Dongbu-ro 221beon-gil, Cheoin-gu, Yongin-si,
Gyeonggi-do, Republic of Korea
Tel: +82-31-339-9970
Fax: +82-31-624-9501

REPORT No.:
CTK-2025-03003
Page (2) / (28) pages

Table of Contents

1. Testing laboratory	3
1.1 Testing laboratory information	3
1.2 Testing laboratory accreditation status	3
2. Product description and equipment information	3
2.1 Product description	3
2.2 Manufacturer information	4
2.3 Equipment information	5
2.4 Pre-test product images	6
2.5 Testing equipment images	7
3. Test Information	8
3.1 Test item particulars and Possible test case verdicts	8
3.2 General remarks and factory information	8
3.3 Type 4X Test information	9
3.4 NEMA 250-2014 Test list	11
3.5 Attachment 1 - Construction Diagram and installation method	14
3.6 Attachment 2 - Parts List	17
4. Hose Down Test (Clause 5.7)	25
4.1 Test date and environmental conditions	25
4.2 Test Conditions and methods	25
4.3 Attachment 3 - Photographs	26
4.4 Test result	27
4.5 Post-test product images	28

	CTK Co., Ltd. 5 Dongbu-ro 221beon-gil, Cheoin-gu, Yongin-si, Gyeonggi-do, Republic of Korea Tel: +82-31-339-9970 Fax: +82-31-624-9501	REPORT No.: CTK-2025-03003 Page (3) / (28) pages	
---	--	--	--

1. Testing laboratory

1.1 Testing laboratory information

Lab. Name	CTK Co., Ltd.
Representative	Young Joseph Seungwon
Address	5 Dongbu-ro 221beon-gil, Cheoin-gu, Yongin-si, Gyeonggi-do, Republic of Korea
Tel.	+82-31-339-9970
Fax.	+82-31-624-9501
E-Mail	all.youngin@element.com
Website	www.elementkorea.kr

1.2 Testing laboratory accreditation status

Country	Classification	Accreditation Number	Logo
International	KOLAS	TESTING NO. KT119	

2. Product description and equipment information

2.1 Product description

Product Name	Model Name	Quantity	Comment
NETWORK CAMERA	XNF-A9014RV	1 EA	—

2.2 Model description

Basic Model	XNF-A9014R
Series model	XNF-A8014R
Model differences	Use of the same external shape and materials (case, finishing material, PCB, cable, etc.), differences in SW.

**CTK Co., Ltd.**

5 Dongbu-ro 221beon-gil, Cheoin-gu, Yongin-si,
Gyeonggi-do, Republic of Korea
Tel: +82-31-339-9970
Fax: +82-31-624-9501

REPORT No.:

CTK-2025-03003

Page (4) / (28) pages

2.3 Manufacturer information

Test item description : NETWORK CAMERA**Trade Mark****Manufacturer**

Lot O-2, Que Vo Industrial Zone extended area, Nam Son ward,
Bac Ninh province, Vietnam

173-25, Saneop-ro, Gwonseon-gu, Suwon-si, Gyeonggi-do, Korea
(Suwon Industrial Complex)

Model/Type reference : XNF-A9014RV

Electrical

XNF-A9014RV

DC12 V $\equiv$ 20.0 W / PoE 53 V $\equiv$ 19.8 W**Ratings** : DC12 V $\equiv$ 1.67 A / PoE 53 V $\equiv$ 0.37 A

XNF-A8014RV

DC12 V $\equiv$ 20.0 W / PoE 53 V $\equiv$ 19.8 WDC12 V $\equiv$ 1.67 A / PoE 53 V $\equiv$ 0.37 A

Dimension:

Ø180 by 565.2 mm, Ø100 by 314 mm, Ø25*2 by 157 mm,

Ø 8.5*4 by 106.76 mm

List of Attachments (including a total number of pages in each attachment):

Attachment 1: 14-16 pages (Construction Diagram including installation method)

Attachment 2: 17-24 pages (Parts List)

Attachment 3: 26-28 pages (photographs)

Summary of testing:**Tests performed (name of test and test clause):**
Clause 5.7(Hose Down Test)**Testing location:**

CTK Co., Ltd.

5 Dongbu-ro 221beon-gil, Cheoin-gu, Yongin-si,
Gyeonggi-do, Republic of Korea



CTK Co., Ltd.

5 Dongbu-ro 221beon-gil, Cheoin-gu, Yongin-si,
Gyeonggi-do, Republic of Korea
Tel: +82-31-339-9970
Fax: +82-31-624-9501

REPORT No.:

CTK-2025-03003

Page (5) / (28) pages

Copy of marking plate: The artwork above may be only a draft.

제품명칭: NETWORK CAMERA 모델명: XNF-A9014RV 정격전압: DC12V $\overline{\text{---}}$ 20.0W PoE(53V $\overline{\text{---}}$) 19.8W M/C: XNF-A9014RV/KDO Fac. ID: D 2025.10 S/N: ZW3J70GY80001HB MAC ADDRESS: E4-30-22-F1-F2-6D 인증번호: R-R-HWVS-XNFA9014RV 상호: 한화비전(주) 제조사/제조국가: 한화비전(주)/한국 IP66 	CE E C UL ITE US LISTED 9T96 E158873 EAC UK CA 10 NETWORK CAMERA, XNF-A9014RV DC 12V $\overline{\text{---}}$ 1.67A PoE (53V $\overline{\text{---}}$) 0.37A M/C: XNF-A9014RV/KEX Fac. ID: D 2025.10 S/N: ZW3J70GY80001HB MAC ADDRESS: E4-30-22-F1-F2-6D CAN ICES-3(A)/NMB-3(A) HANWHA VISION CO., LTD. MADE IN KOREA Rainproof / Étanche IP66
제품명칭: NETWORK CAMERA 모델명: XNF-A8014R 정격전압: DC12V $\overline{\text{---}}$ 20.0W PoE(53V $\overline{\text{---}}$) 19.8W M/C: XNF-A8014R/KDO Fac. ID: D 2025.10 S/N: ZW3J70GY80001HB MAC ADDRESS: E4-30-22-F1-F2-6D 인증번호: R-R-HWVS-XNFA9014R 상호: 한화비전(주) 제조사/제조국가: 한화비전(주)/한국 IP66 	CE E C UL ITE US LISTED 9T96 E158873 EAC UK CA 10 NETWORK CAMERA, XNF-A8014R DC 12V $\overline{\text{---}}$ 1.67A PoE (53V $\overline{\text{---}}$) 0.37A M/C: XNF-A8014R/KEX Fac. ID: D 2025.10 S/N: ZW3J70GY80001HB MAC ADDRESS: E4-30-22-F1-F2-6D CAN ICES-3(A)/NMB-3(A) HANWHA VISION CO., LTD. MADE IN KOREA

2.4 Equipment information

Testing equipment	Model Name	Manufacturer	Manufacturing Number	Next Cal. Date
25.4mm Nozzle	S3-IP18	CTK	S3-IP18	-
Temperature & Humidity Chamber	C4-340	Weisstechnik	54260023190010	Feb.06,2026
Area flow meter	Z-6504	FLOWTECH	229400	Jan.16,2026
Steel measuring meter	5.5 m	KOMELON	225851	Jan.16,2026
Stop Watch	NONE	Casio	612Q01R-1	Jan.15,2027
Digital Vernier Calipers	100 mm	MITUTOYO	A17179462	-



CTK Co., Ltd.

5 Dongbu-ro 221beon-gil, Cheoin-gu, Yongin-si,
Gyeonggi-do, Republic of Korea
Tel: +82-31-339-9970
Fax: +82-31-624-9501

REPORT No.:
CTK-2025-03003
Page (6) / (28) pages

2.5 Pre-test product images

2.5.1 Test sample



Top



Bottom




Front



Rear



Left side



Right side



CTK Co., Ltd.

5 Dongbu-ro 221beon-gil, Cheoin-gu, Yongin-si,
Gyeonggi-do, Republic of Korea
Tel: +82-31-339-9970
Fax: +82-31-624-9501

REPORT No.:
CTK-2025-03003
Page (7) / (28) pages

2.6 Testing equipment images

2.6.1 Test equipment



25.4mm Nozzle



Temperature & Humidity Chamber



Area flow meter



Steel measuring meter



Stop Watch



Digital Vernier Calipers

**CTK Co., Ltd.**

5 Dongbu-ro 221beon-gil, Cheoin-gu, Yongin-si,
Gyeonggi-do, Republic of Korea
Tel: +82-31-339-9970
Fax: +82-31-624-9501

REPORT No.:
CTK-2025-03003
Page (8) / (28) pages

3. Test Information

3.1 Test item particulars and Possible test case verdicts

Test item particulars	NETWORK CAMERA
Classification of installation and use	Outdoor (Watertight/Corrosion Resistant)
Possible test case verdicts:	
- test case does not apply to the test object	N/A
- test object does meet the requirement.....	P (Pass)
- test object does not meet the requirement	F (Fail)
- test case does not evaluate to the test object:	N/E

3.2 General remarks and factory information

General remarks:
"(See Enclosure #)" refers to additional information appended to the report. "(See appended table)" refers to a table appended to the report. Throughout this report a ☐ comma / ☒ point is used as the decimal separator. Clause numbers between brackets refer to clauses in NEMA 250-2014
Name and address of factory (ies):
1. HANWHA VISION VIETNAM COMPANY LIMITED Lot O-2, Que Vo Industrial Zone extended area, Nam Son ward, Bac Ninh city, Bac Ninh province, Vietnam 2. D-TECH CO., LTD. 173-25, Saneop-ro, Gwonseon-gu, Suwon-si, Gyeonggi-do, Korea (Suwon Industrial Complex)



CTK Co., Ltd.

5 Dongbu-ro 221beon-gil, Cheoin-gu, Yongin-si,
Gyeonggi-do, Republic of Korea
Tel: +82-31-339-9970
Fax: +82-31-624-9501

REPORT No.:

CTK-2025-03003

Page (9) / (28) pages

3.3 Type 4X Test information

Type 4X

Enclosures constructed for either indoor or outdoor use to provide a degree of protection to personnel against access to hazardous parts; to provide a degree of protection of the equipment inside the enclosure against ingress of solid foreign objects (falling dirt and windblown dust); to provide a degree of protection with respect to harmful effects on the equipment due to the ingress of water (rain, sleet, snow, splashing water, and hose directed water); that provides an increased level of protection against corrosion; and that will be undamaged by the external formation of ice on the enclosure.

Table 2-1
Comparison of Specific Applications of Enclosures for Indoor Nonhazardous
(Unclassified) Locations

Provides a Degree of Protection against the Following Conditions	Type of Enclosure									
	1	2	4	4X	5	6	6P	12	12K	13
Access to hazardous parts	X	X	X	X	X	X	X	X	X	X
Ingress of solid foreign objects (falling dirt)	X	X	X	X	X	X	X	X	X	X
Ingress of water (dripping and light splashing)	...	X	X	X	X	X	X	X	X	X
Ingress of solid foreign objects (circulating dust, lint, fibers, and flyings **)	...	...	X	X	...	X	X	X	X	X
Ingress of solid foreign objects (settling airborne dust, lint, fibers, and flyings **)	...	...	X	X	X	X	X	X	X	X
Ingress of water (hosedown and splashing water)	...	...	X	X	...	X	X	...	...	...
Oil and coolant seepage	...	...	...	...	...	...	...	X	X	X
Oil or coolant spraying and splashing	...	...	...	...	...	...	...	...	...	X
Corrosive agents	...	...	...	X	...	...	X	...	...	...
Ingress of water (occasional temporary submersion)	...	...	...	...	...	X	X	...	...	...
Ingress of water (occasional prolonged submersion)	...	...	...	...	...	...	X	...	...	...

** These fibers and flyings are not considered Class III type ignitable fibers or combustible flyings. For Class III type ignitable fibers or flyings see the *National Electrical Code*®, Article 500.5(D).

Table 2-2
Comparison of Specific Applications of Enclosures for Indoor & Outdoor Nonhazardous
(Unclassified) Locations

Provides a Degree of Protection Against the Following Conditions	Type of Enclosure									
	3	3X	3R	3RX	3S	3SX	4	4X	6	6P
Access to hazardous parts	X	X	X	X	X	X	X	X	X	X
Ingress of solid foreign objects (falling dirt)	X	X	X	X	X	X	X	X	X	X
Ingress of water (dripping and light splashing)	X	X	X	X	X	X	X	X	X	X
Ingress of water (rain, snow, and sleet **)	X	X	X	X	X	X	X	X	X	X
Sleet ***	...	...	...	...	X	X	...	...	...	...
Ingress of solid foreign objects (windblown dust, lint, fibers, and flyings****)	X	X	...	...	X	X	X	X	X	X
Ingress of water (hosedown and splashing water)	...	...	...	...	...	...	X	X	X	X
Corrosive agents	...	X	...	X	...	X	...	X	...	X
Ingress of water (occasional temporary submersion)	...	...	...	...	...	...	...	...	X	X
Ingress of water (occasional prolonged submersion)	...	...	...	...	...	...	...	...	...	X

** External operating mechanisms are not required to be operable when the enclosure is ice covered.

*** External operating mechanisms are operable when the enclosure is ice covered. See subsection 5.6.

**** These fibers and flyings are not considered Class III type ignitable fibers or combustible flyings. For Class III type ignitable fibers or flyings see the *National Electrical Code*®, Article 500.5(D).

**CTK Co., Ltd.**

5 Dongbu-ro 221beon-gil, Cheoin-gu, Yongin-si,
Gyeonggi-do, Republic of Korea
Tel: +82-31-339-9970
Fax: +82-31-624-9501

REPORT No. :
CTK-2025-03003
Page (10) / (28) pages

Table 5-1A
Degrees of Protection Against Access to Hazardous Parts

Enclosure Type	Test Conditions	Degree of Protection		Corresponding IP First Characteristic Numeral
		Brief Description	Definition	
4X	5.7	Protected against access to hazardous parts with a wire	An access probe of 1.0 mm shall not penetrate	6

Table 5-1B
Degrees of Protection Against Solid Foreign Objects

Enclosure Type	Test Conditions	Degree of Protection		Corresponding IP First Characteristic Numeral
		Brief Description	Definition	
4X	<u>Non-vented</u> 5.7	Windblown dust protected	No ingress of dust	6
	<u>Vented</u> 5.5.1 Dust Blast Method			

Table 5-1C
Degrees of Protection against Water

Enclosure Type	Test Conditions	Degree of Protection		Corresponding IP Second Characteristic Numeral
		Brief Description	Definition	
4X	5.7	Protected against hose directed water	Water projected against the enclosure in any direction shall not enter	6 No Ingress Allowed*

Table 5-1D
Additional Protection

Enclosure Type	Test Conditions	Additional Protection		Corresponding IP Second Characteristic Numeral
		Brief Description	Definition	
4X	5.6 5.9 5.10	Special corrosion protection and undamaged by the external formation of ice	Enclosure provides increased corrosion protection and is not damaged by ice that forms on the outside	None

**CTK Co., Ltd.**

5 Dongbu-ro 221beon-gil, Cheoin-gu, Yongin-si,
Gyeonggi-do, Republic of Korea
Tel: +82-31-339-9970
Fax: +82-31-624-9501

REPORT No. :
CTK-2025-03003
Page (11) / (28) pages

3.4 NEMA 250-2014 Test list

NEMA 250-2014			
Clause	Requirement + Test	Result – Remark	Verdict
3	CONSTRUCTION		
3.1	General		P
3.2	Units of Measurement		P
3.3	Materials-General	Enclosures are made of metal or polymeric materials	P
3.4	Materials-Polymeric	More than 650 mm ² (1 in ²) in area Polymeric Materials used is declared as Min. V-2 Used to UL certified material. (See the attachment 2)	N/E
3.5	Corrosion Protection	Stainless steel and/or aluminium are declared as the materials used (See the attachment 2)	N/E
3.6	Openings	No openings in Product	N/A
3.7	Mounting	Mounting means are external to the equipment cavity (See the attachment 1)	P
3.8	Conduit Connection	No conduit connection (See the attachment 1)	N/A
3.9	Hubs and Fittings	No Hubs and Fittings	N/A
3.10	Knockouts	See the Attachment 1	P
3.11	External Operating Mechanisms	No External Operating Mechanisms	N/A
3.12	Access to Interior	Needs tool to open unit	P
3.13	Closing Hardware	No closing Hardware	N/A

**CTK Co., Ltd.**

5 Dongbu-ro 221beon-gil, Cheoin-gu, Yongin-si,
Gyeonggi-do, Republic of Korea
Tel: +82-31-339-9970
Fax: +82-31-624-9501

REPORT No. :
CTK-2025-03003
Page (12) / (28) pages

NEMA 250-2014

Clause	Requirement + Test	Result – Remark	Verdict
3.14	Gaskets	Gaskets made of a silicone Sponge Rubber (no Elastomeric or Thermoplastic used) (See clause 5.14 and the attachment 2)	P
3.15	Observation Windows	No Observation Window	N/A

4	MARKING		
4.1	Type Designations	“Type 4X” Marking is declared to be on the product before on the market	P
4.2	Supplemental Markings	Supplemental Marking (watertight/corrosion resistant) is declared to be used when it is on the market. The required marking shall be added on the product)	P
4.3	Location of Markings	See the Attachment 3	P
4.4	Enclosure Orientation	No Particular Mounting Orientation	N/A
4.5	Conduit Hubs and Closure Plates	No Conduit Hubs and Closure Plates	N/A
4.6	Equipment Openings	No Openings on Unit	N/A
4.7	Drainage Openings	No Drain Openings	N/A

5	DESIGN TESTS		
5.1	General	See Table 5-1A to 5-1D and 5.1.5 in the General product information	P
5.2	Tests For Protection Against Access to Hazardous Parts	Rated 4X	N/A
5.3	Tests for Protection Against Ingress of Water (Dripping and Light Splashing)	Rated 4X	N/A

**CTK Co., Ltd.**

5 Dongbu-ro 221beon-gil, Cheoin-gu, Yongin-si,
Gyeonggi-do, Republic of Korea
Tel: +82-31-339-9970
Fax: +82-31-624-9501

REPORT No. :
CTK-2025-03003
Page (13) / (28) pages

NEMA 250-2014

Clause	Requirement + Test	Result – Remark	Verdict
5.4	Tests for Protection Against Ingress of Water (Rain)	Rated 4X	N/A
5.5	Tests for Protection Against Ingress of Solid Foreign Objects (Setting Airborne Dust, Lint, Fibers, And Flings)	Non-vented (See clause 5.7)	N/A
5.6	External Icing Test	No external cavities to trap water when mounted in the normal position.	N/A
5.7	Tests for Protection Against Ingress of Water (Hosedown)	No entry of water See the test information	P
5.8	Indoor Corrosion Protection (Rust-Resistance Test (24-Hour Salt Spray Test))	See clause 3.5	N/E
5.9	Outdoor Corrosion Protection	See clause 3.5	N/E
5.10	Corrosion Protection-Type 3X, 3RX, 3SX, 4X Or 6P Enclosures	See clause 3.5	N/E
5.11	Test for Protection Against Ingress of Water (Temporary Submersion)	Rated 4X	N/A
5.12	Test for Protection Against Ingress of Water (Prolonged Submersion)	Rated 4X	N/A
5.13	Oil Exclusion Test	Rated 4X	N/A
5.14	GASKET MATERIAL TESTS	The product itself(including gaskets) was conditioned at 70 °C for 168 hrs according to 5.14.3(Alternate Evaluation) before performing relevant required tests.	P
5.15	Test for Sharpness of Edges	No sharp edges	P




CTK Co., Ltd.

5 Dongbu-ro 221beon-gil, Cheoin-gu, Yongin-si,
Gyeonggi-do, Republic of Korea
Tel: +82-31-339-9970
Fax: +82-31-624-9501


REPORT No.:
CTK-2025-03003
Page (14) / (28) pages

3.5 Attachment 1 - Construction Diagram and installation method


3.5.1 Construction Diagram



3.5.2 installation method



3.5.3 installation method



**CTK Co., Ltd.**

5 Dongbu-ro 221beon-gil, Cheoin-gu, Yongin-si,
Gyeonggi-do, Republic of Korea
Tel: +82-31-339-9970
Fax: +82-31-624-9501

REPORT No.:
CTK-2025-03003
Page (17) / (28) pages

3.5.4 installation method

No.	Part Code	Part name	ea
1	FC18-004000A	SCREW-SPECIAL-PH,TR20,M4,L7+5	6
2	FC15-012305A	COVER-GLASS_IR_XNF-A9014R;PC	1
3	FC29-018500A	CASE-DOME_XNF-A9014RV;ADC12	1
4	HP07-002083A	GASKET-CASE-DOME_XNF-A9014RV	1
5	FC15-012305A	COVER-GLASS_IR_XNF-A9014R;PC	1
6	FC09-018801A	BRACKET-DOME_XNF-A9014R;SECC	1
7	Z6001055901A	SCREW-MACHINE;PWH,+,M3,L4,WHT	7
8	FC29-018418A	CASE-TOP-XNF-A9014R;ADC12	1
9	FC36-001015	SHEET-GORE-ACOUSTIC-GAW3250408P	3
10	FC10-001329A	RUBBER-MIC-XNF-A9014R;RUBBER,-	1
11	HP07-001567A	GASKET-CASE_TOP_XNF-9010RV	1
12	FC09-011731A	BRACKET-CASE_TOP_XNF-9010RV	1
13	AM06-012089A	ASSY,PCB-XNF-A9014RV_MIC	1
14	FC15-012163A	COVER-MIC-XNF-A9014R;ADC,-	1
15	Z6001055201A	SCREW-MACHINE;6001-001708,BH,+,M2,L5,ZP	12
16	Z6001053501A	SCREW-MACHINE;6001-001476,BH,+,M3,L6,Ni	8
17	FC28-004251A	REFLECTOR-IR_XNF-A9014R;-PC	1
18	AM06-012091A	ASSY,PCB-XNF-A9014RV_IR	1
19	FC36-001597A	SHEET-COVER-FRAME_XNF-A9014RV;PC SHEET	1
20	FC39-008057A	FRAME-MAIN-XNF-A9014R;ADC12	1
21	AM07-018056A	ASSY-MODULE-XNF-A9014R_FISHEYE	1
22	FC28-004148A	PAD-THERMAL-14X10XT2,7W/M-K	1
23	FC29-018417A	HOLDER-SENSOR-XNF-A9014R;ADC12	1
24	AM06-012093A	ASSY,PCB-XNF-A9014RV_SD	1
25	AM06-012095A	ASSY,PCB-XNF-A9014RV_SUB	1
26	FC38-001385A	SPRING,COM-PNV-A9082RZ;SUS304	2
27	FC18-005594A	SCREW,ETC-SHOULDER;0.5,-,PWH,M3	2
28	FC28-003323A	PAD-THERMAL-42X20X2T;K=7W/M-K	1
29	AM06-012045A	ASSY,PCB-XNF-A9014RV MAIN	1
30	FC28-004148A	PAD-THERMAL-14X10XT2,7W/M-K	1
31	FC28-002488A	PAD-THERMAL-17X17XT2,2W/M-K	1
32	FC28-004202A	PAD-THERMAL-49X20XT2;K=7.0W/M-K	1
33	HP07-001568A	GASKET-BOTTOM_XNF-9010RV	1
34	FC29-018433A	CASE-BOTTOM-XNF-A9014R;ADC12	1
35	FC15-007735A	COVER-CABLE_XNF-9010RV;-	1
36	MC06-001203A	BUSHING-CABLE-FLEXIBLE;SILICON,TUBE T0.5	2
37	FC18-001116A	SCREW-MACHINE-PH,T20,M4,L6,SUS,FP	1
38	FC39-006226C	MOUNT-PLATE_XNF-A9014RV;ADC12	1



CTK Co., Ltd.

5 Dongbu-ro 221beon-gil, Cheoin-gu, Yongin-si,
Gyeonggi-do, Republic of Korea
Tel: +82-31-339-9970
Fax: +82-31-624-9501

REPORT No.:
CTK-2025-03003
Page (18) / (28) pages

3.6 Attachment 2 - Parts List

3.6.1 Parts List (1)



Component - Plastics

HN-1068(f1)

Yellow Card™

LOTTE CHEMICAL CORPORATION

56 Gosan-ro
Uiwang-si, Gyeonggi-do 16073 Republic of Korea

File Number: E115797

INFINO: HN-1068(f1)

Polycarbonate (PC), pellets

(f1) - Suitable for outdoor use with respect to exposure to Ultraviolet Light, Water Exposure and Immersion in accordance with UL 746C.



Flammability	Value	Test Method
Flame Rating		UL 94
1.5 mm, ALL	V-0	IEC 60695-11-10, -20
3.0 mm, ALL	V-0	
Glow Wire Flammability Index		IEC 60695-2-12
1.5 mm	960 °C	
3.0 mm	960 °C	
Glow Wire Ignition Temperature		IEC 60695-2-13
1.5 mm	825 °C	
3.0 mm	825 °C	
Electrical	Value	Test Method
Hot-wire Ignition (HWI) (1.5 mm)	PLC 3	UL 746A
High Amp Arc Ignition (HAI) (1.5 mm)	PLC 3	UL 746A
Comparative Tracking Index (CTI)	PLC 3	UL 746A
Dielectric Strength	32 kV/mm	ASTM D149
Volume Resistivity	1.0E+17 ohms-cm	ASTM D257 IEC 60093
Thermal	Value	Test Method
RTI Elec		UL 746B
1.5 mm	130 °C	
3.0 mm	130 °C	
RTI Imp		UL 746B
1.5 mm	130 °C	
3.0 mm	130 °C	
RTI Str		UL 746B
1.5 mm	130 °C	
3.0 mm	130 °C	
Ball Pressure Test (130°C)	Pass	IEC 60695-10-2
Physical	Value	Test Method
Outdoor Suitability	f1	UL 746C



CTK Co., Ltd.

5 Dongbu-ro 221beon-gil, Cheoin-gu, Yongin-si,
Gyeonggi-do, Republic of Korea
Tel: +82-31-339-9970
Fax: +82-31-624-9501

REPORT No.:
CTK-2025-03003
Page (19) / (28) pages

3.6.2 Parts List (2)

Component - Plastics			Yellow Card™
S-2000+(f1), S-2001+(f1), S-2003+(f1)			
MITSUBISHI ENGINEERING-PLASTICS CORP			File Number: E41179
ENVIRONMENT & QUALITY ASSURANCE DEPT SHIODOME SUMITOMO-BLDG 25TH FL 1-9-2 HIGASHI-SHINBASHI MINATO-KU, Tokyo 105-0021 Japan			
Iupilon: S-2000+(f1), S-2001+(f1), S-2003+(f1)			
Polycarbonate (PC), insulating material, pellets, powder, sheets			
(f1) - Suitable for outdoor use with respect to exposure to Ultraviolet Light, Water Exposure and Immersion in accordance with UL 746C.			
+ - Suffix optional, exceptions: The following cannot be used as optional suffixes: "N" for grade MB2112+, "S1" for grade F20-54, "V" for grades S-2000+(f1), S-2001+(f1), S-2003+(f1), the last letter "L" for grade CFH2520+, "W" for ELV2010 included in Grade ELV20(a5)+, "V" for grade MB2210+, "K1" for grade EKD3206+ included in Grade EKD32(a6)+, "K2" for grade EKD2213+ included in Grade EKD22(a12)+, "DC" and "UDC" for grade MB4303+, "B9" for grades HL-30(#)(#)+(f1), HL-40(#)(#)+(f1), HL-50(#)(#)+(f1), HL-70(#)(#)+(f1), HL-80(#)(#)+(f1), HL-85(#)(#)+(f1), HL-90(#)(#)+(f1).			
			
Flammability	Value	Test Method	
Flame Rating			
3.0 mm, ALL	HB	UL 94	
6.0 mm, ALL	HB	UL 94	
0.38 mm, ALL	V-2	UL 94 IEC 60695-11-10, -20	
1.5 mm, ALL	V-2	UL 94 IEC 60695-11-10, -20	
1.8 mm, ALL	V-2	UL 94 IEC 60695-11-10, -20	
3.0 mm, ALL	HB40	IEC 60695-11-10, -20	
6.0 mm, ALL	HB40	IEC 60695-11-10, -20	
Electrical	Value	Test Method	
Hot-wire Ignition (HWI)		UL 746A	
1.5 mm	PLC 3		
1.8 mm	PLC 3		
3.0 mm	PLC 3		
6.0 mm	PLC 0		
High Amp Arc Ignition (HAI)		UL 746A	
1.5 mm	PLC 0		
1.8 mm	PLC 0		
3.0 mm	PLC 0		
6.0 mm	PLC 0		
Comparative Tracking Index (CTI)	PLC 2	UL 746A	
Dielectric Strength	20 kV/mm	ASTM D149	
High Voltage Arc Tracking Rate (HVTR)	PLC 0	UL 746A	
Volume Resistivity	1.0E+7 ohms-cm	ASTM D257 IEC 60093	
Arc Resistance	PLC 5	ASTM D495	



CTK Co., Ltd.

5 Dongbu-ro 221beon-gil, Cheoin-gu, Yongin-si,
Gyeonggi-do, Republic of Korea
Tel: +82-31-339-9970
Fax: +82-31-624-9501

REPORT No.:
CTK-2025-03003
Page (20) / (28) pages

3.6.3 Parts List (3)

Component - Plastics

S-2000+(f1), S-2001+(f1), S-2003+(f1)



Thermal	Value	Test Method
RTI Elec		UL 746B
0.38 mm	80.0 °C	
1.5 mm	125 °C	
1.8 mm	125 °C	
3.0 mm	125 °C	
6.0 mm	125 °C	
RTI Imp		UL 746B
0.38 mm	80.0 °C	
1.5 mm	115 °C	
1.8 mm	115 °C	
3.0 mm	115 °C	
6.0 mm	115 °C	
RTI Str		UL 746B
0.38 mm	80.0 °C	
1.5 mm	125 °C	
1.8 mm	125 °C	
3.0 mm	125 °C	
6.0 mm	125 °C	
Physical	Value	Test Method
Dimensional Change	0.0 %	ASTM D1042 ISO 2796
Outdoor Suitability	f1	UL 746C

**CTK Co., Ltd.**

5 Dongbu-ro 221beon-gil, Cheoin-gu, Yongin-si,
Gyeonggi-do, Republic of Korea
Tel: +82-31-339-9970
Fax: +82-31-624-9501

REPORT No.:
CTK-2025-03003
Page (21) / (28) pages

3.6.4 Parts List (4)

**Component - Plastics**
143(f1), 143R(f1)

Yellow Card™

SABIC JAPAN L L C
Moka Jp - Resin
2-2 Kinugaoka
Moka-Shi, Tochigi 321-4392 Japan

File Number: E45587

Lexan: 143(f1), 143R(f1)
Polycarbonate (PC), pellets
(f1) - Suitable for outdoor use with respect to exposure to Ultraviolet Light, Water Exposure and Immersion in accordance with UL 746C.
NOTE - Material designations may be followed by a color nomenclature consisting of either an alpha/numeric or a numeric/alpha combination.


ALSO CERTIFIED TO
IEC REQUIREMENTS

Flammability	Value	Test Method
Flame Rating		
0.75 mm, ALL	HB	UL 94
1.5 mm, ALL	HB	UL 94
3.0 mm, ALL	HB	UL 94
3.0 mm, ALL	HB40	IEC 60695-11-10, -20
0.75 mm, ALL	HB75	IEC 60695-11-10, -20
1.5 mm, ALL	HB75	IEC 60695-11-10, -20
Electrical	Value	Test Method
Hot-wire Ignition (HWI)		UL 746A
1.5 mm	PLC 4	
3.0 mm	PLC 4	
High Amp Arc Ignition (HAI)		UL 746A
1.5 mm	PLC 2	
3.0 mm	PLC 1	
Comparative Tracking Index (CTI)	PLC 2	UL 746A
High Voltage Arc Tracking Rate (HVTR)	PLC 2	UL 746A
Thermal	Value	Test Method
RTI Elec		UL 746B
0.75 mm	120 °C	
1.5 mm	130 °C	
3.0 mm	130 °C	
RTI Imp		UL 746B
0.75 mm	120 °C	
1.5 mm	125 °C	
3.0 mm	130 °C	
RTI Str		UL 746B
0.75 mm	120 °C	
1.5 mm	125 °C	
3.0 mm	130 °C	



CTK Co., Ltd.

5 Dongbu-ro 221beon-gil, Cheoin-gu, Yongin-si,
Gyeonggi-do, Republic of Korea
Tel: +82-31-339-9970
Fax: +82-31-624-9501

REPORT No. :
CTK-2025-03003
Page (22) / (28) pages

3.6.5 Parts List (5)

Component - Plastics

143(f1), 143R(f1)



Physical	Value	Test Method
Dimensional Change	0.0 %	ASTM D1042 ISO 2796
Outdoor Suitability	f1	UL 746C



CTK Co., Ltd.

5 Dongbu-ro 221beon-gil, Cheoin-gu, Yongin-si,
Gyeonggi-do, Republic of Korea
Tel: +82-31-339-9970
Fax: +82-31-624-9501

REPORT No.:
CTK-2025-03003
Page (23) / (28) pages

3.6.6 Parts List (6)



Component - Plastics

EXL1434T(GG)

Yellow Card™

SABIC JAPAN L L C

PACIFIC GRADES - RESIN
2-2 KINUGAOKA
MOKA-SHI, Tochigi 321-4392 Japan

File Number: E207780

Lexan, Elcres: EXL1434T(GG)

PC/Siloxane, UV Stabilized, pellets

(GG) - Denotes a global grade formulation previously in File E161759.

NOTE - Material designation may be followed by a color nomenclature consisting of either an alpha/numeric or numeric/alpha combination.



ALSO CERTIFIED TO IEC REQUIREMENTS

Flammability	Value	Test Method
Flame Rating		
0.40 mm, ALL	HB	UL 94
0.8 mm, ALL	HB	UL 94
1.5 mm, ALL	HB	UL 94
2.5 mm, ALL	HB	UL 94
3.0 mm, ALL	V-2	UL 94 IEC 60695-11-10, -20
0.40 mm, ALL	HB75	IEC 60695-11-10, -20
0.8 mm, ALL	HB75	IEC 60695-11-10, -20
1.5 mm, ALL	HB75	IEC 60695-11-10, -20
2.5 mm, ALL	HB75	IEC 60695-11-10, -20
Glow Wire Flammability Index		IEC 60695-2-12
0.40 mm	825 °C	
0.8 mm	825 °C	
1.5 mm	825 °C	
2.5 mm	825 °C	
3.0 mm	960 °C	
Glow Wire Ignition Temperature		IEC 60695-2-13
0.40 mm	850 °C	
0.8 mm	850 °C	
1.5 mm	850 °C	
2.5 mm	850 °C	
3.0 mm	850 °C	
Thermal	Value	Test Method
RTI Elec		UL 746B
0.40 mm	80.0 °C	
0.8 mm	80.0 °C	
1.5 mm	130 °C	
2.5 mm	130 °C	
3.0 mm	130 °C	



CTK Co., Ltd.

5 Dongbu-ro 221beon-gil, Cheoin-gu, Yongin-si,
Gyeonggi-do, Republic of Korea
Tel: +82-31-339-9970
Fax: +82-31-624-9501

REPORT No.:
CTK-2025-03003
Page (24) / (28) pages

3.6.7 Parts List (7)

Component - Plastics

EXL1434T(GG)



Thermal	Value	Test Method
RTI Imp		UL 746B
0.40 mm	80.0 °C	
0.8 mm	80.0 °C	
1.5 mm	120 °C	
2.5 mm	120 °C	
3.0 mm	120 °C	
RTI Str		UL 746B
0.40 mm	80.0 °C	
0.8 mm	80.0 °C	
1.5 mm	130 °C	
2.5 mm	130 °C	
3.0 mm	130 °C	

**CTK Co., Ltd.**

5 Dongbu-ro 221beon-gil, Cheoin-gu, Yongin-si,
Gyeonggi-do, Republic of Korea
Tel: +82-31-339-9970
Fax: +82-31-624-9501

REPORT No. :
CTK-2025-03003
Page (25) / (28) pages

4. Hose Down Test (Clause 5.7)

4.1 Test date and environmental conditions

4.1.1 Test date: Oct. 10, 2025~ Oct. 17, 2025

4.1.2 Measured Environmental Conditions

Item	Temperature (°C)	Humidity (% R.H.)	Pressure (kPa)
Measurement	25.1	59.8	103.2

4.2 Test Conditions and methods

4.2.1 Description of Test

The enclosure and its external mechanisms were subjected to a stream of water from a hose that has a 25.4 mm (1 in) inside diameter nozzle and delivers at least 240 L (65 gal) per minute. The nozzle was held from 3.0 to 3.5 m (10 to 12 feet) from the enclosure, and the spray of water was directed at all points of potential water entry such as seams, joints, external operating mechanisms, and such. The nozzle was moved along each test point one time at a uniform rate of 6 mm/sec (1/4 in/sec).

4.2.2 Sample Dimension

Ø180 by 565.2 mm, Ø100 by 314 mm, Ø25*2 by 157 mm, Ø 8.5*4 by 106.76 mm
Test Duration = 190.49 secs

4.2.3 Acceptance conditions

The enclosure shall be considered to have met the requirements if at the conclusion of the test no water has entered the enclosure



CTK Co., Ltd.

5 Dongbu-ro 221beon-gil, Cheoin-gu, Yongin-si,
Gyeonggi-do, Republic of Korea
Tel: +82-31-339-9970
Fax: +82-31-624-9501

REPORT No.:
CTK-2025-03003
Page (26) / (28) pages

4.3 Attachment 3 - Photographs

4.3.1 Hose down test



**CTK Co., Ltd.**

5 Dongbu-ro 221beon-gil, Cheoin-gu, Yongin-si,
Gyeonggi-do, Republic of Korea
Tel: +82-31-339-9970
Fax: +82-31-624-9501

REPORT No.:
CTK-2025-03003
Page (27) / (28) pages

4.4 Test result**4.4.1 Test result table**

Sample No (Model)	Water Flow	Presence of water inside	Result
XNF-A9014RV	240 LPM	No	Normal

※ Refer to the product photos after the completion of testing in section 4.5.



CTK Co., Ltd.

5 Dongbu-ro 221beon-gil, Cheoin-gu, Yongin-si,
Gyeonggi-do, Republic of Korea
Tel: +82-31-339-9970
Fax: +82-31-624-9501

REPORT No.:
CTK-2025-03003
Page (28) / (28) pages

4.5 Post-test product images

4.5.1 Test sample image



- End -