



Network

Bullet

# XNO-6080R

2M Ağ IR Bullet Kamera

## Key Features

- En Faz. 2 megapiksel (1920 x 1080) çözünürlük
- 2.8 ~ 12mm (4.3x) motorize değişken odaklı lens
- Tüm çözünürlüklerde en fazla 60 fps (H.265/H.264)
- H.265, H.264, MJPEG kodek destekli, Çoklu akış
- Gündüz ve Gece (ICR), WDR (150dB), Sis Giderme
- İşgal Etme, Yön algılama, Sis algılama, Ses algılama, Dijital otom. izleme, Ses sınıflandırması, Kurcalama
- Hareket algılama, Devir
- SD/SDHC/SDXC bellek yuvası (En fazla 512 GB)
- Koridor izleme, WiseStream II desteği
- IR görüntülenebilir uzunluk 50m, IP67/IP66, NEMA 4X, IK10
- LDC desteği (Lens Bozulmasını Düzeltme)
- PoE / 24V AC, 12V DC, İki yönlü ses desteği

## Compatible Devices



SBP-302PM

## XNO-6080R

2M Ağ IR Bullet Kamera



### Specifications

| Video                         |                       |                                                                                                                   |
|-------------------------------|-----------------------|-------------------------------------------------------------------------------------------------------------------|
| Imaging Device                | Size                  | 1/2.8"                                                                                                            |
|                               | Type                  | CMOS                                                                                                              |
| Resolution                    |                       | 1920x1080, 1280x1024, 1280x960, 1280x720, 1024x768, 800x600, 800x448, 720x576, 720x480, 640x480, 640x360, 320x240 |
| Max. Framerate                | H.265/H.264           | 60fps/50fps(60Hz/50Hz)                                                                                            |
|                               | MJPEG                 | 30fps                                                                                                             |
| Min. Illumination (Lux)       | Color(1/30sec, 30IRE) | 0.015                                                                                                             |
|                               | BW(1/30sec, 30IRE)    | 0.0015                                                                                                            |
| Video Out                     |                       | CVBS: 1.0 Vp-p / 75Ω composite for installation,<br>USB: Micro USB Type B                                         |
| Lens                          |                       |                                                                                                                   |
| Focal Length (mm)             |                       | 2.8~12                                                                                                            |
| Zoom Ratio                    | Optical               | 4.3x                                                                                                              |
| Max Aperture Ratio (F number) | Wide                  | 1.4                                                                                                               |
|                               | Tele                  | 3.6                                                                                                               |
| Angular Field of View         | Horizontal            | 119.5°~27.9°                                                                                                      |
|                               | Vertical              | 62.8°~15.7°                                                                                                       |
|                               | Diagonal              | 142.1°~32.0°                                                                                                      |
| Min. Object Distance          |                       | 0.5m(1.64ft)                                                                                                      |
| Focus Control                 |                       | Simple focus, Manual                                                                                              |
| Lens Type                     |                       | DC auto iris(IR corrected)                                                                                        |
| Operational                   |                       |                                                                                                                   |
| Day & Night                   |                       | Auto(ICR)                                                                                                         |
| Backlight Compensation        |                       | BLC, HLC, WDR, SSDR                                                                                               |
| Wide Dynamic Range (dB)       |                       | 150                                                                                                               |
| Digital Noise Reduction       |                       | SSNR V                                                                                                            |
| Digital Image Stabilization   |                       | Support                                                                                                           |
| Defog                         |                       | Support                                                                                                           |

## Operational

|                                          |                |                                                                                                                                                                                             |
|------------------------------------------|----------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Motion Detection                         | Quantity       | 8ea                                                                                                                                                                                         |
|                                          | Shape          | 8point Polygonal zones                                                                                                                                                                      |
| Privacy Masking                          | Quantity       | 32ea                                                                                                                                                                                        |
|                                          | Shape          | 4point Quadrangle zones                                                                                                                                                                     |
|                                          | Color / Option | Gray, Green, Red, Blue, Black, White, Mosaic                                                                                                                                                |
| Gain Control                             |                | Low, Middle, High                                                                                                                                                                           |
| White Balance                            |                | ATW, AWC, Manual, Indoor, Outdoor                                                                                                                                                           |
| LDC                                      |                | Support                                                                                                                                                                                     |
| Electronic Shutter                       | Mode           | Minimum, Maximum, Anti flicker                                                                                                                                                              |
|                                          | Speed Range    | 2~1/12,000sec                                                                                                                                                                               |
| Video Rotation                           |                | Flip, Mirror, Hallway view(90°/270°)                                                                                                                                                        |
| Alarm Interface                          | In/Out         | Input 1ea, Output 1ea                                                                                                                                                                       |
| Alarm Triggers                           |                | Analytics, Network disconnect, Alarm input                                                                                                                                                  |
| Alarm Events When Alarm Trigger Occurred |                | File upload(image): e-mail/FTP,<br>Notification: e-mail,<br>Recording: SD/SDHC/SDXC or NAS recording at event triggers,Alarm output,<br>Handover: PTZ preset,send message by HTTP/HTTPS/TCP |
| Audio In                                 |                | Selectable(mic in/line in)                                                                                                                                                                  |
| Audio Out                                |                | Line out                                                                                                                                                                                    |
| Light Type                               |                | IR LED                                                                                                                                                                                      |
| Light Viewable Length                    | IR             | 50m(164.04ft)                                                                                                                                                                               |
| IR Wavelength                            |                | 850nm                                                                                                                                                                                       |

## Analytics

|                  |        |                                                                                                                                                                                                                                                  |
|------------------|--------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Analytics Events | Normal | Defocus detection, Motion detection, Tampering, Fog detection, Face detection, Audio detection, Sound classification, Virtual area(Lotering, Intrusion, Enter/Exit, Appear/Disappear), Virtual line(Crossing, Direction) , Digital auto tracking |
|------------------|--------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|

## Network

|                   |                    |                                                                                                                               |
|-------------------|--------------------|-------------------------------------------------------------------------------------------------------------------------------|
| Ethernet          |                    | RJ-45(10/100BASE-T)                                                                                                           |
| Video Compression |                    | H.265/H.264: Main/Baseline/High, MJPEG                                                                                        |
| Audio Compression |                    | G.711 u-law /G.726 selectable,G.726(ADPCM) 8kHz,G.711 8kHz,<br>G.726: 16kbps,24kbps,32kbps,40kbps,<br>AAC-LC: 48kbps at 16kHz |
| Smart Codec       |                    | Manual, WiseStream II                                                                                                         |
| Bitrate Control   |                    | H.265/H.264: CBR or VBR,<br>MJPEG: VBR                                                                                        |
| Streaming         | Unicast            | Up to 20 users                                                                                                                |
|                   | Multicast          | Support                                                                                                                       |
|                   | Multiple Streaming | Up to 10 profiles                                                                                                             |

## Network

|                                   |        |                                                                                                                                                                                                            |
|-----------------------------------|--------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Protocol                          |        | IPv4, IPv6, TCP/IP, UDP/IP, RTP(UDP), RTP(TCP), RTCP, RTSP, NTP, HTTP, HTTPS, SSL/TLS, DHCP, FTP, SMTP, ICMP, IGMP, SNMPv1/v2c/v3(MIB-2), ARP, DNS, DDNS, QoS, UPnP, Bonjour, LLDP, SRTP(TCP, UDP Unicast) |
| Application Programming Interface | ONVIF  | S, G, T                                                                                                                                                                                                    |
|                                   | Others | SUNAPI(HTTP API), Hanwha Vision Open Platform                                                                                                                                                              |
| Direct Cloud Connection           |        | Optional (needs gateway)                                                                                                                                                                                   |

## Security

|                        |  |                                                                         |
|------------------------|--|-------------------------------------------------------------------------|
| OS / Firmware Protect  |  | Encrypted firmware, Secure boot, Signed firmware                        |
| User authentication    |  | Digest authentication                                                   |
| Network authentication |  | IEEE 802.1X(EAP-TLS, EAP-LEAP)                                          |
| Secure Communication   |  | HTTPS, WSS(WebSocket Secure), SRTP                                      |
| Access Control         |  | IP-based access control                                                 |
| Data Protect           |  | Encryption credentials, Encrypt compress for live recording file export |
| Audit                  |  | Access / System / Event Log management                                  |
| Secure Storage         |  | SDcard partition encrypt(AES-256)                                       |

## General

|              |                    |                               |
|--------------|--------------------|-------------------------------|
| Memory       | RAM                | 1GB                           |
|              | Flash              | 256MB                         |
| Edge Storage | Micro SD/SDHC/SDXC | Max. 512GB x 2slot(Total 1TB) |

## Environmental & Electrical

|                     |             |                                        |
|---------------------|-------------|----------------------------------------|
| Operating Condition | Temperature | -40°C~+55°C(-40°F~+131°F)              |
|                     | Humidity    | 0~90% RH(non-condensing)               |
|                     | Others      | Built-in heater for anti-frosting      |
| Storage Condition   | Temperature | -50°C~+60°C(-58°F~+140°F)              |
|                     | Humidity    | 0~90% RH(non-condensing)               |
| Input Voltage       |             | PoE(IEEE802.3af, Class3), 12VDC, 24VAC |
| Power Consumption   | PoE         | Max. 12.95W                            |
|                     | 12VDC       | Max. 12W                               |
|                     | 24VAC       | Max. 15W                               |

## Mechanical

|                    |  |                          |
|--------------------|--|--------------------------|
| Color              |  | Dark grey                |
| Material           |  | Aluminum                 |
| Product Dimensions |  | ø91x368.6mm(3.85x14.51") |
| Product Weight     |  | 2,180g(4.8lb)            |

**Certifications & Standards**

|             |                                                                  |
|-------------|------------------------------------------------------------------|
| Environment | IEC 60529 IP66, IEC 60529 IP67, IEC 62262 IK10, NEMA 250 type 4X |
|-------------|------------------------------------------------------------------|

# XNO-6080R

2M Aġ IR Bullet Kamera



**CAD**

Unit: mm [inch]

