TEST REPORT

KES Co., Ltd.
#3002, #3503, #3701, 40, Simin-daero365beon-gil, Dongan-gu, Anyang-si, Gyeonggi-do, 14057, Republic of Korea
Tel : +82-31-425-6200, Fax : +82-31-341-3838

1. Client

○ Name	:	Hanwha Vision Co., Ltd.
○ Address	:	6, Pangyo-ro 319beon-gil, Bundang-gu, Seongnam-si, Gyeonggi-do, Republic of Korea

2. Sample Description

◯ Product item	:	NETWORK CAMERA
◯ Model name	:	XNP-A6374RH
◯ Variant model	:	-
◯ Manufacturer etc.	:	HANWHA VISION VIETNAM COMPANY LIMITED
◯ Manufacturer address	:	Lot O-2, Que Vo Industrial Zone Extended Area, Nam Son Ward, Bac Ninh Province, Vietnam
◯ Manufacturer etc.	:	D-TECH CO.,LTD.
◯ Manufacturer address	:	173-25, Saneop-ro, Gwonseon-gu, Suwon-si, Gyeonggi-do, Korea (Suwon Industrial Complex)

3. Date of test : 2026. 04. 01. ~ 2026. 04. 03.

4. Location of Test : Permanent Testing Lab

○ Address : 473-21, Gayeo-ro, Yeoju-si, Gyeonggi-do, 12658, Republic of Korea

5. Test method used : EN 55032:2015/A1:2020, EN 50130-4:2011/A1:2014, EN IEC 61000-3-2:2019, EN 61000-3-3:2013/A2:2021

6. Test result : PASS

The results shown in this test report refer only to the sample(s) tested unless otherwise stated.
This test report cannot be reproduced and copied without permission without the written consent of KES Co., Ltd.
This laboratory is not accredited for the test results marked *.
This test report is not related to KOLAS accreditation.

Affirmation	Tested by	Technical Manager by
	Name : SeongMin Jang [장성민]2026/04/08	Name : DongHun Jang [장동훈]2026/04/08

2026. 04. 08.

KES Co., Ltd.

You can check the authenticity of this test report on the authenticity verification page on our website (www.kes.co.kr).

REPORT REVISION HISTORY

Date	Test Report No.	Revision History
2026. 04. 08.	KES-EM260876	Issued

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd. This document may be altered or revised by KES Co., Ltd. personnel only, and shall be noted in the revision section of the document. Any alteration of this document not carried out by KES Co., Ltd. will constitute fraud and shall nullify the document.

Use of uncertainty of measurement for decisions on conformity (decision rule):

■ No decision rule is specified by the standard, when comparing the measurement result with the applicable limit according to the specification in that standard. The decisions on conformity are made without applying the measurement uncertainty(“simple acceptance” decision rule, previously known as “accuracy method”).

□ Other (to be specified, for example when required by the standard or client)

TABLE OF CONTENTS

1 Laboratory Information 4
1.1 Test Location 4
1.2 Laboratory Accreditations and Listings 4
2 Test Summary 5
2.1 Class and Voltage 5
2.2 Summary of Test Results 5
2.3 Remarks when standards applied 6
2.4 Variant Model Differences 6
2.5 Device Modifications 6
3 General Product Description 7
4 EUT Setup and Operation Mode 10
4.1 EUT Configuration 10
4.2 System Configuration 10
4.3 External I/O Cabling 11
4.4 EUT Operating Mode(s) 12
4.5 Test operating S/W 12
4.6 Configuration 13
5 General Performance Criteria 14
6 Test Item 16
6.1 Conducted Emissions at Mains Power Ports 16
6.2 Conducted Emissions at Telecommunication Ports 19
6.3 Radiated Emissions(Below 1 ㎓) 22
6.4 Radiated Emissions(Above 1 ㎓) 25
6.5 Harmonic Current Emissions 28
6.6 Voltage Fluctuations and Flicker 31
6.7 Electrostatic Discharge 33
6.8 Continuous RF electromagnetic field disturbances 37
6.9 Electrical Fast Transients/Bursts 40
6.10 Surge 43
6.11 Continuous Induced RF Disturbances 45
6.12 Voltage Dips and Interruptions 48
7 Test Setup Photos and EUT Photographs 50
7.1 Test Setup Photos 50
7.2 EUT Photographs 63
7.3 Label 68

You can check the authenticity of this test report on the authenticity verification page on our website (www.kes.co.kr).

1 Laboratory Information

1.1 Test Location

Category	Details
Addres	473-21, Gayeo-ro, Yeoju-si, Gyeonggi-do, 12658, Republic of Korea
Telephone Number	031-883-5092
Facsimile Number	031-883-5169

The measurement facility is located at 473-21, Gayeo-ro, Yeoju-si, Gyeonggi-do, 12658, Korea, Republic of. The sites are constructed in conformance with the requirements of ANSI C63.4a-2017 and CISPR 16-1-4:2019

1.2 Laboratory Accreditations and Listings

Country	Agency	Scope of Accreditation	Logo
KOREA	**RRA**	EMI (3 m & 10 m Semi-Anechoic Chamber and conducted test site) EMS (ESD, RS, EFT/Burst, Surge, CS, Magnetic, Dips and interruptions)	KR0100
International	**KOLAS**	EMI (3 m & 10 m Semi-Anechoic Chamber and conducted test site) EMS (ESD, RS, EFT/Burst, Surge, CS, Magnetic, Dips and interruptions)	KT489
USA	**FCC**	3 m & 10 m Semi-Anechoic Chamber Conducted test site to perform FCC Part 15/18 measurements.	KR0100
Canada	**ISED**	3 m & 10 m Semi-Anechoic Chamber and Conducted test site	23298
JAPAN	**VCCI**	EMI (3 m & 10 m Semi-Anechoic Chamber and conducted test site)	C-20136, T-20137, R-20181, G-20176
Europe	**TÜV SÜD**	EMI (3 m & 10 m Semi-Anechoic Chamber and conducted test site) EMS (ESD, RS, EFT/Burst, Surge, CS, Magnetic, Dips and interruptions)	CARAT 001633 0008

You can check the authenticity of this test report on the authenticity verification page on our website (www.kes.co.kr).

2 Test Summary

2.1 Class and Voltage

Test Class	Test Voltage
Class A	AC 230 V, 50 Hz, PoE

2.2 Summary of Test Results

Regulation
EMC Directive 2014/30/EU, EMC Regulations SI 2016/1091

Test Item	Test Standard		Test Result	Remark
Conducted Emissions at Mains Power Ports	EN 55032:2015+A1:2020		PASS	NOTE 1
Conducted Emissions at Telecommunication Ports			PASS	-
Radiated Emissions(Below 1 ㎓)			PASS	-
Radiated Emissions(Above 1 ㎓)			PASS	-
Harmonic Current Emissions	EN IEC 61000-3-2:2019		PASS	NOTE 1
Voltage Fluctuations and Flicker	EN 61000-3-3:2013+A2:2021		PASS	NOTE 1
Electrostatic Discharge	EN 50130-4:2011+A1:2014	EN 61000-4-2:2009	PASS	-
Continuous RF electromagnetic field disturbances		EN IEC 61000-4-3:2020	PASS	-
Electrical Fast Transients/Bursts		EN 61000-4-4:2012	PASS	NOTE 1
Surge		EN 61000-4-5 :2014+A1:2017	PASS	NOTE 1
Continuous Induced RF Disturbances		EN IEC 61000-4-6:2023	PASS	NOTE 1
Voltage Dips and Interruptions		EN IEC 61000-4-11:2020	PASS	NOTE 1

* N/A: Not Applicable

(NOTE 1) PoE Power Mode is powered by the PoE port, PoE port is considered to be wired network port, so power-related test items are excluded.

You can check the authenticity of this test report on the authenticity verification page on our website (www.kes.co.kr).

2.3 Remarks when standards applied
N/A

2.4 Variant Model Differences
N/A

2.5 Device Modifications
N/A

You can check the authenticity of this test report on the authenticity verification page on our website (www.kes.co.kr).

3 General Product Description

	XNP-A6374RH
Video	
Imaging Device	1/2" 2MP CMOS
Resolution	1920x1080, 1280x1024, 1280x960, 1280x720, 1024x768, 800x600, 800x448, 720x576, 720x480, 640x480, 640x360, 320x240
Max. Framerate	H.265/H.264: Max. 60fps/50fps(60Hz/50Hz) MJPEG: Max. 30fps/25fps(60Hz/50Hz)
NETD	None
Pixel Size	None
Min. Illumination	Color: 0.01Lux(F1.5, 1/30sec) BW: 0Lux(IR LED On)
Video Out	CVBS: 1.0 Vp-p / 75Ω composite, 720x480(N), 720x576(P) for installation
Video Transmission Distance	None
Lens	
Focal Length (Zoom Ratio)	6~222mm(37x) zoom
Optical Zoom	37x
Max. Aperture Ratio	F1.5(Wide)~F4.6(Tele)
Angular Field of View	H: 59.3°(Wide)~1.90°(Tele) / V: 35.8°(Wide)~1.1°(Tele)
Min. Object Distance	3.0m
Focus Control	AF / One-Shot AF / Manual
Lens Type	DC auto iris
Mount Type	None
Optional Lens	None
Pan / Tilt / Rotate	
Pan / Tilt / Rotate Range	None
Pan Range	360° Endless
Pan Speed	Preset: 400°/sec, Manual: 0.024°/sec~250°/sec
Tilt Range	95°(-5°~90°)
Tilt Speed	Preset: 300°/sec, Manual: 0.024°/sec ~ 250°/sec (TBD- eflip)
Rotate Range	None
Sequence	Preset(300ea), Swing, Group(6ea), Trace, Tour, Auto Run, Schedule
Preset Accuracy	±0.2°
Operational	
Camera Title	Displayed up to 127 characters
Direction Indicator	Support
Day & Night	Auto(ICR)
Backlight Compensation	BLC, HLC, WDR, SSDR
Wide Dynamic Range	150dB - TBD
Digital Noise Reduction	WiseNRII(Based on AI engine), SSNRV
Digital Image Stabilization	Support(built-in gyro sensor)
Defog	Support
Motion Detection	8ea, 8point polygonal zones
Privacy Masking	Setting area : 32ea, quadrangle zones - 8points(after R/C) - Color: Gray/Green/Red/Blue/Black/White - Mosaic Dynamic Privacy Mask(Based on AI engine) - Color: gray/green/red/blue/black/white/purple/yellow - Mosaic

You can check the authenticity of this test report on the authenticity verification page on our website (www.kes.co.kr).

Gain Control	Low / Middle / High
White Balance	ATW / NarrowATW / AWC / Manual / Indoor / Outdoor / Mercury / Sodium
LDC	None
Electronic Shutter Speed	Minimum / Maximum / Anti flicker (2~1/30,000sec) Prefer shutter control(Based on AI engine)
Digital PTZ	None
Video Rotation	Flip, Mirror
Analytics	Classified object type: Person/Face/Vehicle/License plate Attributes: - Vehicle: (Type: car/bus/truck/motorcycle/bicycle, Color) - Person:(Gender, Clothing top/bottom color, Bag), Face(Age, Gender, Mask, Glasses) Support BestShot Support Re-ID(Person) Analytics events based on AI engine: Motion detection, Object detection, Line crossing(Crossing/Direction), IVA area(Loitering/Intrusion/Enter/Exit/Appear/Disappear), Slip & fall detection Analytics events: Tampering, Shock detection, Audio detection Support analytics by AI pack (WiseAI, Sound pack)
Business Intelligence	None
Serial Interface	RS-485(Samsung-T, Pelco-D/P, Panasonic, Bosch, AD, GE, Vicon, Honeywell)
Alarm I/O	Input 4ea / Output 2ea
Alarm Triggers	Analytics, Network disconnect, Alarm input), Time schedule, MQTT subscription
Alarm Events	When alarm trigger occurred File upload(image): e-mail/FTP/SFTP File upload(video clip): FTP/SFTP Notification: e-mail Recording: SD/SDHC/SDXC or NAS recording at event triggers Alarm output Handover: PTZ preset, send message by HTTP/HTTPS/TCP Audio clip playback(WAV, MP3) MQTT: publication
Audio Streaming	None
Audio In	Selectable(mic in/line in) Supply voltage: 2.5VDC(4mA), Input impedance: 2K Ohm
Audio Out	Line out, Max.output level: 1Vrms
Light Type	IR LED (850nm)
Light Viewable Length	None
IR Viewable Length	350m(1,148.29ft)
IR Illuminator (Optional)	None
IR Radiation angle	None
IR LED	None
IR Wavelength	None
IR Operation	None
Water Removal	None
Auto Tracking	Support Object auto tracking(Person/Vehicle) Target lock tracking
Coaxial Protocol	None
Color Palettes	None
Radiometry	
Temperature Detect Range	None
Temperature Accuracy	None
Temperature Detection	None
Additional	None

You can check the authenticity of this test report on the authenticity verification page on our website (www.kes.co.kr).

Network	
Ethernet	Metal shielded RJ-45(10/100BASE-T), SFP(Optional)
Video Compression	H.265/H.264: Main/Baseline/High, MJPEG
Audio Compression	G.711 u-law /G.726 Selectable G.726(ADPCM) 8KHz, G.711 8KHz G.726: 16Kbps, 24Kbps, 32Kbps, 40Kbps AAC-LC: 48Kbps at 16KHz
Smart Codec	WiseStream(Based on AI engine)
Video Quality Adjustment	None
Bitrate Control	H.264/H.265: CBR or VBR MJPEG: VBR
Streaming	Unicast(20 users) / Multicast (128 user) Multiple streaming(Up to 10 profiles)
Protocol	IPv4, IPv6, TCP/IP, UDP/IP, RTP(UDP), RTP(TCP), RTCP, RTSP, NTP, HTTP, HTTPS, SSL/TLS, DHCP, FTP/SFTP, SMTP, ICMP, IGMP, SNMPv1/v2c/v3(MIB-2), ARP, DNS, DDNS, QoS, UPnP, Bonjour, LLDP, CDP, SRTP(TCP, UDP Unicast) , NTCIP 1205, MQTT
SIP support (VoIP, Peer-to-peer,	Support
Security	None
Application Programming Interf	ONVIF Profile S/G/T/M SUNAPI(HTTP API) Hanwha Vision Open Platform: - WiseAI application included - Cloud connector application included - Sound classification(Based on AI engine) application included
Security	
OS / Firmware Protect	Encrypted Firmware, Secure boot, Signed Firmware
User authentication	Digest Authentication, Prevent brute-force attacks
Network authentication	802.1X Authentication(EAP-TLS, EAP-LEAP, EAP-PEAP MSCHAPv2), 802.1AE(MACsec)
Secure Communication	IP-based access control, MAC-based access control, Auto logout
Access Control	IP-based access control
Data Protect	Encryption Credentials, Encrypt compress for live recording file export
Audit	Access / System / Event Log management
Device ID	Device certificate(Hanwha Vision Root CA)
Secure Storage	Secure element, SDcard partition encrypt
Supply Chain Security	SBOM
Security Certificate	ETSI EN 303 645, Secure element(FIPS 140-3 level3, CC EAL6+), 국정원인증(RK)
General	
Webpage Language	English, Korean, Simplified Chinese, Traditional Chinese, French, Italian, Spanish, German, Japanese, Russian, Portuguese, Czech, Polish, Turkish, Dutch, Hungarian, Greek
Web Viewer	None
Edge Storage	Micro SD/SDHC/SDXC 1slot Max. 1TB * Hanwha Vision branded microSD cards have been certified and recommended for OnCloud edge recording.
Memory	4GB RAM, 16GB eMMC
Environmental & Electrical	
Operating Temperature / Humic	-50°C ~ +55 C°(-58°F ~ +131°F)
Storage Temperature / Humidity	-50°C ~ +60°C (-58°F~+140°F) / Less than 90% RH
Certification	IP66, IK10
Input Voltage	24VAC, PoE++(IEEE802.3bt type3, Class6)
Power Consumption	24VAC: Max 82.4W Typical 27.3W, PoE: Max 51W Typical 26.6W
Mechanical	
Color / Material	Body: White / Aluminum+Plastic, Head: Black / Aluminum+Plastic
RAL Code	RAL9003
Product Dimensions / Weight	ø236.9x407.7mm(9.33x16.05"), 7020g(15.48 lb)

You can check the authenticity of this test report on the authenticity verification page on our website (www.kes.co.kr).

4 EUT Setup and Operation Mode

4.1 EUT Configuration

Product Name	Model Number	Serial Number	Manufacturer	Remarks
NETWORK CAMERA	XNP-A6374RH	-	HANWHA VISION VIETNAM COMPANY LIMITED	EUT
AC/AC Adapter	MKAC-96-246000K	-	Shenzhen MaCable Technology Co., Ltd Dongguan Branch	-
PoE Injector	PT-PSE109GBRO-AH-S	-	Dongguan PROCET Network Technology Co.,Ltd	-
Laptop	NT550XDZ	-	Samsung Electronics	-
Laptop AC/DC Adapter	AD-4019A	-	Chicony	-
Alarm	PRO-SL	-	SENSOR PRO	-
Button Alarm	-	-	-	-
Controller	SPC-1010	C50E67WG10100F	SamSung Techwin Co.,Ltd.	-
Controller AC/DC Adapter	AP-12005A	-	Apower	-
Headset	K550	-	Britz®	-
Micro SD Card	-	-	SanDisk	-

4.2 System Configuration

Product Name	Model Number	Serial Number	Manufacturer	Remarks
-	-	-	-	-

You can check the authenticity of this test report on the authenticity verification page on our website (www.kes.co.kr).

4.3 External I/O Cabling

Mode 1

Start		End		Cable Spec.	
Product Name	**I/O Port**	**Product Name**	**Product Name**	**I/O Port**	**Product Name**
EUT	AC IN	AC/AC Adapter	AC OUT	1.5	U
	RJ-45 (LAN)	Laptop	RJ-45 (LAN)	3.1	U
	6 Pin (Audio OUT)	Headset	3.5 ㎜	1.8	U
	6 Pin (Audio IN)		3.5 ㎜	1.8	U
	6 Pin (RS-485)	Controller	RS-485	3.5	U
	12 Pin (Alarm OUT)	Alarm	Alarm IN	3.5	U
	12 Pin (Alarm IN)	Button Alarm	Alarm OUT	3.5	U
	Micro SD Slot	Micro SD Card	Micro SD Slot	-	-
Laptop	DC Jack	Laptop AC/DC Adapter	DC Jack	1.5	U
Controller	DC Jack	Controller AC/DC Adapter	DC Jack	1.3	U

Mode 2

Start		End		Cable Spec.	
Product Name	**I/O Port**	**Product Name**	**Product Name**	**I/O Port**	**Product Name**
EUT	RJ-45 (PoE)	PoE Injector	RJ-45 (PoE)	3.1	U
	6 Pin (Audio OUT)	Headset	3.5 ㎜	1.8	U
	6 Pin (Audio IN)		3.5 ㎜	1.8	U
	6 Pin (RS-485)	Controller	RS-485	3.5	U
	12 Pin (Alarm OUT)	Alarm	Alarm IN	3.5	U
	12 Pin (Alarm IN)	Button Alarm	Alarm OUT	3.5	U
	Micro SD Slot	Micro SD Card	Micro SD Slot	-	-
Laptop	DC Jack	Laptop AC/DC Adapter	DC Jack	1.5	U
Controller	DC Jack	Controller AC/DC Adapter	DC Jack	1.3	U

* Unshielded=U, Shielded=S

You can check the authenticity of this test report on the authenticity verification page on our website (www.kes.co.kr).

4.4 EUT Operating Mode(s)


Category	Mode	Operating
Mode 1	AC Power	- Monitoring EUT Using Web Viewer, Ping Test - When the Button Alarm is pressed, make sure the Alarm is working - Uploaded the 1 ㎑ tone sound to the Web Viewer and checked if the sound is output to the headset. - Checked the operation of the controller. - After the test, the recorded video stored on the Micro SD Card was checked and the microphone motion was also confirmed.
Mode 2	PoE Power	

4.5 Test operating S/W


Name	Version	Manufacture Company
Web Viewer	-	HANWHA VISION VIETNAM COMPANY LIMITED

You can check the authenticity of this test report on the authenticity verification page on our website (www.kes.co.kr).

4.6 Configuration



Mode 1



Mode 2

You can check the authenticity of this test report on the authenticity verification page on our website (www.kes.co.kr).

5 General Performance Criteria

Criteria for compliance was based on the following guidelines:

EN 50130-4 Alarm systems-Part 4: Electromagnetic compatibility Product family standard: Immunity requirements for components of fire, intruder and social alarm systems

The variety and the diversity of the apparatus within the scope of this document makes it difficult to define precise criteria for the evaluation of the immunity test results.

If as a result of the application of the tests defined in this standard, the apparatus

becomes dangerous or unsafe then the apparatus shall be deemed to have failed the test.

A functional description and a definition of performance by the manufacture and noted in the test

report, based on the following criteria:

Electrostatic discharge

There shall be no damage, malfunction or change of status due to the conditioning.

Flickering of an indicator during the application of discharge is permissible, providing that is no

residual change in the EUT or any change in outputs, which could be interpreted by associated

equipment as a change.

Radiated electromagnetic fields

There shall be no damage, malfunction or change of status due to the conditioning.

Flickering of an indicator during the application of discharge is permissible, providing

which could be interpreted by associated equipment as a change, and no such

Flickering of indicators occurs at a field strength of 3 V/m.

For components of CCTV systems, where the picture is allowed at 10 V/m, providing.

(a) there is no permanent damage or change to EUT

(e.g. no corruption of memory or changes to programmable setting etc.)

(b) at 3 V/m, any deterioration of the picture is so minor that the system could still be used; and

(c) there is no observable deterioration of the picture at 1 V/m.

Fast transient burst / slow high energy voltage surge

There shall be no damage, malfunction or change of status due to the conditioning.

Flickering of an indicator during the application of discharge is permissible, providing

That there is no residual is permissible, providing that there is no residual change in the EUT or any

change in outputs, which could be interpreted by associated equipment as a change.

You can check the authenticity of this test report on the authenticity verification page on our website (www.kes.co.kr).

Conducted RF immunity

There shall be no damage, malfunction or change of status due to the conditioning.

Flickering of an indicator during the application of discharge is permissible, providing

That there is no residual is permissible, providing that there is no residual change in the EUT or any

change in outputs, which could be interpreted by associated equipment as a change,

and no such flickering of indicators oeuvres at U = 130 dBμV.

For component of CCTV systems, where the status is monitored by observing the TV picture,

then deterioration of the picture is allowed at U = 140 dBμV, providing:

(a) there is no permanent damage or change to the EUT

(e.g. no corruption of memory or changes to programmable settings etc.)

(b) at U = 130 dBμV, any deterioration of the picture is so minor that the system could

still be used; and

(c) there in no observable deterioration of the picture at U = 120 dBμV.

Voltage dip/interruption / Voltage variation

There shall be no damage, malfunction or change of status due to the conditioning.

Flickering of an indicator during the conditioning is permissible, providing that there is no residual

change in the EUT or any change in outputs, which could be interpreted by associated equipment

as a change. The EUT shall meet the acceptance criteria for the functional test, after the conditioning.

♦ Calculation

- Conducted Emissions

QuasiPeak[dBuV] / CAverage [dBuV] = Reading Value[dBuV] + Corr. [dB]
QuasiPeak / CAverage : The Final Value
Reading Value : Not shown in the table.
Corr. : Correction values (LISN FACTOR + (Cable Loss + Pulse Limiter FACTOR))

- Radiated Emissions(Below 1 GHz)

Result(QP) [dB(μV/m)] = (Reading(QP)[dB(μV)] + c.f[dB(1/m)]
Margin(QP)[dB] = Limit[dB(μV/m)] - Result(QP) [dB(μV/m)]
Reading(QP) : Reading value, Result(QP) : Reading value + Factor value
Limit(QP) : Limit value, c.f : (ANT Factor + Cable Loss - Preamp Factor), Margin: Margin value

- Radiated Emissions(Above 1 GHz)

Result(PK/CAV) [dB(μV/m)] = (Reading(PK/CAV)[dB(μV)] + c.f[dB(1/m)]
Margin(PK/CAV)[dB] = Limit[dB(μV/m)] - Result(PK/CAV) [dB(μV/m)]
Reading(PK/CAV) : Reading value, Result(PK/CAV) : Reading value + Factor value
Limit(PK/CAV) : Limit value, c.f : (ANT Factor + Cable Loss - Preamp Factor), Margin: Margin value

You can check the authenticity of this test report on the authenticity verification page on our website (www.kes.co.kr).

6 Test Item

6.1 Conducted Emissions at Mains Power Ports

6.1.1 Test Equipment

Equipment Name	Model Number	Manufacturer	Serial No.	Cal. Date	Next Cal. Date	Used
SHIELD ROOM #6	-	DYMSTEC	-	-	-	■
EMC32 Measurement Software	EMC32	R&S	9.12.00	-	-	■
EMI TEST RECEIVER	ESR3	Rohde & Schwarz	101783	2025-11-03	2026-11-03	■
LISN	ENV216	Rohde & Schwarz	101787	2025-09-04	2026-09-04	■
ARTIFICIAL MAINS NETWORK	ESH2-Z5	Rohde & Schwarz	100450	2025-11-03	2026-11-03	■
PULSE LIMITER	ESH3-Z2	Rohde & Schwarz	101915	2025-11-03	2026-11-03	■

6.1.2 Test Location : SHIELD ROOM #6

6.1.3 Test Conditions :

Temperature	Relative Humidity
(23.0 ~ 23.1) °C	(36.2 ~ 36.3) % R.H.

You can check the authenticity of this test report on the authenticity verification page on our website (www.kes.co.kr).

6.1.4 Test Result


○ Test Date : 2026-04-01

● Test Mode : Mode 1

Test Report

1 / 1

Test Description:	Conducted Emission
Job No.:	KES-EM260876
Phase:	L
Mode:	Mode 1
Operator Name:	KES



Final_Result

Frequency (MHz)	QuasiPeak (dBµV)	CAverage (dBµV)	Limit (dBµV)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Line	Corr. (dB)
0.235000	20.70	---	79.00	58.30	1000.0	9.000	L1	19.4
0.235000	---	20.35	66.00	45.65	1000.0	9.000	L1	19.4
3.970000	30.81	---	73.00	42.19	1000.0	9.000	L1	19.7
3.970000	---	28.54	60.00	31.46	1000.0	9.000	L1	19.7
9.145000	28.45	---	73.00	44.55	1000.0	9.000	L1	19.9
9.145000	---	25.10	60.00	34.90	1000.0	9.000	L1	19.9
15.105000	34.79	---	73.00	38.21	1000.0	9.000	L1	20.2
15.105000	---	34.82	60.00	25.18	1000.0	9.000	L1	20.2
15.615000	---	34.64	60.00	25.36	1000.0	9.000	L1	20.2
15.615000	35.54	---	73.00	37.46	1000.0	9.000	L1	20.2
18.175000	---	32.52	60.00	27.48	1000.0	9.000	L1	20.2
18.175000	34.15	---	73.00	38.85	1000.0	9.000	L1	20.2

You can check the authenticity of this test report on the authenticity verification page on our website (www.kes.co.kr).


○ Test Date : 2026-04-01

● Test Mode : Mode 1

Test Report

1 / 1

Test Description:	Conducted Emission
Job No.:	KES-EM260876
Phase:	N
Mode:	Mode 1
Operator Name:	KES



Final_Result

Frequency (MHz)	QuasiPeak (dBµV)	CAverage (dBµV)	Limit (dBµV)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Line	Corr. (dB)
0.705000	---	8.23	60.00	51.77	1000.0	9.000	N	19.5
0.705000	12.76	---	73.00	60.24	1000.0	9.000	N	19.5
3.970000	---	27.88	60.00	32.12	1000.0	9.000	N	19.7
3.970000	30.04	---	73.00	42.96	1000.0	9.000	N	19.7
13.055000	38.42	---	73.00	34.58	1000.0	9.000	N	20.1
13.055000	---	38.17	60.00	21.83	1000.0	9.000	N	20.1
14.080000	40.47	---	73.00	32.53	1000.0	9.000	N	20.1
14.080000	---	40.37	60.00	19.63	1000.0	9.000	N	20.1
14.590000	---	38.84	60.00	21.16	1000.0	9.000	N	20.2
14.590000	38.92	---	73.00	34.08	1000.0	9.000	N	20.2
15.615000	---	37.61	60.00	22.39	1000.0	9.000	N	20.2
15.615000	38.54	---	73.00	34.46	1000.0	9.000	N	20.2

6.1.5 Remark

Complies with the test requirements.

You can check the authenticity of this test report on the authenticity verification page on our website (www.kes.co.kr).

6.2 Conducted Emissions at Telecommunication Ports

6.2.1 Test Equipment

Equipment Name	Model Number	Manufacturer	Serial No.	Cal. Date	Next Cal. Date	Used
SHIELD ROOM #6	-	DYMSTEC	-	-	-	■
EMC32 Measurement Software	EMC32	R&S	9.12.00	-	-	■
EMI TEST RECEIVER	ESR3	Rohde & Schwarz	101783	2025-11-03	2026-11-03	■
LISN	ENV216	Rohde & Schwarz	101787	2025-09-04	2026-09-04	■
ARTIFICIAL MAINS NETWORK	ESH2-Z5	Rohde & Schwarz	100450	2025-11-03	2026-11-03	■
PULSE LIMITER	ESH3-Z2	Rohde & Schwarz	101915	2025-11-03	2026-11-03	■
8-WIRE ISN CAT6	ENY81-CAT6	Rohde & Schwarz	101666	2026-02-24	2027-02-24	■

6.2.2 Test Location : SHIELD ROOM #6

6.2.3 Test Conditions :

Temperature	Relative Humidity
(22.8 ~ 23.1) °C	(36.2 ~ 36.4) % R.H.

You can check the authenticity of this test report on the authenticity verification page on our website (www.kes.co.kr).


6.2.4 Test Result

○ Test Date : 2026-04-01
● Test Mode : Mode 1

Test Report

1 / 1

Test Description:	Telecommunication Emission
Job No.:	KES-EM260876
Mode :	Mode 1
Speed :	100 Mbps
Operator Name:	KES



Final_Result

Frequency (MHz)	QuasiPeak (dBµV)	CAverage (dBµV)	Limit (dBµV)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Line	Corr. (dB)
0.585000	31.76	---	87.00	55.24	1000.0	9.000	Single Line	19.3
0.585000	---	30.31	74.00	43.69	1000.0	9.000	Single Line	19.3
0.820000	34.09	---	87.00	52.91	1000.0	9.000	Single Line	19.3
0.820000	---	31.45	74.00	42.55	1000.0	9.000	Single Line	19.3
2.345000	39.25	---	87.00	47.75	1000.0	9.000	Single Line	19.3
2.345000	---	33.67	74.00	40.33	1000.0	9.000	Single Line	19.3
5.910000	45.70	---	87.00	41.30	1000.0	9.000	Single Line	19.5
5.910000	---	38.49	74.00	35.51	1000.0	9.000	Single Line	19.5
13.480000	47.39	---	87.00	39.61	1000.0	9.000	Single Line	19.6
13.480000	---	42.59	74.00	31.41	1000.0	9.000	Single Line	19.6
23.810000	51.37	---	87.00	35.63	1000.0	9.000	Single Line	19.9
23.810000	---	47.98	74.00	26.02	1000.0	9.000	Single Line	19.9


You can check the authenticity of this test report on the authenticity verification page on our website (www.kes.co.kr).

○ Test Date : 2026-04-01
● Test Mode : Mode 2

Test Report

1 / 1

Test Description:	Telecommunication Emission
Job No.:	KES-EM260876
Mode :	Mode 2
Speed :	100 Mbps
Operator Name:	KES



Final_Result

Frequency (MHz)	QuasiPeak (dBµV)	CAverage (dBµV)	Limit (dBµV)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Line	Corr. (dB)
0.505000	25.22	---	87.00	61.78	1000.0	9.000	Single Line	19.3
0.505000	---	22.15	74.00	51.85	1000.0	9.000	Single Line	19.3
1.025000	31.91	---	87.00	55.09	1000.0	9.000	Single Line	19.3
1.025000	---	28.58	74.00	45.42	1000.0	9.000	Single Line	19.3
3.575000	28.16	---	87.00	58.84	1000.0	9.000	Single Line	19.3
3.575000	---	10.36	74.00	63.64	1000.0	9.000	Single Line	19.3
13.055000	55.42	---	87.00	31.58	1000.0	9.000	Single Line	19.6
13.055000	---	55.33	74.00	18.67	1000.0	9.000	Single Line	19.6
13.570000	55.83	---	87.00	31.17	1000.0	9.000	Single Line	19.6
13.570000	---	55.70	74.00	18.30	1000.0	9.000	Single Line	19.6
14.080000	57.20	---	87.00	29.80	1000.0	9.000	Single Line	19.7
14.080000	---	57.10	74.00	16.90	1000.0	9.000	Single Line	19.7

6.2.5 Remark

Complies with the test requirements.

You can check the authenticity of this test report on the authenticity verification page on our website (www.kes.co.kr).

6.3 Radiated Emissions(Below 1 ㎓)

6.3.1 Test Equipment

Equipment Name	Model Number	Manufacturer	Serial No.	Cal. Date	Next Cal. Date	Used
SEMI ANECHOIC CHAMBER #4(10 m)	-	DYMSTEC	-	-	-	■
EP5/RE Software	EP5/RE	TOYO	6.0.0	-	-	■
EMI TEST RECEIVER	ESU26	Rohde & Schwarz	100551	2026-02-12	2027-02-12	■
AMPLIFIER	SCU 01	Rohde & Schwarz	100603	2025-11-03	2026-11-03	■
BILOG ANTENNA	VULB 9168	SCHWARZBECK	9168-461	2024-05-09	2026-05-09	■

6.3.2 Test Location : SEMI ANECHOIC CHAMBER #4(10 m) Measurement Distance : □ 3 m, ■ 10 m

6.3.3 Test Conditions :


Temperature	Relative Humidity
(22.7 ~ 23.1) °C	(35.5 ~ 35.6) % R.H.

You can check the authenticity of this test report on the authenticity verification page on our website (www.kes.co.kr).

6.3.4 Test Result

○ Test Date : 2026-04-01

● Test Mode : Mode 1



Final Result


No.	Frequency [MHz]	(P)	Reading QP [dB(uV)]	c.f [dB(1/m)]	Result QP [dB(uV/m)]	Limit QP [dB(uV/m)]	Margin QP [dB]	Height [cm]	Angle [deg]	Remark
1	59.343	H	40.8	-20.9	19.9	40.0	20.1	387.0	118.0	
2	84.078	V	53.8	-25.8	28.0	40.0	12.0	102.0	203.0	
3	102.386	V	58.3	-24.3	34.0	40.0	6.0	101.0	196.0	
4	111.238	V	49.3	-23.2	26.1	40.0	13.9	300.0	142.0	
5	185.928	V	43.5	-21.4	22.1	40.0	17.9	101.0	188.0	
6	950.045	H	34.0	-0.9	33.1	47.0	13.9	398.0	278.0	

※ The data is the result measured by the detector in Quasi-Peak mode on the Peak graph.

You can check the authenticity of this test report on the authenticity verification page on our website (www.kes.co.kr).

○ Test Date : 2026-04-01

● Test Mode : Mode 2



Final Result

No.	Frequency [MHz]	(P)	Reading QP [dB(uV)]	c.f [dB(1/m)]	Result QP [dB(uV/m)]	Limit QP [dB(uV/m)]	Margin QP [dB]	Height [cm]	Angle [deg]	Remark
1	101.780	V	51.4	-24.4	27.0	40.0	13.0	111.0	333.0	
2	104.690	V	50.6	-24.0	26.6	40.0	13.4	143.0	337.0	
3	178.046	V	51.3	-20.7	30.6	40.0	9.4	100.0	15.0	
4	183.745	V	51.2	-21.2	30.0	40.0	10.0	101.0	3.0	
5	226.789	V	47.1	-21.0	26.1	40.0	13.9	110.0	159.0	
6	987.875	H	31.4	0.0	31.4	47.0	15.6	289.0	250.0	

※ The data is the result measured by the detector in Quasi-Peak mode on the Peak graph.

6.3.5 Remark

Complies with the test requirements.

You can check the authenticity of this test report on the authenticity verification page on our website (www.kes.co.kr).

6.4 Radiated Emissions(Above 1 ㎓)

6.4.1 Test Equipment

Equipment Name	Model Number	Manufacturer	Serial No.	Cal. Date	Next Cal. Date	Used
SEMI ANECHOIC CHAMBER #5	-	SY Corporation	-	-	-	■
ES10/RE Software	ES10/RE	TOYO	2022.01.000	-	-	■
EMI TEST RECEIVER	ESU26	Rohde & Schwarz	100552	2026-02-12	2027-02-12	■
PREAMPLIFIER	8449B	HP	3008A00538	2025-04-30	2026-04-30	■
ATTENUATOR	8491B	HP	23094	2026-02-12	2027-02-12	■
HORN ANTENNA	BBHA 9120D	SCHWARZBECK	9120D-1802	2025-11-05	2026-11-05	■

6.4.2 Test Location : SEMI ANECHOIC CHAMBER #5

6.4.3 Test Conditions :


Temperature	Relative Humidity
(23.5 ~ 23.7) °C	(37.3 ~ 37.4) % R.H.

You can check the authenticity of this test report on the authenticity verification page on our website (www.kes.co.kr).

6.4.4 Test Result

○ Test Date : 2026-04-01

● Test Mode : Mode 1



Final Result


No.	Frequency [MHz]	Pol	Reading AV [dB(μV)]	Reading PK [dB(μV)]	c.f [dB(1/m)]	Result AV [dB(μV/m)]	Result PK [dB(μV/m)]	Limit AV [dB(μV/m)]	Limit PK [dB(μV/m)]	Margin AV [dB]	Margin PK [dB]	Angle [deg]	Remark
1	2565.216	H	31.2	44.2	5.7	36.9	49.9	60.0	80.0	23.1	30.1	283.1	
2	2904.473	V	29.4	44.0	6.8	36.2	50.8	60.0	80.0	23.8	29.2	196.6	
3	3303.370	H	28.3	45.1	7.4	35.7	52.5	60.0	80.0	24.3	27.5	359.6	
4	3503.797	V	29.1	44.0	7.6	36.7	51.6	60.0	80.0	23.3	28.4	282.5	
5	4885.893	H	28.3	41.8	12.6	40.9	54.4	60.0	80.0	19.1	25.6	43.0	
6	5793.339	V	28.0	41.3	14.2	42.2	55.5	60.0	80.0	17.8	24.5	226.4	

※ The data is the result of measured by the detector in PK and CISPR Average on the Peak graph.
※ The Average of the test data is the cispr average result.

You can check the authenticity of this test report on the authenticity verification page on our website (www.kes.co.kr).

○ Test Date : 2026-04-01

● Test Mode : Mode 2



Final Result

No.	Frequency [MHz]	Pol	Reading AV [dB(μV)]	Reading PK [dB(μV)]	c.f [dB(1/m)]	Result AV [dB(μV/m)]	Result PK [dB(μV/m)]	Limit AV [dB(μV/m)]	Limit PK [dB(μV/m)]	Margin AV [dB]	Margin PK [dB]	Angle [deg]	Remark
1	2597.116	H	31.3	44.5	5.7	37.0	50.2	60.0	80.0	23.0	29.8	2.4	
2	2820.214	V	30.4	43.6	6.5	36.9	50.1	60.0	80.0	23.1	29.9	359.8	
3	3418.493	V	28.9	43.8	7.5	36.4	51.3	60.0	80.0	23.6	28.7	102.0	
4	3586.033	H	29.7	44.0	7.8	37.5	51.8	60.0	80.0	22.5	28.2	0.2	
5	4748.173	V	29.0	41.3	12.0	41.0	53.3	60.0	80.0	19.0	26.7	131.4	
6	5707.111	H	28.2	41.2	13.9	42.1	55.1	60.0	80.0	17.9	24.9	23.5	

※ The data is the result of measured by the detector in PK and CISPR Average on the Peak graph.
※ The Average of the test data is the cispr average result.

6.4.5 Remark

Complies with the test requirements.

You can check the authenticity of this test report on the authenticity verification page on our website (www.kes.co.kr).

6.5 Harmonic Current Emissions

6.5.1 Test Equipment

Equipment Name	Model Number	Manufacturer	Serial No.	Cal. Date	Next Cal. Date	Used
SHIELD ROOM #7	-	DYMSTEC	-	-	-	■
net.control Software	net.control	EM TEST	2.1.4	-	-	■
DIGITAL POWER ANALYZER (Harmonic)	DPA 500N	EM TEST	V1024106759	2026-04-06	2027-04-06	■
POWER SOURCE	ACS 500N6	EM TEST	V1024106760	-	-	■

6.5.2 Test Location : SHIELD ROOM #7

6.5.3 Test Conditions :

Temperature	Relative Humidity
(22.4 ~ 22.7) °C	(36.2 ~ 36.3) % R.H.

6.5.4 Classification of Equipment for Harmonic Current Emissions

■ Limits for Class A equipment
□ Limits for Class B equipment
□ Limits for Class C equipment(Rated Power > 25 W)
□ Limits for Class C equipment(Rated Power ≥ 5 W and ≤ 25 W)
□ Limits for Class D equipment

You can check the authenticity of this test report on the authenticity verification page on our website (www.kes.co.kr).

6.5.5 Test Result

○ Test Date : 2026-04-01

● Test Mode : Mode 1

Maximum harmonic current results

Hn	Ieff [A]	% of Limit	Limit [A]	Result
1	0.131			
2	0.003	0.202	1.620	n/a
3	0.052	1.510	3.450	PASS
4	0.002	0.276	0.645	n/a
5	0.057	3.331	1.710	PASS
6	0.001	0.228	0.450	n/a
7	0.029	2.478	1.155	PASS
8	0.001	0.243	0.345	n/a
9	0.015	2.431	0.600	PASS
10	0.001	0.363	0.276	n/a
11	0.006	1.182	0.495	PASS
12	0.001	0.335	0.230	n/a
13	0.006	2.005	0.315	PASS
14	0.001	0.486	0.197	n/a
15	0.005	2.338	0.225	PASS
16	0.001	0.475	0.173	n/a
17	0.003	1.613	0.199	n/a
18	0.001	0.533	0.153	n/a
19	0.003	1.564	0.178	n/a
20	0.001	0.611	0.138	n/a
21	0.003	1.885	0.161	n/a
22	0.001	0.570	0.125	n/a
23	0.002	1.567	0.147	n/a
24	0.001	0.699	0.115	n/a
25	0.002	1.274	0.135	n/a
26	0.001	0.656	0.106	n/a
27	0.002	1.437	0.125	n/a
28	0.001	1.018	0.099	n/a
29	0.002	1.581	0.116	n/a
30	0.001	0.916	0.092	n/a
31	0.002	1.379	0.109	n/a
32	0.001	0.917	0.086	n/a
33	0.001	1.246	0.102	n/a
34	0.001	0.951	0.081	n/a
35	0.001	1.328	0.096	n/a
36	0.001	1.071	0.077	n/a
37	0.001	1.403	0.091	n/a
38	0.001	1.315	0.073	n/a
39	0.001	1.247	0.087	n/a
40	0.001	1.157	0.069	n/a

Harmonic currents less than 0.6% of the input current measured under the test conditions, or less than 5 mA, whichever is greater, are disregarded.

You can check the authenticity of this test report on the authenticity verification page on our website (www.kes.co.kr).

Test Data - Harmonics (continued)

Average harmonic current results

Hn	Ieff [A]	% of Limit	Limit [A]	Result
1	0.131			
2	0.003	0.287	1.080	n/a
3	0.052	2.254	2.300	PASS
4	0.002	0.367	0.430	n/a
5	0.057	4.976	1.140	PASS
6	0.001	0.303	0.300	n/a
7	0.028	3.701	0.770	PASS
8	0.001	0.310	0.230	n/a
9	0.014	3.615	0.400	PASS
10	0.001	0.469	0.184	n/a
11	0.006	1.742	0.330	PASS
12	0.001	0.449	0.153	n/a
13	0.006	2.917	0.210	PASS
14	0.001	0.658	0.131	n/a
15	0.005	3.450	0.150	PASS
16	0.001	0.637	0.115	n/a
17	0.003	2.140	0.132	n/a
18	0.001	0.699	0.102	n/a
19	0.003	2.233	0.118	n/a
20	0.001	0.832	0.092	n/a
21	0.003	1.790	0.161	n/a
22	0.001	0.769	0.084	n/a
23	0.002	1.235	0.147	n/a
24	0.001	0.942	0.077	n/a
25	0.002	1.189	0.135	n/a
26	0.001	0.866	0.071	n/a
27	0.002	1.338	0.125	n/a
28	0.001	1.234	0.066	n/a
29	0.001	1.267	0.116	n/a
30	0.001	1.140	0.061	n/a
31	0.001	1.074	0.109	n/a
32	0.001	1.213	0.058	n/a
33	0.001	1.139	0.102	n/a
34	0.001	1.233	0.054	n/a
35	0.001	1.196	0.096	n/a
36	0.001	1.422	0.051	n/a
37	0.001	1.032	0.091	n/a
38	0.001	1.762	0.048	n/a
39	0.001	1.077	0.087	n/a
40	0.001	1.518	0.046	n/a

Note: Harmonic currents less than 0.6 % of the input current measured under the test conditions, or less than 5 mA, whichever is greater, are disregarded.
* Application of limits for average is 100% except for odd harmonics from 21 to 39, where 150% applies.

6.5.6 Remark

Complies with the test requirements.

You can check the authenticity of this test report on the authenticity verification page on our website (www.kes.co.kr).

6.6 Voltage Fluctuations and Flicker

6.6.1 Test Equipment

Equipment Name	Model Number	Manufacturer	Serial No.	Cal. Date	Next Cal. Date	Used
SHIELD ROOM #7	-	DYMSTEC	-	-	-	■
net.control Software	net.control	EM TEST	2.1.4	-	-	■
DIGITAL POWER ANALYZER (Flicker)	DPA 500N	EM TEST	V1024106759	2026-04-06	2027-04-06	■
POWER SOURCE	ACS 500N6	EM TEST	V1024106760	-	-	■

6.6.2 Test Location : SHIELD ROOM #7

6.6.3 Test Conditions :

Temperature	Relative Humidity
(22.4 ~ 22.6) °C	(36.1 ~ 36.3) % R.H.

You can check the authenticity of this test report on the authenticity verification page on our website (www.kes.co.kr).

6.6.4 Test Result

○ Test Date : 2026-04-01

● Test Mode : Mode 1

Flicker Measurements					
	P_{lt}	Max P_{st}	Max D_c	Max D_{max}	Max T_{max}
Line 1:	0.028	0.028	0	< 0.2	0
Limits:	0.65	1	3.3	4	0.5
Results:	PASS	PASS	PASS	PASS	PASS

6.6.5 Remark

Complies with the test requirements.

You can check the authenticity of this test report on the authenticity verification page on our website (www.kes.co.kr).

6.7 Electrostatic Discharge

6.7.1 Test Equipment

Equipment Name	Model Number	Manufacturer	Serial No.	Cal. Date	Next Cal. Date	Used
SHIELD ROOM #6	-	DYMSTEC	-	-	-	■
ESD SIMULATOR	ESS-2000	NoiseKen	ESS01Z0454	2026-01-13	2027-01-13	■
HCP	-	KES	-	-	-	■
VCP	-	Noise Ken	-	-	-	■

6.7.2 Test Location : SHIELD ROOM #6

6.7.3 Test Conditions :

Temperature	Relative Humidity
Temperature(15 ~ 35) °C	(22.8 ~ 23.0) °C
Relative Humidity(30 ~ 60) % R.H.	(36.2 ~ 36.3) % R.H.
Atmospheric Pressure(86 ~ 106) kPa	(100.4 ~ 100.5) kPa

6.7.4 Test Specifications :

Discharge Factor : 1 s

Discharge Impedance : 330 Ω / 150 pF

Kind of Discharge : Direct Discharge - Contact Discharge, Air Discharge
Indirect Discharge - HCP, VCP

Polarity : Positive and Negative

Number of Discharge : 10 at all locations for Contact Discharge,
10 at all locations for Air Discharge


Performance Criteria : Complied

Discharge Voltage :


Type	Direct Discharge		Indirect Discharge	
	Contact Discharge	Air Discharge	Horizontal Coupling Plane	Vertical Coupling Plane
Test Voltage	-	± 2 kV	-	-
	± 6 kV	± 4 kV	± 6 kV	± 6 kV
	-	± 8 kV	-	-

You can check the authenticity of this test report on the authenticity verification page on our website (www.kes.co.kr).

6.7.5 Location of Discharge




<Location of Discharge-1> Mode 1




<Location of Discharge-2> Mode 1

You can check the authenticity of this test report on the authenticity verification page on our website (www.kes.co.kr).



<Location of Discharge-1> Mode 2



<Location of Discharge-2> Mode 2

You can check the authenticity of this test report on the authenticity verification page on our website (www.kes.co.kr).

6.7.6 Test Result

○ Test Date : 2026-04-01
● Test Mode : Mode 1

○ **Indirect Discharge**

No.	Test Point	Discharge Method	Observations	Remarks
1	HCP Contact	Contact Discharge	Complied	-
2	VCP Contact	Contact Discharge	Complied	-

○ **Direct Discharge**

No.	Test Point	Discharge Method	Observations	Remarks
1	Enclosure 1	Air Discharge	Complied	-
2	Enclosure 2	Contact Discharge	Complied	-
3	Screws	Contact Discharge	Complied	-

○ Test Date : 2026-04-01
● Test Mode : Mode 2

○ **Indirect Discharge**

No.	Test Point	Discharge Method	Observations	Remarks
1	HCP Contact	Contact Discharge	Complied	-
2	VCP Contact	Contact Discharge	Complied	-

○ **Direct Discharge**

No.	Test Point	Discharge Method	Observations	Remarks
1	Enclosure 1	Air Discharge	Complied	-
2	Enclosure 2	Contact Discharge	Complied	-
3	Screws	Contact Discharge	Complied	-

6.7.7 Remark

No loss of performance of function.

You can check the authenticity of this test report on the authenticity verification page on our website (www.kes.co.kr).

6.8 Continuous RF electromagnetic field disturbances

6.8.1 Test Equipment

Equipment Name	Model Number	Manufacturer	Serial No.	Cal. Date	Next Cal. Date	Used
SEMI ANECHOIC CHAMBER #3	-	DYMSTEC	-	-	-	■
EMC32 Measurement Software	EMC32	R&S	10.10.02	-	-	■
SIGNAL GENERATOR	SMB 100A	Rohde & Schwarz	108252	2025-07-28	2026-07-28	■
HIGH POWER DUAL AMP	SSA532	SUNGSAN	SSA532-001	-	-	■
POWER METER	E4419B	Agilent	GB40203000	2026-02-12	2027-02-12	■
AVERAGE POWER SENSOR	E9301A	Agilent	MY52170007	2026-02-12	2027-02-12	■
AVERAGE POWER SENSOR	E9301A	Agilent	MY41498669	2026-02-12	2027-02-12	■
STACKED DOUBLE LOG-PER- ANTENNA	STPL9128 E	SCHWARZBECK	9128ES-121	-	-	■
DOUBLE RIDGED HORN ANTENNA	SAS-571	A.H. SYSTEM,INC	781	2026-03-06	2027-03-06	■

6.8.2 Test Location : SEMI ANECHOIC CHAMBER #3

6.8.3 Test Conditions :

Temperature	Relative Humidity
(23.1 ~ 23.4) °C	(36.0 ~ 36.1) % R.H.

You can check the authenticity of this test report on the authenticity verification page on our website (www.kes.co.kr).

6.8.4 Test Specifications :

Antenna Polarization	:	Horizontal & Vertical unless indicated otherwise
Antenna Distance	:	3 m
Field Strength	:	10 V/m (rms)
Frequency Range	:	80 MHz ~ 2.7 GHz
Modulation	:	AM 80 %, 1 kHz, Sine wave PM 1 Hz (0.5 s ON : 0.5 s OFF)
Dwell Time	:	3 s
Frequency Step	:	1 %
Application method	:	4
Performance Criteria	:	Complied

You can check the authenticity of this test report on the authenticity verification page on our website (www.kes.co.kr).

6.8.5 Test Result

○ Test Date : 2026-04-03
● Test Mode : Mode 1

○ Enclosure Port

Side Exposed	Observations	
	Horizontal	Vertical
Front	Complied	Complied
Rear	Complied	Complied
Right	Complied	Complied
Left	Complied	Complied

○ Test Date : 2026-04-03
● Test Mode : Mode 2

○ Enclosure Port

Side Exposed	Observations	
	Horizontal	Vertical
Front	Complied	Complied
Rear	Complied	Complied
Right	Complied	Complied
Left	Complied	Complied

6.8.6 Remark

No loss of performance of function.

You can check the authenticity of this test report on the authenticity verification page on our website (www.kes.co.kr).

6.9 Electrical Fast Transients/Bursts

6.9.1 Test Equipment

Equipment Name	Model Number	Manufacturer	Serial No.	Cal. Date	Next Cal. Date	Used
SHIELD ROOM #7	-	DYMSTEC	-	-	-	■
iec.control Software	iec.control	EM TEST	5.4.8	-	-	■
ULTRA COMPACT SIMULATOR	UCS 500N7	EM TEST	P1608172950	2025-11-05	2026-11-05	■
MOTOR VARIAC	MV 2616	EM TEST	P1552169719	2025-11-05	2026-11-05	■
CAPACITIVE COUPLING CLAMP	HFK	EM TEST	P1633183115	2025-11-05	2026-11-05	■

6.9.2 Test Location : SHIELD ROOM #7

6.9.3 Test Conditions :

Temperature	Relative Humidity
(22.4 ~ 22.8) °C	(36.2 ~ 36.4) % R.H.

6.9.4 Test Specifications :

Pulse Amplitude & Polarity	:	Input a.c power ports ± 2.0 kV
		Other supply and Signal ports ± 1 kV
Repetition Rate	:	100 kHz
Impulse Rise Time	:	5 ns ± 30 %
Impulse Period	:	50 ns ± 30 %
Burst Duration	:	15 ms ± 20 %
Burst Period	:	300 ms ± 20 %
Duration of Test Voltage	:	1 min
Application Method	:	a.c / d.c power ports (Coupling / Decoupling Network)
		Other than a.c / d.c power poerts (Capacitive Coupling Clamp)
Performance Criteria	:	Complied

You can check the authenticity of this test report on the authenticity verification page on our website (www.kes.co.kr).

6.9.5 Test Result

○ Test Date : 2026-04-01
● Test Mode : Mode 1

○ Input a.c power ports

Mode of Application	Observations	
	(+) Burst	(-) Burst
L	Complied	Complied
N	Complied	Complied
L-N	Complied	Complied

○ Input d.c power ports

Mode of Application	Observations	
	(+) Burst	(-) Burst
N/A	-	-

○ Signal ports and telecommunication ports

Mode of Application	Observations	
	(+) Burst	(-) Burst
RJ-45(LAN)	Complied	Complied
6 Pin(RS-485)	Complied	Complied
12 Pin(Alarm OUT)	Complied	Complied
12 Pin(Alarm IN)	Complied	Complied

You can check the authenticity of this test report on the authenticity verification page on our website (www.kes.co.kr).

○ Test Date : 2026-04-01
● Test Mode : Mode 2

○ Input a.c power ports

Mode of Application	Observations	
	(+) Burst	(-) Burst
N/A	-	-

○ Input d.c power ports

Mode of Application	Observations	
	(+) Burst	(-) Burst
N/A	-	-

○ Signal ports and telecommunication ports

Mode of Application	Observations	
	(+) Burst	(-) Burst
RJ-45(PoE)	Complied	Complied
6 Pin(RS-485)	Complied	Complied
12 Pin(Alarm OUT)	Complied	Complied
12 Pin(Alarm IN)	Complied	Complied

6.9.6 Remark

No loss of performance of function.

You can check the authenticity of this test report on the authenticity verification page on our website (www.kes.co.kr).

6.10 Surge

6.10.1 Test Equipment

Equipment Name	Model Number	Manufacturer	Serial No.	Cal. Date	Next Cal. Date	Used
SHIELD ROOM #7	-	DYMSTEC	-	-	-	■
iec.control Software	iec.control	EM TEST	5.4.8	-	-	■
ULTRA COMPACT SIMULATOR	UCS 500N7	EM TEST	P1608172950	2025-11-05	2026-11-05	■
MOTOR VARIAC	MV 2616	EM TEST	P1552169719	2025-11-05	2026-11-05	■
CDN	CNV 508N1	EM TEST	P1610176296	2025-11-05	2026-11-05	■

6.10.2 Test Location : SHIELD ROOM #7

6.10.3 Test Conditions :

Temperature	Relative Humidity
(22.4 ~ 22.8) °C	(36.1 ~ 36.3) % R.H.

6.10.4 Test Specifications :

Surge : Input a.c power ports — Line to Line ±0.5 kV, ±1.0 kV

Line to Ground ±0.5 kV, ±1.0 kV, ±2.0 kV

Other supply / Signal lines — Line to Ground ±0.5 kV, ±1.0 kV

Input a.c / Other supply / Signal lines

Open-Circuit Voltage Waveform : 1.2/50 μs

Short-Circuit Current Waveform : 8/20 μs

Number of Applications : Apply 5 surges for each polarity

Phase Angle : 0˚ ~ 270˚ (input a.c. power port)

Polarity : Positive and Negative

Repetition Rate : 1 surge per 30 s

Performance Criteria : Complied

You can check the authenticity of this test report on the authenticity verification page on our website (www.kes.co.kr).

6.10.5 Test Result

○ Test Date : 2026-04-01
● Test Mode : Mode 1

○ Input a.c power ports

Mode of Application	Observations	
	(+) Surge	(-) Surge
L-N	Complied	Complied

○ Signal ports and telecommunication ports

Mode of Application	Coupling Method	Observations	
		(+) Surge	(-) Surge
RJ-45(LAN)	CDN	Complied	Complied
	LINE	Complied	Complied

○ Test Date : 2026-04-01
● Test Mode : Mode 2

○ Input a.c power ports

Mode of Application	Observations	
	(+) Surge	(-) Surge
N/A	-	-

○ Signal ports and telecommunication ports

Mode of Application	Coupling Method	Observations	
		(+) Surge	(-) Surge
RJ-45(PoE)	CDN	Complied	Complied
	LINE	Complied	Complied

6.10.6 Remark

No loss of performance of function.

You can check the authenticity of this test report on the authenticity verification page on our website (www.kes.co.kr).

6.11 Continuous Induced RF Disturbances

6.11.1 Test Equipment

Equipment Name	Model Number	Manufacturer	Serial No.	Cal. Date	Next Cal. Date	Used
SHIELD ROOM #7	-	DYMSTEC	-	-	-	■
icd.control Software	icd.control	EM TEST	8.0.0	-	-	■
TEST SYSTEM FOR CONDUCTED AND RADIATED	NSG4070	TESEQ	65585	2025-11-03	2026-11-03	■
ATTENUATOR	ATT 6/80	EM TEST	P1614178148	2025-11-03	2026-11-03	■
CDN	CDN M016	TESEQ	43694	2025-11-03	2026-11-03	■
CDN	CDN M016	TESEQ	43697	2025-11-03	2026-11-03	■
CDN	CDN T8 RJ45	SCHWARZBECK	00103	2025-07-07	2026-07-07	■
EM CLAMP	KEMZ 801A	TESEQ	44099	2025-11-05	2026-11-05	■

6.11.2 Test Location : SHIELD ROOM #7

6.11.3 Test Conditions :

Temperature	Relative Humidity
(22.4 ~ 22.8)°C	(36.2 ~ 36.5) % R.H.

6.11.4 Test Specifications

Frequency range and Voltage Level	:	0.15 MHz ~ 100 MHz : 10 V(r.m.s)
Modulation	:	AM 80 %, 1 kHz, Sine wave
		PM 1 Hz (0.5 s ON : 0.5 s OFF)
Dwell Time	:	3 s
Frequency Step	:	1 %
Performance Criteria	:	Complied

You can check the authenticity of this test report on the authenticity verification page on our website (www.kes.co.kr).

6.11.5 Test Result

○ Test Date : 2026-04-01

● Test Mode : Mode 1

○ Input a.c power ports

Coupling Location (Line Stressed)	Coupling Method	Observations
L-N	CDN	Complied

○ Input d.c power ports

Coupling Location (Line Stressed)	Coupling Method	Observations
N/A	-	-

○ Signal ports and telecommunication ports

Coupling Location (Line Stressed)	Coupling Method	Observations
RJ-45(LAN)	CDN	Complied
6 Pin(RS-485)	Clamp	Complied
12 Pin(Alarm OUT)	Clamp	Complied
12 Pin(Alarm IN)	Clamp	Complied

○ Test Date : 2026-04-01

● Test Mode : Mode 2

○ Input a.c power ports

Coupling Location (Line Stressed)	Coupling Method	Observations
N/A	-	-

○ Input d.c power ports

Coupling Location (Line Stressed)	Coupling Method	Observations
N/A	-	-

○ Signal ports and telecommunication ports

Coupling Location (Line Stressed)	Coupling Method	Observations
RJ-45(PoE)	CDN	Complied
6 Pin(RS-485)	Clamp	Complied
12 Pin(Alarm OUT)	Clamp	Complied
12 Pin(Alarm IN)	Clamp	Complied

You can check the authenticity of this test report on the authenticity verification page on our website (www.kes.co.kr).

6.11.6 Remark

No loss of performance of function.

You can check the authenticity of this test report on the authenticity verification page on our website (www.kes.co.kr).

6.12 Voltage Dips and Interruptions

6.12.1 Test Equipment

Equipment Name	Model Number	Manufacturer	Serial No.	Cal. Date	Next Cal. Date	Used
SHIELD ROOM #7	-	DYMSTEC	-	-	-	■
iec.control Software	iec.control	EM TEST	5.4.8	-	-	■
ULTRA COMPACT SIMULATOR	UCS 500N7	EM TEST	P1608172950	2025-11-05	2026-11-05	■
MOTOR VARIAC	MV 2616	EM TEST	P1552169719	2025-11-05	2026-11-05	■

6.12.2 Test Location : SHIELD ROOM #7

6.12.3 Test Conditions :

Temperature	Relative Humidity
(22.6 ~ 22.6) °C	(36.2 ~ 36.3) % R.H.

6.12.4 Test Specifications

Instantaneous peak overshoot/undershoot of the actual voltage	:	Less than 5 %
Voltage Rise Time, Voltage Fall Time	:	Between 1 μs and 5 μs
Test Voltage Frequency Deviation for Voltage Dips	:	with in ± 2 %
EUT Voltage	:	AC 230 V, 50 Hz
Number of Applications	:	3 cycles
Test Interval	:	10 s
Performance Criteria	:	Complied

Voltage Dips and Interruptions	Duration [in period]
20 % Voltage reduction	250 T
30 % Voltage reduction	25 T
60 % Voltage reduction	10 T
100 % Voltage reduction	250 T

Voltage Variations	Supply Voltage
Supply Voltage max (Umax)	Unom a + 10 %
Supply Voltage min (Umin)	Unom a - 15 %

You can check the authenticity of this test report on the authenticity verification page on our website (www.kes.co.kr).

6.12.5 Test Result

○ Test Date: 2026-04-01

● Test Mode: Mode 1

○ Voltage Dips and Short Interruptions

Depth	Duration [in period]	Observations
20 % Voltage reduction	250 T	Complied
30 % Voltage reduction	25 T	Complied
60 % Voltage reduction	10 T	Complied
100 % Voltage reduction	250 T	Degradation

○ Voltage variations

Voltage Variations	Supply Voltage	Observations
Supply voltage max (Umax = Unom a + 10 %)	253 V	Complied
Supply voltage min (Umin = Unom a - 15 %)	195.5 V	Complied

U_{nom} = Nominal mains voltage, U_{max} = (Maximum U_{nom}) + 10 %, U_{min} = (Minimum U_{nom}) – 15 %.

6.12.6 Remark

Degradation : During the test(100%, 250cycle), EUT was turned off but after the test, it was recovered without operator’s intervention

You can check the authenticity of this test report on the authenticity verification page on our website (www.kes.co.kr).

7 Test Setup Photos and EUT Photographs

7.1 Test Setup Photos



<Conducted Emissions at Mains Power Ports - Front> Mode 1




<Conducted Emissions at Mains Power Ports - Rear> Mode 1

You can check the authenticity of this test report on the authenticity verification page on our website (www.kes.co.kr).



<Conducted Emissions at Telecommunication Ports - Front>Mode 1



<Conducted Emissions at Telecommunication Ports - Rear> Mode 1

You can check the authenticity of this test report on the authenticity verification page on our website (www.kes.co.kr).



<Conducted Emissions at Telecommunication Ports - Front>Mode 2




<Conducted Emissions at Telecommunication Ports - Rear> Mode 2

You can check the authenticity of this test report on the authenticity verification page on our website (www.kes.co.kr).



<Radiated Emissions(Below 1 ㎓) - Front> Mode 1




<Radiated Emissions(Below 1 ㎓) - Rear> Mode 1

You can check the authenticity of this test report on the authenticity verification page on our website (www.kes.co.kr).




<Radiated Emissions(Below 1 ㎓) - Front> Mode 2




<Radiated Emissions(Below 1 ㎓) - Rear> Mode 2

You can check the authenticity of this test report on the authenticity verification page on our website (www.kes.co.kr).




<Radiated Emissions(Above 1 ㎓) - Front> Mode 1




<Radiated Emissions(Above 1 ㎓) - Rear> Mode 1

You can check the authenticity of this test report on the authenticity verification page on our website (www.kes.co.kr).



<Radiated Emissions(Above 1 ㎓) - Front> Mode 2




<Radiated Emissions(Above 1 ㎓) - Rear> Mode 2

You can check the authenticity of this test report on the authenticity verification page on our website (www.kes.co.kr).




<Harmonic Current Emissions and Voltage Fluctuations and Flicker> Mode 1




<Electrostatic Discharge> Mode 1

You can check the authenticity of this test report on the authenticity verification page on our website (www.kes.co.kr).




<Electrostatic Discharge> Mode 2



<Continuous RF electromagnetic field disturbances> Mode 1

You can check the authenticity of this test report on the authenticity verification page on our website (www.kes.co.kr).



<Continuous RF electromagnetic field disturbances> Mode 2



<Electrical Fast Transients/Bursts> Mode 1

You can check the authenticity of this test report on the authenticity verification page on our website (www.kes.co.kr).



<Electrical Fast Transients/Bursts> Mode 2




<Surge> Mode 1

You can check the authenticity of this test report on the authenticity verification page on our website (www.kes.co.kr).




<Surge> Mode 2



<Continuous Induced RF Disturbances> Mode 1

You can check the authenticity of this test report on the authenticity verification page on our website (www.kes.co.kr).



<Continuous Induced RF Disturbances> Mode 2



<Voltage Dips and Interruptions> Mode 1

You can check the authenticity of this test report on the authenticity verification page on our website (www.kes.co.kr).

7.2 EUT Photographs




<EUT External Photographs - Top>




<EUT External Photographs - Bottom>

You can check the authenticity of this test report on the authenticity verification page on our website (www.kes.co.kr).




<Components -1>




<Port-1>

You can check the authenticity of this test report on the authenticity verification page on our website (www.kes.co.kr).



<Port-2>




<Port-3>

You can check the authenticity of this test report on the authenticity verification page on our website (www.kes.co.kr).



<Port-4>



<Port-5>

You can check the authenticity of this test report on the authenticity verification page on our website (www.kes.co.kr).



<EUT Internal Photographs>

You can check the authenticity of this test report on the authenticity verification page on our website (www.kes.co.kr).

7.3 Label

Name	:	Hanwha Vision Co., Ltd.
Product item	:	NETWORK CAMERA
Model name	:	XNP-A6374RH

The End.

You can check the authenticity of this test report on the authenticity verification page on our website (www.kes.co.kr).