

TEST REPORT

**CTK Co., Ltd.**

5 Dongbu-ro 221beon-gil, Cheoin-gu, Yongin-si,
Gyeonggi-do, Republic of Korea
Tel: +82-31-339-9970
Fax: +82-31-624-9501

REPORT No.:
CTK-2023-02177
Page (1) / (13) pages

1. Applicant

◦ Name : Hanwha Vision Co., Ltd
◦ Address : 6 Pangyo-ro 319Beon-gil, Bundang-gu, Seongnam-si,
Gyeonggi-do, 13488 KOREA
◦ Date of Receipt : 2023-09-01

2. Manufacturer

◦ Name : Hanwha Vision Co., Ltd

3. Use of Report

: Quality control

4. Test sample / Model

: NETWORK CAMERA / XNP-C9303RW

5. Date(s) of test

: 2023-10-11

6. Location of Test

: ☒ Permanent Testing Lab ☐ On Site Testing

Address: (144, Dongbu-ro, Cheoin-gu, Yongin-si,
Gyeonggi-do, Republic of Korea)

7. Test Standard (Method) used

: Specifications presented by the sponsor
(reference NEMA TS 2.2.9)

8. Testing Environment

: Temperature: (20.0 ± 1.0) °C,
Humidity: (50.0 ± 1.0) %R.H.

9. Test Results

: Refer to each test items


The results shown in this test report refer only to the sample(s) tested unless otherwise stated.
This Test Report cannot be reproduced, except in full.

Affirmation	Tested by	Technical Manager
	Min-Gi Mun (Signature)	SooChan Bae (Signature)

Remark, This report is not related to KOLAS accreditation and relevant regulation.

2023-10-12

CTK Co., Ltd.



 CTK Co., Ltd. The Prime Leader of Global Regulatory Certification	CTK Co., Ltd. 5 Dongbu-ro 221beon-gil, Cheoin-gu, Yongin-si, Gyeonggi-do, Republic of Korea Tel: +82-31-339-9970 Fax: +82-31-624-9501	REPORT No.: CTK-2023-02177 Page (2) / (13) pages	
---	--	--	--

1. Shock

1.1. Test equipment

Test equipment	Model	manufacturer	Serial
VIBRATION TESTING SYSTEM	GT1000M	FAMTECH	D1803072
Vibration VIEW	2017.1.2 Unicode 64-bit	Vibration Research Corp.	9526607B
VIBRATION TESTING SYSTEM	GT1000M	FAMTECH	D1803072-1
Vibration VIEW	2017.1.2 Unicode 64-bit	Vibration Research Corp.	955826DB
Acceleration sensor	8703A250M5	KISTLER	5241941

1.2. Test condition

- Acceleration : 10 G
- Test axis : $\pm X$, $\pm Y$, $\pm Z$
- Number of impacts : 1 per direction (total 6)

1.3. Check Item

- No mechanical damage.

1.4. Test Result

- Pass

 CTK Co., Ltd. The Prime Leader of Global Regulatory Certification	CTK Co., Ltd. 5 Dongbu-ro 221beon-gil, Cheoin-gu, Yongin-si, Gyeonggi-do, Republic of Korea Tel: +82-31-339-9970 Fax: +82-31-624-9501	REPORT No.: CTK-2023-02177 Page (3) / (13) pages	
---	--	--	--

Manufacturer's name

Name and address of factory (ies)	1) HANWHA TECHWIN SECURITY VIETNAM CO.,LTD Lot O-2, Que Vo Industrial Zone extended area, Nam Son commune, Bac Ninh city, Bac Ninh province, Vietnam 2) D-TECH CO.,LTD. 173-25, Saneop-ro, Gwonseon-gu, Suwon-si, Gyeonggi-do, Korea (Suwon Industrial Complex)
--------------------------------------	---

Model description

Basic Model:	XNP-C9303RW
Series model:	XNP-C8303RW
Model differences:	Use of the same external shape and materials (case, finishing material, PCB, cable, etc.), differences in electronic parts inside the product.

2. APPENDIX

2.1. Product Photographs

< Photo 1 > Product External view



< Photo 2 > Product External view




 CTK Co., Ltd. The Prime Leader of Global Regulatory Certification	CTK Co., Ltd. 5 Dongbu-ro 221beon-gil, Cheoin-gu, Yongin-si, Gyeonggi-do, Republic of Korea Tel: +82-31-339-9970 Fax: +82-31-624-9501	REPORT No.: CTK-2023-02177 Page (5) / (13) pages	
---	--	--	--

< Photo 3 > Product label




2.2. Test photos


[X axis]



[Y axis]




[Z axis]



2.3. Data

[Shock]



10 10, 2023 09:29:57 Level 1) 100 %

Output: 0.7101 Volts peak NEMA TS-2 2.2.9

Demand: 10 G


Control: 9.915 G

Pulse: 1 of 1

Running

[X+ axis]

[Shock]



10 10, 2023 09:30:03 Level 2) 100 %

Output: 0.7085 Volts peak NEMA TS-2 2.2.9

Demand: 10 G


Control: 10.19 G

Pulse: 1 of 1

End of Test

[X- axis]

[Shock]



10.11.2023 16:41:19 Level 1) 100 %

Output: 0.683 Volts peak NEMA TS-2 2.2.9

Demand: 10 G


Control: 10.11 G

Pulse: 1 of 1

Running

[Y+ axis]

[Shock]



10 11, 2023 16:41:25 Level 2) 100 %

Output: 0.6822 Volts peak NEMA TS-2 2.2.9

Demand: 10 G


Control: 10.25 G

Pulse: 1 of 1

End of Test

[Y- axis]

[Shock]



10 11. 2023 16:50:51 Level 1) 100 %

Output: 0.6687 Volts pea NEMA TS-2 2.2.

Demand: 10 G


Control: 10.05 G

Pulse: 1 of 1

Running

[Z+ axis]

[Shock]



10 11. 2023 16:50:51 Level 2) 100 %

Output: 0.6671 Volts pea NEMA TS-2 2.2.

Demand: 10 G

Control: 9.976 G

Pulse: 1 of 1

End of Test

[Z- axis]

- End -