EMC TEST REPORT For VCCI

Test Report No.	:	KES-E1-17T0114
Date of Issue	:	Feb, 13, 2017
Product name	:	NETWORK CAMERA
Model/Type No.	:	XNV-6020RN
Variant Model	:	-
Applicant	:	Hanwha Techwin Co., Ltd.
Applicant Address	:	1204, Changwon-daero, Seongsan-gu Changwon-si, Gyeongsangnam-do
Manufacturer	:	Hanwha Techwin (Tianjin) Co.,Ltd.
Manufacturer Address	:	No.11 Weiliu Rd,Micro-Electronic Industrial Park, TEDA,Tianjin,300385,People's Republic of China
Date of Receipt	:	Jan, 10, 2017
Test date	:	Feb, 06, 2017 ~ Feb, 07, 2017
Test Results	:	☒ **In Compliance** ☐ **Not in Compliance**

Tested by

Jin Bae, Lee
EMC Test Engineer

Reviewed by

Dong-Hun, Jang
EMC Technical Manager

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.

REPORT REVISION HISTORY

Date	Test Report No.	Revision History
Feb. 13, 2017	KES-E1-17T0114	Issued

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd. This document Sep be altered or revised by KES Co., Ltd. personnel only, and shall be noted in the revision section of the document. Any alteration of this document not carried out by KES Co., Ltd. will constitute fraud and shall nullify the document.

TABLE OF CONTENTS

1.0 General Product Description 4
1.1 Test Voltage & Frequency 7
1.2 Variant Model Differences 7
1.3 Device Modifications 7
1.4 Equipment Under Test 7
1.5 Support Equipments 7
1.6 External I/O Cabling 8
1.7 EUT Operating Mode(s) 9
1.8 Configuration 10
1.9 Calibration Details of Equipment Used for Measurement 11
1.10 Test Facility 11
1.11 Laboratory Accreditations and Listings 11
2.0 Test Regulations 12
2.1 Conducted Emissions Mains Power Ports 14
2.2 Conducted Emissions at Telecommunication Ports 15
2.3 Radiated Electric Field Emissions(Below 1 ㎓) 16
2.4 Radiated Electric Field Emissions(Above 1 ㎓) 17
APPENDIX A – TEST DATA 18
Conducted Emissions at Mains Power Ports 18
Conducted Emissions at Telecommunication Ports 20
Radiated Electric Field Emissions(Below 1 ㎓) 24
Radiated Electric Field Emissions(Above 1 ㎓) 25
Test Setup Photos and Configuration 33
Conducted Voltage Emissions 33
Conducted Telecommunication Emissions 34
Radiated Electric Field Emissions(Below 1 ㎓) 36
Radiated Electric Field Emissions(Above 1 ㎓) 38
EUT External Photographs 40
EUT Internal Photographs 41

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.

1.0 General Product Description

Main Specifications of EUT are:

Video	
Imaging Device	1/2.8" 2M CMOS
Total Pixels	1945(H) x 1109(V) 2.16M
Effective Pixels	1945(H) x 1097(V) 2.13M
Scanning System	Progressive Scan
Min. Illumination	Color : 0.015 lux(F1.4, 1/30sec) B/W : 0Lux(IR LED On)
S / N Ratio	50dB
Video Out	CVBS : 1.0 Vp-p / 75Ω composite, 720x480(N), 720x576(P), for installation USB : Micro USB type B, 1280x720, for installation
Lens	
Focal Length (Zoom Ratio	4mm Fixed
Max. Aperture Ratio	F1.4
Angular Field of View	H: 88.6°, V:47.5°, D: 104.8°
Min. Object Distance	0.4m
Focus Control	Manual
Lens Type	Fixed
Mount Type	Board-in type
Pan / Tilt / Rotate	
Pan / Tilt / Rotate range	0° ~ 354° / 0° ~ 67° / 0° ~ 355°
Operational	
IR Viewable Length	30m(98.43ft)
Camera Title	Off / On (Displayed up to 85 characters) - W/W : English/Numeric/Special Characters - China : English/Numeric/Special/Chinese Characters - Common : Multi-line (Max 5), Color (Grey/Green/Red/Blue/Black/White), Transparency, Auto Scale by Resolution
Day & Night	Auto (ICR) / Color / B/W / External / Schedule
Backlight Compensation	Off / BLC / HLC(Masking/Dimming), WDR
Wide Dynamic Range	150dB
Contrast Enhancement	SSDR (Off / On)
Digital Noise Reduction	SSNR5 (2D+3D Noise Filter) (Off / On)
Digital Image Stabilization	Off / On
Defog	Auto(input from fog detection) / Manual / Off
Motion Detection	Off/ On(8ea, 8point Polygonal zones), Handover
Privacy Masking	Off / On (32ea, polygonal zones) - Color : Grey/Green/Red/Blue/Black/White - Mosaic
Gain Control	Off / Low / Middle / High
White Balance	ATW / AWC / Manual / Indoor / Outdoor((included Mercury & Sodium)
Contrast	level adjustment
LDC	On/Off (5 levels with Min/Max)
Electronic Shutter Speed	Minimum / Maximum / Anti flicker (2 ~ 1/12,000sec)
Digital PTZ	24X, 'Digital PTZ(Preset, Group)
Flip / Mirror	Flip : On/Off Mirror : On/Off Hallway view : 90°/270°
Video & Audio Analytics	Tampering, Loitering, Directional Detection, Defocus Detection, Fog&Dust Detection, Virtual Line, Enter/Exit, Appear / Disappear, Audio Detection, Face Detection, Motion Detection, Digital Auto Tracking, Sound Classification, People counting, Heat map, Queue management
Alarm I/O	Input 1ea / Output 1ea
Alarm Triggers	Alarm Input, Motion Detection, Video & Audio Analytics, Network Disconnect

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.

Alarm events	File upload via FTP, E-Mail Notification via E-Mail local storage(SD/SDHC/SDXC) or NAS recording at Event Triggers External output DPTZ preset
Audio In	Selectable (Mic IN/Line IN) Supply voltage: 2.5VDC(4mA), Input impedance: approx. 2K Ohm
Audio out	Line out, Max output level: 1 Vrms
Pixel Counter	Support
Network	
Ethernet	RJ-45 (10/100BASE-T)
Video Compression Forma	H.265/H.264 (MPEG-4 Part 10/AVC) : Main/Baseline/High , Motion JPEG
Resolution	1920x1080, 1280x1024, 1280x960, 1280x720, 1024x768, 800x600, 800x448, 720x576, 720x480, 640x480, 640x360, 320x240
Max. Framerate	H.265/H.264 : Max. 60fps at all resolutions Motion JPEG : Max. 30fps
Smart Codec	Manual Mode (area-based : 5EA)
WiseStream II	Support
Video Quality Adjustment	H.264/H.265 : Target Bitrate Level Control MJPEG : Target Bitrate Level Control
Bitrate Control Method	H.264/H.265 : CBR or VBR MJPEG : VBR
Streaming Capability	Multiple Streaming (Up to 10 Profiles)
Audio Compression Forma	G.711 u-law /G.726 Selectable G.726 (ADPCM) 8KHz, G.711 8KHz G.726 : 16Kbps, 24Kbps, 32Kbps, 40Kbps AAC-LC : 48Kbps at 8/16/32/48KHz
Audio Communication	Bi-dierctional (2-Way)
IP	IPv4, IPv6
Protocol	TCP/IP, UDP/IP, RTP(UDP), RTP(TCP), RTCP,RTSP, NTP, HTTP, HTTPS, SSL/TLS, DHCP, PPPoE, FTP, SMTP, ICMP, IGMP, SNMPv1/v2c/v3(MIB-2), ARP, DNS, DDNS, QoS, PIM-SM, UPnP, Bonjour
Security	HTTPS(SSL) Login Authentication Digest Login Authentication IP Address Filtering User access Log 802.1X Authentication (EAP-TLS, EAP-LEAP)
Streaming Method	Unicast / Multicast
Max. User Access	20 users at Unicast Mode
Edge Storage	SD/SDHC/SDXC 2slot (up to 512 GB) - Continuous recording(1'st slot to 2'nd slot) - Motion Images recorded in the SD/SDHC/SDXC memory card can be downloaded. NAS(Network Attached Storage) Local PC for Instant Recording
Application Programming	ONVIF Profile S/G SUNAPI(HTTP API) Open Platform
Webpage Language	English, Korean, Chinese, French, Italian, Spanish, German, Japanese, Russian, Swedish,, Portuguese, Czech, Polish, Turkish, Dutch, Hungarian, Greek
Web Viewer	Supported OS: Windows 7, 8.1, 10, Mac OS X 10.10. 10.11 10.12 **Non-plugin Webviewer** Supported Browser: Google Chrome 54, MS Edge 38, Mozilla Firefox 49(Window 64bit only) , Apple Safari 9 (Mac OS X only) **Plug-in Webviewer** Supported Browser : MS Explore 11, Apple Safari 9 (Mac OS X only)
Central Management Soft	SmartViewer, SSM
Environmental	
Operating Temperature / Humidity	-30°C ~ +55°C (-22°F ~ +131°F) / Less than 90% RH *Start up should be done at above -20°C
Storage Temperature / Humidity	-50°C ~ +60°C (-22°F ~ +140°F) / Less than 90% RH
Ingress Protection	IP67, IP66

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.

Vandal Resistance	IK10
Electrical	
Input Voltage / Current	DC12V,PoE(IEEE802.3af,Class3)
Power Consumption	Max. 8W(12VDC), Max. 9W(PoE)
Mechanical	
Color / Material	Ivory / Metal
Dimension (WxHxD)	Ø120xH97.5mm(Ø4.72" x 3.84")
Weight	625g (1.37lb)

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.

1.1 Test Voltage & Frequency

Unless indicated otherwise on the individual data sheet or test results, the test voltage and frequency was as indicated below.

Voltage ☐ 100 Vac ☐ 110 Vac ☐ 24 Vac ☒ 12 Vdc ☒ PoE

Frequency ☐ 50 Hz ☐ 60 Hz ☐ Hz

1.2 Variant Model Differences

Not applicable

1.3 Device Modifications

Not applicable

1.4 Equipment Under Test

Description	Model Number	Serial Number	Manufacturer	Remarks
NETWORK CAMERA	XNV-6020RN	-	Hanwha Techwin(Tianjin) Co.,Ltd.	E.U.T

1.5 Support Equipments

Description	Model Number	Serial Number	Manufacturer	Remarks
POE Adapter	PD-3001GC/AC	RD9356082016964200	Power Dsine	-
Notebook	X56K	HN11N5151FJ0045W	HANSUNG	-
Notebook Adapter	A12-120P1A	F180271552011758	CHICONY POWER TECHNOLOGY CO.,LTD.	-
Phone	A1530	-	APPLE	-
MIC	CMK-303	-	CAMAC	-
Speaker	BR10000A CUVE	-	BEIJING EDIFIER HI-TECH GROUP.	-
Alarm	-	-	-	-
SD card	-	-	SanDisk	-

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.

1.6 External I/O Cabling

- DC 12 V Mode

Start		END		Cable Spec.	
Description	I/O Port	Description	I/O Port	Length	Shield
NETWORK CAMERA (E.U.T)	RJ-45	Notebook	RJ-45	3.0	U
	7 Pin	MIC	3.5 ㎜	1.7	U
		Speaker	3.5 ㎜	1.6	U
		Alarm	2 pin	3.0	U
	Slot	SD card	Slot	-	-
Notebook	Audio in	Phone	Audio out	1.7	U

- PoE Mode

Start		END		Cable Spec.	
Description	I/O Port	Description	I/O Port	Length	Shield
NETWORK CAMERA (E.U.T)	RJ-45 (POE)	POE Adapter	RJ-45 (POE)	3.0	U
	7 Pin	MIC	3.5 ㎜	1.7	U
		Speaker	3.5 ㎜	1.6	U
		Alarm	2 pin	3.0	U
	Slot	SD card	Slot	-	-
Notebook	Audio in	Phone	Audio out	1.7	U
	RJ-45 (DATA)	POE Adapter	RJ-45 (DATA)	3.0	U

* Unshielded = U, Shielded = S

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.

1.7 EUT Operating Mode(s)

Test mode	operating
DC 12 V, POE	E.U.T Monitoring, 1 ㎑, Ping Test


E.U.T Test operating S/W		
Name	Version	Manufacture Company
-	-	-

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.


1.8 Configuration

■ AC Main
□ DC Main

- DC 12 V Mode



- PoE Mode



This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.

1.9 Calibration Details of Equipment Used for Measurement

Test equipment and test accessories are calibrated on regular basis. The maximum time between calibrations is one year or what is recommended by the manufacturer, whichever is less.

1.10 Test Facility

The measurement facility is located at 473-21 Gayeo-ro, Yeoju-si, Gyeonggi-do, 12658, Korea. The sites are constructed in conformance with the requirements of ANSI C63.4 and CISPR Publication 22.

1.11 Laboratory Accreditations and Listings

Country	Agency	Scope of Accreditation	Logo
USA	**FCC**	3 & 10 meter Open Area Test Sites and one conducted site to perform FCC Part 15/18 measurements.	
JAPAN	**VCCI**	Mains Ports Conducted Interference Measurement, Telecommunication Ports Conducted Disturbance Measurement and Radiation 10 meter site, Facility for measuring radiated disturbance above 1 GHz	R-4308, C-4798, T-2311, G-914
KOREA	**MSIP**	EMI (10 meter Open Area Test Site and two conducted sites) Radio(3 & 10 meter Open Area Test Sites and one conducted site) EMS (ESD, RS, EFT/Burst, Surge, CS, Magnetic, Dips and interruptions)	KR0100
Canada	**IC**	3 & 10 meter Open Area Test Sites and one conducted site	4769B-1
Europe	**CE**	EMI (10 meter Open Area Test Site and two conducted sites) Radio(3 & 10 meter Open Area Test Sites and one conducted site) EMS (ESD, RS, EFT/Burst, Surge, CS, Magnetic, Dips and interruptions)	
International	**KOLAS**	EMI (10 meter Open Area Test Site and two conducted sites) Radio(3 & 10 meter Open Area Test Sites and one conducted site) EMS (ESD, RS, EFT/Burst, Surge, CS, Magnetic, Dips and interruptions)	

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.

2.0 Test Regulations

The emissions tests were performed according to following regulations:

☐ **EMC – Directive 2014/30/EU**

☐ EN 61000-6-3:2011		
☐ EN 61000-6-1:2007		
☐ EN 61000-6-4:2007 +A1:2011		
☐ EN 61000-6-2:2005		
☐ EN 55011:2007 +A1:2010	☐ Group 1 ☐ Class A	☐ Group 2 ☐ Class B
☐ EN 55014-1:2006 +A2:2011		
☐ EN 55014-2:1997 +A2:2008		
☐ EN 55015:2013		
☐ EN 61547 :2009		
☐ EN 55022:2010	☐ Class A	☐ Class B
☐ EN 55024:2010 +A1:2015		
☐ EN 50130-4:2011 +A1:2014		
☐ EN 61000-3-2:2014		
☐ EN 61000-3-3:2013		
☐ EN 61326-1:2013		

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.

☒ **VCCI V-3 / 2015.04** ☒ Class A ☐ Class B

☐ **AS/NZS CISPR22:2009 +A1:2010** ☐ Class A ☐ Class B

☐ **47 CFR Part 15, Subpart B**

- ☐ CISPR 22:2009 +A1:2010 ☐ Class A ☐ Class B
- ☐ ANSI C63.4-2009

☐ **IC Regulation ICES-003 : 2016**

- ☐ CAN/CSA CISPR 22-10 ☐ Class A ☐ Class B
- ☐ ANSI C63.4-2014

☐ **RE– Directive 2014/53/EU**

☐ EN 301 489-1 V1.9.2

- ☐ Equipment for fixed use
- ☐ Equipment for vehicular use
- ☐ Equipment for portable use

☐ EN 301 489-3 V1.6.1

☐ EN 301 489-17 V2.2.1

☐ EN 60945:2002

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.

2.1 Conducted Emissions Mains Power Ports

Test Date
N/A

Test Location
Electro wave Shieldroom

Test Equipment

Used	Description	Model Number	Manufacturer	Serial Number	Cal. Due
☐	EMI Test Receiver	ESR3	R & S	101783	05, 03, 2017
☐	LISN	ENV216	R & S	101137	02, 03, 2018
☐	LISN	ENV216	R & S	101786	05, 02, 2017
☐	Electro wave Shieldroom	-	SEMITEC	-	-
☐	EMI Test S/W	EMC32	R & S	9.12.00	-

Test Conditions
Temperature: ℃
Relative Humidity: %

Frequency Range of Measurement
150 ㎑ to 30 ㎒

Instrument Settings
IF Band Width: 9 ㎑

Test Results
The requirements are:

☐ PASS
☐ NOT PASS
☒ NOT APPLICABLE

Remarks
N/A Because the E.U.T power is 12 v (dc) power and PoE, limits are not specified.

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.

2.2 Conducted Emissions at Telecommunication Ports

Test Date
Feb, 06, 2017

Test Location
Electro wave Shieldroom

Test Equipment

Used	Description	Model Number	Manufacturer	Serial Number	Cal. Due
☒	EMI Test Receiver	ESR3	R & S	101783	05, 03, 2017
☒	LISN	ENV216	R & S	101137	02, 03, 2018
☒	LISN	ENV216	R & S	101786	05, 02, 2017
☒	8-Wire ISN CAT3	CAT3 8158	Schwarzbeck Mess	8158-0019	04, 01, 2017
☒	8-Wire ISN CAT5	CAT5 8158	Schwarzbeck Mess	8158-0030	04, 01, 2017
☐	8-Wire ISN CAT6	NTFM 8158	Schwarzbeck Mess	8158-0029	08, 11, 2017
☒	PULSE LIMITER	ESH3-Z2	R & S	101914	12, 13, 2017
☒	Shield Room #3	-	SEMITEC	-	-
☒	EMI Test S/W	EMC32	R & S	9.12.00	-

Test Conditions
Temperature: 23,4 ℃
Relative Humidity: 40,6 %

Frequency Range of Measurement
150 ㎑ to 30 ㎒

Instrument Settings
IF Band Width: 9 ㎑

Test Results
The requirements are:

☒ PASS
☐ NOT PASS
☐ NOT APPLICABLE

Remarks
See Appendix A for test data.

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.

2.3 Radiated Electric Field Emissions(Below 1 ㎓)

Test Date
Feb, 06, 2017

Test Location
☐ Open Area Test Site #1 ☒ Open Area Test Site #2

Test Equipment

Used	Description	Model Number	Manufacturer	Serial Number	Cal. Due
☒	EMI TEST Receiver	ESR3	R & S	101781	05, 03, 2017
☒	Trilog-Broadband Antenna	VULB9163	Schwarzbeck	714	11, 28, 2018
☒	OATS	-	KES	-	-
☒	Antenna Mast	-	DAEIL EMC	-	-
☒	Turn Table	-	DAEIL EMC	-	-
☒	EMI Test S/W	-	-	-	-

Test Conditions
Temperature: 2,3 ℃
Relative Humidity: 47,0 %

Frequency Range of Measurement
30 ㎒ to 1 ㎓

Instrument Settings
IF Band Width: 120 ㎑

Test Results
The requirements are:

☒ PASS
☐ NOT PASS
☐ NOT APPLICABLE

Remarks
See Appendix A for test data.

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.

2.4 Radiated Electric Field Emissions(Above 1 ㎓)

Test Date
Feb, 07, 2017

Test Location
Semi Anechoic Chamber #2

Test Equipment

Used	Description	Model Number	Manufacturer	Serial Number	Cal. Due
☒	DOUBLE RIDGED HORN ANTENNA	SAS-571	A.H.SYSTEM,INC	781	05, 07, 2017
☒	EMI Test Receiver	ESU26	R & S	100552	04, 24, 2017
☒	Broadband Coaxial Preamplifier	BBV 9718	Schwarzbeck Mess - Elektronik	9718-246	10, 14, 2017
☒	Semi Anechoic Chamber #2	-	SEMITEC	-	-
☒	Antenna Mast	-	AUDIX	-	-
☒	Turn Table	-	AUDIX	-	-
☒	EMI Test S/W	e3	AUDIX	8.083b	-

Test Conditions
Temperature: 21,2 ℃
Relative Humidity: 38,4 %

Frequency Range of Measurement
1 ㎓ to 6 ㎓

Instrument Settings
IF Band Width: 1 ㎒

Test Results
The requirements are:

☒ PASS
☐ NOT PASS
☐ NOT APPLICABLE

Remarks
See Appendix A for test data.

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.

APPENDIX A – TEST DATA

Conducted Emissions at Mains Power Ports

[HOT]

N/A

♦ Calculation
QuasiPeak[dBuV] / CAverage [dBuV] = Reading Value[dBuV] + Corr. [dB]
QuasiPeak / CAverage : The Final Value
Reading Value : Not shown in the table.
Corr. : Correction values (LISN FACTOR+ Cable Loss)

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.

[NEUTRAL]

N/A

♦ Calculation
QuasiPeak[dBuV] / CAverage [dBuV] = Reading Value[dBuV] + Corr. [dB]
QuasiPeak / CAverage : The Final Value
Reading Value : Not shown in the table.
Corr. : Correction values (LISN FACTOR+ Cable Loss)

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.


Conducted Emissions at Telecommunication Ports

- DC 12 V Mode

[10 Mbps]

Common Information

Test Description:	Telecommunication Emission
Model No.:	XNV-6020RN
Mode	DC 12 V _ 10 Mbps
Operator Name:	KES



Final_Result

Frequency (MHz)	QuasiPeak (dBµV)	CAverage (dBµV)	Limit (dBµV)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Line	Corr. (dB)
0.330000	---	50.10	77.45	27.35	1000.0	9.000	Single Line	21.1
0.330000	57.85	---	90.45	32.60	1000.0	9.000	Single Line	21.1
0.345000	---	55.16	77.08	21.92	1000.0	9.000	Single Line	21.1
0.345000	62.65	---	90.08	27.43	1000.0	9.000	Single Line	21.1
3.585000	---	45.16	74.00	28.84	1000.0	9.000	Single Line	19.8
3.585000	51.85	---	87.00	35.15	1000.0	9.000	Single Line	19.8
4.400000	---	45.04	74.00	28.96	1000.0	9.000	Single Line	19.8
4.400000	50.50	---	87.00	36.50	1000.0	9.000	Single Line	19.8
6.195000	---	48.80	74.00	25.20	1000.0	9.000	Single Line	19.9
6.195000	54.73	---	87.00	32.27	1000.0	9.000	Single Line	19.9


♦ Calculation
QuasiPeak[dBuV] / CAverage [dBuV] = Reading Value[dBuV] + Corr. [dB]
QuasiPeak / CAverage : The Final Value
Reading Value : Not shown in the table.
Corr. : Correction values (ISN FACTOR+ Cable Loss)

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.

[100 Mbps]

Common Information

Test Description:	Telecommunication Emission
Model No.:	XNV-6020RN
Mode	DC 12 V _ 100 Mbps
Operator Name:	KES



Final_Result

Frequency (MHz)	QuasiPeak (dBµV)	CAverage (dBµV)	Limit (dBµV)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Line	Corr. (dB)
0.335000	---	53.94	77.33	23.39	1000.0	9.000	Single Line	20.6
0.335000	59.82	---	90.33	30.51	1000.0	9.000	Single Line	20.6
0.350000	---	54.39	76.96	22.57	1000.0	9.000	Single Line	20.6
0.350000	62.33	---	89.96	27.63	1000.0	9.000	Single Line	20.6
3.040000	---	41.79	74.00	32.21	1000.0	9.000	Single Line	19.3
3.040000	45.92	---	87.00	41.08	1000.0	9.000	Single Line	19.3
4.415000	---	40.52	74.00	33.48	1000.0	9.000	Single Line	19.3
4.415000	45.28	---	87.00	41.72	1000.0	9.000	Single Line	19.3
23.130000	---	62.82	74.00	11.18	1000.0	9.000	Single Line	19.5
23.130000	65.18	---	87.00	21.82	1000.0	9.000	Single Line	19.5
26.610000	---	64.18	74.00	9.82	1000.0	9.000	Single Line	19.6
26.610000	66.28	---	87.00	20.72	1000.0	9.000	Single Line	19.6

♦ Calculation
QuasiPeak[dBuV] / CAverage [dBuV] = Reading Value[dBuV] + Corr. [dB]
QuasiPeak / CAverage : The Final Value
Reading Value : Not shown in the table.
Corr. : Correction values (ISN FACTOR+ Cable Loss)


This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.

- PoE Mode

[10 Mbps]

Common Information

Test Description:	Telecommunication Emission
Model No.:	XNV-6020RN
Mode	POE 10 Mbps
Operator Name:	KES



Final_Result

Frequency (MHz)	QuasiPeak (dBµ)	CAverage (dBµ)	Limit (dBµ)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Line	Corr. (dB)
0.630000	---	55.13	74.00	18.87	1000.0	9.000	Single Line	20.7
0.630000	55.33	---	87.00	31.67	1000.0	9.000	Single Line	20.7
4.945000	---	49.39	74.00	24.61	1000.0	9.000	Single Line	19.8
4.945000	54.97	---	87.00	32.03	1000.0	9.000	Single Line	19.8
7.505000	---	51.23	74.00	22.77	1000.0	9.000	Single Line	19.9
7.505000	57.73	---	87.00	29.27	1000.0	9.000	Single Line	19.9
7.555000	---	50.50	74.00	23.50	1000.0	9.000	Single Line	19.9
7.555000	57.06	---	87.00	29.94	1000.0	9.000	Single Line	19.9


♦ Calculation
QuasiPeak[dBuV] / CAverage [dBuV] = Reading Value[dBuV] + Corr. [dB]
QuasiPeak / CAverage : The Final Value
Reading Value : Not shown in the table.
Corr. : Correction values (ISN FACTOR+ Cable Loss)

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.

[100 Mbps]

Common Information

Test Description:	Telecommunication Emission
Model No.:	XNV-6020RN
Mode	POE 100 Mbps
Operator Name:	KES



Final_Result

Frequency (MHz)	QuasiPeak (dBµV)	CAverage (dBµV)	Limit (dBµV)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Line	Corr. (dB)
0.420000	---	50.66	75.45	24.79	1000.0	9.000	Single Line	20.5
0.420000	51.45	---	88.45	37.00	1000.0	9.000	Single Line	20.5
0.630000	---	54.91	74.00	19.09	1000.0	9.000	Single Line	20.2
0.630000	55.30	---	87.00	31.70	1000.0	9.000	Single Line	20.2
1.795000	---	44.62	74.00	29.38	1000.0	9.000	Single Line	19.5
1.795000	55.26	---	87.00	31.74	1000.0	9.000	Single Line	19.5
5.040000	---	50.80	74.00	23.20	1000.0	9.000	Single Line	19.3
5.040000	52.63	---	87.00	34.37	1000.0	9.000	Single Line	19.3
18.245000	---	58.34	74.00	15.66	1000.0	9.000	Single Line	19.6
18.245000	59.96	---	87.00	27.04	1000.0	9.000	Single Line	19.6

♦ Calculation
QuasiPeak[dBuV] / CAverage [dBuV] = Reading Value[dBuV] + Corr. [dB]
QuasiPeak / CAverage : The Final Value
Reading Value : Not shown in the table.
Corr. : Correction values (ISN FACTOR+ Cable Loss)

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.

Radiated Electric Field Emissions(Below 1 ㎓)

- DC 12 V Mode

Frequency	Amplitude	ANT Polar. (H/V)	ANT. Height	Correction Factor		Corrected Amplitude	Applicable Limit	Margin [dB]
[㎒]	[dBμV]		[m]	ANT. [dB/m]	Cable [dB]	[dBμV/m]	[dBμV/m]	
49.45	17.52	V	1.00	13.18	2.08	32.78	40.00	7.22
176.08	11.70	V	1.00	9.02	3.86	24.58	40.00	15.42
260.88	17.62	H	3.78	12.69	4.81	35.12	47.00	11.88
375.42	16.89	H	3.74	15.07	5.91	37.87	47.00	9.13
400.18	10.01	V	1.42	15.61	6.18	31.80	47.00	15.20
480.02	11.76	H	3.59	17.00	6.92	35.68	47.00	11.32

* H : Horizontal, V : Vertical

♦ Calculation
Corrected Amplitude [㏈uV] = Amplitude[㏈uV] + Correction Factor [㏈]
Corrected Amplitude : The Final Value, Amplitude : Reading Value,
Correction Factor : ANT FACTOR + Cable loss

- PoE Mode

Frequency	Amplitude	ANT Polar. (H/V)	ANT. Height	Correction Factor		Corrected Amplitude	Applicable Limit	Margin [dB]
[㎒]	[dBμV]		[m]	ANT. [dB/m]	Cable [dB]	[dBμV/m]	[dBμV/m]	
251.81	12.63	H	3.82	12.52	4.73	29.88	47.00	17.12
260.88	11.23	V	1.00	12.69	4.81	28.73	47.00	18.27
274.94	9.80	V	2.14	12.95	4.93	27.68	47.00	19.32
350.16	9.22	H	4.00	14.52	5.64	29.38	47.00	17.62
450.01	13.55	H	3.83	16.48	6.80	36.83	47.00	10.17
475.26	10.81	V	1.28	16.92	6.90	34.63	47.00	12.37


* H : Horizontal, V : Vertical

♦ Calculation
Corrected Amplitude [㏈uV] = Amplitude[㏈uV] + Correction Factor [㏈]
Corrected Amplitude : The Final Value, Amplitude : Reading Value,
Correction Factor : ANT FACTOR + Cable loss

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.

Radiated Electric Field Emissions(Above 1 ㎓)

- DC 12 V Mode



Site : chamber
Condition: CISPR22 CLASS-A PK 3m HORN781(2015.05.07) horizontal
: RBW:1000.000kHz VBW:1000.000kHz SWT:Auto
Project :
Model : XNV-6020RN
Mode : DC 12 V
Memo :


	Freq	Read Level	Ant Factor	Cable Loss	Preamp Factor	TPos	Limit Line	Over Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	deg	dBuV/m	dB		
1	1234.00	34.04	24.84	7.24	39.53	325	56.00	-29.41	horizontal	Average
2 pk	1234.00	54.99	24.84	7.24	39.53	325	76.00	-28.46	horizontal	Peak
3	1838.00	29.22	27.24	8.92	39.33	124	56.00	-29.95	horizontal	Average
4	1838.00	48.07	27.24	8.92	39.33	124	76.00	-31.10	horizontal	Peak
5 pp	2400.00	32.91	28.86	10.32	39.42	85	56.00	-23.33	horizontal	Average
6	2400.00	42.87	28.86	10.32	39.42	85	76.00	-33.37	horizontal	Peak

♦ Calculation

Over Limit [㏈] = (Read Level[㏈uV] + Ant Factor[㏈/m] + Cable Loss [㏈] − Preamp Factor [㏈]) − Limit Line[㏈uV]

Over Limit : Margin Value, Read Level : Reading Value, Ant Factor : Ant Factor, Cable Loss : Cable loss, Preamp Factor : Preamp Factor

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.




```
Site      : chamber
Condition: CISPR22 CLASS-A PK 3m HORN781(2015.05.07) vertical
         : RBW:1000.000kHz VBW:1000.000kHz SWT:Auto
Project   :
Model     : XNV-6020RN
Mode      : DC 12 V
Memo      :
```


	Freq	Read Level	Ant Factor	Cable Loss	Preamp Factor	TPos	Limit Line	Over Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	deg	dBuV/m	dB		
1 av	1272.00	34.59	24.99	7.35	39.44	337	56.00	-28.51	vertical	Average
2	1272.00	54.68	24.99	7.35	39.44	337	76.00	-28.42	vertical	Peak
3	1994.00	28.49	27.86	9.32	39.41	348	56.00	-29.74	vertical	Average
4 pp	1994.00	57.18	27.86	9.32	39.41	348	76.00	-21.05	vertical	Peak
5	2384.00	24.86	28.82	10.28	39.42	112	56.00	-31.46	vertical	Average
6	2384.00	51.54	28.82	10.28	39.42	112	76.00	-24.78	vertical	Peak

♦ Calculation

Over Limit [dB] = (Read Level[dBuV] + Ant Factor[dB/m] + Cable Loss [dB] − Preamp Factor [dB]) − Limit Line[dBuV]

Over Limit : Margin Value, Read Level : Reading Value, Ant Factor : Ant Factor, Cable Loss : Cable loss, Preamp Factor : Preamp Factor

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.



Site : chamber
Condition: CISPR22 CLASS-A PK 3m HORN781(2015.05.07) horizontal
: RBW:1000.000kHz VBW:1000.000kHz SWT:Auto
Project :
Model : XNV-6020RN
Mode : DC 12 V
Memo :


	Freq	Read Level	Ant Factor	Cable Loss	Preamp Factor	TPos	Limit Line	Over Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	deg	dBuV/m	dB		
1	3591.00	25.09	31.32	12.79	40.85	204	60.00	-31.65	horizontal	Average
2	3591.00	38.37	31.32	12.79	40.85	204	80.00	-38.37	horizontal	Peak
3	4269.00	24.06	33.55	14.05	40.74	353	60.00	-29.08	horizontal	Average
4	4269.00	36.70	33.55	14.05	40.74	353	80.00	-36.44	horizontal	Peak
5 pp	5202.00	22.91	37.31	15.71	40.61	71	60.00	-24.68	horizontal	Average
6 pk	5202.00	36.11	37.31	15.71	40.61	71	80.00	-31.48	horizontal	Peak

♦ Calculation

Over Limit [dB] = (Read Level[dBuV] + Ant Factor[dB/m] + Cable Loss [dB] − Preamp Factor [dB]) − Limit Line[dBuV]

Over Limit : Margin Value, Read Level : Reading Value, Ant Factor : Ant Factor, Cable Loss : Cable loss, Preamp Factor : Preamp Factor

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.




Site : chamber
Condition: CISPR22 CLASS-A PK 3m HORN781(2015.05.07) vertical
: RBW:1000.000kHz VBW:1000.000kHz SWT:Auto
Project :
Model : XNV-6020RN
Mode : DC 12 V
Memo :

	Freq	Read Level	Ant Factor	Cable Loss	Preamp Factor	TPos	Limit Line	Over Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	deg	dBuV/m	dB		
1	3594.00	25.05	31.33	12.79	40.85	244	60.00	-31.68	vertical	Average
2	3594.00	38.13	31.33	12.79	40.85	244	80.00	-38.60	vertical	Peak
3	4335.00	24.26	33.92	14.16	40.75	121	60.00	-28.41	vertical	Average
4	4335.00	36.88	33.92	14.16	40.75	121	80.00	-35.79	vertical	Peak
5 pp	4890.00	23.59	37.09	15.20	40.38	269	60.00	-24.50	vertical	Average
6 pk	4890.00	37.52	37.09	15.20	40.38	269	80.00	-30.57	vertical	Peak

♦ Calculation
Over Limit [㏈] = (Read Level[㏈uV] + Ant Factor[㏈/m] + Cable Loss [㏈] − Preamp Factor [㏈]) − Limit Line[㏈uV]
Over Limit : Margin Value, Read Level : Reading Value, Ant Factor : Ant Factor, Cable Loss : Cable loss, Preamp Factor : Preamp Factor

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.

- PoE Mode




```
Site      : chamber
Condition: CISPR22 CLASS-A PK 3m HORN781(2015.05.07) horizontal
          : RBW:1000.000kHz VBW:1000.000kHz SWT:Auto
Project   :
Model     : XNV-6020RN
Mode      : POE
Memo      :
```


	Freq	Read Level	Ant Factor	Cable Loss	Preamp Factor	TPos	Limit Line	Over Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	deg	dBuV/m	dB		
1	1150.00	31.47	24.51	6.97	39.73	170	56.00	-32.78	horizontal	Average
2	1150.00	57.44	24.51	6.97	39.73	170	76.00	-26.81	horizontal	Peak
3	1302.00	32.86	25.11	7.44	39.37	17	56.00	-29.96	horizontal	Average
4	1302.00	54.24	25.11	7.44	39.37	17	76.00	-28.58	horizontal	Peak
5	1738.00	26.56	26.84	8.67	39.29	64	56.00	-33.22	horizontal	Average
6	1738.00	41.27	26.84	8.67	39.29	64	76.00	-38.51	horizontal	Peak
7 av	2742.00	25.24	29.70	11.09	39.81	308	56.00	-29.78	horizontal	Average
8 pp	2742.00	50.22	29.70	11.09	39.81	308	76.00	-24.80	horizontal	Peak

♦ Calculation

Over Limit [dB] = (Read Level[dBuV] + Ant Factor[dB/m] + Cable Loss [dB] − Preamp Factor [dB]) − Limit Line[dBuV]

Over Limit : Margin Value, Read Level : Reading Value, Ant Factor : Ant Factor, Cable Loss : Cable loss, Preamp Factor : Preamp Factor

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.



Site : chamber
Condition: CISPR22 CLASS-A PK 3m HORN781(2015.05.07) vertical
: RBW:1000.000kHz VBW:1000.000kHz SWT:Auto
Project :
Model : XNV-6020RN
Mode : POE
Memo :


	Freq	Read Level	Ant Factor	Cable Loss	Preamp Factor	TPos	Limit Line	Over Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	deg	dBuV/m	dB		
1	1146.00	32.27	24.49	6.96	39.74	317	56.00	-32.02	vertical	Average
2	1146.00	59.44	24.49	6.96	39.74	317	76.00	-24.85	vertical	Peak
3	1246.00	32.38	24.89	7.27	39.50	323	56.00	-30.96	vertical	Average
4	1246.00	53.01	24.89	7.27	39.50	323	76.00	-30.33	vertical	Peak
5	1998.00	26.98	27.87	9.33	39.41	357	56.00	-31.23	vertical	Average
6 pp	1998.00	58.23	27.87	9.33	39.41	357	76.00	-19.98	vertical	Peak
7 av	2738.00	27.24	29.69	11.08	39.81	211	56.00	-27.80	vertical	Average
8	2738.00	51.20	29.69	11.08	39.81	211	76.00	-23.84	vertical	Peak

♦ Calculation

Over Limit [dB] = (Read Level[dBuV] + Ant Factor[dB/m] + Cable Loss [dB] − Preamp Factor [dB]) − Limit Line[dBuV]

Over Limit : Margin Value, Read Level : Reading Value, Ant Factor : Ant Factor, Cable Loss : Cable loss, Preamp Factor : Preamp Factor

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.




Site : chamber
Condition: CISPR22 CLASS-A PK 3m HORN781(2015.05.07) horizontal
: RBW:1000.000kHz VBW:1000.000kHz SWT:Auto
Project :
Model : XNV-6020RN
Mode : POE
Memo :

	Freq	Read Level	Ant Factor	Cable Loss	Preamp Factor	TPos	Limit Line	Over Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	deg	dBuV/m	dB		
1	3585.00	25.38	31.31	12.78	40.85	126	60.00	-31.38	horizontal	Average
2	3585.00	38.13	31.31	12.78	40.85	126	80.00	-38.63	horizontal	Peak
3	3996.00	24.87	32.00	13.56	40.70	245	60.00	-30.27	horizontal	Average
4	3996.00	37.74	32.00	13.56	40.70	245	80.00	-37.40	horizontal	Peak
5 pp	4764.00	24.16	36.37	15.02	40.51	217	60.00	-24.96	horizontal	Average
6 pk	4764.00	36.97	36.37	15.02	40.51	217	80.00	-32.15	horizontal	Peak

♦ Calculation
Over Limit [dB] = (Read Level[dBuV] + Ant Factor[dB/m] + Cable Loss [dB] − Preamp Factor [dB]) − Limit Line[dBuV]
Over Limit : Margin Value, Read Level : Reading Value, Ant Factor : Ant Factor,
Cable Loss : Cable loss, Preamp Factor : Preamp Factor

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.



Site : chamber
Condition: CISPR22 CLASS-A PK 3m HORN781(2015.05.07) vertical
: RBW:1000.000kHz VBW:1000.000kHz SWT:Auto
Project :
Model : XNV-6020RN
Mode : POE
Memo :

	Freq	Read Level	Ant Factor	Cable Loss	Preamp Factor	TPos	Limit Line	Over Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	deg	dBuV/m	dB		
1	3594.00	24.82	31.33	12.79	40.85	162	60.00	-31.91	vertical	Average
2	3594.00	37.26	31.33	12.79	40.85	162	80.00	-39.47	vertical	Peak
3	4539.00	24.10	35.09	14.54	40.73	252	60.00	-27.00	vertical	Average
4	4539.00	36.91	35.09	14.54	40.73	252	80.00	-34.19	vertical	Peak
5 pp	4995.00	23.11	37.69	15.31	40.28	208	60.00	-24.17	vertical	Average
6 pk	4995.00	35.71	37.69	15.31	40.28	208	80.00	-31.57	vertical	Peak

♦ Calculation

Over Limit [dB] = (Read Level[dBuV] + Ant Factor[dB/m] + Cable Loss [dB] − Preamp Factor [dB]) − Limit Line[dBuV]

Over Limit : Margin Value, Read Level : Reading Value, Ant Factor : Ant Factor, Cable Loss : Cable loss, Preamp Factor : Preamp Factor

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.

Test Setup Photos and Configuration

Conducted Voltage Emissions


N/A


N/A

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.

Conducted Telecommunication Emissions


- DC 12 V Mode






This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.

- PoE Mode





This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.

Radiated Electric Field Emissions(Below 1 ㎓)

- DC 12 V Mode





This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.

- PoE Mode






This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.

Radiated Electric Field Emissions(Above 1 ㎓)


- DC 12 V Mode






This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.

- PoE Mode





This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.

EUT External Photographs

(Top)



(Bottom)



This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.

EUT Internal Photographs

(Internal View)




This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.

EUT Internal View – Board 1

(Top)




(Bottom)




This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.

EUT Internal View – Board 2

(Top)



(Bottom)




This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.

EUT Internal View – Board 3

(Top)




(Bottom)




This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.

EUT Internal View – Board 4

(Top)



(Bottom)



This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.