



Network

Dome

XNV-6085

2M H.265 Camera (extraLUX)



Key Features

- Max. 2Megapixel (1920 x 1080) resolution
- 4.1 ~ 16.4mm (4x) motorized varifocal lens
- 0.004 Lux@F0.94 (Color), 0.0004 Lux@F0.94 (B/W)
- Max.60fps@all resoluotons (H.265 / H.264)
- H.265, H.264, MJPEG codec Supported, Multiple streaming
- Day & Night (ICR), WDR (150dB), Defog
- IVA, Motion detection, Handover
- SD / SDHC / SDXC memory slot (Max. 512GB)
- Hallway View, WiseStreamII Support
- IP67 / IP66, NEMA 4X, IK10 support
- Remote controlled PTRZ (PAN / TILT / ROTATE / ZOOM) maximizes angle adjustment convenience

Compatible Devices



SBP-300HM6



SBP-300CM



SBV-158G



SBP-300PM



SBP-300KM



SBP-300WM1



SPB-VAN81



SBP-300LM



SBP-390WM2




SBP-300WM



SBP-300B



SHD-1600FPW



SBP-160TM



SHP-1680FW



SBP-300NB

XNV-6085

2M H.265 Camera (extraLUX)



Specifications

Video		
Imaging Device	Size	1/2"
	Type	CMOS
Resolution		1920x1080, 1280x1024, 1280x960, 1280x720, 1024x768, 800x600, 800x448, 720x576, 720x480, 640x480, 640x360, 320x240
Max. Framerate	H.265/H.264	60fps/50fps(60Hz/50Hz)
	MJPEG	30fps
Min. Illumination (Lux)	Color(1/30sec, 30IRE)	0.004
	BW(1/30sec, 30IRE)	0.0004
Video Out		CVBS: 1.0 Vp-p / 75Ω composite for installation, USB: Micro USB Type B. Preview and installation ONLY. Requires WiFi dongle.

Lens		
Focal Length (mm)		4.1~16.4
Zoom Ratio	Optical	4x
Max Aperture Ratio (F number)	Wide	0.94
	Tele	2.4
Angular Field of View	Horizontal	100.0°~26.2°
	Vertical	54°~14.8°
	Diagonal	116.0°~30.0°
Min. Object Distance		0.7m(2.30ft)
Focus Control		Simple focus, Manual
Lens Type		DC auto iris

Pan / Tilt / Rotate		
Pan / Tilt / Rotate Range	Pan	-175°~175°
	Tilt	-73°~73°
	Rotate	-175°~175°
	Others	Remote adjustment(Max. 200cycles)

Operational		
Day & Night		Auto(ICR)

Operational

Backlight Compensation		BLC, HLC, WDR, SSSDR
Wide Dynamic Range (dB)		150
Digital Noise Reduction		SSNR V
Digital Image Stabilization		Support
Defog		Support
Motion Detection	Quantity	8ea
	Shape	8point Polygonal zones
Privacy Masking	Quantity	32ea
	Shape	Polygonal zones
	Color / Option	Gray, Green, Red, Blue, Black, White, Mosaic
Gain Control		Low, Middle, High
White Balance		ATW, AWC, Manual, Indoor, Outdoor
LDC		Support
Electronic Shutter	Mode	Minimum, Maximum, Anti flicker
	Speed Range	2~1/12,000sec
Video Rotation		Flip, Mirror, Hallway view(90°/270°)
Alarm Interface	In/Out	Input 1ea, Output 1ea
Alarm Triggers		Analytics, Network disconnect, Alarm input
Alarm Events When Alarm Trigger Occurred		File upload(image): e-mail/FTP, Notification: e-mail, Recording: SD/SDHC/SDXC or NAS recording at event triggers.Alarm output, Handover: PTZ preset,send message by HTTP/HTTPS/TCP
Audio In		Selectable(mic in/line in)
Audio Out		Line out

Analytics

Analytics Events	Normal	Defocus detection, Motion detection, Tampering, Fog detection, Face detection, Audio detection, Sound classification, Virtual area(Lotering, Intrusion, Enter/Exit, Appear/Disappear), Virtual line(Crossing, Direction) , Digital auto tracking
------------------	--------	--

Network

Ethernet		RJ-45(10/100BASE-T)
Video Compression		H.265/H.264: Main/Baseline/High, MJPEG
Audio Compression		G.711 u-law /G.726 selectable,G.726(ADPCM) 8kHz,G.711 8kHz, G.726: 16kbps,24kbps,32kbps,40kbps, AAC-LC: 48kbps at 16kHz
Smart Codec		Manual, WiseStream II
Bitrate Control		H.265/H.264: CBR or VBR, MJPEG: VBR

Network

Streaming	Unicast	Up to 20 users
	Multicast	Support
	Multiple Streaming	Up to 10 profiles
Protocol		IPv4, IPv6, TCP/IP, UDP/IP, RTP(UDP), RTP(TCP), RTCP, RTSP, NTP, HTTP, HTTPS, SSL/TLS, DHCP, FTP, SMTP, ICMP, IGMP, SNMPv1/v2c/v3(MIB-2), ARP, DNS, DDNS, QoS, UPnP, Bonjour, LLDP, SRTP(TCP, UDP Unicast), PIM-SM
Application Programming Interface	ONVIF	S, G, T
	Others	SUNAPI(HTTP API), Hanwha Vision Open Platform
Direct Cloud Connection		Optional (needs gateway)

Security

OS / Firmware Protect	Encrypted firmware, Secure boot, Signed firmware	
User authentication	Digest authentication	
Network authentication	IEEE 802.1X(EAP-TLS, EAP-LEAP)	
Secure Communication	HTTPS, WSS(WebSocket Secure), SRTP	
Access Control	IP-based access control	
Data Protect	Encryption credentials, Encrypt compress for live recording file export	
Audit	Access / System / Event Log management	
Secure Storage	SDcard partition encrypt(AES-256)	

General

Memory	RAM	1GB
	Flash	256MB
Edge Storage	Micro SD/SDHC/SDXC	Max. 512GB x 2slot(Total 1TB)

Environmental & Electrical

Operating Condition	Temperature	-40°C~+55°C(-40°F~+131°F)
	Humidity	0~90% RH(non-condensing)
	Others	Start up should be done at above -35°C
Storage Condition	Temperature	-40°C~+60°C(-40°F~+140°F)
	Humidity	0~90% RH(non-condensing)
Input Voltage		PoE(IEEE802.3af, Class3), 12VDC, 24VAC
Power Consumption	PoE	Max 12.1W
	12VDC	Max. 11.1W
	24VAC	Max. 13.5W

Mechanical

Color	Ivory
Material	Aluminum

Mechanical

Product Dimensions	ø160x140.0mm(6.30x5.51")
Product Weight	1,400g(3.09lb)

Certifications & Standards

Environment	IEC 60529 IP66, IEC 60529 IP67, IEC 62262 IK10, NEMA 250 type 4X
-------------	--

XNV-6085

2M H.265 Camera (extraLUX)



CAD

Unit: mm [inch]

XNV-6085

