



TEST REPORT



Report No. : KES-EM253633

Page 1 / 39

KES Co., Ltd.

#3002, #3503, #3701, 40, Simin-daero365beon-gil, Dongan-gu, Anyang-si, Gyeonggi-do, 14057, Republic of Korea
Tel : +82-31-425-6200, Fax : +82-31-341-3838

1. Client

- Name : Hanwha Vision Co., Ltd.
- Address : 6, Pangyo-ro 319beon-gil, Bundang-gu, Seongnam-si, Gyeonggi-do, Republic of Korea

2. Sample Description

- Product item : NETWORK CAMERA
- Model name : XNV-A8085R
- Variant model : -
- Manufacturer etc. : HANWHA VISION VIETNAM COMPANY LIMITED
- Manufacturer address : Lot O-2, Que Vo Industrial Zone Extended Area, Nam Son Ward, Bac Ninh Province, Vietnam
- Manufacturer etc. : D-TECH CO.,LTD.
- Manufacturer address : 173-25, Saneop-ro, Gwonseon-gu, Suwon-si, Gyeonggi-do, Korea (Suwon Industrial Complex)

3. Date of test : 2025. 10. 24. ~ 2025. 10. 26.

4. Location of Test : Permanent Testing Lab

- Address : 473-21, Gayeo-ro, Yeuju-si, Gyeonggi-do, 12658, Republic of Korea

5. Test method used : FCC 47 CFR Part 15, Subpart B (ANSI C63.4a-2017),
IC ICES-003 Issue 7 (ANSI C63.4a-2017)

6. Test result : PASS

The results shown in this test report refer only to the sample(s) tested unless otherwise stated.

This test report cannot be reproduced and copied without permission without the written consent of KES Co., Ltd.

This test report is not related to KOLAS accreditation.

Affirmation	Tested by	Technical Manager by
	Name : DaeSoo Kim	Name : DongHun Jang

2025. 11. 06.

KES Co., Ltd.

**REPORT REVISION HISTORY**

Date	Test Report No.	Revision History
2025. 11. 06.	KES-EM253633	Issued

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd. This document may be altered or revised by KES Co., Ltd. personnel only, and shall be noted in the revision section of the document. Any alteration of this document not carried out by KES Co., Ltd. will constitute fraud and shall nullify the document.

Use of uncertainty of measurement for decisions on conformity (decision rule):

■ No decision rule is specified by the 1 standard, when comparing the measurement result with the applicable limit according to the specification in that standard. The decisions on conformity are made without applying the measurement uncertainty ("simple acceptance" decision rule, previously known as "accuracy method").

□ Other (to be specified, for example when required by the standard or client)



TABLE OF CONTENTS

1	Laboratory Information	4
1.1	Test Location.....	4
1.2	Laboratory Accreditations and Listings	4
2	Test Summary	5
2.1	Class and Voltage.....	5
2.2	Summary of Test Results	5
2.3	Remarks when standards applied	5
2.4	Variant Model Differences	5
2.5	Device Modifications	5
3	General Product Description	6
4	EUT Setup and Operation Mode	10
4.1	EUT Configuration	10
4.2	System Configuration	10
4.3	External I/O Cabling	11
4.4	EUT Operating Mode(s).....	12
4.5	Test operating S/W	12
4.6	Configuration	13
5	Measurement Procedure.....	14
6	Test Item.....	15
6.1	Conducted Emissions at Mains Power Ports.....	15
6.2	Radiated Emissions(Below 1 GHz)	20
6.3	Radiated Emissions(Above 1 GHz)	25
7	Test Setup Photos and EUT Photographs	30
7.1	Test Setup Photos	30
7.2	EUT Photographs	36
7.3	Label	39



1 Laboratory Information

1.1 Test Location

Category	Details
Address	473-21, Gayeo-ro, Yeosu-si, Gyeonggi-do, 12658, Republic of Korea
Telephone Number	031-883-5092
Facsimile Number	031-883-5169

The measurement facility is located at 473-21, Gayeo-ro, Yeosu-si, Gyeonggi-do, 12658, Korea, Republic of. The sites are constructed in conformance with the requirements of ANSI C63.4a-2017 and CISPR 16-1-4:2019

1.2 Laboratory Accreditations and Listings

Country	Agency	Scope of Accreditation	Logo
KOREA	RRA	EMI (3 m & 10 m Semi-Anechoic Chamber and conducted test site) EMS (ESD, RS, EFT/Burst, Surge, CS, Magnetic, Dips and interruptions)	 KR0100
International	KOLAS	EMI (3 m & 10 m Semi-Anechoic Chamber and conducted test site) EMS (ESD, RS, EFT/Burst, Surge, CS, Magnetic, Dips and interruptions)	 KT489
USA	FCC	3 m & 10 m Semi-Anechoic Chamber Conducted test site to perform FCC Part 15/18 measurements.	 KR0100
Canada	ISED	3 m & 10 m Semi-Anechoic Chamber and Conducted test site	 23298
JAPAN	VCCI	EMI (3 m & 10 m Semi-Anechoic Chamber and conducted test site)	 C-20136, T-20137, R-20181, G-20176
Europe	TÜV SÜD	EMI (3 m & 10 m Semi-Anechoic Chamber and conducted test site) EMS (ESD, RS, EFT/Burst, Surge, CS, Magnetic, Dips and interruptions)	 CARAT 001633 0008



2 Test Summary

2.1 Class and Voltage

Test Class	Test Voltage
Class A	AC 120 V, 60 Hz

2.2 Summary of Test Results

Regulation			
47 CFR Part 15, Subpart B, ICES-003 Issue 7			
Test Item	Test Standard	Test Result	Remark
Conducted Emissions at Mains Power Ports	ANSI C63.4a-2017	PASS	-
Radiated Emissions(Below 1 GHz)		PASS	-
Radiated Emissions(Above 1 GHz)		PASS	-
* N/A: Not Applicable			

2.3 Remarks when standards applied

N/A

2.4 Variant Model Differences

N/A

2.5 Device Modifications

N/A



3 General Product Description

Division		Specificity
Internal maximum operating frequency		3 200 MHz
Power	Rated power	DC 12 V, PoE 56 V
	Test power	AC 230 V / 50 Hz
I/O Port	User port	DC IN 1 EA, RJ-45 1 EA, ALARM AUDIO 1 EA, Micro SD Slot 2 EA
	Unused/Administrator Ports	USB-TYPE C 1 EA
function	Product function	NETWORK CAMERA
	Wireless function	Not applicable
Components		Main body 1 EA, DC Cable 1 EA, ALARM AUDIO Cable 1 EA
Other		Not applicable

	XNV-A8085R
Video	
Imaging Device	1/2.8" CMOS
Resolution	2560x1920, 2560x1440, 1920x1080, 1600x1200, 1280x960, 1280x720, 1024x768, 800x600, 640x480, 640x360, 320x240, 320x180
Max. Framerate	H.265/H.264: Max. 30fps/25fps(60Hz/50Hz) MJPEG: Max. 30fps(@5MP Max. 5fps)
NETD	None
Pixel Size	None
Min. Illumination	Color: 0.04Lux(F1.3, 1/30sec, 30IRE) BW: 0.004Lux(F1.3, 1/30sec, 30IRE), 0Lux(IR LED on)
Video Out	USB: Micro USB Type C for installation
Video Transmission Distance	None
Lens	
Focal Length (Zoom Ratio)	3.3~9.3mm(2.8x) motorized varifocal
Optical Zoom	None
Max. Aperture Ratio	F1.3(Wide)~F2.3(Tele)
Angular Field of View	H: 99°(Wide)~31°(Tele) V: 71°(Wide)~23°(Tele) D: 133°(Wide)~39°(Tele)
Min. Object Distance	0.5m(1.64ft)
Focus Control	Simple focus, manual
Lens Type	P-iris(IR corrected)
Mount Type	None
Optional Lens	None
Pan / Tilt / Rotate	
Pan / Tilt / Rotate Range	0°~360° / 0°~85° / 0°~355°
Operational	
Camera Title	Displayed up to 85 characters



Direction Indicator	None
Day & Night	Auto(ICR)
Backlight Compensation	BLC, HLC, WDR, SSSR
Wide Dynamic Range	extremeWDR (120dB)
Digital Noise Reduction	SSNR V, WiseNR II (Based on AI engine)
Digital Image Stabilization	Support (built-in gyro sensor)
Defog	Support
Motion Detection	8ea, 8point polygonal zones
Privacy Masking	32ea, 8point polygonal zones - Color: gray/green/red/blue/black/white/purple/yellow - Mosaic Dynamic Privacy Mask(Based on AI engine) - Color: gray/green/red/blue/black/white/purple/yellow - Mosaic
Gain Control	Off / Max Gain / Manual
White Balance	ATW / NarrowATW / AWC / Manual / Indoor / Outdoor
LDC	Support(Fill/Stretch mode)
Electronic Shutter Speed	Minimum / Maximum / Anti flicker(2~1/30,000sec) Prefer shutter control(Based on AI engine)
Digital PTZ	None
Video Rotation	Flip, mirror, hallway view(90°/270°)
Analytics	Classified object type: Person/Face/Vehicle(Type: car/bus/truck/motorcycle/bicycle)/License plate Attributes: Person(Gender, Clothing top/bottom color, Bag), Face(Age, Gender, Mask, Glasses), Vehicle(Type: car/bus/truck/motorcycle/bicycle, Color) Support BestShot Support Re-ID(Person) Analytics events based on AI engine - Motion detection, Object detection, Virtual line(Crossing/Direction), Virtual area(Loitering/Intrusion/Enter/Exit/Appear/Disappear), Slip & fall detection, Face mask detection, Social distancing detection, Sound classification(To be released) Analytics events - Defocus detection, Tampering, Shock detection, Audio detection
Business Intelligence	Based on AI engine: People/Vehicle/Crowd counting, Queue management, Heatmap
Serial Interface	None
Alarm I/O	2 configurable I/O ports, DC 12V output(Max. 50mA) *Support extra alarm I/O via optional I/O box
Alarm Triggers	Analytics, Network disconnection, Alarm input, Time schedule, MQTT subscription, Day/Night, Storage disruption, Case tampering
Alarm Events	When alarm trigger occurred - File upload(image): e-mail/FTP/SFTP - File upload(video clip): FTP/SFTP - Notification: e-mail - Recording: SD/SDHC/SDXC or NAS recording at event triggers - Alarm output - Handover: PTZ preset, send message by HTTP/HTTPS/TCP - Audio clip playback(WAV, MP3) - MQTT: publication - SIP: call generation



Audio Streaming	None
Audio In	Selectable(mic in/line in)
Audio Out	Line out
Light Type	IR LED
Light Viewable Length	WiseIR PoE+: 50m(164.04ft) PoE: 30m(98.43ft)
Network	
Ethernet	Metal shielded RJ-45(10/100/1000 BASE-T)
Video Compression	H.265/H.264: Main/Baseline/High MJPEG
Audio Compression	G.711(PCM): 8kHz(64Kbps) G.726(ADPCM): 8kHz(16/24/32/40Kbps) AAC-LC: 16kHz(48Kbps) OPUS: 48kHz(64Kbps)
Smart Codec	WiseStream(Based on AI engine)
Video Quality Adjustment	None
Bitrate Control	H.264/H.265: CBR or VBR MJPEG: VBR
Streaming	Unicast(20 users) / Multicast Multiple streaming(Up to 5 profiles, 3 virtual channel support)
Protocol	IPv4, IPv6, TCP/IP, UDP/IP, RTP(UDP), RTP(TCP), RTCP, RTSP, NTP, HTTP, HTTPS, SSL/TLS, DHCP, FTP/SFTP, SMTP(StartTLS), ICMP, IGMP, SNMPv1/v2c/v3(MIB-2), ARP, DNS, DDNS, QoS, UPnP, Bonjour, LLDP, SRTP(TCP, UDP Unicast), CDP, MQTT, Syslog, SIP
SIP support (VoIP, Peer-to-peer, SIP/PBX integration)	Support
Security	None
Application Programming Interface	ONVIF Profile S/G/T/M SUNAPI(HTTP API) Hanwha Vision Open Platform
Security	
OS / Firmware Protect	Encrypted Firmware, Secure boot, Signed Firmware
User authentication	Digest Authentication, Prevent brute-force attack
Network authentication	802.1X Authentication(EAP-TLS, EAP-LEAP, EAP-PEAP MSCHAPv2)
Secure Communication	HTTPS, SRTP, WSS(Websocket secure)
Access Control	IP-based access control, MAC-based access control, Auto logout
Data Protect	Encryption Credentials, Encrypt compress for live recording file export
Audit	Access / System / Event Log management
Device ID	Device Certificate(Hanwha vision Root CA)
Secure Storage	Secure element, SDcard partition encrypt
Security Certificate	ETSI EN 303 645(TBD), Secure element(FIPS 140-3 level3, CC EAL6+)
General	
Webpage Language	English, Korean, Simplified Chinese, Traditional Chinese, French, Italian, Spanish, German, Japanese, Russian, Portuguese, Czech, Polish, Turkish, Dutch, Hungarian, Greek
Web Viewer	None
Edge Storage	Micro SD/SDHC/SDXC 2slot Max. 2TB(1TBx2)
Memory	4GB RAM, 8GB eMMC
Environmental &	



Electrical	
Operating Temperature / Humidity	-50°C~+60°C(-58°F~+140°F) +74°C(+165°F)(MAX) based on NEMA-TS 2(2.2.7) * Start up should be done at above -30°C 0~100%RH(Condensing) Humidity control with AIR vent
Storage Temperature / Humidity	-50°C~+60°C(-58°F~+140°F) / 0~90% RH
Wind Load	None
EPA(Effective Projected Area)	0.017 m ²
Certification	IP66/IP67/IP6K9K, NEMA4X, IK11, NEMA-TS 2(2.2.7.2-8, 2.2.8, 2.2.9)
Input Voltage	PoE(IEEE802.3af, Class3), PoE+(IEEE802.3at Type2, Class4), 12VDC
Power Consumption	PoE+ : Max. 14.2W, typical 9.4W PoE : Max. 12.9W, typical 8.3W 12VDC: Max. 9.5W, typical 14.5W Support Wisepower - Power monitoring(Max./Current/Avg.)
Mechanical	
Color / Material	White / Aluminum Bubble: Hard-coated dome
RAL Code	RAL9003
Product Dimensions / Weight	ø180x125mm(ø7.09x4.92"), 1860g(4.10 lb)
Compatible Conduit hole / Gangbox	19.1mm(3/4")(M25) single, double, 4" octagon, 4" square



4 EUT Setup and Operation Mode

4.1 EUT Configuration

Product Name	Model Number	Serial Number	Manufacturer	Remarks
NETWORK CAMERA	XNV-A8085R	-	HANWHA VISION VIETNAM COMPANY LIMITED	EUT
AC/DC ADAPTOR	FSP060-DIBAN2	-	Zhonghan Electronics(Shenzhen) Co., Ltd.	-
PoE Injector	PT-PSE109GBRO-AH	PT1933220259	Dongguan PROCET Network Technology Co.,Ltd	-
Micro SD CARD 1	-	-	Transcend	-
Micro SD CARD 2	-	-	Transcend	-
SMART PHONE	V50	-	LG	-
LAPTOP	NT630Z5J	JK9091EF400142M	SAMSUNG	-
LAPTOP ADAPTOR	PA-1400-14	AA-PA2N40W	LITEON	-
HEADSET	K550	-	Britz®	-
Button Alarm	-	-	-	-
LED Alarm	SIP-1201DD D0	-	SAMSUNG TECHWIN CO., LTD.	-

4.2 System Configuration

Product Name	Model Number	Serial Number	Manufacturer	Remarks
-	-	-	-	-



4.3 External I/O Cabling

Mode 1

Start		End		Cable Spec.	
Product Name	I/O Port	Product Name	I/O Port	Length(m)	Shield
NETWORK CAMERA (EUT)	DC IN (2 PIN)	AC/DC ADAPTOR	DC OUT (2 PIN)	1.0	U
	RJ-45 (PoE)	LAPTOP	RJ-45	3.1	U
	Alarm In (2 PIN)	Button Alarm	Alarm OUT	3.1	U
	Alarm OUT (2 PIN)	LED Alarm	Alarm IN	4.1	U
	AUDIO OUT (3.5 mm)	HEADSET	3.5 mm	2.0	U
	AUDIO IN (3.5 mm)		3.5 mm		
	Micro SD SLOT	Micro SD CARD 1	Micro SD SLOT	-	-
	Micro SD SLOT	Micro SD CARD 2	Micro SD SLOT	-	-
LAPTOP	3.5 mm	SMARTPHONE	3.5 mm	1.5	U
	DC JACK	LAPTOP ADAPTOR	DC JACK	1.0	U

Mode 2

Start		End		Cable Spec.	
Product Name	I/O Port	Product Name	I/O Port	Length(m)	Shield
NETWORK CAMERA (EUT)	RJ-45 (PoE)	PoE Injector	RJ-45 (PoE)	3.1	U
	Alarm In (2 PIN)	Button Alarm	Alarm OUT	3.1	U
	Alarm OUT (2 PIN)	LED Alarm	Alarm IN	4.1	U
	AUDIO OUT (3.5 mm)	HEADSET	3.5 mm	2.0	U
	AUDIO IN (3.5 mm)		3.5 mm		
	Micro SD SLOT	Micro SD CARD 1	Micro SD SLOT	-	-
	Micro SD SLOT	Micro SD CARD 2	Micro SD SLOT	-	-
LAPTOP	3.5 mm	SMARTPHONE	3.5 mm	1.5	U
	RJ-45	PoE Injector	RJ-45 (LAN)	1.0	U
	DC JACK	LAPTOP ADAPTOR	DC JACK	1.0	U

* Unshielded=U, Shielded=S

**4.4 EUT Operating Mode(s)**


Category	Mode	Operating
Mode 1	DC	1. By connecting the test equipment and the DC power supply with a wired connection, the image output of the test equipment is confirmed by the WEB VIEWER. 2. After activating the operation of the microphone, run a 1 KHz Tone voice file on a smartphone connected to a laptop to check whether the headset outputs sound normally or not on the headset connected to the test equipment. 3. Check the ping test of the laptop to see if the network of the test equipment is operating normally or not. 4. After the test, it was confirmed that the recorded image stored in the Micro SD Card was checked.
Mode 2	PoE	1. By connecting the test equipment and the PoE Injector by wire, the image output of the test equipment is checked by WEB VIEWER. 2. After activating the operation of the microphone, run a 1 KHz Tone voice file on a smartphone connected to a laptop to check whether the headset outputs sound normally or not on the headset connected to the test equipment. 3. Check the ping test of the laptop to see if the network of the test equipment is operating normally or not. 4. After the test, it was confirmed that the recorded image stored in the Micro SD Card was checked.

4.5 Test operating S/W


Name	Version	Manufacture Company
WEB VIEWER	-	Hanwha Vision Co., Ltd.



4.6 Configuration



Mode 1



Mode 2



5 Measurement Procedure

- Conducted Emissions

The conducted emission levels were measured on each current-carrying line with the spectrum analyzer operating in the CISPR quasi-peak mode (or peak mode if applicable). The initial step in collecting conducted data is a spectrum analyzer peak scan of the measurement range. If the conducted emission exceed the average limit with the instrument set to the quasi-peak mode, the measurements are made in the average mode. The emission spectrum was scanned from 150 kHz to 30 MHz. The highest emission amplitudes relative to the appropriate limits were measured and have been recorded. Quasi-peak readings are distinguished with a "QP".

- Radiated Electric Field Emissions

The test was done at a SEMI ANECHOIC CHAMBER with quasi-peak detector. The final test data was measured using a Quasi-Peak detector below 1 GHz at 10 m or 3 m distance and a Peak and Average detector above 1 GHz at 3 m distance. Test was proceeded worst case test mode and cable configuration. Measurements were made with the antenna positioned in both the horizontal and vertical planes of polarization. The antenna height was varied from 1 m to 4 m and the EUT was rotated 360° to find the maximum emitting point for each frequency.

Measurement procedures was In accordance with ANSI C63.4 or CISPR 32.

◆ Calculation

- Conducted Emissions

QuasiPeak[dBuV] / CAverage[dBuV] = Reading Value[dBuV] + Corr. [dB]

QuasiPeak / CAverage : The Final Value

Reading Value : Not shown in the table.

Corr. : Correction values (LISN FACTOR + (Cable Loss + Pulse Limiter FACTOR))

- Radiated Emissions(Below 1 GHz)

Result(QP) [dB(μV/m)] = (Reading(QP)[dB(μV)] + c.f[dB(1/m)])

Margin(QP)[dB] = Limit[dB(μV/m)] - Result(QP) [dB(μV/m)]

Reading(QP) : Reading value, Result(QP) : Reading value + Factor value

Limit(QP) : Limit value, c.f : (ANT Factor + Cable Loss - Preamp Factor), Margin: Margin value

- Radiated Emissions(Above 1 GHz)

Result(PK/CAV) [dB(μV/m)] = (Reading(PK/CAV)[dB(μV)] + c.f[dB(1/m)])

Margin(PK/CAV)[dB] = Limit[dB(μV/m)] - Result(PK/CAV) [dB(μV/m)]

Reading(PK/CAV) : Reading value, Result(PK/CAV) : Reading value + Factor value

Limit(PK/CAV) : Limit value, c.f : (ANT Factor + Cable Loss - Preamp Factor), Margin: Margin value



6 Test Item

6.1 Conducted Emissions at Mains Power Ports

6.1.1 Test Equipment


Equipment Name	Model Number	Manufacturer	Serial No.	Cal. Date	Next Cal. Date	Used
SHIELD ROOM #6	-	DYMSTEC	-	-	-	■
EMC32 Measurement Software	EMC32	R&S	9.12.00	-	-	■
EMI TEST RECEIVER	ESR3	Rohde & Schwarz	101783	2024-11-06	2025-11-06	■
LISN	ENV216	Rohde & Schwarz	101786	2025-01-09	2026-01-09	■
ARTIFICIAL MAINS NETWORK	ESH2-Z5	Rohde & Schwarz	100450	2024-11-06	2025-11-06	■
PULSE LIMITER	ESH3-Z2	Rohde & Schwarz	101915	2024-11-06	2025-11-06	■

6.1.2 Test Location : SHIELD ROOM #6

6.1.3 Test Conditions :

Temperature	Relative Humidity
(23.3 ~ 23.4) °C	(50.3 ~ 50.4) % R.H.

6.1.4 Diagram of test setup






6.1.5 Test Result

- Test Date : 2025-10-24
- Test Mode : Mode 1

Test Report

1 / 1

Test Description: Conducted Emission
Job No.: KES-EM253633
Phase: L
Mode: Mode 1
Operator Name: KES



Final_Result

Frequency (MHz)	QuasiPeak (dB μV)	CAverage (dB μV)	Limit (dB μV)	Margin (dB)	Meas. Time	Bandwidth (kHz)	Line	Corr. (dB)
0.160000	---	24.94	66.00	41.06	1000.0	9.000	L1	19.5
0.160000	43.97	---	79.00	35.03	1000.0	9.000	L1	19.5
0.500000	---	29.41	66.00	36.59	1000.0	9.000	L1	19.6
0.500000	35.89	---	73.00	37.11	1000.0	9.000	L1	19.6
4.940000	---	20.33	60.00	39.67	1000.0	9.000	L1	19.9
4.940000	25.61	---	73.00	47.39	1000.0	9.000	L1	19.9
5.125000	---	21.00	60.00	39.00	1000.0	9.000	L1	19.9
5.125000	26.35	---	73.00	46.65	1000.0	9.000	L1	19.9
6.595000	---	23.93	60.00	36.07	1000.0	9.000	L1	20.0
6.595000	29.11	---	73.00	43.89	1000.0	9.000	L1	20.0
6.695000	---	25.84	60.00	34.16	1000.0	9.000	L1	20.0
6.695000	30.90	---	73.00	42.10	1000.0	9.000	L1	20.0



Report No. : KES-EM253633

Page 17 / 39


○ Test Date : 2025-10-24

● Test Mode : Mode 1

Test Report

1 / 1

Test Description: Conducted Emission
Job No.: KES-EM253633
Phase: N
Mode: Mode 1
Operator Name: KES



Final_Result

Frequency (MHz)	QuasiPeak (dB μ V)	CAverage (dB μ V)	Limit (dB μ V)	Margin (dB)	Meas. Time	Bandwidth (kHz)	Line	Corr. (dB)
0.165000	43.40	—	79.00	35.60	1000.0	9.000	N	19.5
0.165000	—	25.08	66.00	40.92	1000.0	9.000	N	19.5
0.180000	43.66	—	79.00	35.34	1000.0	9.000	N	19.5
0.180000	—	25.68	66.00	40.32	1000.0	9.000	N	19.5
0.500000	35.40	—	73.00	37.60	1000.0	9.000	N	19.5
0.500000	—	28.61	66.00	37.39	1000.0	9.000	N	19.5
5.015000	26.08	—	73.00	46.92	1000.0	9.000	N	19.9
5.015000	—	20.80	60.00	39.20	1000.0	9.000	N	19.9
6.570000	28.71	—	73.00	44.29	1000.0	9.000	N	19.9
6.570000	—	23.38	60.00	36.62	1000.0	9.000	N	19.9
6.695000	30.55	—	73.00	42.45	1000.0	9.000	N	20.0
6.695000	—	25.51	60.00	34.49	1000.0	9.000	N	20.0



Report No. : KES-EM253633

Page 18 / 39


○ Test Date : 2025-10-24

● Test Mode : Mode 2

Test Report

1 / 1

Test Description: Conducted Emission
Job No.: KES-EM253633
Phase: L
Mode: Mode 2
Operator Name: KES



Final_Result

Frequency (MHz)	QuasiPeak (dB μV)	CAverage (dB μV)	Limit (dB μV)	Margin (dB)	Meas. Time	Bandwidth (kHz)	Line	Corr. (dB)
0.420000	60.36	---	79.00	18.64	1000.0	9.000	L1	19.6
0.420000	---	54.40	66.00	11.60	1000.0	9.000	L1	19.6
0.450000	54.72	---	79.00	24.28	1000.0	9.000	L1	19.6
0.450000	---	48.51	66.00	17.49	1000.0	9.000	L1	19.6
1.005000	45.94	---	73.00	27.06	1000.0	9.000	L1	19.6
1.005000	---	37.23	60.00	22.77	1000.0	9.000	L1	19.6
1.340000	45.63	---	73.00	27.37	1000.0	9.000	L1	19.6
1.340000	---	38.66	60.00	21.34	1000.0	9.000	L1	19.6
5.365000	42.00	---	73.00	31.00	1000.0	9.000	L1	19.9
5.365000	---	34.82	60.00	25.18	1000.0	9.000	L1	19.9
5.530000	41.88	---	73.00	31.12	1000.0	9.000	L1	19.9
5.530000	---	33.87	60.00	26.13	1000.0	9.000	L1	19.9



Report No. : KES-EM253633

Page 19 / 39


○ Test Date : 2025-10-24

● Test Mode : Mode 2

Test Report

1 / 1

Test Description: Conducted Emission
Job No.: KES-EM253633
Phase: N
Mode: Mode 2
Operator Name: KES



Final_Result

Frequency (MHz)	QuasiPeak (dB μV)	CAverage (dB μV)	Limit (dB μV)	Margin (dB)	Meas. Time	Bandwidth (kHz)	Line	Corr. (dB)
0.420000	60.47	---	79.00	18.53	1000.0	9.000	N	19.5
0.420000	---	54.81	66.00	11.19	1000.0	9.000	N	19.5
0.455000	52.95	---	79.00	26.05	1000.0	9.000	N	19.5
0.455000	---	49.59	66.00	16.41	1000.0	9.000	N	19.5
1.000000	46.20	---	73.00	26.80	1000.0	9.000	N	19.6
1.000000	---	40.96	60.00	19.04	1000.0	9.000	N	19.6
1.130000	44.63	---	73.00	28.37	1000.0	9.000	N	19.6
1.130000	---	31.75	60.00	28.25	1000.0	9.000	N	19.6
5.945000	41.32	---	73.00	31.68	1000.0	9.000	N	19.9
5.945000	---	33.91	60.00	26.09	1000.0	9.000	N	19.9
6.210000	41.96	---	73.00	31.04	1000.0	9.000	N	19.9
6.210000	---	35.08	60.00	24.92	1000.0	9.000	N	19.9

6.1.6 Remark

Complies with the test requirements.



6.2 Radiated Emissions(Below 1 GHz)

6.2.1 Test Equipment


Equipment Name	Model Number	Manufacturer	Serial No.	Cal. Date	Next Cal. Date	Used
SEMI ANECHOIC CHAMBER #4(10 m)	-	DYMSTEC	-	-	-	■
EP5/RE Software	EP5/RE	TOYO	6.0.0	-	-	■
EMI TEST RECEIVER	ESU26	Rohde & Schwarz	100551	2025-02-13	2026-02-13	■
AMPLIFIER	SCU 01	Rohde & Schwarz	100603	2024-11-06	2025-11-06	■
BILOG ANTENNA	VULB 9168	SCHWARZBEC K	9168-461	2024-05-09	2026-05-09	■
ATTENUATOR	6806.17.A	HUBER+SUHNER	-	2025-02-13	2026-02-13	■

6.2.2 Test Location : SEMI ANECHOIC CHAMBER #4(10 m) Measurement Distance : □ 3 m, ■ 10 m

6.2.3 Test Conditions :

Temperature	Relative Humidity
(21.0 ~ 21.3) °C	(52.6 ~ 52.9) % R.H.


6.2.4 Diafram of test setup





6.2.5 Test Result

- Test Date : 2025-10-26
- Test Mode : Mode 1_FCC



Final Result

No.	Frequency [MHz]	(P)	Reading QP [dB(uV)]	c.f [dB(1/m)]	Result QP [dB(uV/m)]	Limit QP [dB(uV/m)]	Margin QP [dB]	Height [cm]	Angle [deg]	Remark
1	52.431	H	41.4	-21.0	20.4	39.0	18.6	400.0	269.0	
2	67.830	H	41.1	-22.3	18.8	39.0	20.2	296.0	225.0	
3	69.891	V	49.1	-22.7	26.4	39.0	12.6	114.0	282.0	
4	81.168	V	50.3	-25.8	24.5	39.0	14.5	125.0	145.0	
5	97.173	V	51.5	-25.4	26.1	43.5	17.4	100.0	266.0	
6	104.205	H	45.3	-24.3	21.0	43.5	22.5	381.0	29.0	
7	183.866	V	46.3	-21.2	25.1	43.5	18.4	112.0	169.0	
8	191.990	H	44.7	-21.8	22.9	43.5	20.6	350.0	113.0	
9	311.421	V	49.0	-16.6	32.4	46.5	14.1	107.0	200.0	
10	424.305	H	44.8	-12.6	32.2	46.5	14.3	289.0	12.0	
11	624.974	V	43.9	-6.5	37.4	46.5	9.1	116.0	242.0	
12	875.113	H	36.4	-2.4	34.0	46.5	12.5	272.0	251.0	


※ The data is the result measured by the detector in Quasi-Peak mode on the Peak graph.



Report No. : KES-EM253633

Page 22 / 39

- Test Date : 2025-10-26
- Test Mode : Mode 2_FCC



Final Result

No.	Frequency [MHz]	(P)	Reading QP [dB(uV)]	c.f [dB(1/m)]	Result QP [dB(uV/m)]	Limit QP [dB(uV/m)]	Margin QP [dB]	Height [cm]	Angle [deg]	Remark
1	41.883	V	55.2	-21.7	33.5	39.0	5.5	112.0	284.0	
2	42.004	H	43.0	-21.7	21.3	39.0	17.7	283.0	253.0	
3	72.559	V	50.1	-23.5	26.6	39.0	12.4	142.0	173.0	
4	74.014	H	44.5	-23.9	20.6	39.0	18.4	400.0	7.0	
5	114.269	H	50.4	-23.1	27.3	43.5	16.2	362.0	292.0	
6	116.330	V	56.4	-22.8	33.6	43.5	9.9	114.0	158.0	
7	144.945	V	50.7	-19.6	31.1	43.5	12.4	123.0	46.0	
8	192.596	H	50.2	-21.8	28.4	43.5	15.1	329.0	337.0	
9	226.304	V	51.9	-21.0	30.9	46.5	15.6	125.0	71.0	
10	249.948	H	51.9	-19.5	32.4	46.5	14.1	324.0	206.0	
11	332.640	V	48.0	-16.0	32.0	46.5	14.5	100.0	342.0	
12	624.974	H	42.4	-6.5	35.9	46.5	10.6	287.0	185.0	


※ The data is the result measured by the detector in Quasi-Peak mode on the Peak graph.



Report No. : KES-EM253633

Page 23 / 39

- Test Date : 2025-10-26
- Test Mode : Mode 1_IC



Final Result

No.	Frequency [MHz]	(P)	Reading QP [dB(μV)]	c.f [dB(1/m)]	Result QP [dB(μV/m)]	Limit QP [dB(μV/m)]	Margin QP [dB]	Height [cm]	Angle [deg]	Remark
1	52.431	H	41.4	-21.0	20.4	40.0	19.6	400.0	269.0	
2	67.830	H	41.1	-22.3	18.8	40.0	21.2	296.0	225.0	
3	69.891	V	49.1	-22.7	26.4	40.0	13.6	114.0	282.0	
4	81.168	V	50.3	-25.8	24.5	40.0	15.5	125.0	145.0	
5	97.173	V	51.5	-25.4	26.1	43.5	17.4	100.0	266.0	
6	104.205	H	45.3	-24.3	21.0	43.5	22.5	381.0	29.0	
7	183.866	V	46.3	-21.2	25.1	43.5	18.4	112.0	169.0	
8	191.990	H	44.7	-21.8	22.9	43.5	20.6	350.0	113.0	
9	311.421	V	49.0	-16.6	32.4	47.0	14.6	107.0	200.0	
10	424.305	H	44.8	-12.6	32.2	47.0	14.8	289.0	12.0	
11	624.974	V	43.9	-6.5	37.4	47.0	9.6	116.0	242.0	
12	875.113	H	36.4	-2.4	34.0	47.0	13.0	272.0	251.0	


※ The data is the result measured by the detector in Quasi-Peak mode on the Peak graph.



Report No. : KES-EM253633

Page 24 / 39

- Test Date : 2025-10-26
- Test Mode : Mode 2_IC



Final Result

No.	Frequency [MHz]	(P)	Reading QP [dB(μV)]	c.f [dB(1/m)]	Result QP [dB(μV/m)]	Limit QP [dB(μV/m)]	Margin QP [dB]	Height [cm]	Angle [deg]	Remark
1	41.883	V	55.2	-21.7	33.5	40.0	6.5	112.0	284.0	
2	42.004	H	43.0	-21.7	21.3	40.0	18.7	283.0	253.0	
3	72.559	V	50.1	-23.5	26.6	40.0	13.4	142.0	173.0	
4	74.014	H	44.5	-23.9	20.6	40.0	19.4	400.0	7.0	
5	114.269	H	50.4	-23.1	27.3	43.5	16.2	362.0	292.0	
6	116.330	V	56.4	-22.8	33.6	43.5	9.9	114.0	158.0	
7	144.945	V	50.7	-19.6	31.1	43.5	12.4	123.0	46.0	
8	192.596	H	50.2	-21.8	28.4	43.5	15.1	329.0	337.0	
9	226.304	V	51.9	-21.0	30.9	46.4	15.5	125.0	71.0	
10	249.948	H	51.9	-19.5	32.4	47.0	14.6	324.0	206.0	
11	332.640	V	48.0	-16.0	32.0	47.0	15.0	100.0	342.0	
12	624.974	H	42.4	-6.5	35.9	47.0	11.1	287.0	185.0	

※ The data is the result measured by the detector in Quasi-Peak mode on the Peak graph.

6.2.6 Remark

Complies with the test requirements.



6.3 Radiated Emissions(Above 1 GHz)

6.3.1 Test Equipment


Equipment Name	Model Number	Manufacturer	Serial No.	Cal. Date	Next Cal. Date	Used
SEMI ANECHOIC CHAMBER #5	-	SY Corporation	-	-	-	■
ES10/RE Software	ES10/RE	TOYO	2022.01.000	-	-	■
EMI TEST RECEIVER	ESU26	Rohde & Schwarz	100552	2025-02-13	2026-02-13	■
PREAMPLIFIER	8449B	HP	3008A00538	2025-04-30	2026-04-30	■
ATTENUATOR	8491B	HP	23094	2025-02-13	2026-02-13	■
HORN ANTENNA	BBHA 9120D	SCHWARZBEC K	9120D-1802	2024-11-04	2025-11-04	■

6.3.2 Test Location : SEMI ANECHOIC CHAMBER #5

6.3.3 Test Conditions :

Temperature	Relative Humidity
(22.1 ~ 22.2) °C	(54.3 ~ 54.4) % R.H.


6.3.4 Diagram of test setup





6.3.5 Test Result

- Test Date : 2025-10-24
- Test Mode : Mode 1



Final Result

No.	Frequency [MHz]	Pol	Reading AV [dB(μV)]	Reading PK [dB(μV)]	c.f. [dB(1/m)]	Result AV [dB(μV/m)]	Result PK [dB(μV/m)]	Limit AV [dB(μV/m)]	Limit PK [dB(μV/m)]	Margin AV [dB]	Margin PK [dB]	Height [cm]	Angle [deg]
1	1369.111	H	30.3	44.1	0.6	30.9	44.7	60.0	80.0	29.1	35.3	277.0	138.1
2	1380.446	V	30.7	44.1	0.6	31.3	44.7	60.0	80.0	28.7	35.3	106.0	353.3
3	1844.078	V	29.8	42.9	2.5	32.3	45.4	60.0	80.0	27.7	34.6	154.0	256.3
4	1894.309	H	29.8	43.0	2.6	32.4	45.6	60.0	80.0	27.6	34.4	312.0	308.8
5	2286.800	V	28.9	42.7	4.3	33.2	47.0	60.0	80.0	26.8	33.0	122.0	40.6
6	2497.209	H	29.4	43.6	5.2	34.6	48.8	60.0	80.0	25.4	31.2	292.0	280.2
7	2765.165	V	28.5	41.7	6.0	34.5	47.7	60.0	80.0	25.5	32.3	107.0	193.7
8	2844.105	H	28.4	41.5	6.3	34.7	47.8	60.0	80.0	25.3	32.2	253.0	355.2
9	3356.227	V	28.6	41.7	7.2	35.8	48.9	60.0	80.0	24.2	31.1	115.0	267.0
10	3436.308	H	28.8	42.4	7.4	36.2	49.8	60.0	80.0	23.8	30.2	331.0	56.6
11	4760.116	V	28.1	41.1	11.5	39.6	52.6	60.0	80.0	20.4	27.4	100.0	6.2
12	4848.188	H	27.6	40.9	11.9	39.5	52.8	60.0	80.0	20.5	27.2	290.0	156.7

✂ The data is the result of measured by the detector in PK and CISPR Average on the Peak graph.

✂ The Average of the test data is the cispr average result.



○ Test Date : 2025-10-24

● Test Mode : Mode 1

PK									
Frequency (MHz)	Reading PK (dBuV)	Polarization	Height (m)	ANT Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)
6 908.400	39.500	H	1.000	35.860	9.970	34.690	50.640	80.000	29.360
8 737.500	39.300	V	1.000	37.500	10.860	33.930	53.730	80.000	26.270
9 858.100	38.900	H	1.000	39.430	11.970	34.000	56.300	80.000	23.700
10 873.400	40.300	V	1.000	39.800	12.740	32.680	60.160	80.000	19.840
CISPR AV									
Frequency (MHz)	Reading CISPR AV (dBuV)	Polarization	Height (m)	ANT Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)
6 908.400	32.800	H	1.000	35.860	9.970	34.690	43.940	60.000	16.060
8 737.500	32.800	V	1.000	37.500	10.860	33.930	47.230	60.000	12.770
9 858.100	32.500	H	1.000	39.430	11.970	34.000	49.900	60.000	10.100
10 873.400	33.500	V	1.000	39.800	12.740	32.680	53.360	60.000	6.640

※ No spurious emission were detected above 16 GHz




Report No. : KES-EM253633

Page 28 / 39

○ Test Date : 2025-10-24

● Test Mode : Mode 2



Final Result

No.	Frequency [MHz]	Pol	Reading AV [dB(μV)]	Reading PK [dB(μV)]	c.f [dB(1/m)]	Result AV [dB(μV/m)]	Result PK [dB(μV/m)]	Limit AV [dB(μV/m)]	Limit PK [dB(μV/m)]	Margin AV [dB]	Margin PK [dB]	Height [cm]	Angle [deg]
1	1274.400	H	30.2	43.1	0.0	30.2	43.1	60.0	80.0	29.8	36.9	100.0	115.3
2	1374.800	V	31.0	45.4	0.6	31.6	46.0	60.0	80.0	28.4	34.0	100.0	31.7
3	1668.800	H	30.1	43.5	1.8	31.9	45.3	60.0	80.0	28.1	34.7	100.0	281.6
4	1890.000	V	29.3	43.2	2.6	31.9	45.8	60.0	80.0	28.1	34.2	100.0	355.3
5	2144.800	H	28.9	42.5	3.5	32.4	46.0	60.0	80.0	27.6	34.0	100.0	303.9
6	2378.400	V	28.8	42.5	4.8	33.6	47.3	60.0	80.0	26.4	32.7	100.0	265.9
7	2574.800	H	29.3	42.8	5.3	34.6	48.1	60.0	80.0	25.4	31.9	100.0	308.4
8	2930.000	V	28.3	41.8	6.4	34.7	48.2	60.0	80.0	25.3	31.8	100.0	293.9
9	3166.800	H	28.3	41.2	6.8	35.1	48.0	60.0	80.0	24.9	32.0	100.0	335.2
10	3436.800	V	28.6	41.3	7.4	36.0	48.7	60.0	80.0	24.0	31.3	100.0	65.2
11	4817.600	H	27.4	40.4	11.7	39.1	52.1	60.0	80.0	20.9	27.9	100.0	241.7
12	4873.200	V	27.1	40.3	12.0	39.1	52.3	60.0	80.0	20.9	27.7	100.0	239.8

※ The data is the result of measured by the detector in PK and CISPR Average on the Peak graph.

※ The Average of the test data is the cispr average result.



○ Test Date : 2025-10-24

● Test Mode : Mode 2

PK									
Frequency (MHz)	Reading PK (dBuV)	Polarization	Height (m)	ANT Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)
6 648.400	38.900	V	1.000	34.610	10.050	34.800	48.760	80.000	31.240
6 973.400	39.800	H	1.000	36.170	9.970	34.660	51.280	80.000	28.720
9 823.000	39.300	V	1.000	39.340	11.960	33.920	56.680	80.000	23.320
10 922.800	40.800	H	1.000	39.800	12.760	32.870	60.490	80.000	19.510
CISPR AV									
Frequency (MHz)	Reading CISPR AV (dBuV)	Polarization	Height (m)	ANT Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)
6 648.400	32.300	V	1.000	34.610	10.050	34.800	42.160	60.000	17.840
6 973.400	33.200	H	1.000	36.170	9.970	34.660	44.680	60.000	15.320
9 823.000	32.600	V	1.000	39.340	11.960	33.920	49.980	60.000	10.020
10 922.800	34.200	H	1.000	39.800	12.760	32.870	53.890	60.000	6.110

※ No spurious emission were detected above 16 GHz

6.3.6 Remark

Complies with the test requirements.



7 Test Setup Photos and EUT Photographs

7.1 Test Setup Photos



<Conducted Emissions at Mains Power Ports - Front> Mode 1




<Conducted Emissions at Mains Power Ports - Rear> Mode 1




<Conducted Emissions at Mains Power Ports - Front> Mode 2




<Conducted Emissions at Mains Power Ports - Rear> Mode 2




<Radiated Emissions(Below 1 GHz) - Front> Mode 1




<Radiated Emissions(Below 1 GHz) - Rear> Mode 1




<Radiated Emissions(Below 1 GHz) - Front> Mode 2




<Radiated Emissions(Below 1 GHz) - Rear> Mode 2




<Radiated Emissions(Above 1 GHz) - Front> Mode 1



<Radiated Emissions(Above 1 GHz) - Rear> Mode 1



<Radiated Emissions(Above 1 GHz) - Front> Mode 2



<Radiated Emissions(Above 1 GHz) - Rear> Mode 2



7.2 EUT Photographs



<EUT External Photographs - Top>




<EUT External Photographs - Bottom>



<Components>



<Port-1>



<EUT Internal Photographs>



7.3 Label



Name : Hanwha Vision Co., Ltd.
Product item : NETWORK CAMERA
Model name : XNV-A8085R

This device complies with Part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) This device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.

The above label is only an example. The specific format is left to the manufacturer to decide, as long as the label includes the required information, in accordance with ICES-Gen. The requirements specified in ICES-Gen shall apply. An example ISED compliance label, to be placed on each unit of an equipment model (or in the user manual, if allowed), is given below:

CAN ICES-003(A) / NMB-003(A)

The End.