

TEST REPORT

**CTK Co., Ltd.**

5 Dongbu-ro 221beon-gil, Cheoin-gu, Yongin-si,
Gyeonggi-do, Republic of Korea
Tel: +82-31-339-9970
Fax: +82-31-624-9501

REPORT No.:

CTK-2026-00012

Page (1) / (24) pages

1. Applicant

- Name : Hanwha Vision Co., Ltd
◦ Address : 6, Pangyo-ro 319Beon-gil, Bundang-gu, Seongnam-si,
Gyeonggi-do, 13488 Republic of Korea
◦ Date of Receipt : Nov. 17, 2025

2. Manufacturer

- Name : Hanwha Vision Co., Ltd

3. Use of Report :

Quality control

4. Test sample / Model :

NETWORK CAMERA / XNV-A9016R

5. Date(s) of test :

Dec. 02, 2025~ Dec. 09, 2025

6. Test Standard (Method) used :

NEMA 250-2014

Enclosures for Electrical Equipment (1000 Volts Maximum)

7. Testing Environment :

Temperature: (25 ±10) °C, Humidity: (50 ±25) % R.H.

Pressure: (96 ±10) kPa

8. Test Results :

Refer to the test results

9. Location of Test :☒ Permanent Testing Lab ☐ On Site Testing

(5 Dongbu-ro 221beon-gil, Cheoin-gu, Yongin-si, Gyeonggi-do, Republic of Korea)

The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This report cannot be reproduced or copied without the written consent of CTK.

Approval	Tested by	Technical Manager
	Name: HyungUk Jeon (Signature)	Name: HoHyun Lee (Signature)

Remark. This report is not related to KOLAS accreditation and relevant regulation.

Jan. 02, 2025

CTK Co., Ltd.

**CTK Co., Ltd.**

5 Dongbu-ro 221beon-gil, Cheoin-gu, Yongin-si,
Gyeonggi-do, Republic of Korea
Tel: +82-31-339-9970
Fax: +82-31-624-9501

REPORT No.:
CTK-2026-00012
Page (2) / (24) pages

Table of Contents

1. Testing laboratory	3
1.1 Testing laboratory information	3
1.2 Testing laboratory accreditation status	3
2. Product description and equipment information	3
2.1 Product description	3
2.2 Manufacturer information	4
2.3 Equipment information	6
2.4 Pre-test product images	7
2.5 Testing equipment images	8
3. Test Information	9
3.1 Test item particulars and Possible test case verdicts	9
3.2 General remarks and factory information	9
3.3 Type 4X Test information	10
3.4 NEMA 250-2014 Test list	12
3.5 Attachment 1 - Construction Diagram and installation method	15
3.6 Attachment 2 - Parts List	18
4. Hose Down Test (Clause 5.7)	21
4.1 Test date and environmental conditions	21
4.2 Test Conditions and methods	21
4.3 Attachment 3 - Photographs	22
4.4 Test result	23
4.5 Post-test product images	24

 CTK Co., Ltd. 5 Dongbu-ro 221beon-gil, Cheoin-gu, Yongin-si, Gyeonggi-do, Republic of Korea Tel: +82-31-339-9970 Fax: +82-31-624-9501	REPORT No.: CTK-2026-00012 Page (3) / (24) pages	
--	--	--

1. Testing laboratory

1.1 Testing laboratory information

Lab. Name	CTK Co., Ltd.
Representative	Young Joseph Seungwon
Address	5 Dongbu-ro 221beon-gil, Cheoin-gu, Yongin-si, Gyeonggi-do, Republic of Korea
Tel.	+82-31-339-9970
Fax.	+82-31-624-9501
E-Mail	all.youngin@element.com
Website	www.elementkorea.kr

1.2 Testing laboratory accreditation status

Country	Classification	Accreditation Number	Logo
International	KOLAS	TESTING NO. KT119	

2. Product description and equipment information

2.1 Product description

Product Name	Model Name	Quantity	Comment
NETWORK CAMERA	XNV-A9016R	1 EA	—

2.2 Model description

Basic Model	XNV-A9016R
Series model	XNV-A8016R, XNV-A6016R
Model differences	Use of the same external shape and materials (case, finishing material, PCB, cable, etc.), Image sensor and Lens difference.

**CTK Co., Ltd.**

5 Dongbu-ro 221beon-gil, Cheoin-gu, Yongin-si,
Gyeonggi-do, Republic of Korea
Tel: +82-31-339-9970
Fax: +82-31-624-9501

REPORT No.:

CTK-2026-00012

Page (4) / (24) pages

2.3 Manufacturer information

Test item description : NETWORK CAMERA**Trade Mark****Manufacturer**

Lot O-2, Que Vo Industrial Zone extended area, Nam Son ward,
Bac Ninh province, Vietnam

173-25, Saneop-ro, Gwonseon-gu, Suwon-si, Gyeonggi-do, Korea
(Suwon Industrial Complex)

Model/Type reference : XNV-A9016R

Electrical

XNV-A9016R

PoE 48 V $\approx$ 10.0 W / PoE 48 V $\approx$ 0.21 A**Ratings**

XNV-A8016R

PoE 48 V $\approx$ 7.9 W / PoE 48 V $\approx$ 0.17 A

XNV-A6016R

PoE 48 V $\approx$ 6.6 W / PoE 48 V $\approx$ 0.14 A

Dimension:

Ø120 by 376.8 mm, Ø52 by 163.28 mm, Ø5.2*2 by 32.6 mm, 81.76
mm, 81.76 mm

List of Attachments (including a total number of pages in each attachment):

Attachment 1: 15-17 pages (Construction Diagram including installation method)

Attachment 2: 18-20 pages (Parts List)

Attachment 3: 22-24 pages (photographs)

Summary of testing:

Tests performed (name of test and test clause):
Clause 5.7(Hose Down Test)

Testing location:

CTK Co., Ltd.

5 Dongbu-ro 221beon-gil, Cheoin-gu, Yongin-si,
Gyeonggi-do, Republic of Korea



CTK Co., Ltd.

5 Dongbu-ro 221beon-gil, Cheoin-gu, Yongin-si,
Gyeonggi-do, Republic of Korea
Tel: +82-31-339-9970
Fax: +82-31-624-9501

REPORT No.:
CTK-2026-00012
Page (5) / (24) pages

Copy of marking plate: The artwork above may be only a draft.



NETWORK CAMERA,XNV-A9016R
PoE (48V $\overline{\text{---}}$) 0.21A

M/C: XNV-A9016R/KEX Fac.ID:D
DATE S/N: Serial No.
MAC ADDRESS: XX-XX-XX-XX-XX-XX
CAN ICES-3(A)/NMB-3(A)
HANWHA VISION CO.,LTD.
MADE IN KOREA

Rainproof/ Étanche
IP66

제품명칭: NETWORK CAMERA
모델명: XNV-A9016R
정격전압: PoE(48V $\overline{\text{---}}$) 10.0W

M/C: XNV-A9016R/KDO Fac. ID: D
DATE S/N: Serial No.
MAC ADDRESS: XX-XX-XX-XX-XX-XX
인증번호: R-R-HWVS-XNVA9016R
상호: 한화비전(주)
제조사/제조국가:한화비전(주)/한국



NETWORK CAMERA,XNV-A8016R
PoE (48V $\overline{\text{---}}$) 0.17A

M/C: XNV-A8016R/KEX Fac.ID:D
DATE S/N: Serial No.
MAC ADDRESS: XX-XX-XX-XX-XX-XX
CAN ICES-3(A)/NMB-3(A)
HANWHA VISION CO.,LTD.
MADE IN KOREA

Rainproof/ Étanche
IP66

제품명칭: NETWORK CAMERA
모델명: XNV-A8016R
정격전압: PoE(48V $\overline{\text{---}}$) 7.9W

M/C: XNV-A8016R/KDO Fac. ID: D
DATE S/N: Serial No.
MAC ADDRESS: XX-XX-XX-XX-XX-XX
인증번호: R-R-HWVS-XNVA8016R
상호: 한화비전(주)
제조사/제조국가:한화비전(주)/한국



NETWORK CAMERA,XNV-A6016R
PoE (48V $\overline{\text{---}}$) 0.14A

M/C: XNV-A6016R/KEX Fac.ID:D
DATE S/N: Serial No.
MAC ADDRESS: XX-XX-XX-XX-XX-XX
CAN ICES-3(A)/NMB-3(A)
HANWHA VISION CO.,LTD.
MADE IN KOREA

Rainproof/ Étanche
IP66

제품명칭: NETWORK CAMERA
모델명: XNV-A6016R
정격전압: PoE(48V $\overline{\text{---}}$) 6.6W

M/C: XNV-A6016R/KDO Fac. ID: D
DATE S/N: Serial No.
MAC ADDRESS: XX-XX-XX-XX-XX-XX
인증번호: R-R-HWVS-XNVA6016R
상호: 한화비전(주)
제조사/제조국가:한화비전(주)/한국



**CTK Co., Ltd.**

5 Dongbu-ro 221beon-gil, Cheoin-gu, Yongin-si,
Gyeonggi-do, Republic of Korea
Tel: +82-31-339-9970
Fax: +82-31-624-9501

REPORT No.:
CTK-2026-00012
Page (6) / (24) pages

2.4 Equipment information

Testing equipment	Model Name	Manufacturer	Manufacturing Number	Next Cal. Date
25.4mm Nozzle	S3-IP18	CTK	S3-IP18	-
Temperature & Humidity Chamber	C4-340	Weisstechnik	54260023190010	Feb.06,2026
Area flow meter	Z-6504	FLOWTECH	229400	Jan.16,2026
Steel measuring meter	5.5 m	KOMELON	225851	Jan.16,2026
Stop Watch	NONE	Casio	612Q01R-1	Jan.15,2027
Digital Vernier Calipers	100 mm	MITUTOYO	A17179462	-



CTK Co., Ltd.

5 Dongbu-ro 221beon-gil, Cheoin-gu, Yongin-si,
Gyeonggi-do, Republic of Korea
Tel: +82-31-339-9970
Fax: +82-31-624-9501

REPORT No.:
CTK-2026-00012
Page (7) / (24) pages

2.5 Pre-test product images

2.5.1 Test sample



Top



Bottom



Front



Rear



Left side



Right side



CTK Co., Ltd.

5 Dongbu-ro 221beon-gil, Cheoin-gu, Yongin-si,
Gyeonggi-do, Republic of Korea
Tel: +82-31-339-9970
Fax: +82-31-624-9501

REPORT No.:
CTK-2026-00012
Page (8) / (24) pages

2.6 Testing equipment images

2.6.1 Test equipment



25.4mm Nozzle



Temperature & Humidity Chamber



Area flow meter



Steel measuring meter



Stop Watch



Digital Vernier Calipers

**CTK Co., Ltd.**

5 Dongbu-ro 221beon-gil, Cheoin-gu, Yongin-si,
Gyeonggi-do, Republic of Korea
Tel: +82-31-339-9970
Fax: +82-31-624-9501

REPORT No.:

CTK-2026-00012

Page (9) / (24) pages

3. Test Information

3.1 Test item particulars and Possible test case verdicts

Test item particulars	NETWORK CAMERA
Classification of installation and use	Outdoor (Watertight/Corrosion Resistant)
Possible test case verdicts:	
- test case does not apply to the test object	N/A
- test object does meet the requirement.....	P (Pass)
- test object does not meet the requirement	F (Fail)
- test case does not evaluate to the test object:	N/E

3.2 General remarks and factory information

General remarks:
"(See Enclosure #)" refers to additional information appended to the report. "(See appended table)" refers to a table appended to the report. Throughout this report a ☐ comma / ☒ point is used as the decimal separator. Clause numbers between brackets refer to clauses in NEMA 250-2014
Name and address of factory (ies):
1. HANWHA VISION VIETNAM COMPANY LIMITED Lot O-2, Que Vo Industrial Zone extended area, Nam Son ward, Bac Ninh city, Bac Ninh province, Vietnam 2. D-TECH CO., LTD. 173-25, Saneop-ro, Gwonseon-gu, Suwon-si, Gyeonggi-do, Korea (Suwon Industrial Complex)



CTK Co., Ltd.

5 Dongbu-ro 221beon-gil, Cheoin-gu, Yongin-si,
Gyeonggi-do, Republic of Korea
Tel: +82-31-339-9970
Fax: +82-31-624-9501

REPORT No.:

CTK-2026-00012

Page (10) / (24) pages

3.3 Type 4X Test information

Type 4X

Enclosures constructed for either indoor or outdoor use to provide a degree of protection to personnel against access to hazardous parts; to provide a degree of protection of the equipment inside the enclosure against ingress of solid foreign objects (falling dirt and windblown dust); to provide a degree of protection with respect to harmful effects on the equipment due to the ingress of water (rain, sleet, snow, splashing water, and hose directed water); that provides an increased level of protection against corrosion; and that will be undamaged by the external formation of ice on the enclosure.

Table 2-1
Comparison of Specific Applications of Enclosures for Indoor Nonhazardous (Unclassified) Locations

Provides a Degree of Protection against the Following Conditions	Type of Enclosure									
	1	2	4	4X	5	6	6P	12	12K	13
Access to hazardous parts	X	X	X	X	X	X	X	X	X	X
Ingress of solid foreign objects (falling dirt)	X	X	X	X	X	X	X	X	X	X
Ingress of water (dripping and light splashing)	...	X	X	X	X	X	X	X	X	X
Ingress of solid foreign objects (circulating dust, lint, fibers, and flyings **)	...	...	X	X	...	X	X	X	X	X
Ingress of solid foreign objects (settling airborne dust, lint, fibers, and flyings **)	...	...	X	X	X	X	X	X	X	X
Ingress of water (hosedown and splashing water)	...	...	X	X	...	X	X	...	...	...
Oil and coolant seepage	...	...	...	...	...	...	...	X	X	X
Oil or coolant spraying and splashing	...	...	...	...	...	...	...	...	...	X
Corrosive agents	...	...	...	X	...	...	X	...	...	...
Ingress of water (occasional temporary submersion)	...	...	...	...	...	X	X	...	...	...
Ingress of water (occasional prolonged submersion)	...	...	...	...	...	...	X	...	...	...

** These fibers and flyings are not considered Class III type ignitable fibers or combustible flyings. For Class III type ignitable fibers or flyings see the *National Electrical Code*®, Article 500.5(D).

Table 2-2
Comparison of Specific Applications of Enclosures for Indoor & Outdoor Nonhazardous (Unclassified) Locations

Provides a Degree of Protection Against the Following Conditions	Type of Enclosure									
	3	3X	3R	3RX	3S	3SX	4	4X	6	6P
Access to hazardous parts	X	X	X	X	X	X	X	X	X	X
Ingress of solid foreign objects (falling dirt)	X	X	X	X	X	X	X	X	X	X
Ingress of water (dripping and light splashing)	X	X	X	X	X	X	X	X	X	X
Ingress of water (rain, snow, and sleet **)	X	X	X	X	X	X	X	X	X	X
Sleet ***	...	...	...	...	X	X	...	...	...	...
Ingress of solid foreign objects (windblown dust, lint, fibers, and flyings****)	X	X	...	...	X	X	X	X	X	X
Ingress of water (hosedown and splashing water)	...	...	...	...	...	...	X	X	X	X
Corrosive agents	...	X	...	X	...	X	...	X	...	X
Ingress of water (occasional temporary submersion)	...	...	...	...	...	...	...	...	X	X
Ingress of water (occasional prolonged submersion)	...	...	...	...	...	...	...	...	...	X

** External operating mechanisms are not required to be operable when the enclosure is ice covered.

*** External operating mechanisms are operable when the enclosure is ice covered. See subsection 5.6.

**** These fibers and flyings are not considered Class III type ignitable fibers or combustible flyings. For Class III type ignitable fibers or flyings see the *National Electrical Code*®, Article 500.5(D).

**CTK Co., Ltd.**

5 Dongbu-ro 221beon-gil, Cheoin-gu, Yongin-si,
Gyeonggi-do, Republic of Korea
Tel: +82-31-339-9970
Fax: +82-31-624-9501

REPORT No.:
CTK-2026-00012
Page (11) / (24) pages

Table 5-1A
Degrees of Protection Against Access to Hazardous Parts

Enclosure Type	Test Conditions	Degree of Protection		Corresponding IP First Characteristic Numeral
		Brief Description	Definition	
4X	5.7	Protected against access to hazardous parts with a wire	An access probe of 1.0 mm shall not penetrate	6

Table 5-1B
Degrees of Protection Against Solid Foreign Objects

Enclosure Type	Test Conditions	Degree of Protection		Corresponding IP First Characteristic Numeral
		Brief Description	Definition	
4X	<u>Non-vented</u> 5.7	Windblown dust protected	No ingress of dust	6
	<u>Vented</u> 5.5.1 Dust Blast Method			

Table 5-1C
Degrees of Protection against Water

Enclosure Type	Test Conditions	Degree of Protection		Corresponding IP Second Characteristic Numeral
		Brief Description	Definition	
4X	5.7	Protected against hose directed water	Water projected against the enclosure in any direction shall not enter	6 No Ingress Allowed*

Table 5-1D
Additional Protection

Enclosure Type	Test Conditions	Additional Protection		Corresponding IP Second Characteristic Numeral
		Brief Description	Definition	
4X	5.6 5.9 5.10	Special corrosion protection and undamaged by the external formation of ice	Enclosure provides increased corrosion protection and is not damaged by ice that forms on the outside	None

**CTK Co., Ltd.**

5 Dongbu-ro 221beon-gil, Cheoin-gu, Yongin-si,
Gyeonggi-do, Republic of Korea
Tel: +82-31-339-9970
Fax: +82-31-624-9501

REPORT No. :
CTK-2026-00012
Page (12) / (24) pages

3.4 NEMA 250-2014 Test list

NEMA 250-2014			
Clause	Requirement + Test	Result – Remark	Verdict
3	CONSTRUCTION		
3.1	General		P
3.2	Units of Measurement		P
3.3	Materials-General	Enclosures are made of metal or polymeric materials	P
3.4	Materials-Polymeric	More than 650 mm ² (1 in ²) in area Polymeric Materials used is declared as Min. V-2 Used to UL certified material. (See the attachment 2)	N/E
3.5	Corrosion Protection	Stainless steel and/or aluminium are declared as the materials used (See the attachment 2)	N/E
3.6	Openings	No openings in Product	N/A
3.7	Mounting	Mounting means are external to the equipment cavity (See the attachment 1)	P
3.8	Conduit Connection	No conduit connection (See the attachment 1)	N/A
3.9	Hubs and Fittings	No Hubs and Fittings	N/A
3.10	Knockouts	See the Attachment 1	P
3.11	External Operating Mechanisms	No External Operating Mechanisms	N/A
3.12	Access to Interior	Needs tool to open unit	P
3.13	Closing Hardware	No closing Hardware	N/A

**CTK Co., Ltd.**

5 Dongbu-ro 221beon-gil, Cheoin-gu, Yongin-si,
Gyeonggi-do, Republic of Korea
Tel: +82-31-339-9970
Fax: +82-31-624-9501

REPORT No. :
CTK-2026-00012
Page (13) / (24) pages

NEMA 250-2014

Clause	Requirement + Test	Result – Remark	Verdict
3.14	Gaskets	Gaskets made of a silicone Sponge Rubber (no Elastomeric or Thermoplastic used) (See clause 5.14 and the attachment 2)	P
3.15	Observation Windows	No Observation Window	N/A

4	MARKING		
4.1	Type Designations	“Type 4X” Marking is declared to be on the product before on the market	P
4.2	Supplemental Markings	Supplemental Marking (watertight/corrosion resistant) is declared to be used when it is on the market. The required marking shall be added on the product)	P
4.3	Location of Markings	See the Attachment 3	P
4.4	Enclosure Orientation	No Particular Mounting Orientation	N/A
4.5	Conduit Hubs and Closure Plates	No Conduit Hubs and Closure Plates	N/A
4.6	Equipment Openings	No Openings on Unit	N/A
4.7	Drainage Openings	No Drain Openings	N/A

5	DESIGN TESTS		
5.1	General	See Table 5-1A to 5-1D and 5.1.5 in the General product information	P
5.2	Tests For Protection Against Access to Hazardous Parts	Rated 4X	N/A
5.3	Tests for Protection Against Ingress of Water (Dripping and Light Splashing)	Rated 4X	N/A

**CTK Co., Ltd.**

5 Dongbu-ro 221beon-gil, Cheoin-gu, Yongin-si,
Gyeonggi-do, Republic of Korea
Tel: +82-31-339-9970
Fax: +82-31-624-9501

REPORT No. :
CTK-2026-00012
Page (14) / (24) pages

NEMA 250-2014

Clause	Requirement + Test	Result – Remark	Verdict
5.4	Tests for Protection Against Ingress of Water (Rain)	Rated 4X	N/A
5.5	Tests for Protection Against Ingress of Solid Foreign Objects (Setting Airborne Dust, Lint, Fibers, And Flings)	Non-vented (See clause 5.7)	N/A
5.6	External Icing Test	No external cavities to trap water when mounted in the normal position.	N/A
5.7	Tests for Protection Against Ingress of Water (Hosedown)	No entry of water See the test information	P
5.8	Indoor Corrosion Protection (Rust-Resistance Test (24-Hour Salt Spray Test))	See clause 3.5	N/E
5.9	Outdoor Corrosion Protection	See clause 3.5	N/E
5.10	Corrosion Protection-Type 3X, 3RX, 3SX, 4X Or 6P Enclosures	See clause 3.5	N/E
5.11	Test for Protection Against Ingress of Water (Temporary Submersion)	Rated 4X	N/A
5.12	Test for Protection Against Ingress of Water (Prolonged Submersion)	Rated 4X	N/A
5.13	Oil Exclusion Test	Rated 4X	N/A
5.14	GASKET MATERIAL TESTS	The product itself(including gaskets) was conditioned at 70 °C for 168 hrs according to 5.14.3(Alternate Evaluation) before performing relevant required tests.	P
5.15	Test for Sharpness of Edges	No sharp edges	P




CTK Co., Ltd.

5 Dongbu-ro 221beon-gil, Cheoin-gu, Yongin-si,
Gyeonggi-do, Republic of Korea
Tel: +82-31-339-9970
Fax: +82-31-624-9501


REPORT No.:
CTK-2026-00012
Page (15) / (24) pages

3.5 Attachment 1 - Construction Diagram and installation method

3.5.1 Construction Diagram



3.5.2 installation method





CTK Co., Ltd.

5 Dongbu-ro 221beon-gil, Cheoin-gu, Yongin-si,
Gyeonggi-do, Republic of Korea
Tel: +82-31-339-9970
Fax: +82-31-624-9501

REPORT No.:
CTK-2026-00012
Page (17) / (24) pages

3.5.3 installation method



**CTK Co., Ltd.**

5 Dongbu-ro 221beon-gil, Cheoin-gu, Yongin-si,
Gyeonggi-do, Republic of Korea
Tel: +82-31-339-9970
Fax: +82-31-624-9501

REPORT No.:
CTK-2026-00012
Page (18) / (24) pages

3.6 Attachment 2 - Parts List**3.6.1 Parts List (1)****Component - Plastics**

File Number: E115797

LOTTE CHEMICAL CORPORATION
56 GOSAN-RO
UIWANG-SI, GYEONGGI-DO 16073 Republic of Korea

**INFINO: HN-1068(+)(f1)**

Polycarbonate (PC), pellets

(+) - May be replaced by one, two, or three numbers and/or letter(s)

(f1) - Suitable for outdoor use with respect to exposure to Ultraviolet Light, Water Exposure and Immersion in accordance with UL 746C.

Flammability	Value	Test Method
Flame Rating		UL 94
1.5 mm, ALL	V-0	IEC 60695-11-10, -20
3.0 mm, ALL	V-0	
Glow Wire Flammability Index		IEC 60695-2-12
1.5 mm	960 °C	
3.0 mm	960 °C	
Glow Wire Ignition Temperature		IEC 60695-2-13
1.5 mm	825 °C	
3.0 mm	825 °C	
Electrical	Value	Test Method
Hot-wire Ignition (HWI) (1.5 mm)	PLC 3	UL 746
High Amp Arc Ignition (HAI) (1.5 mm)	PLC 3	UL 746
Comparative Tracking Index (CTI)	PLC 3	UL 746
Dielectric Strength	32 kV/mm	ASTM D149 IEC 60243-1
Volume Resistivity	1.0E+17 ohms-cm	ASTM D257 IEC 60093
Thermal	Value	Test Method
RTI Elec		UL 746
1.5 mm	130 °C	
3.0 mm	130 °C	
RTI Imp		UL 746
1.5 mm	130 °C	
3.0 mm	130 °C	
RTI Str		UL 746
1.5 mm	130 °C	
3.0 mm	130 °C	
Ball Pressure Test (130°C, 3.00 mm)	Pass	IEC 60695-10-2
Physical	Value	Test Method
Outdoor Suitability	f1	UL 746C

**CTK Co., Ltd.**

5 Dongbu-ro 221beon-gil, Cheoin-gu, Yongin-si,
Gyeonggi-do, Republic of Korea
Tel: +82-31-339-9970
Fax: +82-31-624-9501

REPORT No. :
CTK-2026-00012
Page (19) / (24) pages

3.6.2 Parts List (2)

**Component - Plastics**

File Number: E115797

LOTTE CHEMICAL CORPORATION
56 GOSAN-RO
UIWANG-SI, GYEONGGI-DO 16073 Republic of Korea

**INFINO: QC-122(+)(f1)**

Polycarbonate (PC), pellets

(+) - May be replaced by one, two, or three numbers and/or letter(s)

(f1) - Suitable for outdoor use with respect to exposure to Ultraviolet Light, Water Exposure and Immersion in accordance with UL 746C.

Flammability	Value	Test Method
Flame Rating		UL 94
1.6 mm, ALL	V-2	IEC 60695-11-10, -20
3.2 mm, ALL	V-2	
Glow Wire Flammability Index		IEC 60695-2-12
1.6 mm	850 °C	
3.2 mm	850 °C	
Glow Wire Ignition Temperature		IEC 60695-2-13
1.6 mm	900 °C	
3.2 mm	875 °C	
Electrical	Value	Test Method
Hot-wire Ignition (HWI)		UL 746
1.6 mm	PLC 3	
3.2 mm	PLC 2	
High Amp Arc Ignition (HAI)		UL 746
1.6 mm	PLC 0	
3.2 mm	PLC 0	
Comparative Tracking Index (CTI)	PLC 0	UL 746
High Voltage Arc Tracking Rate (HVTR)	PLC 2	UL 746
Volume Resistivity	1.0E+16 ohms-cm	ASTM D257 IEC 60093
Arc Resistance	PLC 5	ASTM D495
Thermal	Value	Test Method
RTI Elec		UL 746
1.6 mm	130 °C	
3.2 mm	130 °C	
RTI Imp		UL 746
1.6 mm	125 °C	
3.2 mm	130 °C	
RTI Str		UL 746
1.6 mm	125 °C	
3.2 mm	130 °C	
Physical	Value	Test Method
Outdoor Suitability	f1	UL 746C



CTK Co., Ltd.

5 Dongbu-ro 221beon-gil, Cheoin-gu, Yongin-si,
Gyeonggi-do, Republic of Korea
Tel: +82-31-339-9970
Fax: +82-31-624-9501

REPORT No.:
CTK-2026-00012
Page (20) / (24) pages

3.6.3 Parts List (3)

Component - Plastics			Yellow Card™
S-2000V+(f1), S-2001V+(f1)			File Number: E41179
MITSUBISHI ENGINEERING-PLASTICS CORP ENVIRONMENT & QUALITY ASSURANCE DEPT SHIODOME SUMITOMO-BLDG 25TH FL 1-9-2 HIGASHI-SHINBASHI MINATO-KU, TOKYO 105-0021 Japan			
S-2000V+(f1), S-2001V+(f1) Polycarbonate (PC), unreinforced, pellets (f1) - Suitable for outdoor use with respect to exposure to Ultraviolet Light, Water Exposure and Immersion in accordance with UL 746C. + - Suffix optional, exceptions: The following cannot be used as optional suffixes: "NF" for grade NXG5050, "N" for grade NXG5030, "H" for grade MB2112+, "S1" for grade F20-54, "V" for grades S-2000+(f1), S-2001+(f1), S-2003+(f1), the last letter "L" for grade CFH2520+, "W" for ELV2010 included in Grade ELV20(a5)+, "V" for grade MB2210+.			
Flammability	Value	Test Method	
Flame Rating		UL 94	
0.38 mm, ALL	V-2	IEC 60695-11-10, -20	
1.5 mm, ALL	V-2		
3.0 mm, ALL	V-2		
Electrical	Value	Test Method	
Hot-wire Ignition (HWI)		UL 746A	
1.5 mm	PLC 3		
3.0 mm	PLC 3		
High Amp Arc Ignition (HAI)		UL 746A	
1.5 mm	PLC 0		
3.0 mm	PLC 0		
Comparative Tracking Index (CTI)	PLC 2	UL 746A	
Dielectric Strength	20 kV/mm	ASTM D149	
High Voltage Arc Tracking Rate (HVTR)	PLC 0	UL 746A	
Volume Resistivity	1.0E+7 ohms-cm	ASTM D257 IEC 60093	
Arc Resistance	PLC 5	ASTM D495	

Component - Plastics

S-2000V+(f1), S-2001V+(f1)



Thermal	Value	Test Method
RTI Elec		UL 746B
0.38 mm	80.0 °C	
1.5 mm	125 °C	
3.0 mm	125 °C	
RTI Imp		UL 746B
0.38 mm	80.0 °C	
1.5 mm	115 °C	
3.0 mm	115 °C	
RTI Str		UL 746B
0.38 mm	80.0 °C	
1.5 mm	125 °C	
3.0 mm	125 °C	
Physical	Value	Test Method
Dimensional Change	0.0 %	ASTM D1042 ISO 2796
Outdoor Suitability	f1	UL 746C

**CTK Co., Ltd.**

5 Dongbu-ro 221beon-gil, Cheoin-gu, Yongin-si,
Gyeonggi-do, Republic of Korea
Tel: +82-31-339-9970
Fax: +82-31-624-9501

REPORT No.:
CTK-2026-00012
Page (21) / (24) pages

4. Hose Down Test (Clause 5.7)

4.1 Test date and environmental conditions

4.1.1 Test date: Dec. 02, 2025~ Dec. 09, 2025

4.1.2 Measured Environmental Conditions

Item	Temperature (°C)	Humidity (% R.H.)	Pressure (kPa)
Measurement	23.5	62.2	103.1

4.2 Test Conditions and methods

4.2.1 Description of Test

The enclosure and its external mechanisms were subjected to a stream of water from a hose that has a 25.4 mm (1 in) inside diameter nozzle and delivers at least 240 L (65 gal) per minute. The nozzle was held from 3.0 to 3.5 m (10 to 12 feet) from the enclosure, and the spray of water was directed at all points of potential water entry such as seams, joints, external operating mechanisms, and such. The nozzle was moved along each test point one time at a uniform rate of 6 mm/sec (1/4 in/sec).

4.2.2 Sample Dimension

Ø120 by 376.8 mm, Ø52 by 163.28 mm, Ø5.2*2 by 32.6 mm, 81.76 mm, 81.76 mm
Test Duration = 122.7 secs

4.2.3 Acceptance conditions

The enclosure shall be considered to have met the requirements if at the conclusion of the test no water has entered the enclosure



CTK Co., Ltd.

5 Dongbu-ro 221beon-gil, Cheoin-gu, Yongin-si,
Gyeonggi-do, Republic of Korea
Tel: +82-31-339-9970
Fax: +82-31-624-9501

REPORT No.:
CTK-2026-00012
Page (22) / (24) pages

4.3 Attachment 3 - Photographs

4.3.1 Hose down test



**CTK Co., Ltd.**

5 Dongbu-ro 221beon-gil, Cheoin-gu, Yongin-si,
Gyeonggi-do, Republic of Korea
Tel: +82-31-339-9970
Fax: +82-31-624-9501

REPORT No.:
CTK-2026-00012
Page (23) / (24) pages

4.4 Test result

4.4.1 Test result table

Sample No (Model)	Water Flow	Presence of water inside	Result
XNV-A9016R	240 LPM	No	Normal

※ Refer to the product photos after the completion of testing in section 4.5.

4.5 Post-test product images

4.5.1 Test sample image



- End -