



TEST REPORT



Report No. : KES-EM253702

Page 1 / 43

KES Co., Ltd.

#3002, #3503, #3701, 40, Simin-daero365beon-gil, Dongan-gu, Anyang-si, Gyeonggi-do, 14057, Republic of Korea
Tel : +82-31-425-6200, Fax : +82-31-341-3838

1. Client

- Name : Hanwha Vision Co., Ltd.
- Address : 6, Pangyo-ro 319beon-gil, Bundang-gu, Seongnam-si, Gyeonggi-do, Republic of Korea

2. Sample Description

- Product item : NETWORK CAMERA
- Model name : XNV-A9084RS
- Variant model : -
- Manufacturer etc. : HANWHA VISION VIETNAM COMPANY LIMITED
- Manufacturer address : Lot O-2, Que Vo Industrial Zone Extended Area, Nam Son Ward, Bac Ninh Province, Vietnam
- Manufacturer etc. : D-TECH CO.,LTD.
- Manufacturer address : 173-25, Saneop-ro, Gwonseon-gu, Suwon-si, Gyeonggi-do, Korea (Suwon Industrial Complex)

3. Date of test

: 2025. 10. 28. ~ 2025. 11. 05.

4. Location of Test

- Address : Permanent Testing Lab
- Address : 473-21, Gayeo-ro, Yeuju-si, Gyeonggi-do, 12658, Republic of Korea

5. Test method used

: EN 55032:2015/A1:2020, EN 50130-4:2011/A1:2014

6. Test result

: PASS

The results shown in this test report refer only to the sample(s) tested unless otherwise stated.

This test report cannot be reproduced and copied without permission without the written consent of KES Co., Ltd.

This test report is not related to KOLAS accreditation.

Affirmation	Tested by	Technical Manager by
	Name : DaeSoo Kim	Name : DongHun Jang

2025. 11. 26.

KES Co., Ltd.

**REPORT REVISION HISTORY**

Date	Test Report No.	Revision History
2025. 11. 26.	KES-EM253702	Issued

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd. This document may be altered or revised by KES Co., Ltd. personnel only, and shall be noted in the revision section of the document. Any alteration of this document not carried out by KES Co., Ltd. will constitute fraud and shall nullify the document.

Use of uncertainty of measurement for decisions on conformity (decision rule):

■ No decision rule is specified by the 1 standard, when comparing the measurement result with the applicable limit according to the specification in that standard. The decisions on conformity are made without applying the measurement uncertainty ("simple acceptance" decision rule, previously known as "accuracy method").

☐ Other (to be specified, for example when required by the standard or client)



TABLE OF CONTENTS

1	Laboratory Information	3
1.1	Test Location.....	3
1.2	Laboratory Accreditations and Listings	3
2	Test Summary	4
2.1	Class and Voltage.....	4
2.2	Summary of Test Results	4
2.3	Remarks when standards applied	5
2.4	Variant Model Differences	5
2.5	Device Modifications	5
3	General Product Description	6
4	EUT Setup and Operation Mode	11
4.1	EUT Configuration	11
4.2	System Configuration	11
4.3	External I/O Cabling	12
4.4	EUT Operating Mode(s).....	12
4.5	Test operating S/W	12
4.6	Configuration	13
5	General Performance Criteria	14
6	Test Item	16
6.1	Conducted Emissions at Telecommunication Ports	16
6.2	Radiated Emissions(Below 1 GHz)	18
6.3	Radiated Emissions(Above 1 GHz)	20
6.4	Electrostatic Discharge.....	22
6.5	Continuous RF electromagnetic field disturbances.....	25
6.6	Electrical Fast Transients/Bursts	28
6.7	Surge.....	30
6.8	Continuous Induced RF Disturbances	32
7	Test Setup Photos and EUT Photographs	34
7.1	Test Setup Photos	34
7.2	EUT Photographs	39
7.3	Label	42



1 Laboratory Information

1.1 Test Location

Category	Details
Address	473-21, Gayeo-ro, Yeosu-si, Gyeonggi-do, 12658, Republic of Korea
Telephone Number	031-883-5092
Facsimile Number	031-883-5169

The measurement facility is located at 473-21, Gayeo-ro, Yeosu-si, Gyeonggi-do, 12658, Korea, Republic of. The sites are constructed in conformance with the requirements of ANSI C63.4a-2017 and CISPR 16-1-4:2019

1.2 Laboratory Accreditations and Listings

Country	Agency	Scope of Accreditation	Logo
KOREA	RRA	EMI (3 m & 10 m Semi-Anechoic Chamber and conducted test site) EMS (ESD, RS, EFT/Burst, Surge, CS, Magnetic, Dips and interruptions)	 KR0100
International	KOLAS	EMI (3 m & 10 m Semi-Anechoic Chamber and conducted test site) EMS (ESD, RS, EFT/Burst, Surge, CS, Magnetic, Dips and interruptions)	 KT489
USA	FCC	3 m & 10 m Semi-Anechoic Chamber Conducted test site to perform FCC Part 15/18 measurements.	 KR0100
Canada	ISED	3 m & 10 m Semi-Anechoic Chamber and Conducted test site	 23298
JAPAN	VCCI	EMI (3 m & 10 m Semi-Anechoic Chamber and conducted test site)	 C-20136, T-20137, R-20181, G-20176
Europe	TÜV SÜD	EMI (3 m & 10 m Semi-Anechoic Chamber and conducted test site) EMS (ESD, RS, EFT/Burst, Surge, CS, Magnetic, Dips and interruptions)	 CARAT 001633 0008



2 Test Summary

2.1 Class and Voltage

Test Class	Test Voltage
Class A	AC 230 V, 50 Hz

2.2 Summary of Test Results

Regulation
EMC Directive 2014/30/EU, EMC Regulations SI 2016/1091

Test Item	Test Standard		Test Result	Remark
Conducted Emissions at Mains Power Ports	EN 55032:2015/A1:2020		N/A	NOTE 1
Conducted Emissions at Telecommunication Ports			PASS	-
Radiated Emissions(Below 1 GHz)			PASS	-
Radiated Emissions(Above 1 GHz)			PASS	-
Harmonic Current Emissions	EN IEC 61000-3-2:2019		N/A	NOTE 1
Voltage Fluctuations and Flicker	EN 61000-3-3:2013/A2:2021		N/A	NOTE 1
Electrostatic Discharge	EN 50130-4:2011/A1:2014	EN 61000-4-2:2009	PASS	-
Continuous RF electromagnetic field disturbances		EN IEC 61000-4-3:2020	PASS	-
Electrical Fast Transients/Bursts		EN 61000-4-4:2012	PASS	NOTE 1
Surge		EN 61000-4-5 :2014/A1:2017	PASS	NOTE 1
Continuous Induced RF Disturbances		EN IEC 61000-4-6:2023	PASS	NOTE 1
Voltage Dips and Interruptions		EN IEC 61000-4-11:2020	N/A	NOTE 1

* N/A: Not Applicable

(NOTE) PoE port is considered a wired network port, so power-related test items are excluded.



2.3 Remarks when standards applied

N/A

2.4 Variant Model Differences

N/A

2.5 Device Modifications

N/A





3 General Product Description

Division		Specificity
Internal maximum operating frequency		1.2 GHz
Power	Rated power	PoE 48 V
	Test power	AC 230 V / 50 Hz
I/O Port	User port	RJ-45 1 EA, ALARM AUDIO 1 EA, Micro SD Slot 1 EA
	Unused/Administrator Ports	USB-TYPE C 1 EA
function	Product function	NETWORK CAMERA
	Wireless function	Not applicable
Components		Main 1 EA
Other		Not applicable

Video		
Imaging Device	Size	1/1.8"
	Type	CMOS
Resolution		3840x2160, 3328x1872, 3072x1728, 2592x1944, 2560x1440, 1920x1080, 1600x1200, 1280x960, 1280x720, 1024x768, 800x600, 640x480, 640x360, 320x240, 320x180, 2688x1512
Max. Framerate	H.265/H.264	30fps/25fps(60Hz/50Hz)
	MJPEG	30fps(@8MP Max. 5fps)
	Others	None
Spectral Range		None
NETD		None
Pixel Size		None
Min. Illumination (Lux)	Color(1/30sec, 30IRE)	0.04
	BW(1/30sec, 30IRE)	0.004
Video Out		USB: Micro USB Type C
Video Transmission Distance		None
Lens		
Focal Length (mm)		4.4~9.3
Zoom Ratio	Optical	2.1x
	Digital	None
Max Aperture Ratio (F number)	Wide	1.3
	Tele	2.15
Angular Field of View	Horizontal	113°~47°
	Vertical	58°~26°
	Diagonal	138°~54°



iFoV		None
Min. Object Distance		0.5m(1.64ft)
Focus Control		Simple focus, Manual
Lens Type		P iris(IR corrected)
Mount Type		None
Optional Lens		None
Pan / Tilt / Rotate		
Pan / Tilt / Rotate Range	Pan	0°~360°
	Tilt	0°~75°
	Rotate	0°~355°
Operational		
Direction Indicator		None
Day & Night		Auto(ICR)
Backlight Compensation		BLC, HLC, WDR, SSDR
Wide Dynamic Range (dB)		120
Digital Noise Reduction		WiseNR II (Based on AI engine), SSNR V
Digital Image Stabilization		Support
Defog		Support
Motion Detection	Quantity	8ea
	Shape	8point Polygonal zones
Privacy Masking	Quantity	32ea
	Shape	8point Polygonal zones
	Color / Option	Gray, Green, Red, Blue, Black, White, Mosaic, Purple, Yellow
	Dynamic Privacy Masking: Color / Option	Gray, Green, Red, Blue, Black, White, Mosaic, Purple, Yellow
Gain Control		Off, Max gain, Manual
White Balance		ATW, NarrowATW, AWC, Manual, Indoor, Outdoor
LDC		Support(Fill/stretch mode)
Electronic Shutter	Mode	Minimum, Maximum, Anti flicker, Prefer shutter control(Based on AI engine)
	Speed Range	2~1/30,000sec
Digital PTZ		None
Video Rotation		Flip, Mirror, Hallway view(90°/270°)
Serial Interface		None
Alarm Interface	In/Out	2 configurable I/O ports
	Others	Support extra alarm I/O via optional I/O box



Alarm Triggers		Analytics, Network disconnect, Alarm input, Time schedule, MQTT subscription, Day/Night, Storage disruption
Alarm Events When Alarm Trigger Occurred		File upload(image): e-mail/FTP/SFTP, File upload(video clip): FTP/SFTP, Notification: e-mail, Recording: SD/SDHC/SDXC or NAS recording at event triggers, Alarm output, Handover: PTZ preset, send message by HTTP/HTTPS/TCP, Audio clip playback, MQTT: publication
Audio Streaming		None
Audio In		Selectable(mic in/line in)
Audio Out		Line out
Light Type		IR LED
Light Viewable Length	Warm Light	None
	IR	WiseIR 40m(131.23ft)
IR Wavelength		850nm
Water Removal		None
Auto Tracking		None
Coaxial Protocol		None
Color Palettes		None
Analytics		
Classified Object Type		Person, Face, Vehicle, License plate
Attributes	Person	Upper/Lower clothes color, Gender, Bag
	Vehicle	Type(car, bus, truck, motorcycle, bicycle), Color
	Face	Age, Gender, Face mask, Glasses
Thumbnail		BestShot
Analytics Events	Based on AI Engine	Object detection, Virtual line(Crossing/Direction), Motion detection, Face mask detection, Social distancing detection, Slip & fall detection, Virtual area(Loitering/Intrusion/Enter/Exit/Appear/Disappear)
	Normal	Defocus detection, Tampering, Audio detection, Shock detection
Business Intelligence	Based on AI Engine	People counting, Queue management, Heatmap, Vehicle counting, Crowd counting
	Normal	None
Network		
Ethernet		Metal shielded RJ-45(10/100BASE-T)
Video Compression		H.265/H.264: Main/Baseline/High, MJPEG



Audio Compression		G.711(PCM): 8KHz(64Kbps), G.726(ADPCM): 8KHz(16/24/32/40Kbps), AAC-LC: 16KHz(48Kbps), OPUS: 48KHz(64Kbps)
Smart Codec		WiseStream(Based on AI engine)
Bitrate Control		H.265/H.264: CBR or VBR, MJPEG: VBR
Streaming	Unicast	Up to 20 users
	Multicast	Support
	Multiple Streaming	Up to 5 profiles, 3 virtual channel support
Protocol		IPv4, IPv6, TCP/IP, UDP/IP, RTP(UDP), RTP(TCP), RTCP, RTSP, NTP, HTTP, HTTPS, SSL/TLS, DHCP, FTP, SFTP, ICMP, IGMP, SNMPv1/v2c/v3(MIB-2), ARP, DNS, DDNS, QoS, UPnP, Bonjour, LLDP, CDP, SRTP(TCP, UDP Unicast), MQTT, SMTP(StartTLS), Syslog
SIP support (VoIP, Peer-to-peer, SIP/PBX integration)		None
Application Programming Interface	ONVIF	S, G, T, M
	Others	SUNAPI(HTTP API), Hanwha Vision Open Platform
Direct Cloud Connection		Support
Security		
OS / Firmware Protect		Encrypted firmware, Secure boot, Signed firmware
User authentication		Digest authentication, Prevent brute-force attack
Network authentication		IEEE 802.1X(EAP-TLS, EAP-LEAP, EAP-PEAP, MSCHAPv2)
Secure Communication		HTTPS, WSS(WebSocket Secure), SRTP
Access Control		IP-based access control, MAC-based access control, Auto logout
Data Protect		Encryption credentials, Encrypt compress for live recording file export
Audit		Access / System / Event Log management
Device ID		Device certificate(Hanwha Vision Root CA)
Secure Storage		SDcard partition encrypt(AES-256), Secure element
Supply Chain Security		SBOM
Security Certificate		Secure element(FIPS 140-3 level3, CC EAL6+), ETSI EN 303 645, IEC 62443-4-1
General		
Memory	RAM	4GB
	Flash	8GB eMMC



Edge Storage	Micro SD/SDHC/SDXC	Max. 1TB x 1slot
	SSD	None
Edge Storage(OnCloud)	Micro SD/SDHC/SDXC	Max. 1TB x 1slot *Hanwha Vision branded microSD cards have been certified and recommended for OnCloud edge recording.
Environmental & Electrical		
Operating Condition	Temperature	-50°C~+60°C(-58°F~+140°F)
	Humidity	0~100% RH(condensing)
	Others	+74°C(+165°F)(Max) based on NEMA-TS 2(2.2.7), Start up should be done at above -30°C, Humidity control with AIR vent
Storage Condition	Temperature	-50°C~+60°C(-58°F~+140°F)
	Humidity	0~90% RH(non-condensing)
Wind Load		None
Input Voltage		PoE(IEEE802.3af, Class3)
Power Consumption	PoE	Max. 11.2W
Wisepower		Power monitoring, ECO mode
Power Redundance Failover		None
Mechanical		
Color		Silver
Material		Stainless(STS316L), Nylon dome
Material Management	Declaration	RoHS(EU RoHS directive 2011/65/EU and IEC/EN 63000:2018), REACH(Regulation (EC) No. 1907/2006), Conflict mineral policy(Section 1502 of US Dodd Frank Act)
	Recycle Rate	None
RAL Code		None
Product Dimensions		Ø175 x 120.0mm
Product Weight		2.01Kg
Compatible Conduit Hole		12.7mm(1/2")(M20)
Compatible Gang Box		Single, Double, 4" Octagon, Square



4 EUT Setup and Operation Mode

4.1 EUT Configuration

Product Name	Model Number	Serial Number	Manufacturer	Remarks
NETWORK CAMERA	XNV-A9084RS	-	HANWHA VISION VIETNAM COMPANY LIMITED	EUT
PoE Injector	PT-PSE109GBRO-AH	PT1933220259	Dongguan PROCET Network Technology Co.,Ltd	-
Micro SD CARD	-	-	Transcend	-
SMART PHONE	V50	-	LG	-
LAPTOP	NT630Z5J	JK9091EF400142M	SAMSUNG	-
LAPTOP ADAPTOR	PA-1400-14	AA-PA2N40W	LITEON	-
HEADSET	K550	-	Britz®	-
Button Alarm	-	-	-	-
LED Alarm	SIP-1201DD D0	-	SAMSUNG TECHWIN CO., LTD.	-

4.2 System Configuration

Product Name	Model Number	Serial Number	Manufacturer	Remarks
-	-	-	-	-



4.3 External I/O Cabling

Mode 1

Start		End		Cable Spec.	
Product Name	I/O Port	Product Name	Product Name	I/O Port	Product Name
NETWORK CAMERA (EUT)	RJ-45 (PoE)	PoE Injector	RJ-45 (PoE)	3.1	U
	Alarm In (2 PIN)	Button Alarm	Alarm OUT	3.1	U
	Alarm OUT (2 PIN)	LED Alarm	Alarm IN	4.1	U
	AUDIO OUT (3.5 mm)	HEADSET	3.5 mm	2.0	U
	AUDIO IN (3.5 mm)		3.5 mm		
	Micro SD SLOT	Micro SD CARD	Micro SD SLOT	-	-
LAPTOP	3.5 mm	SMARTPHONE	3.5 mm	1.5	U
	RJ-45	PoE Injector	RJ-45 (LAN)	1.0	U
	DC JACK	LAPTOP ADAPTOR	DC JACK	1.5	U

* Unshielded=U, Shielded=S

4.4 EUT Operating Mode(s)


Category	Mode	Operating
Mode 1	OPERATION	1. By connecting the test equipment and the PoE Injector by wire, the image output of the test equipment is checked by WEB VIEWER. 2. After activating the operation of the microphone, run a 1 KHz Tone voice file on a smartphone connected to a laptop to check whether the headset outputs sound normally or not on the headset connected to the test equipment. 3. Check the ping test of the laptop to see if the network of the test equipment is operating normally or not. 4. After the test, it was confirmed that the recorded image stored in the Micro SD Card was checked.

4.5 Test operating S/W

Name	Version	Manufacture Company
WEB VIEWER	-	Hanwha Vision Co., Ltd.



4.6 Configuration



Mode 1



5 General Performance Criteria

Criteria for compliance was based on the following guidelines:

EN 50130-4 Alarm systems-Part 4: Electromagnetic compatibility Product family standard: Immunity requirements for components of fire, intruder and social alarm systems

The variety and the diversity of the apparatus within the scope of this document makes it difficult to define precise criteria for the evaluation of the immunity test results.

If as a result of the application of the tests defined in this standard, the apparatus becomes dangerous or unsafe then the apparatus shall be deemed to have failed the test.

A functional description and a definition of performance by the manufacture and noted in the test report, based on the following criteria:

Electrostatic discharge

There shall be no damage, malfunction or change of status due to the conditioning.

Flickering of an indicator during the application of discharge is permissible, providing that is no residual change in the EUT or any change in outputs, which could be interpreted by associated equipment as a change.

Radiated electromagnetic fields

There shall be no damage, malfunction or change of status due to the conditioning.

Flickering of an indicator during the application of discharge is permissible, providing which could be interpreted by associated equipment as a change, and no such Flickering of indicators occurs at a field strength of 3 V/m.

For components of CCTV systems, where the picture is allowed at 10 V/m, providing.

- (a) there is no permanent damage or change to EUT
(e.g. no corruption of memory or changes to programmable setting etc.)
- (b) at 3 V/m, any deterioration of the picture is so minor that the system could still be used; and
- (c) there is no observable deterioration of the picture at 1 V/m.

Fast transient burst / slow high energy voltage surge

There shall be no damage, malfunction or change of status due to the conditioning.

Flickering of an indicator during the application of discharge is permissible, providing

That there is no residual is permissible, providing that there is no residual change in the EUT or any change in outputs, which could be interpreted by associated equipment as a change.

**Conducted RF immunity**

There shall be no damage, malfunction or change of status due to the conditioning.

Flickering of an indicator during the application of discharge is permissible, providing

That there is no residual is permissible, providing that there is no residual change in the EUT or any

change in outputs, which could be interpreted by associated equipment as a change,

and no such flickering of indicators oeuvres at $U = 130 \text{ dB}\mu\text{V}$.

For component of CCTV systems, where the status is monitored by observing the TV picture,

then deterioration of the picture is allowed at $U = 140 \text{ dB}\mu\text{V}$, providing:

(a) there is no permanent damage or change to the EUT

(e.g. no corruption of memory or changes to programmable settings etc.)

(b) at $U = 130 \text{ dB}\mu\text{V}$, any deterioration of the picture is so minor that the system could still be used; and

(c) there in no observable deterioration of the picture at $U = 120 \text{ dB}\mu\text{V}$.

Voltage dip/interruption / Voltage variation

There shall be no damage, malfunction or change of status due to the conditioning.

Flickering of an indicator during the conditioning is permissible, providing that there is no residual change in the EUT or any change in outputs, which could be interpreted by associated equipment as a change. The EUT shall meet the acceptance criteria for the functional test, after the conditioning.

◆ Calculation**- Conducted Emissions**

QuasiPeak[dBuV] / CAverage [dBuV] = Reading Value[dBuV] + Corr. [dB]

QuasiPeak / CAverage : The Final Value

Reading Value : Not shown in the table.

Corr. : Correction values (LISN FACTOR + (Cable Loss + Pulse Limiter FACTOR))

- Radiated Emissions(Below 1 GHz)

Result(QP) [$\text{dB}(\mu\text{V}/\text{m})$] = (Reading(QP)[$\text{dB}(\mu\text{V})$] + c.f[$\text{dB}(1/\text{m})$])

Margin(QP)[dB] = Limit[$\text{dB}(\mu\text{V}/\text{m})$] - Result(QP) [$\text{dB}(\mu\text{V}/\text{m})$]

Reading(QP) : Reading value, Result(QP) : Reading value + Factor value

Limit(QP) : Limit value, c.f : (ANT Factor + Cable Loss - Preamp Factor), Margin: Margin value

- Radiated Emissions(Above 1 GHz)

Result(PK/CAV) [$\text{dB}(\mu\text{V}/\text{m})$] = (Reading(PK/CAV)[$\text{dB}(\mu\text{V})$] + c.f[$\text{dB}(1/\text{m})$])

Margin(PK/CAV)[dB] = Limit[$\text{dB}(\mu\text{V}/\text{m})$] - Result(PK/CAV) [$\text{dB}(\mu\text{V}/\text{m})$]

Reading(PK/CAV) : Reading value, Result(PK/CAV) : Reading value + Factor value

Limit(PK/CAV) : Limit value, c.f : (ANT Factor + Cable Loss - Preamp Factor), Margin: Margin value



6 Test Item

6.1 Conducted Emissions at Telecommunication Ports

6.1.1 Test Equipment

Equipment Name	Model Number	Manufacturer	Serial No.	Cal. Date	Next Cal. Date	Used
SHIELD ROOM #6	-	DYMSTEC	-	-	-	■
EMC32 Measurement Software	EMC32	R&S	9.12.00	-	-	■
EMI TEST RECEIVER	ESR3	Rohde & Schwarz	101783	2024-11-06	2025-11-06	■
LISN	ENV216	Rohde & Schwarz	101786	2025-01-09	2026-01-09	■
ARTIFICIAL MAINS NETWORK	ESH2-Z5	Rohde & Schwarz	100450	2025-11-03	2026-11-03	■
PULSE LIMITER	ESH3-Z2	Rohde & Schwarz	101915	2025-11-03	2026-11-03	■
8-WIRE ISN CAT5	CAT5 8158	SCHWARZBEC K	8158-0030	2025-01-09	2026-01-09	■

6.1.2 Test Location : SHIELD ROOM #6

6.1.3 Test Conditions :

Temperature	Relative Humidity
(20.5 ~ 20.5) °C	(39.9 ~ 39.9) % R.H.




6.1.4 Test Result

- Test Date : 2025-11-04
- Test Mode : Mode 1

Test Report

1 / 1

Test Description: Telecommunication Emission
Job No.: KES-EM253702
Mode : Mode 1
Speed : 100 Mbps
Operator Name: KES



Final_Result

Frequency (MHz)	QuasiPeak (dB μV)	CAverage (dB μV)	Limit (dB μV)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Line	Corr. (dB)
0.725000	---	58.92	74.00	15.08	1000.0	9.000	Single Line	19.3
0.725000	59.85	---	87.00	27.15	1000.0	9.000	Single Line	19.3
0.830000	---	54.87	74.00	19.13	1000.0	9.000	Single Line	19.3
0.830000	59.88	---	87.00	27.12	1000.0	9.000	Single Line	19.3
1.245000	---	58.37	74.00	15.63	1000.0	9.000	Single Line	19.3
1.245000	63.70	---	87.00	23.30	1000.0	9.000	Single Line	19.3
1.350000	---	60.58	74.00	13.42	1000.0	9.000	Single Line	19.3
1.350000	65.95	---	87.00	21.05	1000.0	9.000	Single Line	19.3
9.235000	---	56.55	74.00	17.45	1000.0	9.000	Single Line	19.6
9.235000	60.60	---	87.00	26.40	1000.0	9.000	Single Line	19.6
18.575000	---	56.38	74.00	17.62	1000.0	9.000	Single Line	19.8
18.575000	61.21	---	87.00	25.79	1000.0	9.000	Single Line	19.8

6.1.5 Remark

Complies with the test requirements.



6.2 Radiated Emissions(Below 1 GHz)

6.2.1 Test Equipment

Equipment Name	Model Number	Manufacturer	Serial No.	Cal. Date	Next Cal. Date	Used
SEMI ANECHOIC CHAMBER #4(10 m)	-	DYMSTEC	-	-	-	■
EP5/RE Software	EP5/RE	TOYO	6.0.0	-	-	■
EMI TEST RECEIVER	ESU26	Rohde & Schwarz	100551	2025-02-13	2026-02-13	■
AMPLIFIER	SCU 01	Rohde & Schwarz	100603	2024-11-06	2025-11-06	■
BILOG ANTENNA	VULB 9168	SCHWARZBEC K	9168-461	2024-05-09	2026-05-09	■
ATTENUATOR	6806.17.A	HUBER+SUHNE R	-	2025-02-13	2026-02-13	■

6.2.2 Test Location : SEMI ANECHOIC CHAMBER #4(10 m) Measurement Distance : □ 3 m, ■ 10 m


6.2.3 Test Conditions :

Temperature	Relative Humidity
(18.8 ~ 18.8) °C	(41.6 ~ 41.6) % R.H.



6.2.4 Test Result

- Test Date : 2025-10-28
- Test Mode : Mode 1



Final Result

No.	Frequency [MHz]	(P)	Reading QP [dB(uV)]	c.f [dB(1/m)]	Result QP [dB(uV/m)]	Limit QP [dB(uV/m)]	Margin QP [dB]	Height [cm]	Angle [deg]	Remark
1	31.213	V	53.1	-22.7	30.4	40.0	9.6	107.0	240.0	
2	72.195	V	56.0	-23.4	32.6	40.0	7.4	112.0	263.0	
3	99.598	H	52.4	-25.0	27.4	40.0	12.6	334.0	215.0	
4	107.721	V	57.7	-23.8	33.9	40.0	6.1	100.0	148.0	
5	168.710	H	47.4	-20.0	27.4	40.0	12.6	381.0	212.0	
6	221.211	H	47.8	-21.2	26.6	40.0	13.4	297.0	102.0	

※ The data is the result measured by the detector in Quasi-Peak mode on the Peak graph.

6.2.5 Remark

Complies with the test requirements.



6.3 Radiated Emissions(Above 1 GHz)

6.3.1 Test Equipment

Equipment Name	Model Number	Manufacturer	Serial No.	Cal. Date	Next Cal. Date	Used
SEMI ANECHOIC CHAMBER #5	-	SY Corporation	-	-	-	■
ES10/RE Software	ES10/RE	TOYO	2022.01.000	-	-	■
EMI TEST RECEIVER	ESU26	Rohde & Schwarz	100552	2025-02-13	2026-02-13	■
PREAMPLIFIER	8449B	HP	3008A00538	2025-04-30	2026-04-30	■
ATTENUATOR	8491B	HP	23094	2025-02-13	2026-02-13	■
HORN ANTENNA	SAS-571	A.H.	414	2025-01-13	2026-01-13	■

6.3.2 Test Location : SEMI ANECHOIC CHAMBER #5

6.3.3 Test Conditions :

Temperature	Relative Humidity
(21.1 ~ 21.1) °C	(41.9 ~ 41.9) % R.H.



Report No. : KES-EM253702

Page 21 / 43

6.3.4 Test Result

6.3.5 Remark

Complies with the test requirements.





6.4 Electrostatic Discharge

6.4.1 Test Equipment

Equipment Name	Model Number	Manufacturer	Serial No.	Cal. Date	Next Cal. Date	Used
SHIELD ROOM #6	-	DYMSTEC	-	-	-	■
ESD SIMULATOR	ESS-2000	NoiseKen	ESS01Z0454	2025-01-21	2026-01-21	■
HCP	-	KES	-	-	-	■
VCP	-	Noise Ken	-	-	-	■

6.4.2 Test Location : SHIELD ROOM #6

6.4.3 Test Conditions :

Temperature	Relative Humidity
Temperature(15 ~ 35) °C	(20.5 ~ 20.5) °C
Relative Humidity(30 ~ 60) % R.H.	(39.9 ~ 39.9) % R.H.
Atmospheric Pressure(86 ~ 106) kPa	(100.9 ~ 100.9) kPa


6.4.4 Test Specifications :

Discharge Factor	: 1 s
Discharge Impedance	: 330 Ω / 150 pF
Kind of Discharge	: Direct Discharge - Contact Discharge, Air Discharge Indirect Discharge - HCP, VCP
Polarity	: Positive and Negative
Number of Discharge	: 10 at all locations for Contact Discharge, 10 at all locations for Air Discharge
Performance Criteria	: Complied
Discharge Voltage	:

Type	Direct Discharge		Indirect Discharge	
	Contact Discharge	Air Discharge	Horizontal Coupling Plane	Vertical Coupling Plane
Test Voltage	-	± 2 kV	-	-
	± 6 kV	± 4 kV	± 6 kV	± 6 kV
	-	± 8 kV	-	-



6.4.5 Location of Discharge



<Location of Discharge>



6.4.6 Test Result

- Test Date : 2025-11-05
- Test Mode : Mode 1

○ Indirect Discharge

No.	Test Point	Discharge Method	Observations	Remarks
1	HCP Contact	Contact Discharge	Complied	-
2	VCP Contact	Contact Discharge	Complied	-

○ Direct Discharge

No.	Test Point	Discharge Method	Observations	Remarks
1	Around LENS, SENSOR, LED	Air Discharge	Complied	-
2	Enclosure, Screw	Contact Discharge	Complied	-

6.4.7 Remark

No loss of performance of function.



6.5 Continuous RF electromagnetic field disturbances

6.5.1 Test Equipment

Equipment Name	Model Number	Manufacturer	Serial No.	Cal. Date	Next Cal. Date	Used
SEMI ANECHOIC CHAMBER #3	-	DYMSTEC	-	-	-	■
EMC32 Measurement Software	EMC32	R&S	10.10.02	-	-	■
SIGNAL GENERATOR	SMB 100A	Rohde & Schwarz	108252	2025-07-28	2026-07-28	■
HIGH POWER DUAL AMP	SSA532	SUNGSAN	SSA532-001	-	-	■
POWER METER	E4419B	Agilent	GB40203000	2025-02-13	2026-02-13	■
DOUBLE RIDGED HORN ANTENNA	SAS-571	A.H. SYSTEM,INC	781	2025-03-05	2026-03-05	■
AVERAGE POWER SENSOR	E9301A	Agilent	MY52170007	2025-02-13	2026-02-13	■
AVERAGE POWER SENSOR	E9301A	Agilent	MY41498669	2025-02-13	2026-02-13	■
STACKED DOUBLE LOG-PER- ANTENNA	STPL9128 E	SCHWARZBEC K	9128ES-121	-	-	■

6.5.2 Test Location : SEMI ANECHOIC CHAMBER #3

6.5.3 Test Conditions :

Temperature	Relative Humidity
(22.0 ~ 22.2) °C	(37.1 ~ 37.3) % R.H.



6.5.4 Test Specifications :

Antenna Polarization	:	Horizontal & Vertical unless indicated otherwise
Antenna Distance	:	3 m
Field Strength	:	10 V/m (rms)
Frequency Range	:	80 MHz ~ 2.7 GHz
Modulation	:	AM 80 %, 1 kHz, Sine wave PM 1 Hz (0.5 s ON : 0.5 s OFF)
Dwell Time	:	3 s
Frequency Step	:	1 %
Application method	:	4
Performance Criteria	:	Complied



6.5.5 Test Result

- Test Date : 2025-10-31
- Test Mode : Mode 1
- Enclosure Port

Side Exposed	Observations	
	Horizontal	Vertical
Front	Complied	Complied
Rear	Complied	Complied
Right	Complied	Complied
Left	Complied	Complied

6.5.6 Remark

No loss of performance of function.



6.6 Electrical Fast Transients/Bursts

6.6.1 Test Equipment

Equipment Name	Model Number	Manufacturer	Serial No.	Cal. Date	Next Cal. Date	Used
SHIELD ROOM #7	-	DYMSTEC	-	-	-	■
iec.control Software	iec.control	EM TEST	5.4.8	-	-	■
ULTRA COMPACT SIMULATOR	UCS 500N7	EM TEST	P1608172950	2024-11-06	2025-11-06	■
MOTOR VARIAC	MV 2616	EM TEST	P1552169719	2024-11-07	2025-11-07	■
CAPACITIVE COUPLING CLAMP	HFK	EM TEST	P1633183115	2024-11-06	2025-11-06	■

6.6.2 Test Location : SHIELD ROOM #7

6.6.3 Test Conditions :

Temperature	Relative Humidity
(24.6 ~ 24.7) °C	(31.3 ~ 31.4) % R.H.

6.6.4 Test Specifications :

Pulse Amplitude & Polarity	: Input a.c power ports ± 2.0 kV Other supply and Signal ports ± 1 kV
Repetition Rate	: 100 kHz
Impulse Rise Time	: 5 ns ± 30 %
Impulse Period	: 50 ns ± 30 %
Burst Duration	: 15 ms ± 20 %
Burst Period	: 300 ms ± 20 %
Duration of Test Voltage	: 1 min
Application Method	: a.c / d.c power ports (Coupling / Decoupling Network) Other than a.c / d.c power poerts (Capacitive Coupling Clamp)
Performance Criteria	: Complied



6.6.5 Test Result

○ Test Date : 2025-10-30

● Test Mode : Mode 1

○ Input a.c power ports

Mode of Application	Observations	
	(+) Burst	(-) Burst
N/A	-	-

○ Input d.c power ports

Mode of Application	Observations	
	(+) Burst	(-) Burst
N/A	-	-

○ Signal ports and telecommunication ports

Mode of Application	Observations	
	(+) Burst	(-) Burst
RJ-45	Complied	Complied
ALARM IN	Complied	Complied
ALARM OUT	Complied	Complied

6.6.6 Remark

No loss of performance of function.



6.7 Surge

6.7.1 Test Equipment

Equipment Name	Model Number	Manufacturer	Serial No.	Cal. Date	Next Cal. Date	Used
SHIELD ROOM #7	-	DYMSTEC	-	-	-	■
iec.control Software	iec.control	EM TEST	5.4.8	-	-	■
ULTRA COMPACT SIMULATOR	UCS 500N7	EM TEST	P1608172950	2024-11-07	2025-11-07	■
MOTOR VARIAC	MV 2616	EM TEST	P1552169719	2024-11-07	2025-11-07	■
CDN	CNV 508N1	EM TEST	P1610176296	2024-11-08	2025-11-08	■

6.7.2 Test Location : SHIELD ROOM #7

6.7.3 Test Conditions :

Temperature	Relative Humidity
(24.6 ~ 24.7) °C	(31.3 ~ 31.4) % R.H.

6.7.4 Test Specifications :

Surge	: Input a.c power ports	Line to Line ±0.5 kV, ±1.0 kV
		Line to Ground ±0.5 kV, ±1.0 kV, ±2.0 kV
	Other supply / Signal lines	Line to Ground ±0.5 kV, ±1.0 kV
Input a.c / Other supply / Signal lines		
Open-Circuit Voltage Waveform	: 1.2/50 μs	
Short-Circuit Current Waveform	: 8/20 μs	
Number of Applications	: Apply 5 surges for each polarity	
Phase Angle	: 0° ~ 270° (input a.c. power port)	
Polarity	: Positive and Negative	
Repetition Rate	: 1 surge per 30 s	
Performance Criteria	: Complied	

**6.7.5 Test Result**

- Test Date : 2025-10-30
- Test Mode : Mode 1

- Input a.c power ports

Mode of Application	Observations	
	(+) Surge	(-) Surge
N/A	-	-

- Signal ports and telecommunication ports

Mode of Application	Coupling Method	Observations	
		(+) Surge	(-) Surge
RJ-45	CDN	Complied	Complied
RJ-45	LINE	Complied	Complied

6.7.6 Remark

No loss of performance of function.



6.8 Continuous Induced RF Disturbances

6.8.1 Test Equipment

Equipment Name	Model Number	Manufacturer	Serial No.	Cal. Date	Next Cal. Date	Used
SHIELD ROOM #7	-	DYMSTEC	-	-	-	■
icd.control Software	icd.control	EM TEST	8.0.0	-	-	■
TEST SYSTEM FOR CONDUCTED AND RADIATED	NSG4070	TESEQ	65585	2024-11-18	2025-11-18	■
ATTENUATOR	ATT 6/80	EM TEST	P1614178148	2024-11-06	2025-11-06	■
CDN	CDN M016	TESEQ	43694	2024-11-07	2025-11-07	■
CDN	CDN M016	TESEQ	43697	2024-11-07	2025-11-07	■
CDN	CDN T8 RJ45	SCHWARZBEC K	00103	2025-07-07	2026-07-07	■
EM CLAMP	KEMZ 801A	TESEQ	44099	2024-11-08	2025-11-08	■

6.8.2 Test Location : SHIELD ROOM #7

6.8.3 Test Conditions :

Temperature	Relative Humidity
(24.7 ~ 24.9)°C	(31.7 ~ 31.9) % R.H.

6.8.4 Test Specifications

Frequency range and Voltage Level	: 0.15 MHz ~ 100 MHz : 10 V(r.m.s)
Modulation	: AM 80 %, 1 kHz, Sine wave PM 1 Hz (0.5 s ON : 0.5 s OFF)
Dwell Time	: 3 s
Frequency Step	: 1 %
Performance Criteria	: Complied



6.8.5 Test Result

- Test Date : 2025-10-30
- Test Mode : Mode 1
- Input a.c power ports

Coupling Location (Line Stressed)	Coupling Method	Observations
N/A	CDN	-

- Input d.c power ports

Coupling Location (Line Stressed)	Coupling Method	Observations
N/A	-	-

- Signal ports and telecommunication ports

Coupling Location (Line Stressed)	Coupling Method	Observations
RJ-45	CDN	Complied
ALARM IN	Clamp	Complied
ALARM OUT	Clamp	Complied

6.8.6 Remark

No loss of performance of function.




7 Test Setup Photos and EUT Photographs


7.1 Test Setup Photos




<Conducted Emissions at Telecommunication Ports - Front>




<Conducted Emissions at Telecommunication Ports - Rear>




<Radiated Emissions(Below 1 GHz) - Front>



<Radiated Emissions(Below 1 GHz) - Rear>




<Radiated Emissions(Above 1 GHz) - Front>



<Radiated Emissions(Above 1 GHz) - Rear>




<Continuous RF electromagnetic field disturbances>



<Electrical Fast Transients/Bursts>



<Surge>




<Continuous Induced RF Disturbances>



7.2 EUT Photographs




<EUT External Photographs - Top>



<EUT External Photographs - Bottom>



<Port>



<EUT Internal Photographs>



7.3 Label



Name : Hanwha Vision Co., Ltd.
Product item : NETWORK CAMERA
Model name : XNV-A9084RS

The End.

