TEST REPORT

KES Co., Ltd.
#3002, #3503, #3701, 40, Simin-daero365beon-gil, Dongan-gu, Anyang-si, Gyeonggi-do, 14057, Republic of Korea
Tel : +82-31-425-6200, Fax : +82-31-341-3838

1. Client

○ Name	:	Hanwha Vision Co., Ltd.
○ Address	:	6, Pangyo-ro 319beon-gil, Bundang-gu, Seongnam-si, Gyeonggi-do, Republic of Korea

2. Sample Description

◯ Product item	:	NETWORK CAMERA
◯ Model name	:	XNV-A9085RZ
◯ Variant model	:	-
◯ Manufacturer etc.	:	HANWHA VISION VIETNAM COMPANY LIMITED
◯ Manufacturer address	:	Lot O-2, Que Vo Industrial Zone Extended Area, Nam Son Ward, Bac Ninh Province, Vietnam
◯ Manufacturer etc.	:	D-TECH CO.,LTD.
◯ Manufacturer address	:	173-25, Saneop-ro, Gwonseon-gu, Suwon-si, Gyeonggi-do, Korea (Suwon Industrial Complex)

3. Date of test	:	2026. 07. 06. ~ 2026. 07. 08.
4. Location of Test	:	Permanent Testing Lab
○ Address	:	473-21, Gayeo-ro, Yeoju-si, Gyeonggi-do, 12658, Republic of Korea
5. Test method used	:	VCCI-CISPR 32:2016
6. Test result	:	PASS

The results shown in this test report refer only to the sample(s) tested unless otherwise stated.
This test report cannot be reproduced and copied without permission without the written consent of KES Co., Ltd.
This laboratory is not accredited for the test results marked *.
This test report is not related to KOLAS accreditation.

Affirmation	Tested by	Technical Manager by
	Name : YeonSeung Yu [유연승]2026/07/13	Name : DaeJung,Choi [최대중]2026/07/13

2026. 07. 13.

KES Co., Ltd.

You can check the authenticity of this test report on the authenticity verification page on our website (www.kes.co.kr).

REPORT REVISION HISTORY

Date	Test Report No.	Revision History
2026. 07. 13.	KES-EM262094	Issued

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd. This document may be altered or revised by KES Co., Ltd. personnel only, and shall be noted in the revision section of the document. Any alteration of this document not carried out by KES Co., Ltd. will constitute fraud and shall nullify the document.

Use of uncertainty of measurement for decisions on conformity (decision rule):

■ No decision rule is specified by the standard, when comparing the measurement result with the applicable limit according to the specification in that standard. The decisions on conformity are made without applying the measurement uncertainty(“simple acceptance” decision rule, previously known as “accuracy method”).

□ Other (to be specified, for example when required by the standard or client)

TABLE OF CONTENTS

1 Laboratory Information 4
1.1 Test Location 4
1.2 Laboratory Accreditations and Listings 4
2 Test Summary 5
2.1 Class and Voltage 5
2.2 Summary of Test Results 5
2.3 Remarks when standards applied 5
2.4 Variant Model Differences 5
2.5 Device Modifications 5
3 General Product Description 6
4 EUT Setup and Operation Mode 9
4.1 EUT Configuration 9
4.2 System Configuration 9
4.3 External I/O Cabling 10
4.4 EUT Operating Mode(s) 11
4.5 Test operating S/W 11
4.6 Configuration 12
5 Measurement Procedure 13
6 Test Item 14
6.1 Conducted Emissions at Mains Power Ports 14
6.2 Conducted Emissions at Telecommunication Ports 17
6.3 Radiated Emissions(Below 1 ㎓) 20
6.4 Radiated Emissions(Above 1 ㎓) 23
7 Test Setup Photos and EUT Photographs 26
7.1 Test Setup Photos 26
7.2 EUT Photographs 33
7.3 Label 38

You can check the authenticity of this test report on the authenticity verification page on our website (www.kes.co.kr).

1 Laboratory Information

1.1 Test Location

Category	Details
Addres	473-21, Gayeo-ro, Yeoju-si, Gyeonggi-do, 12658, Republic of Korea
Telephone Number	031-883-5092
Facsimile Number	031-883-5169

The measurement facility is located at 473-21, Gayeo-ro, Yeoju-si, Gyeonggi-do, 12658, Republic of Korea. The sites are constructed in conformance with the requirements of ANSI C63.4a-2017 and CISPR 16-1-4:2019

1.2 Laboratory Accreditations and Listings

Country	Agency	Scope of Accreditation	Logo
KOREA	**RRA**	EMI (3 m & 10 m Semi-Anechoic Chamber and conducted test site) EMS (ESD, RS, EFT/Burst, Surge, CS, Magnetic, Dips and interruptions)	KR0100
International	**KOLAS**	EMI (3 m & 10 m Semi-Anechoic Chamber and conducted test site) EMS (ESD, RS, EFT/Burst, Surge, CS, Magnetic, Dips and interruptions)	KT489
USA	**FCC**	3 m & 10 m Semi-Anechoic Chamber Conducted test site to perform FCC Part 15/18 measurements.	KR0100
Canada	**ISED**	3 m & 10 m Semi-Anechoic Chamber and Conducted test site	23298
JAPAN	**VCCI**	EMI (3 m & 10 m Semi-Anechoic Chamber and conducted test site)	C-20136, T-20137, R-20181, G-20176
Europe	**TÜV SÜD**	EMI (3 m & 10 m Semi-Anechoic Chamber and conducted test site) EMS (ESD, RS, EFT/Burst, Surge, CS, Magnetic, Dips and interruptions)	CARAT 001633 0008

You can check the authenticity of this test report on the authenticity verification page on our website (www.kes.co.kr).

2 Test Summary

2.1 Class and Voltage

Test Class	Test Voltage
■ Class A □ Calss B	AC 100 V, 60 Hz, PoE

2.2 Summary of Test Results

Test Item	Test Standard	Test Result	Remark
Conducted Emissions at Mains Power Ports	VCCI CISPR 32:2016	PASS	NOTE 1
Conducted Emissions at Telecommunication Ports		PASS	-
Radiated Emissions(Below 1 ㎓)		PASS	-
Radiated Emissions(Above 1 ㎓)		PASS	-
* N/A: Not Applicable (NOTE 1) PoE port is considered a wired network port, so power-related test items are excluded.			

2.3 Remarks when standards applied

N/A

2.4 Variant Model Differences

N/A

2.5 Device Modifications

N/A

You can check the authenticity of this test report on the authenticity verification page on our website (www.kes.co.kr).

3 General Product Description

Internal maximum operating frequency : 3.2 GHz

Video		
Imaging Device	Size	1/1.8"
	Type	CMOS
Resolution		3840x2160, 3328x1872, 3072x1728, 2688x1512, 2592x1944, 2560x1440, 1920x1080, 1600x1200, 1280x960, 1280x720, 1024x768, 800x600, 640x480, 640x360, 320x240, 320x180
Max. Framerate	H.265/H.264	30fps/25fps(60Hz/50Hz)
	MJPEG	30fps(@8MP Max. 5fps)
Min. Illumination (Lux)	Color(1/30sec, 30IRE)	0.04
	BW(1/30sec, 30IRE)	0.004
Video Out		USB: USB Type C. Preview and installation ONLY. Requires WiFi dongle.
Video Transmission Distance		None
Lens		
Focal Length (mm)		4.4~9.3
Zoom Ratio	Optical	2.1x
	Digital	None
Max Aperture Ratio (F number)	Wide	1.3
	Tele	2.15
Angular Field of View	Horizontal	113°~47°
	Vertical	58°~26°
	Diagonal	138°~54°
iFoV		None
Min. Object Distance		0.5m(1.64ft)
Focus Control		Simple focus
Lens Type		P iris(IR corrected)
Mount Type		None
Optional Lens		None
Pan / Tilt / Rotate		
Pan / Tilt / Rotate Range	Pan	0°~350°
	Tilt	-0°~85°
	Rotate	-95°~95°
	Others	Remote adjustment(Max. 3,650cycles)
Operational		
Direction Indicator		None
Day & Night		Auto(ICR)
Backlight Compensation		BLC, HLC, WDR, SSDR
Wide Dynamic Range (dB)		120
Digital Noise Reduction		WiseNRⅡ(Based on AI engine), SSNRⅤ
Digital Image Stabilization		Support
Defog		Support
Motion Detection	Quantity	8ea
	Shape	8point Polygonal zones
Privacy Masking	Quantity	32ea
	Shape	8point Polygonal zones
	Color / Option	Gray, Green, Red, Blue, Black, White, Mosaic, Purple, Yellow
	Dynamic Privacy Masking: Color / Option	Gray, Green, Red, Blue, Black, White, Mosaic, Purple, Yellow
Gain Control		Off, Max gain, Manual

You can check the authenticity of this test report on the authenticity verification page on our website (www.kes.co.kr).

White Balance		ATW, NarrowATW, AWC, Manual, Indoor, Outdoor
LDC		Support(Fill/stretch mode)
Electronic Shutter	Mode	Minimum, Maximum, Anti flicker, Prefer shutter control(Based on AI engine)
	Speed Range	2~1/30,000sec
Digital PTZ		None
Video Rotation		Flip, Mirror, Hallway view(90°/270°)
Serial Interface		None
Alarm Interface	In/Out	2 configurable I/O ports
	Others	12VDC output, Support alarm I/O via optional I/O box
Alarm Triggers		Analytics, Network disconnect, Alarm input, Time schedule, MQTT subscription, Case tampering, Day/Night, Storage disruption
Alarm Events When Alarm Trigger Occurred		File upload(image): e-mail/FTP/SFTP, File upload(video clip): FTP/SFTP, Notification: e-mail, Recording: SD/SDHC/SDXC or NAS recording at event triggers, Alarm output, Handover: PTZ preset, send message by HTTP/HTTPS/TCP, Audio clip playback, MQTT: publication
Audio Streaming		None
Audio In		Selectable(mic in/line in)
Audio Out		Line out
Light Type		IR LED
Light Viewable Length	Warm Light	None
	IR	WiseIR PoE+: 50m(164.04ft)
IR Wavelength		850nm
Analytics		
Classified Object Type		Person, Face, Vehicle, License plate
Attributes	Person	Upper/Lower clothes color, Gender, Bag
	Vehicle	Type(car, bus, truck, motorcycle, bicycle), Color
	Face	Age, Gender, Face mask, Glasses
Thumbnail		BestShot
Analytics Events	Based on AI Engine	Object detection, Virtual line(Crossing/Direction), Motion detection, Face mask detection, Social distancing detection, Slip & fall detection, Virtual area(Loitering/Intrusion/Enter/Exit/Appear/Disappear), Advanced loitering detection
	Normal	Defocus detection, Tampering, Audio detection, Shock detection
Business Intelligence	Based on AI Engine	People counting, Queue management, Heatmap, Vehicle counting, Crowd counting
	Normal	None
Network		
Ethernet		Metal shielded RJ-45(10/100/1000BASE-T)
Video Compression		H.265/H.264: Main/Baseline/High, MJPEG
Audio Compression		G.711(PCM): 8kHz(64kbps), G.726(ADPCM): 8kHz(16/24/32/40kbps), AAC-LC: 16kHz(48kbps), OPUS: 48kHz(64kbps)
Smart Codec		WiseStream(Based on AI engine)
Bitrate Control		H.265/H.264: CBR or VBR, MJPEG: VBR
Streaming	Unicast	Up to 20 users
	Multicast	Support
	Multiple Streaming	Up to 5 profiles, 3 virtual channel support
Protocol		IPv4, IPv6, TCP/IP, UDP/IP, RTP(UDP), RTP(TCP), RTCP, RTSP, NTP, HTTP, HTTPS, SSL/TLS, DHCP, FTP, SFTP, ICMP, IGMP, SNMPv1/v2c/v3(MIB-2), ARP, DNS, DDNS, QoS, UPnP, Bonjour, LLDP, CDP, SRTP(TCP, UDP Unicast), MQTT, SMTP(StartTLS), Syslog
SIP support (VoIP, Peer-to-peer, SIP/PBX integration)		None
Application Programming Interface	ONVIF	S, G, T, M
	Others	SUNAPI(HTTP API), Hanwha Vision Open Platform
Direct Cloud Connection		Support

You can check the authenticity of this test report on the authenticity verification page on our website (www.kes.co.kr).

Security		
OS / Firmware Protect		Encrypted firmware, Secure boot, Signed firmware
User authentication		Digest authentication, Prevent brute-force attack
Network authentication		IEEE 802.1X(EAP-TLS, EAP-LEAP, EAP-PEAP, MSCHAPv2)
Secure Communication		HTTPS, WSS(WebSocket Secure), SRTP
Access Control		IP-based access control, MAC-based access control, Auto logout
Data Protect		Encryption credentials, Encrypt compress for live recording file export
Audit		Access / System / Event Log management
Device ID		Device certificate(Hanwha Vision Root CA)
Secure Storage		SDcard partition encrypt(AES-256), Secure element
Supply Chain Security		SBOM
Security Certificate		Secure element(FIPS 140-3 level3, CC EAL6+), Consumer IoT Security Standard (ETSI EN 303 645)
General		
SoC	Type	Wisenet 9
	Dual NPU	Support
Memory	RAM	4GB
	Flash	8GB eMMC
Edge Storage	Micro SD/SDHC/SDXC	Max. 1TB x 2slot(Total 2TB)
	SSD	None
Edge Storage(OnCloud)	Micro SD/SDHC/SDXC	Max. 1TB x 2slots (Total 2TB) *Hanwha Vision branded microSD cards have been certified and recommended for OnCloud edge recording.
Environmental & Electrical		
Operating Condition	Temperature	-50°C~+60°C(-58°F~+140°F)
	Humidity	0~100% RH(condensing)
	Others	+74°C(+165°F)(Max) based on NEMA-TS 2(2.2.7), Start up should be done at above -30°C, Humidity control with AIR vent
Storage Condition	Temperature	-50°C~+60°C(-58°F~+140°F)
	Humidity	0~90% RH(non-condensing)
Wind Load		None
EPA(Effective Projected Area)		0.017㎡
Input Voltage		PoE(IEEE802.3af, Class3), PoE+(IEEE802.3at, Class4), 12VDC
Power Consumption	PoE	PoE+ : Max. 17.9W, typical 11.7W
	12VDC	Max. 17.7W, typical 11.3W
WisePower		Power monitoring
Mechanical		
Color		White
Material		Aluminum, Hard-coated dome
Material Management	Declaration	RoHS(EU RoHS directive 2011/65/EU and IEC/EN 63000:2018), REACH(Regulation (EC) No. 1907/2006), Conflict mineral policy(Section 1502 of US Dodd Frank Act)
RAL Code		RAL9003
Product Dimensions		ø180x135mm(ø7.09x5.31")
Product Weight		1,860g(4.10lb)
Compatible Conduit Hole		19.1mm(3/4")(M25)
Compatible Gang Box		Single, Double, 4" Octagon, Square

You can check the authenticity of this test report on the authenticity verification page on our website (www.kes.co.kr).

4 EUT Setup and Operation Mode

4.1 EUT Configuration

Product Name	Model Number	Serial Number	Manufacturer	Remarks
NETWORK CAMERA	XNV-A9085RZ	-	HANWHA VISION VIETNAM COMPANY LIMITED	EUT
AC/DC Adaptor	2ACB022F	-	Channel Well Technology (Guangzhou) Co.,Ltd.	-
PoE Injector	PT-PSE109GBRO-AH-S	-	Dongguan PROCET Network Technology Co.,Ltd	-
Laptop	15U47	-	LG Electronics	-
Laptop Adaptor	A13-040N3A	-	CHICONYPOWER TECHNOLOGY (SUZHOU)CO., LTD.	-
Button Alarm	-	-	-	-
LED Alarm	-	-	-	-
Micro SD Card 1	-	-	Sandisk	-
Micro SD Card 2			Sandisk	
Headset	-	-	-	-
Smartphone	-	-	-	-

4.2 System Configuration

Product Name	Model Number	Serial Number	Manufacturer	Remarks
-	-	-	-	-

You can check the authenticity of this test report on the authenticity verification page on our website (www.kes.co.kr).

4.3 External I/O Cabling

-Mode 1

Start		End		Cable Spec.	
Product Name	**I/O Port**	**Product Name**	**I/O Port**	**Length(m)**	**Shield**
EUT	2 Pin	AC/DC Adaptor	2 Pin	0.8	U
	RJ-45 (LAN)	Laptop	RJ-45 (LAN)	3.1	U
	Micro SD Card Slot	Micro SD Card 1	Micro SD Card Slot	-	-
	Micro SD Card Slot	Micro SD Card 2	Micro SD Card Slot	-	-
	Alarm OUT	LED Alarm	Alarm IN	3.1	U
	Alarm IN	Button Alarm	Alarm OUT	3.3	U
	3.5 mm (Mic-in)	Headset	3.5 mm (Mic-out)	2.0	U
	3.5 mm (Line-out)	Headset	3.5 mm (Line-in)	2.0	U
Laptop	DC Jack	Laptop Adaptor	DC Jack	1.6	U
	3.5 mm	Smartphone	3.5 mm	1.5	U

-Mode 2

Start		End		Cable Spec.	
Product Name	**I/O Port**	**Product Name**	**I/O Port**	**Length(m)**	**Shield**
EUT	RJ-45 (PoE)	PoE Injector	RJ-45 (PoE)	3.1	U
	Micro SD Card Slot	Micro SD Card 1	Micro SD Card Slot	-	-
	Micro SD Card Slot	Micro SD Card 2	Micro SD Card Slot	-	-
	Alarm OUT	LED Alarm	Alarm IN	3.1	U
	Alarm IN	Button Alarm	Alarm OUT	3.3	U
	3.5 mm (Mic-in)	Headset	3.5 mm (Mic-out)	2.0	U
	3.5 mm (Line-out)	Headset	3.5 mm (Line-in)	2.0	U
Laptop	DC Jack	Laptop Adaptor	DC Jack	1.6	U
	RJ-45(LAN)	PoE Injector	RJ-45(LAN)	1.4	U
	3.5 mm	Smartphone	3.5 mm	1.5	U

* Unshielded=U, Shielded=S

You can check the authenticity of this test report on the authenticity verification page on our website (www.kes.co.kr).

4.4 EUT Operating Mode(s)


Category	Mode	Operating
Mode 1	AC/DC Adaptor	- Monitoring EUT Using Web Viewer, Ping Test. - When the Button Alarm is pressed, make sure the Alarm is working. - After the test, the recorded video stored on the Micro SD Card was checked and the microphone motion was also confirmed. - Play a 1 kHz tone file on Smartphone and test it while checking if it is output normally to the Headset.
Mode 2	PoE	

4.5 Test operating S/W


Name	Version	Manufacture Company
Web Viewer	-	HANWHA VISION VIETNAM COMPANY LIMITED

You can check the authenticity of this test report on the authenticity verification page on our website (www.kes.co.kr).

4.6 Configuration



Mode 1



Mode 2

You can check the authenticity of this test report on the authenticity verification page on our website (www.kes.co.kr).

5 Measurement Procedure

- Conducted Emissions

The conducted emission levels were measured on each current-carrying line with the spectrum analyzer operating in the CISPR quasi-peak mode (or peak mode if applicable). The initial step in collecting conducted data is a spectrum analyzer peak scan of the measurement range. If the conducted emission exceed the average limit with the instrument set to the quasi-peak mode, the measurements are made in the average mode. The emission spectrum was scanned from 150 ㎑ to 30 ㎒. The highest emission amplitudes relative to the appropriate limits were measured and have been recorded. Quasi-peak readings are distinguished with a "QP".

- Radiated Electric Field Emissions

The test was done at a SEMI ANECHOIC CHAMBER with quasi-peak detector. The final test data was measured using a Quasi-Peak detector below 1 ㎓ at 10 m or 3 m distance and a Peak and Average detector above 1 ㎓ at 3 m distance. Test was proceeded worst case test mode and cable configuration. Measurements were made with the antenna positioned in both the horizontal and vertical planes of polarization. The antenna height was varied from 1 m to 4 m (Radiated Emissions(Below 1 ㎓)) and 1 m (Radiated Emissions(Above 1 ㎓)) and the EUT was rotated 360° to find the maximum emitting point for each frequency.

Measurement procedures was In accordance with ANSI C63.4 or CISPR 32.

♦ Calculation

- Conducted Emissions

QuasiPeak[㏈uV] / CAverage [㏈uV] = Reading Value[㏈uV] + Corr. [㏈]
QuasiPeak / CAverage : The Final Value
Reading Value : Not shown in the table.
Corr. : Correction values (LISN FACTOR + (Cable Loss + Pulse Limiter FACTOR))

- Radiated Emissions(Below 1 ㎓)

Result(QP) [㏈(㎶/m)] = (Reading(QP)[㏈(㎶)] + c.f[㏈(1/m)]
Margin(QP)[㏈] = Limit[㏈(㎶/m)] - Result(QP) [㏈(㎶/m)]
Reading(QP) : Reading value, Result(QP) : Reading value + Factor value
Limit(QP) : Limit value, c.f : (ANT Factor + Cable Loss - Preamp Factor), Margin: Margin value

- Radiated Emissions(Above 1 ㎓)

Result(PK/CAV) [㏈(㎶/m)] = (Reading(PK/CAV)[㏈(㎶)] + c.f[㏈(1/m)]
Margin(PK/CAV)[㏈] = Limit[㏈(㎶/m)] - Result(PK/CAV) [㏈(㎶/m)]
Reading(PK/CAV) : Reading value, Result(PK/CAV) : Reading value + Factor value
Limit(PK/CAV) : Limit value, c.f : (ANT Factor + Cable Loss - Preamp Factor), Margin: Margin value

You can check the authenticity of this test report on the authenticity verification page on our website (www.kes.co.kr).

6 Test Item

6.1 Conducted Emissions at Mains Power Ports

6.1.1 Test Equipment

Equipment Name	Model Number	Manufacturer	Serial No.	Cal. Date	Next Cal. Date	Used
SHIELD ROOM #6	-	DYMSTEC	-	-	-	■
EMC32 Measurement Software	EMC32	R&S	9.12.00	-	-	■
EMI TEST RECEIVER	ESR3	Rohde & Schwarz	101783	2025-11-03	2026-11-03	■
LISN	ENV216	Rohde & Schwarz	101787	2025-09-04	2026-09-04	■
ARTIFICIAL MAINS NETWORK	ESH2-Z5	Rohde & Schwarz	100450	2025-11-03	2026-11-03	■
PULSE LIMITER	ESH3-Z2	Rohde & Schwarz	101915	2025-11-03	2026-11-03	■

6.1.2 Test Location : SHIELD ROOM #6

6.1.3 Test Conditions :

Temperature	Relative Humidity
(27.7 ~ 27.8) °C	(58.2 ~ 58.3) % R.H.

You can check the authenticity of this test report on the authenticity verification page on our website (www.kes.co.kr).

6.1.4 Test Result


○ Test Date : 2026-07-07

● Test Mode : Mode 1

Test Report

1 / 1

Test Description:	Conducted Emission
Job No.:	KES-EM262094
Phase:	L
Mode:	Mode 1
Operator Name:	KES



Final_Result

Frequency (MHz)	QuasiPeak (dBµV)	CAverage (dBµV)	Limit (dBµV)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Line	Corr. (dB)
0.165000	---	33.60	66.00	32.40	1000.0	9.000	L1	19.4
0.165000	49.60	---	79.00	29.40	1000.0	9.000	L1	19.4
1.110000	---	22.35	60.00	37.65	1000.0	9.000	L1	19.5
1.110000	28.82	---	73.00	44.18	1000.0	9.000	L1	19.5
1.115000	---	22.37	60.00	37.63	1000.0	9.000	L1	19.5
1.115000	28.94	---	73.00	44.06	1000.0	9.000	L1	19.5
15.200000	---	25.63	60.00	34.37	1000.0	9.000	L1	20.2
15.200000	33.36	---	73.00	39.64	1000.0	9.000	L1	20.2
15.345000	---	25.75	60.00	34.25	1000.0	9.000	L1	20.2
15.345000	33.19	---	73.00	39.81	1000.0	9.000	L1	20.2


You can check the authenticity of this test report on the authenticity verification page on our website (www.kes.co.kr).

○ Test Date : 2026-07-07
● Test Mode : Mode 1

Test Report

1 / 1

Test Description:	Conducted Emission
Job No.:	KES-EM262094
Phase:	N
Mode:	Mode 1
Operator Name:	KES



Final_Result

Frequency (MHz)	QuasiPeak (dBµV)	CAverage (dBµV)	Limit (dBµV)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Line	Corr. (dB)
0.175000	---	31.86	66.00	34.14	1000.0	9.000	N	19.4
0.175000	47.69	---	79.00	31.31	1000.0	9.000	N	19.4
1.045000	---	21.65	60.00	38.35	1000.0	9.000	N	19.5
1.045000	29.52	---	73.00	43.48	1000.0	9.000	N	19.5
1.070000	---	21.57	60.00	38.43	1000.0	9.000	N	19.5
1.070000	29.44	---	73.00	43.56	1000.0	9.000	N	19.5
15.360000	---	27.17	60.00	32.83	1000.0	9.000	N	20.2
15.360000	34.95	---	73.00	38.05	1000.0	9.000	N	20.2
15.560000	---	27.45	60.00	32.55	1000.0	9.000	N	20.2
15.560000	35.06	---	73.00	37.94	1000.0	9.000	N	20.2

6.1.5 Remark

Complies with the test requirements.

You can check the authenticity of this test report on the authenticity verification page on our website (www.kes.co.kr).

6.2 Conducted Emissions at Telecommunication Ports

6.2.1 Test Equipment

Equipment Name	Model Number	Manufacturer	Serial No.	Cal. Date	Next Cal. Date	Used
SHIELD ROOM #6	-	DYMSTEC	-	-	-	■
EMC32 Measurement Software	EMC32	R&S	9.12.00	-	-	■
EMI TEST RECEIVER	ESR3	Rohde & Schwarz	101783	2025-11-03	2026-11-03	■
LISN	ENV216	Rohde & Schwarz	101787	2025-09-04	2026-09-04	■
ARTIFICIAL MAINS NETWORK	ESH2-Z5	Rohde & Schwarz	100450	2025-11-03	2026-11-03	■
PULSE LIMITER	ESH3-Z2	Rohde & Schwarz	101915	2025-11-03	2026-11-03	■
8-WIRE ISN CAT6	ENY81-CAT6	Rohde & Schwarz	101666	2026-02-24	2027-02-24	■

6.2.2 Test Location : SHIELD ROOM #6

6.2.3 Test Conditions :

Temperature	Relative Humidity
(27.7 ~ 27.7) °C	(58.2 ~ 58.2) % R.H.

You can check the authenticity of this test report on the authenticity verification page on our website (www.kes.co.kr).


6.2.4 Test Result

○ Test Date : 2026-07-07
● Test Mode : Mode 1

Test Report

1 / 1

Test Description:	Telecommunication Emission
Job No.:	KES-EM262094
Mode :	Mode 1
Speed :	1 000 Mbps
Operator Name:	KES



Final_Result

Frequency (MHz)	QuasiPeak (dBµV)	CAverage (dBµV)	Limit (dBµV)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Line	Corr. (dB)
0.315000	---	44.06	77.84	33.78	1000.0	9.000	Single Line	19.4
0.315000	51.54	---	90.84	39.30	1000.0	9.000	Single Line	19.4
0.330000	---	42.31	77.45	35.14	1000.0	9.000	Single Line	19.4
0.330000	53.12	---	90.45	37.33	1000.0	9.000	Single Line	19.4
1.105000	---	36.42	74.00	37.58	1000.0	9.000	Single Line	19.3
1.105000	43.58	---	87.00	43.42	1000.0	9.000	Single Line	19.3
1.125000	---	35.40	74.00	38.60	1000.0	9.000	Single Line	19.3
1.125000	43.06	---	87.00	43.94	1000.0	9.000	Single Line	19.3
15.770000	---	41.22	74.00	32.78	1000.0	9.000	Single Line	19.7
15.770000	49.08	---	87.00	37.92	1000.0	9.000	Single Line	19.7
16.185000	---	41.29	74.00	32.71	1000.0	9.000	Single Line	19.7
16.185000	48.81	---	87.00	38.19	1000.0	9.000	Single Line	19.7


You can check the authenticity of this test report on the authenticity verification page on our website (www.kes.co.kr).

○ Test Date : 2026-07-07
● Test Mode : Mode 2

Test Report

1 / 1

Test Description:	Telecommunication Emission
Job No.:	KES-EM262094
Mode :	Mode 2
Speed :	1 000 Mbps
Operator Name:	KES



Final_Result

Frequency (MHz)	QuasiPeak (dBµV)	CAverage (dBµV)	Limit (dBµV)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Line	Corr. (dB)
0.205000	---	53.13	81.41	28.28	1000.0	9.000	Single Line	19.6
0.205000	53.20	---	94.41	41.21	1000.0	9.000	Single Line	19.6
0.410000	---	41.95	75.65	33.70	1000.0	9.000	Single Line	19.4
0.410000	46.67	---	88.65	41.98	1000.0	9.000	Single Line	19.4
1.335000	---	34.09	74.00	39.91	1000.0	9.000	Single Line	19.3
1.335000	37.49	---	87.00	49.51	1000.0	9.000	Single Line	19.3
1.340000	---	34.53	74.00	39.47	1000.0	9.000	Single Line	19.3
1.340000	37.82	---	87.00	49.18	1000.0	9.000	Single Line	19.3
29.635000	---	54.02	74.00	19.98	1000.0	9.000	Single Line	20.1
29.635000	56.18	---	87.00	30.82	1000.0	9.000	Single Line	20.1

6.2.5 Remark

Complies with the test requirements.

You can check the authenticity of this test report on the authenticity verification page on our website (www.kes.co.kr).

6.3 Radiated Emissions(Below 1 ㎓)

6.3.1 Test Equipment

Equipment Name	Model Number	Manufacturer	Serial No.	Cal. Date	Next Cal. Date	Used
SEMI ANECHOIC CHAMBER #4(10 m)	-	DYMSTEC	-	-	-	■
EP5/RE Software	EP5/RE	TOYO	6.0.0	-	-	■
EMI TEST RECEIVER	ESU26	Rohde & Schwarz	100551	2026-02-12	2027-02-12	■
AMPLIFIER	SCU 01	Rohde & Schwarz	100574	2026-04-24	2027-04-24	■
TRILOG-BROADBAND ANTENNA	VULB9163	Schwarzbeck	715	2024-11-08	2026-11-08	■

6.3.2 Test Location : SEMI ANECHOIC CHAMBER #4(10 m) Measurement Distance : □ 3 m, ■ 10 m

6.3.3 Test Conditions :


Temperature	Relative Humidity
(25.7 ~ 25.9) °C	(58.6 ~ 58.8) % R.H.

You can check the authenticity of this test report on the authenticity verification page on our website (www.kes.co.kr).

6.3.4 Test Result

○ Test Date : 2026-07-06

● Test Mode : Mode 1



Final Result


No.	Frequency [MHz]	(P)	Reading QP [dB(uV)]	c.f [dB(1/m)]	Result QP [dB(uV/m)]	Limit QP [dB(uV/m)]	Margin QP [dB]	Height [cm]	Angle [deg]	Remark
1	124.986	V	57.2	-24.1	33.1	40.0	6.9	102.0	81.0	
2	125.003	H	56.6	-24.1	32.5	40.0	7.5	388.0	228.0	
3	318.775	H	47.1	-16.6	30.5	47.0	16.5	394.0	161.0	
4	319.205	V	46.4	-16.6	29.8	47.0	17.2	101.0	238.0	
5	374.998	V	56.2	-14.5	41.7	47.0	5.3	105.0	206.0	
6	375.001	H	55.9	-14.5	41.4	47.0	5.6	203.0	180.0	

※ The data is the result measured by the detector in Quasi-Peak mode on the Peak graph.

You can check the authenticity of this test report on the authenticity verification page on our website (www.kes.co.kr).

○ Test Date : 2026-07-06

● Test Mode : Mode 2



Final Result

No.	Frequency [MHz]	(P)	Reading QP [dB(uV)]	c.f [dB(1/m)]	Result QP [dB(uV/m)]	Limit QP [dB(uV/m)]	Margin QP [dB]	Height [cm]	Angle [deg]	Remark
1	41.155	V	53.1	-22.2	30.9	40.0	9.1	103.0	196.0	
2	124.939	V	57.1	-24.1	33.0	40.0	7.0	101.0	105.0	
3	196.321	V	48.9	-21.4	27.5	40.0	12.5	100.0	172.0	
4	202.547	H	46.7	-20.9	25.8	40.0	14.2	388.0	58.0	
5	374.956	V	55.6	-14.5	41.1	47.0	5.9	104.0	164.0	
6	375.003	H	55.0	-14.5	40.5	47.0	6.5	193.0	333.0	

※ The data is the result measured by the detector in Quasi-Peak mode on the Peak graph.

6.3.5 Remark

Complies with the test requirements.

You can check the authenticity of this test report on the authenticity verification page on our website (www.kes.co.kr).

6.4 Radiated Emissions(Above 1 ㎓)

6.4.1 Test Equipment

Equipment Name	Model Number	Manufacturer	Serial No.	Cal. Date	Next Cal. Date	Used
SEMI ANECHOIC CHAMBER #3	-	DYMSTEC	-	-	-	■
EP5/RE Software	EP5/RE	TOYO	6.0.0	-	-	■
EMI TEST RECEIVER	ESU26	Rohde & Schwarz	100552	2026-02-12	2027-02-12	■
PREAMPLIFIER	8449B	AGILENT	3008A01967	2026-03-04	2027-03-04	■
ATTENUATOR	8491A	HP	35496	2026-02-12	2027-02-12	■
DOUBLE RIDGED HORN ANTENNA	SAS-571	A.H. SYSTEM,INC	781	2026-03-06	2027-03-06	■

6.4.2 Test Location : SEMI ANECHOIC CHAMBER #3

6.4.3 Test Conditions :


Temperature	Relative Humidity
(23.9 ~ 24.1) °C	(52.8 ~ 53.0) % R.H.

You can check the authenticity of this test report on the authenticity verification page on our website (www.kes.co.kr).

6.4.4 Test Result

○ Test Date : 2026-07-08

● Test Mode : Mode 1



Final Result


No.	Frequency [MHz]	(P)	Reading PK [dB(uV)]	Reading CAV [dB(uV)]	c.f [dB(1/m)]	Result PK [dB(uV/m)]	Result CAV [dB(uV/m)]	Limit PK [dB(uV/m)]	Limit AV [dB(uV/m)]	Margin PK [dB]	Margin CAV [dB]	Angle [deg]	Remark
1	2412.081	H	42.6	28.6	6.0	48.6	34.6	76.0	56.0	27.4	21.4	48.9	
2	2451.650	V	46.4	29.7	6.1	52.5	35.8	76.0	56.0	23.5	20.2	263.1	
3	2659.618	V	46.9	29.4	6.3	53.2	35.7	76.0	56.0	22.8	20.3	188.4	
4	2857.850	H	41.5	28.1	7.0	48.5	35.1	76.0	56.0	27.5	20.9	327.2	
5	5720.912	V	38.2	24.7	14.9	53.1	39.6	80.0	60.0	26.9	20.4	197.1	
6	5918.025	H	38.4	24.2	15.1	53.5	39.3	80.0	60.0	26.5	20.7	321.4	

※ The data is the result of measured by the detector in PK and CISPR Average on the Peak graph.

You can check the authenticity of this test report on the authenticity verification page on our website (www.kes.co.kr).

○ Test Date : 2026-07-08

● Test Mode : Mode 2



Final Result

No.	Frequency [MHz]	(P)	Reading PK [dB(uV)]	Reading CAV [dB(uV)]	c.f [dB(1/m)]	Result PK [dB(uV/m)]	Result CAV [dB(uV/m)]	Limit PK [dB(uV/m)]	Limit AV [dB(uV/m)]	Margin PK [dB]	Margin CAV [dB]	Angle [deg]	Remark
1	1751.881	H	43.3	29.7	3.0	46.3	32.7	76.0	56.0	29.7	23.3	311.8	
2	2055.006	V	45.8	30.7	3.4	49.2	34.1	76.0	56.0	26.8	21.9	154.4	
3	2409.831	V	44.9	29.5	6.0	50.9	35.5	76.0	56.0	25.1	20.5	126.8	
4	2450.525	H	43.5	29.9	6.1	49.6	36.0	76.0	56.0	26.4	20.0	303.9	
5	5719.443	V	38.9	24.9	14.9	53.8	39.8	80.0	60.0	26.2	20.2	243.8	
6	5721.587	H	38.9	24.9	14.9	53.8	39.8	80.0	60.0	26.2	20.2	259.6	

※ The data is the result of measured by the detector in PK and CISPR Average on the Peak graph.


6.4.5 Remark

Complies with the test requirements.

You can check the authenticity of this test report on the authenticity verification page on our website (www.kes.co.kr).

7 Test Setup Photos and EUT Photographs

7.1 Test Setup Photos




<Conducted Emissions at Mains Power Ports - Front> Mode 1



<Conducted Emissions at Mains Power Ports - Rear> Mode 1

You can check the authenticity of this test report on the authenticity verification page on our website (www.kes.co.kr).




<Conducted Emissions at Telecommunication Ports - Front> Mode 1



<Conducted Emissions at Telecommunication Ports - Rear> Mode 1

You can check the authenticity of this test report on the authenticity verification page on our website (www.kes.co.kr).



<Conducted Emissions at Telecommunication Ports - Front> Mode 2




<Conducted Emissions at Telecommunication Ports - Rear> Mode 2

You can check the authenticity of this test report on the authenticity verification page on our website (www.kes.co.kr).



<Radiated Emissions(Below 1 ㎓) - Front> Mode 1




<Radiated Emissions(Below 1 ㎓) - Rear> Mode 1

You can check the authenticity of this test report on the authenticity verification page on our website (www.kes.co.kr).




<Radiated Emissions(Below 1 ㎓) - Front> Mode 2



<Radiated Emissions(Below 1 ㎓) - Rear> Mode 2

You can check the authenticity of this test report on the authenticity verification page on our website (www.kes.co.kr).



<Radiated Emissions(Above 1 ㎓) - Front> Mode 1



<Radiated Emissions(Above 1 ㎓) - Rear> Mode 1

You can check the authenticity of this test report on the authenticity verification page on our website (www.kes.co.kr).



<Radiated Emissions(Above 1 ㎓) - Front> Mode 2



<Radiated Emissions(Above 1 ㎓) - Rear> Mode 2

You can check the authenticity of this test report on the authenticity verification page on our website (www.kes.co.kr).

7.2 EUT Photographs



<EUT External Photographs - Top>



<EUT External Photographs - Bottom>

You can check the authenticity of this test report on the authenticity verification page on our website (www.kes.co.kr).



<Components-1>



<Components-2>

You can check the authenticity of this test report on the authenticity verification page on our website (www.kes.co.kr).



<Port-1>



<Port-2>

You can check the authenticity of this test report on the authenticity verification page on our website (www.kes.co.kr).



<Port-3>

You can check the authenticity of this test report on the authenticity verification page on our website (www.kes.co.kr).



<EUT Internal Photographs>

You can check the authenticity of this test report on the authenticity verification page on our website (www.kes.co.kr).

7.3 Label

Name	:	Hanwha Vision Co., Ltd.
Product item	:	NETWORK CAMERA
Model name	:	XNV-A9085RZ

この装置は、クラスＡ情報技術装置です。この装置を家庭環境で使用すると電波妨害を引き起こすことがあります。この場合には使用者が適切な対策を講ずるよう要求されることがあります。 ＶＣＣＩ－Ａ

The End.

You can check the authenticity of this test report on the authenticity verification page on our website (www.kes.co.kr).