G4B(www.g4b.go.kr)진위확인코드 : HDuSyNx0Wf
정부시점확인센터 2026-07-21 15:25:12 KST

시 험 성 적 서
TEST REPORT

성적서 번호 Report No.		ICRT-TR-I260457-0A
신청자 Client	기관명 Name	Hanwha Vision Co., Ltd.
	주 소 Address	6, Pangyo-ro 319Beon-gil, Bundang-gu, Seongnam-si, Gyeonggi-do, 13488 KOREA
시험대상품목 Sample description		NETWORK CAMERA
모델명 Type designation		XNV-A9095RZ
정 격 Ratings		-
시험장소 Place of test		■ 고정시험(Inside test) □ 현장시험(Field test) 주소지(Address) : ICR, 112, Hwanggeum 3-ro 7beon-gil, Yangchon-eup, Gimpo-si, Gyeonggi-do
시험기간 Date of test		2026. 06. 24 ~ 2026. 06. 25
시험방법/항목 Test Method/Item		ISO 20653 : 2023 Road vehicles — Degrees of protection (IP code) — Protection of electrical equipment against foreign objects, water and access (IP6K9K)
시험결과 Test Results		Test Results Reference
확 인 Affirmation	작성자 Tested by 성 명 이 우 신 (서명) Name W. S. Lee (Signature)	기술책임자 Technical Manager 성 명 권 상 혁 (서 명) Name S. H. Gwon (Signature)

□ 이 시험결과는 의뢰자가 제시한 시료 및 시료명에만 한정되며 * 표시된 시험결과는 당 시험기관의 인정범위 밖의 것임을 밝힙니다.
The result shown in this test report refer only to the sample(s) tested unless otherwise stated and this laboratory is not accredited for the test results marked *.

□ 위 성적서는 KS Q ISO/IEC 17025 및 한국인정기구(KOLAS)인정과 관련이 있습니다.
The above test report is related to accreditation by KS Q ISO/IEC 17025 and Korea Laboratory Accreditation scheme.

□ 위 성적서는 국제시험기관인정협력체(International Laboratory Accreditation Cooperation) 상호인정협정 (Mutual Recognition Arrangement)에 서명한 한국인정기구(KOLAS)로부터 공인받은 분야에 대한 시험결과입니다.
The above testing certificate is the accredited test result by Korea Laboratory Accreditation scheme, which signed the ILAC-MRA.

□ 위 성적서는 주식회사 아이씨알의 승인 없이는 일부 복제에 대해 금지됩니다.
The test report is prohibited for some reproduction without the approval of the ICR.

2026. 07. 21

한국인정기구 인정 **주식회사 아이씨알 대표이사**

The head of INTERNATIONAL CERTIFICATION REGISTRAR

Accredited by KOLAS, Republic of KOREA

본 성적서의 진위 확인은 G4B 혹은 ICR 홈페이지에서 가능합니다.
The authenticity of the test report can be checked on the G4B or ICR website.

경기도 김포시 양촌읍 황금3로7번길 112 / Tel: 02-6351-9001 ~ 6
112, Hwanggeum3-ro 7beon-gil, Yangchon-eup, Gimpo-si, Gyeonggi-do, Korea / Tel: 02-6351-9001 ~ 6

G4B(www.g4b.go.kr)진위확인코드 : HDuSyN7JWfc=

1. Test Overview

This test is carried out according to the specimen and specifications requested by the applicant.

2. Specimen information

2.1 Specimen information

Applicant	:	Hanwha Vision Co., Ltd.
manufacturer	:	Hanwha Vision Co., Ltd.
Product Name	:	NETWORK CAMERA
Model name	:	XNV-A9095RZ
Derived model	:	XNV-A9085RZ
Quantity	:	1 EA
Ratings	:	-
Note	:	-

2.2 Product photo



Figure 1) Photo of the specimen

G4B(www.g4b.go.kr)진위확인코드 : HDuSyN7JWfc=

3. Test conditions

3.1 1st characteristic numeral (IP6KX, Protection against access.)

3.1.1 Test standard : ISO 20653 : 2023 Road vehicles - Degrees of protection (IP code) – Protection of electrical equipment against foreign objects, water and access (IP6KX)

3.1.2 Date of test : 2026. 06. 25

3.1.3 Test method

a) The test access probes and conditions are conducted according to Table 1).

3.1.4 Test judgment

a) An approach probe with a diameter of 1.0 mm shall not pass through.


1st characteristic numeral	Extra character	Access probe	Test force
6K	D		1 N ± 10 %

Table 1) Test conditions (Human protection approaching dangerous areas

3.1.5 Test photos - 1st characteristic number (IP5X, Protection against access)



Figure 2) Test measurement probe photo



Figure 3) Test measuring equipment (Push pull gauge)

G4B(www.g4b.go.kr)진위확인코드 : HDuSyN7JWfc=

3.2 1st characteristic numeral (IP6KX, Protection against foreign objects.)

3.2.1 Test standard : ISO 20653 : 2023 Road vehicles - Degrees of protection (IP code) – Protection of electrical equipment against foreign objects, water and access (IP6KX)

3.2.2 Date of test : 2026. 06. 25

3.2.3 Test method

a) Set the test product in the dust tester.

b) Table 2) Test will be conducted according to the conditions.

c) Remove dust from the outer part of the test product after the test.


3.2.4 Test judgment

a) Visually check if dust penetrates inside the test product.

1st characteristic numeral	Dust type	Test conditions (1 cycle)		Test cycles
		movement of the air – dust mixture	Break time	
6K	A2 (Arizona dust)	6 s	15 min	20 cycles

Table 2) Test conditions (Protection against external dust)

G4B(www.g4b.go.kr)진위확인코드 : HDuSyN7JWfc=



Equipment 1 - Test device for checking protection against dust (Dust chamber)

G4B(www.g4b.go.kr)진위확인코드 : HDuSyN7JWfc=

3.2.5 Test photos - 1st characteristic number (IP6KX, Protection against foreign objects)



Figure 4) Specimen installation photo



Figure 5) Specimen installation photo (Enlarge)



Figure 6) Photo after the test



Figure 7) Photo after the test (Enlarge)



Figure 8) Test condition (Test time)

G4B(www.g4b.go.kr)진위확인코드 : HDuSyN7JWfc=

3.3 2nd characteristic number (IPX9K, Protection against water)

3.3.1 Test standard : ISO 20653 : 2023 Road vehicles - Degrees of protection (IP code) – Protection of electrical equipment against foreign objects, water and access (IPX9K)

3.3.2 Date of test : 2026. 06. 24

3.3.3 Test Methods

a) Before the test, measure the impact force of the water.

b) Install the specimen on the waterproof tester.

c) The test is carried out according to the conditions in Table 3).

d) After the test, remove moisture from the outside of the specimen.

3.3.4 Test judgment

a) Visually check whether or not water has penetrated the inside of the specimen.

2nd characteristic numeral	Test methods	Water flow rate	Water pressure	Water temperature	test time
9K	Fan jet noozzle Turntable speed - (5±1) r/min Spray at 0°, 30°, 60°, 90° Distance (100 ~ 150) mm	(14 ~ 16) L/min	(8 000 ~ 10 000) kPa	(80 ± 5) ℃	30 s per position

Table 3) Test method and main test conditions for waterproof test




Figure 9) Photo of the measuring the impact force of the water (Test set-up)



Figure 10) Check the impact force of the water (0.9 ~ 1.2) N

G4B(www.g4b.go.kr)진위확인코드 : HDuSyN7JWfc=

Dimensions in millimetres



Key

1 fan jet nozzle
2 DUT
3 turntable / holder
4 swivel axis
5 reference points (0°, 30°, 60°, 90°) endorsing cylinder for DUT
6 position 1
7 position 2
8 position 3
9 position 4

$\alpha = (30 \pm 10)°$

Speed of DUT (5 ± 1) r/min.

Equipment 2 - Test set-up for determining the protection against high-pressure/steam-jet cleaning

G4B(www.g4b.go.kr)진위확인코드 : HDuSyN7JWfc=

3.3.5 Test photos – 2nd characteristic number (IPX9K, Protection against water)



Figure 11) Specimen installation photo




Figure 12) Specimen installation photo
(Distance measurement)



Figure 13) Test condition photo
(Distance measurement, Enlarge)




Figure 14) Photo during the test

G4B(www.g4b.go.kr)진위확인코드 : HDuSyN7JWfc=




Figure 15) Test condition (Flow rate)



Figure 16) Test condition photo (Test time)

G4B(www.g4b.go.kr)진위확인코드 : HDuSyN7JWfc=

4. Test result

4.1 1st characteristic number (IP6KX, Protection against access)



Figure 17) Test photo (Measurement 1)



Figure 18) Test photo (Measurement 2)

4.2 1st characteristic number (IP6KX, Protection against foreign objects)



Figure 19) Photo after the test (Body 1)




Figure 20) Photo after the test (Body 2)




Figure 21) Photo after the test (Cover)

G4B(www.g4b.go.kr)진위확인코드 : HDuSyN7JWfc=

4.3 2nd characteristic number (IPX9K, Protection against water)




Figure 22) Photo after the test (Body 1)




Figure 23) Photo after the test (Body 2)




Figure 24) Photo after the test (Cover)

G4B(www.g4b.go.kr)진위확인코드 : HDuSyN7JWfc=

Test Class	Test Checklist	Test result	note
1st characteristic number (IP6KX)	Check whether probe passing through the hazardous area.	There's no passing through of the probe.	Check visually
	After the test, check whether the dust penetrated into the specimen.	There's no penetrate of the dust.	
2nd characteristic number (IPX9K)	After the test, check whether the water penetrated into the specimen.	There's no penetrate of the water.	Check visually

Table 4) Test results


5. Test Equipment List

Equipment name	Model name	Manufacturing company	Next calibration date
Dust proof tester	JFMD-0005	JFMTECH	2027. 03. 04
Waterproof tester	JFMB-008-9K	JFMTECH	2027. 01. 14
Push Pull Gauge	DST-20N	IMADA	2026. 10. 16
Tape measure	KMC-34(5.5 m * 19 mm)	KOMELON	2026. 10. 21
Probe Kit	TRK-05	JFMTECH	2028. 12. 05

Table 5) Test equipment

G4B(www.g4b.go.kr)진위확인코드 : HDuSyN7JWfc=

***Appending 1. product blueprint.**



The End.