



# XRN-1620B2

16CH 4K 140Mbps H.265 NVR



## Key Features

- Up to 16 channels, Supports up to 32 megapixel camera resolution
- 140Mbps network camera recording
- Support 4K video out on HDMI monitor
- Support dual monitor HDMI/VGA video out
- H.265, H.264, MJPEG compression
- WiseStream support
- Maximum 8 internal HDDs (80TB)
- ARB & failover (N+1), dynamic event, Wisenet AI metadata search support

# XRN-1620B2

16CH 4K 140Mbps H.265 NVR



## Specifications

### Display

|                |                      |                                                                                                                                                                                                                                                                                                                                                                                                                               |
|----------------|----------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Network camera | Inputs               | Max. 16CH                                                                                                                                                                                                                                                                                                                                                                                                                     |
|                | Resolution           | 32MP ~ CIF                                                                                                                                                                                                                                                                                                                                                                                                                    |
|                | Protocols            | SUNAPI, ONVIF                                                                                                                                                                                                                                                                                                                                                                                                                 |
| Decoding       | Local Display        | FHD : HDMI & VGA Dual monitor UHD : HDMI Single monitor                                                                                                                                                                                                                                                                                                                                                                       |
|                | Multi Screen Display | [Local Monitor] - Dynamic layout,<br>Virtual channel view - Clone mode : Up to 16 Division - Expand mode : Up to 9 Division<br>[Web] 1/ 2H/ 2V/ 3V/ 4/ 6/ 8/ 9                                                                                                                                                                                                                                                                |
|                | Resolution           | [Local Monitor] FHD Clone mode : 32M(15fps,H.265 Only),12M(30fps,H.265 Only),8.3M(2ch@25fps),1080p(8ch@30fps),<br>D1(16ch@30fps) UHD Single mode : 32M(15fps,H.265 Only),12M(30fps,H.265 Only),8.3M(2ch@25fps),1080p(8ch@30fps),<br>D1(9ch@30fps) FHD Expand mode : 32M(12fps,H.265 Only),12M(25fps,H.265 Only),8.3M(30fps),1080p(3ch@30fps),<br>D1(8ch@25fps) Clone/Single mode : Up to 25fps when displaying more than 10CH |

### Performance

|                  |                       |                                                                                                                  |
|------------------|-----------------------|------------------------------------------------------------------------------------------------------------------|
| Operating System | Embedded              | Linux                                                                                                            |
| Record           | Compression           | H.265, H.264, MJPEG                                                                                              |
|                  | Recording Bandwidth   | Max. 140Mbps                                                                                                     |
|                  | Resolution            | 32MP ~ CIF                                                                                                       |
|                  | Mode                  | Normal, Dual Stream, Schedule(Continuous/Event), Event (Pre/Post), Bookmark                                      |
|                  | Event Trigger         | Alarm Input, Video Loss, Camera Event(Sensor, MD, Video Analytics, Defocus, Audio),<br>Dynamic Event, User Event |
|                  | Event Action          | e-Mail, Event Push, PTZ Preset, Alarm Out, Buzzer, Monitor Out, FTP, SUNAPI Command,<br>Shutdown                 |
| Search & Play    | Playback Bandwidth    | Max. 32Mbps                                                                                                      |
|                  | User                  | Max. 4 Users (Local 1, Remote 3)                                                                                 |
|                  | Simultaneous playback | Max. 64CH(Local 16CH, Remote 16CH per user)                                                                      |
|                  | Fisheye Dewarping     | CMS                                                                                                              |
|                  | Mode                  | Date & Time(Calendar), Event list, Text Search, Smart Search                                                     |
|                  | Resolution            | CIF ~ 32MP (Up to H.264 9MP, H.265 32MP)                                                                         |
|                  | Playback Control      | Fast/Slow Forward / Backward, Move one step Up / Down                                                            |

## Performance

|         |               |                                                         |
|---------|---------------|---------------------------------------------------------|
| Storage | Supported HDD | Up to 10TB                                              |
|         | HDD Slot      | SATA 8ea(Max. 80TB)                                     |
| Backup  | File backup   | BU/Exe/AVI(GUI), JPG/AVI(Network)                       |
|         | Function      | Multi channel(Up to 16CH) Play, Date-Time/Title display |

## Network

|                        |                     |                                                                                                                                                                                          |
|------------------------|---------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Protocol               |                     | IPv4, IPv6, TCP/IP, UDP/IP, RTP (UDP), RTP (TCP), RTSP, NTP, HTTP, DHCP (Server, Client), SMTP, ICMP, IGMP, ARP, DNS, DDNS, uPnP, HTTPS, SNMP, ONVIF (Profile-S), SUNAPI(Server, Client) |
| DDNS                   |                     | Hanwha DDNS                                                                                                                                                                              |
| Transmission Bandwidth |                     | Max. 140Mbps                                                                                                                                                                             |
| Audio                  | Input/Output        | 16 CH(network)                                                                                                                                                                           |
|                        | Compression         | G.711, G.726, AAC(16/48KHz)                                                                                                                                                              |
|                        | Audio Communication | 2-Way                                                                                                                                                                                    |
| Max Remote Users       |                     | Search(3), Live Unicast(10), Multicast(20)                                                                                                                                               |
| Security               |                     | IP address filtering, User access Log, 802.1x, Encryption Device certificate(Hanwha Techwin Root CA), Signed firmware                                                                    |
| Web viewer             | Supported OS        | Windows 10, macOS 10.13                                                                                                                                                                  |
|                        | Supported browser   | Google Chrome, Microsoft Edge, Mac Safari                                                                                                                                                |
| Viewer Software        |                     | WAVE, SSM, Webviewer, Smart Viewer, Wisenet mobile Support CGI(SUNAPI) for integration to 3'rd party VMS                                                                                 |

## Function

|                    |                   |                                                                                                                                                                                                                                                                                  |
|--------------------|-------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Camera Setup       | Register          | Auto, Manual                                                                                                                                                                                                                                                                     |
|                    | Item              | IP address, Add profile edit, Bitrate, Compression, GOP, Quality, Camera MD setup (4, 8 point polygon) Camera video setup (Simple focus, Brightness/Contrast, Flip/Mirror, IRIS, WDR, D&N, SSNR, Shutter, SDR, DIS),, Fisheye Dewarping Mode, Hallway View Setup, Camera Webpage |
| PTZ                | Control           | Via GUI, Webviewer, SPC-2000                                                                                                                                                                                                                                                     |
|                    | Preset            | 300 Presets                                                                                                                                                                                                                                                                      |
| Smart phone        | Support Model     | iOS, Android                                                                                                                                                                                                                                                                     |
|                    | Protocol Support  | RTP, RTSP, HTTP, CGI(SUNAPI)                                                                                                                                                                                                                                                     |
|                    | Control           | Live 16CH(Multi-Profile Support), Playback 4CH                                                                                                                                                                                                                                   |
|                    | Max. Remote Users | Search(3), Live Unicast(10)                                                                                                                                                                                                                                                      |
| Redundancy         | Failover          | N+1                                                                                                                                                                                                                                                                              |
|                    | ARB               | Support                                                                                                                                                                                                                                                                          |
| Easy configuration |                   | P2P(QR code)                                                                                                                                                                                                                                                                     |

## Interface

|         |           |                                            |
|---------|-----------|--------------------------------------------|
| Front   | Indicator | HDD, Alarm, Power, Record, Backup, Network |
| Storage |           | OK                                         |

## Interface

|             |                                          |
|-------------|------------------------------------------|
| HDMI        | 1EA 3840x2160 30Hz                       |
| VGA         | 1920x1080 30Hz                           |
| Audio       | Out 1EA (3.5mm Audio Jack)               |
| Ethernet    | RJ-45 2EA (LAN/WAN, 1Gbps)               |
| Alarm       | In 4EA, Out 2EA                          |
| USB         | 3EA(Front 2 x USB 2.0, Rear 1 x USB 3.0) |
| Power inlet | AC 1EA                                   |

## System

|                |          |                                                                                                                                                                                                                       |
|----------------|----------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Log            | Log List | Max. 100,000 (System Log, Event Log each)                                                                                                                                                                             |
| System Control |          | Mouse, Keyboard, Web, Controller (SPC-2000)                                                                                                                                                                           |
| Language       |          | English, French, German, Italian, Spanish, Russian, Turkish, Polish, Dutch, Czech, Portuguese, Danish, Rumanian, Serbian, Croatian, Hungarian, Greek, Norwegian, Finnish, Korean, Chinese, Japanese, Thai, Vietnamese |

## Environmental

|                       |                             |
|-----------------------|-----------------------------|
| Operating Temperature | 0°C to +40°C(32°F to 104°F) |
| Operating Humidity    | 20% ~ 85% RH                |

## Electrical

|                   |                             |
|-------------------|-----------------------------|
| Power Input       | 100 ~ 240 VAC ±10%, 50/60Hz |
| Power Consumption | 130W                        |

## Mechanical

|                  |                                                     |
|------------------|-----------------------------------------------------|
| Color / Material | Black / Metal                                       |
| Dimension        | 440.0 x 89.8 x 428.4 mm (17.32 x 3.54 x 16.87 inch) |
| Weight           | 5.71Kg(12.59lb)                                     |

## Intelligent Analysis

|           |                  |                                   |
|-----------|------------------|-----------------------------------|
| AI Search | Object Attribute | Compatible with Hanwha AI Cameras |
|-----------|------------------|-----------------------------------|

# XRN-1620B2

16CH 4K 140Mbps H.265 NVR



## CAD

Unit: mm [inch]

