



XRN-3220B2

32CH NVR with 12th gen. Intel® Processor



Key Features

- 32CH, 32MP resolution
- SATA 8 HDD Bays (up to 80TB)
- Up to 520Mbps recording / transmission bandwidth
- Easy Channel/Event/Alarm configuration
- Virtual Channel View
- Dynamic layout
- Built-in Support for Web Management (up to 100)
- Compatible with Wisenet Viewer, Wisenet mobile
- NDAA compliant and TPM integrated
- Manual event support

XRN-3220B2

32CH NVR with 12th gen. Intel® Processor



Specifications

Display

Telecamera di rete	Ingressi	Max. 32CH
	Risoluzione	32MP ~ CIF
	Protocolli	SUNAPI, ONVIF
Decodifica	Display locale	[Dual Display] HDMI 1: 3840 x 2160 (30Hz) HDMI 2: 1920x1080 (60Hz)
	Display multischermo	[Local Monitor] - Dynamic layout, Virtual channel view - Clone Mode : Up to 64 Division - Expand Mode : HDMI1 up to 32 Div. HDMI2 up to 32 Div. [Web] 1/ 2H/ 2V/ 3V/ 4/ 6/ 8/ 9
	Risoluzione	32M(15fps, H.265 Only), 12M(30fps, H.265 Only), 8.3M(4ch@30fps), 1080p(16ch@30fps), 720P(32ch@30fps), D1(48ch@30fps)

Performance

Sistema operativo	Integrato	Linux
Registrazione	Compressione	H.265, H.264, MJPEG
	Larghezza di banda di registrazione	Distributed mode : Up to 520 Mbps, Normal mode : Up to 300 Mbps
	Risoluzione	32MP ~ CIF
	Modalità	Normal, Dual Stream, Schedule(Continuous/Event), Event (Pre/Post), Bookmark
	Attivazione evento	Alarm Input, Video Loss, Camera Event(Sensor, MD, Video Analytics, Defocus, Audio), Dynamic Event, User Event
	Azione evento	e-Mail, Event Push, PTZ Preset, Alarm Out, Buzzer, Monitor Out, FTP, SUNAPI Command, Shutdown
Cerca e Riproduci	Larghezza di banda di riproduzione	Up to 200Mbps(32CH simultaneously)
	Utente	Max. 4 Users (Local 1, Remote 3)
	Riproduzione simultanea	Max. 80CH(Local 32CH, Remote 16CH per user)
	Dewarping Fisheye	Support (Local 1CH), CMS
	Modalità	Time/Event/Text/ARB/Bookmark/Smart search
	Risoluzione	CIF ~ 32MP (Up to H.264 9MP, H.265 32MP)
	Controllo riproduzione	Fast/Slow Forward / Backward, Move one step Up / Down
Archiviazione	HDD supportato	Up to 10TB
	Slot HDD	SATA 8ea(Max. 80TB)
	Esterna	iSCSI storage

Performance

Backup	Backup dei file	Recorder/SEC/AVI/JPG(Local), AVI/PNG(Network)
	Funzione	Multi channel(Up to 16CH) Play, Date-Time/Title display

Rete

Protocollo		IPv4, IPv6, TCP/IP, UDP/IP, RTP (UDP), RTP (TCP), RTSP, RTCP, NTP, HTTP, DHCP (Server, Client), SMTP, ICMP, IGMP, ARP, DNS, DDNS, uPnP, HTTPS, SNMP, ONVIF (Profile-S), SUNAPI(Server, Client)
DDNS		Hanwha DDNS
Larghezza di banda di trasmissione		Max. 520Mbps
Audio	Ingresso/Uscita	32 CH(network)
	Compressione	G.711, G.726, AAC(16/48KHz)
	Comunicazione audio	2-Way
Numero max. utenti da remoto		Search(3), Live Unicast(10), Multicast(20)
Sicurezza		IP address filtering, User access Log, 802.1x, TLS, Encryption Device certificate(Hanwha Techwin Root CA), Signed firmware, TPM support
Visualizzatore web	Sistema operativo supportato	Windows10 or higher, macOS 13.5.2 or higher
	Browser supportato	Google Chrome, Microsoft Edge, Mac Safari
Software di visualizzazione		WAVE, SSM, Webviewer, Wisenet Viewer, Wisenet mobile Support CGI(SUNAPI) for integration to 3'rd party VMS

Funzione

Configurazione telecamera	Registro	Auto, Manual
	Articolo	IP address, Add profile edit, Bitrate, Compression, GOP, Quality, Camera MD setup (4, 8 point polygon) Camera video setup (Simple focus, Brightness/Contrast, Flip/Mirror, IRIS, WDR, D&N, SSNR, Shutter, SDR, DIS), Fisheye Dewarping Mode, Hallway View Setup, Camera Webpage
PTZ	Controllo	Via GUI, Webviewer, SPC-2000/2001
	Preimpostato	300 Presets
Smartphone	Modello supporto	iOS, Android
	Supporto del protocollo	RTP, RTSP, HTTP, CGI(SUNAPI)
	Controllo	Live 16CH(Multi-Profile Support), Playback 4CH
	Max. Utenti da remoto	Search(3), Live Unicast(10)
Ridondanza	Failover	N+1
	ARB	Support
Configurazione semplice		P2P(QR code)

Interfaccia

Anteriore	Indicatore	HDD, Alarm, Power, Record, Backup, Network
Archiviazione		Yes
Reset		Power button
HDMI		2EA (Playback/Setup → HDMI1) HDMI1 : 3840x2160 30Hz HDMI2 : 1920x1080 60Hz

Interfaccia

Audio	Out 1EA (3.5mm Audio Jack)
Ethernet	RJ-45 3EA (LAN/WAN, 1Gbps)
Allarme	In 8EA, Out 4EA
USB	4EA(Front 2 x USB2.0 + Rear 2 x USB 3.0)
Ingresso alimentazione	AC 1EA

Sistema

Registro	Elenco registro	Max. 100,000 (System Log, Event Log each)
Controllo del sistema		Mouse(include wireless), Keyboard(include wireless), Web, Controller (SPC-2000/2001)
Lingua		English, French, German, Italian, Spanish, Russian, Turkish, Polish, Dutch, Czech, Portuguese, Danish, Rumanian, Serbian, Croatian, Hungarian, Greek, Norwegian, Finnish, Korean, Chinese, Japanese, Thai, Vietnamese

Certificazioni

Temperatura di esercizio	0°C to +40°C(32°F to 104°F)
Umidità di esercizio	20% ~ 85% RH

Elettrico

Ingresso alimentazione	100 ~ 240 VAC $\pm$ 10%; 50/60Hz, 1.5A(Single SMPS)
Consumo energetico	Max. 143W (488BTU with HDD 8ea)

Meccanico

Colore / Materiale	Black / Metal
Dimensioni	438.0 x 86.0 x 434.9 mm (17.47 x 3.39 x 17.12 inch)
Peso	7.3Kg (16.1lb, Except HDD)

Analisi intelligente

Ricerca IA	Attributo oggetto	Compatible with Hanwha AI Cameras
------------	-------------------	-----------------------------------

XRN-3220B2


32CH NVR with 12th gen. Intel® Processor



CAD

Unit: mm [inch]

XRN-6420B2_XRN-3220B2 RECORDER



Revision	V1.1
Revision Date	25/01/17
Paper Size	A1
Unit	mm [inch]
Scale	1:2

© Hanwha Vision Co., Ltd. All right reserved.